

Name:Roll Number:

*****	SELECT ALL POSSIBLE ANSWERS. DO YOUR OWN WORK. DO NOT LOOK AROUND	*****
-------	--	-------

1. Azure app service is a
 - a. REST based service
 - b. TCP based service
 - c. HTTP based service

Ans: c

2. Azure app service allows application to run on:
 - a. Windows
 - b. Android
 - c. macOS
 - d. Linux

Ans: a, d

3. Shared Azure app service plans can
 - a. Scale out to max 3 instances
 - b. Shares VM with other app services with your own apps
 - c. Shared compute with other app services with apps from other users
 - d. Not scale out

Ans: d

4. The below app service plans give you dedicated compute from your apps:
 - a. Shared
 - b. Basic
 - c. Standard
 - d. Premium
 - e. Isolated

Ans: c, d, e

5. The difference between premium and isolated app service plans is:
 - a. Premium plan provides compute in your virtual network
 - b. Isolated plan provides higher security and confinement to your own network
 - c. Premium plan does better scaling than isolated plan
 - d. Isolated plan provides Higher performance

Ans: b, [d]

6. You can deploy your code to app service through:
 - a. ftp
 - b. ftp/s
 - c. cli
 - d. git

Name:Roll Number:

*****	SELECT ALL POSSIBLE ANSWERS. DO YOUR OWN WORK. DO NOT LOOK AROUND	*****
-------	--	-------

- e. ci/cd pipelines
- f. zipdeploy

Ans: All of the above

7. The purpose of deployment slots is to:
- a. Deploy code with the same environment settings
 - b. Test code with the settings and environment of production app
 - c. Customize settings for a specific deployment
 - d. Hassle-free deployment of new code to production and rollback

Ans: All of the above

8. The built-in authentication feature for App Service and Azure Functions:
- a. providing out-of-the-box authentication with federated identity providers
 - b. allowing you to focus on the rest of your application
 - c. allows you to integrate various auth capabilities into your web app or API without implementing them yourself
 - d. Allow you to integrate with 2 key identity providers: Microsoft Live, Google

Ans: a,b,c [d]

9. The authentication and authorization middleware component is a feature of the platform that:
- a. Runs as Azure PaaS Service
 - b. Runs on your own app service plan
 - c. Manages the authenticated session
 - d. Injects identity information into HTTP request headers

Ans: b, c, d

10. The main deployment types for Azure App Service are:
- a. Multitenant public service hosts App Service plans in the Free, Shared, Basic, Standard, Premium, PremiumV2, and PremiumV3 pricing SKUs.
 - b. The single-tenant App Service Environment (ASE) hosts Isolated SKU App Service plans directly in your Azure virtual network.
 - c. Isolated deployment type that hosts premium and isolated plans in your own network
 - d. Shared and basic service plans which are hosted in shared compute

Ans: a, b

11. Following App Service plan categories provides the maximum scale-out capabilities:
- a. Dedicated compute
 - b. Isolated
 - c. Shared Compute

Ans: b

Name:Roll Number:

*****	SELECT ALL POSSIBLE ANSWERS. DO YOUR OWN WORK. DO NOT LOOK AROUND	*****
-------	--	-------

12. Which of the following networking features of App Service can be used to control outbound network traffic?

- a. App-assigned address
- b. Hybrid Connections
- c. Service endpoints

Ans: b

13. Deploying your application to a nonproduction slot has the following benefits:

- a. You can validate app changes in a staging deployment slot before swapping it with the production slot.
- b. Deploy an app to a slot first and swapping it into production makes sure that all instances of the slot are warmed up before being swapped into production.
- c. You can configure auto swap when pre-swap validation isn't needed.
- d. After a swap, the previous production app is located in the staging slot. If the changes swapped into the production slot aren't as you expect, you can perform the same swap immediately to get your "last known good site" back.

Ans:a,b,c,d

14. When you create a new deployment slot:

- a. The new slot has no content
- b. The new slot has copy of the application and settings in production slot
- c. The new slot has copy of the application and settings in production slot if you clone the settings from a different slot.
- d. You cannot deploy to the slot from a different repository branch or a different repository.
- e. You can deploy the same code from the same git repository in the other slots

Ans:a,e

15. Select all the settings which are swapped:

- a. General settings, such as framework version, 32/64-bit, web sockets
- b. App settings (can be configured to stick to a slot)
- c. Custom domain names
- d. Publishing endpoints

Ans: a, b

16. Select all the settings which are not swapped:

- a. Public certificates
- b. WebJobs content
- c. IP restrictions
- d. Hybrid connections
- e. Always On

Name:Roll Number:

*****	SELECT ALL POSSIBLE ANSWERS. DO YOUR OWN WORK. DO NOT LOOK AROUND	*****
-------	--	-------

Ans:

17. To configure an app setting or connection string to stick to a specific slot:

- a. Select **Deployment slot setting** in the setting properties
- b. Selecting this check box tells App Service that the setting isn't swappable.
- c. Selecting this check box tells App Service that the setting is swappable.
- d. Select **Slot specific setting** in the setting properties

Ans:a, b

18. When you perform a swap with preview:

- a. App Service performs the swap operation but pauses after swapping the code.
- b. App Service performs the swap operation but pauses before swapping the code.
- c. App Service performs the swap operation but pauses after swapping the settings.
- d. App Service performs the swap operation but pauses before swapping the settings.
- e. You can then verify the result on the staging slot before completing the swap.
- f. If you cancel the swap, App Service reapplies configuration elements to the source slot.

Ans: c, e, f

19. If any errors occur in the target slot (for example, the production slot) after a slot swap:

- a. You can restore the slots to their pre-swap states by swapping the same two slots immediately.
- b. You can restore the slots to their pre-swap states by deploying the production code.
- c. You can restore the slots to their pre-swap states by deploying the test code in staging slot.

Ans:a

20. With multiple slots:

- a. You can route a portion of the traffic to another slot.
- b. You can route traffic to one slot only
- c. Routing traffic to different slots is done using cookies

Ans:a, c

21. By default, all client requests to the app's production URL (http://<app_name>.azurewebsites.net) are routed to the production slot. One can automatically route a portion of the traffic to another slot.

What is the default routing rule applied to new deployment slots?

- a. 0%
- b. 10%
- c. 20%
- d. 50%
- e. 100%

Ans:a

Name:Roll Number:

*****	SELECT ALL POSSIBLE ANSWERS. DO YOUR OWN WORK. DO NOT LOOK AROUND	*****
-------	--	-------

22. Some configuration elements follow the content across a swap (not slot specific), whereas other configuration elements stay in the same slot after a swap (slot specific). Which of the following settings are swapped?
- a. Publishing endpoints
 - b. WebJobs content
 - c. WebJobs schedulers

Ans: b