

## UML UNIT – III

The UML is a graphical language for visualizing, specifying, constructing, and documenting the artefacts of a software-intensive system. The UML gives you a standard way to write a system's blueprints, covering conceptual things, such as business processes and system functions, as well as concrete things, such as classes written in a specific programming language, database schemas, and reusable software components.

### **Model**

A model is a simplification of reality. A model provides the blueprints of a system. A model may be structural, emphasizing the organization of the system, or it may be behavioral, emphasizing the dynamics of the system.

### **Why do we model**

We build models so that we can better understand the system we are developing.

Through modeling, we achieve four aims.

1. Models help us to visualize a system as it is or as we want it to be.
2. Models permit us to specify the structure or behavior of a system.
3. Models give us a template that guides us in constructing a system.
4. Models document the decisions we have made.

We build models of complex systems because we cannot comprehend such a system in its entirety.

### **Principles of Modeling**

There are four basic principles of model

1. The choice of what models to create has a profound influence on how a problem is attacked and how a solution is shaped.
2. Every model may be expressed at different levels of precision.
3. The best models are connected to reality.
4. No single model is sufficient. Every nontrivial system is best approached through a small set of nearly independent models.

### **Object Oriented Modeling**

In software, there are several ways to approach a model. The two most common ways are

1. Algorithmic perspective
2. Object-oriented perspective

### **Algorithmic Perspective**

The traditional view of software development takes an algorithmic perspective.

In this approach, the main building block of all software is the procedure or function.

This view leads developers to focus on issues of control and the decomposition of larger algorithms into smaller ones.

As requirements change and the system grows, systems built with an algorithmic focus turn out to be very hard to maintain.

## **Object-oriented perspective**

The contemporary view of software development takes an object-oriented perspective.

In this approach, the main building block of all software systems is the object or class.

A class is a description of a set of common objects.

Every object has identity, state, and behavior.

Object-oriented development provides the conceptual foundation for assembling systems out of components using technology such as Java Beans or COM+.

## **An Overview of UML**

- The Unified Modeling Language is a standard language for writing software blueprints. The UML may be used to visualize, specify, construct, and document the artifacts of a software-intensive system.
- The UML is appropriate for modeling systems ranging from enterprise information systems to distributed Web-based applications and even to hard real time embedded systems. It is a very expressive language, addressing all the views needed to develop and then deploy such systems.

The UML is a language for

- Visualizing
  - Specifying
  - Constructing
  - Documenting
- **Visualizing** The UML is more than just a bunch of graphical symbols. Rather, behind each symbol in the UML notation is a well-defined semantics. In this manner, one developer can write a model in the UML, and another developer, or even another tool, can interpret that model unambiguously
- **Specifying** means building models that are precise, unambiguous, and complete.
- **Constructing** the UML is not a visual programming language, but its models can be directly connected to a variety of programming languages
- **Documenting** a healthy software organization produces all sorts of artifacts in addition to raw executable code. These artifacts include
  - Requirements
  - Architecture
  - Design
  - Source code
  - Project plans
  - Tests
  - Prototypes
  - Releases

## 3.2 The Conceptual Model Of UML

To understand the UML, you need to form a **conceptual model of the language**, and this requires learning three major elements:

1. Things
2. Relationships
3. Diagrams

### Things in the UML

There are four kinds of things in the

UML: Structural things

Behavioral things


Grouping things

Annotational things

**Structural things** are the nouns of UML models. These are the mostly static parts of a model, representing elements that are either conceptual or physical. In all, there are seven kinds of structural things.

1. Classes
2. Interfaces
3. Collaborations
4. Use cases
5. Active classes
6. Components
7. Nodes

**Class** is a description of a set of objects that share the same attributes, operations, relationships, and semantics. A class implements one or more interfaces. Graphically, a class is rendered as a rectangle, usually including its name, attributes, and operations.



### Interface

Interface is a collection of operations that specify a service of a class or component.

An interface therefore describes the externally visible behavior of that element.

An interface might represent the complete behavior of a class or component or only a part of that behavior.

An interface is rendered as a circle together with its name. An interface rarely stands alone. Rather, it is typically attached to the class or component that realizes the interface



**Collaboration** defines an interaction and is a society of roles and other elements that work together to provide some cooperative behavior that's bigger than the sum of all the elements. Therefore, collaborations have structural, as well as behavioral, dimensions. A given class might participate in several collaborations.


---

Graphically, a collaboration is rendered as an ellipse with dashed lines, usually including only its name




### Usecase


- Use case is a description of set of sequence of actions that a system performs that yields an observable result of value to a particular actor
- Use case is used to structure the behavioral things in a model.
- A use case is realized by a collaboration. Graphically, a use case is rendered as an ellipse with solid lines, usually including only its name



**Active class** is just like a class except that its objects represent elements whose behavior is concurrent with other elements. Graphically, an active class is rendered just like a class, but with heavy lines, usually including its name, attributes, and operations




**Component** is a physical and replaceable part of a system that conforms to and provides the realization of a set of interfaces. Graphically, a component is rendered as a rectangle with tabs



**Node** is a physical element that exists computational resource, generally having at processing capability. Graphically, a node including only its name

at run time and represents a least some memory and, often, is rendered as a cube, usually



**Behavioral Things** are the dynamic parts of UML models. These are the verbs of a model, representing behavior over time and space. In all, there are two primary kinds of behavioral things

Interaction  
state machine

### **Interaction**

Interaction is a behavior that comprises a set of messages exchanged among a set of objects within a particular context to accomplish a specific purpose

An interaction involves a number of other elements, including messages, action sequences and links

Graphically a message is rendered as a directed line, almost always including the name of its operation




### **State Machine**

State machine is a behavior that specifies the sequences of states an object or an interaction goes through during its lifetime in response to events, together with its responses to those events

State machine involves a number of other elements, including states, transitions, events and activities

Graphically, a state is rendered as a rounded rectangle, usually including its name and its substates




### **Grouping Things:-**

1. are the organizational parts of UML models. These are the boxes into which a model can be decomposed
2. There is one primary kind of grouping thing, namely, packages.

### **Package:-**


- A package is a general-purpose mechanism for organizing elements into groups. Structural things, behavioral things, and even other grouping things may be placed in a package
- Graphically, a package is rendered as a tabbed folder, usually including only its name and, sometimes, its contents



**Annotational things** are the explanatory parts of UML models. These are the comments you may apply to describe about any element in a model.

**A note** is simply a symbol for rendering constraints and comments attached to an element or a collection of elements.

Graphically, a note is rendered as a rectangle with a dog-eared corner, together with a textual or graphical comment



**Relationships in the UML:** There are four kinds of relationships in the UML:

1. Dependency
2. Association
3. Generalization
4. Realization

**Dependency:-**

Dependency is a semantic relationship between two things in which a change to one thing may affect the semantics of the other thing

Graphically a dependency is rendered as a dashed line, possibly directed, and occasionally including a label



**Association** is a structural relationship that describes a set of links, a link being a connection among objects.

Graphically an association is rendered as a solid line, possibly directed, occasionally including a label, and often containing other adornments, such as multiplicity and role names



**Generalization** is a special kind of association, representing a structural relationship between a whole and its parts. Graphically, a generalization relationship is rendered as a solid line with a hollow arrowhead pointing to the parent



**Realization** is a semantic relationship between classifiers, wherein one classifier specifies a contract that another classifier guarantees to carry out. Graphically a realization relationship is rendered as a cross between a generalization and a dependency relationship



## **Diagrams in the UML**

- **Diagram** is the graphical presentation of a set of elements, most often rendered as a connected graph of vertices (things) and arcs (relationships).
- In theory, a diagram may contain any combination of things and relationships.
- For this reason, the UML includes nine such diagrams:
  - Class diagram
  - Object diagram
  - Use case diagram
  - Sequence diagram
  - Collaboration diagram
  - Statechart diagram
  - Activity diagram
  - Component diagram
  - Deployment diagram

### **Class diagram**

A class diagram shows a set of classes, interfaces, and collaborations and their relationships.

Class diagrams that include active classes address the static process view of a system.

### **Object diagram**

- Object diagrams represent static snapshots of instances of the things found in class diagrams
- These diagrams address the static design view or static process view of a system
- An object diagram shows a set of objects and their relationships

### **Use case diagram**

- A use case diagram shows a set of use cases and actors and their relationships
- Use case diagrams address the static use case view of a system.
- These diagrams are especially important in organizing and modeling the behaviors of a system.

### **Interaction Diagrams**

Both sequence diagrams and collaboration diagrams are kinds of interaction diagrams

Interaction diagrams address the dynamic view of a system

**A sequence diagram** is an interaction diagram that emphasizes the time-ordering of messages

**A collaboration diagram** is an interaction diagram that emphasizes the structural organization of the objects that send and receive messages

Sequence diagrams and collaboration diagrams are isomorphic, meaning that you can take one and transform it into the other

### **Statechart diagram**

- A statechart diagram shows a state machine, consisting of states, transitions, events, and activities
- Statechart diagrams address the dynamic view of a system



- They are especially important in modeling the behavior of an interface, class, or collaboration and emphasize the event-ordered behavior of an object

### **Activity diagram**

An activity diagram is a special kind of a statechart diagram that shows the flow from activity to activity within a system

Activity diagrams address the dynamic view of a system

They are especially important in modeling the function of a system and emphasize the flow of control among objects

### **Component diagram**

- A component diagram shows the organizations and dependencies among a set of components.
- Component diagrams address the static implementation view of a system
- They are related to class diagrams in that a component typically maps to one or more classes, interfaces, or collaborations

### **Deployment diagram**

- A deployment diagram shows the configuration of run-time processing nodes and the components that live on them
- Deployment diagrams address the static deployment view of an architecture

### **Rules of the UML**

The UML has semantic rules for

- |               |  |
|---------------|--|
| 1. Names      | What you can call things, relationships, and diagrams      |
| 2. Scope      | The context that gives specific meaning to a name          |
| 3. Visibility | How those names can be seen and used by others             |
| 4. Integrity  | How things properly and consistently relate to one another |
| 5. Execution  | What it means to run or simulate a dynamic model           |

Models built during the development of a software-intensive system tend to evolve and may be viewed by many stakeholders in different ways and at different times. For this reason, it is common for the development team to not only build models that are well-formed, but also to build models that are

1. Elided Certain elements are hidden to simplify the view
2. Incomplete Certain elements may be missing
3. Inconsistent The integrity of the model is not guaranteed

### **Common Mechanisms in the UML**


UML is made simpler by the presence of four common mechanisms that apply consistently throughout the language.

1. Specifications
2. Adornments
3. Common divisions
4. Extensibility mechanisms

**Specification** that provides a textual statement of the syntax and semantics of that building block. The UML's specifications provide a semantic backplane that

contains all the parts of all the models of a system, each part related to one another in a consistent fashion

**Adornments** Most elements in the UML have a unique and direct graphical notation that provides a visual representation of the most important aspects of the element. A class's specification may include other details, such as whether it is abstract or the visibility of its attributes and operations. Many of these details can be rendered as graphical or textual adornments to the class's basic rectangular notation.



### **Extensibility Mechanisms**

The UML's extensibility mechanisms include

1. Stereotypes
2. Tagged values
3. Constraints

### **Stereotype**

- Stereotype extends the vocabulary of the UML, allowing you to create new kinds of building blocks that are derived from existing ones but that are specific to your problem
- A tagged value extends the properties of a UML building block, allowing you to create new information in that element's specification
- A constraint extends the semantics of a UML building block, allowing you to add new rules or modify existing ones

## **2.3 Architecture**

A system's architecture is perhaps the most important artifact that can be used to manage these different viewpoints and so control the iterative and incremental development of a system throughout its life cycle.

Architecture is the set of significant decisions  
about The organization of a software system



The selection of the structural elements and their interfaces by which the system is composed

Their behavior, as specified in the collaborations among those elements

The composition of these structural and behavioral elements into progressively larger subsystems

The architectural style that guides this organization: the static and dynamic elements and their interfaces, their collaborations, and their composition.

Software architecture is not only concerned with structure and behavior, but also with usage, functionality, performance, resilience, reuse, comprehensibility, economic and technology constraints and trade-offs, and aesthetic concerns.



## Modeling a System's Architecture

**The use case view:** The use case view of a system encompasses the use cases that describe the behavior of the system as seen by its end users, analysts, and testers.

With the UML, the static aspects of this view are captured in use case diagrams

The dynamic aspects of this view are captured in interaction diagrams, state chart diagrams, and activity diagrams.

### **Design View**

- The design view of a system encompasses the classes, interfaces, and collaborations that form the vocabulary of the problem and its solution.
- This view primarily supports the functional requirements of the system, meaning the services that the system should provide to its end users.

### **Process View**

- The process view of a system encompasses the threads and processes that form the system's concurrency and synchronization mechanisms.
- This view primarily addresses the performance, scalability, and throughput of the system

### **Implementation View**

The implementation view of a system encompasses the components and files that are used to assemble and release the physical system.

This view primarily addresses the configuration management of the system's releases, made up of somewhat independent components and files that can be assembled in various ways to produce a running system.

### **Deployment Diagram**


The deployment view of a system encompasses the nodes that form the system's hardware topology on which the system executes.

This view primarily addresses the distribution, delivery, and installation of the parts that make up the physical system.



## 3.4 Classes

- A class is a description of a set of objects that share the same attributes, operations, relationships, and semantics.
- A class implements one or more interfaces.
- The UML provides a graphical representation of class, a class is rendered as a rectangle



### Graphical Representation of Class in

#### UML Terms and Concepts

##### Names

Every class must have a name that distinguishes it from other classes. A name is a textual string that name alone is known as a simple name; a path name is the class name prefixed by the name of the package in which that class lives.

Customer


**Simple Name**

java::awt::Rectangle

**Path Name**


##### Attributes

- An attribute is a named property of a class that describes a range of values that instances of the property may hold.
- A class may have any number of attributes or no attributes at all.
- An attribute represents some property of thing you are modeling that is shared by all objects of that class
- You can further specify an attribute by stating its class and possibly a default initial value
- 




## **Operations**

- An *operation* is the implementation of a service that can be requested from any object of the class to affect behavior.
- A class may have any number of operations or no operations at all
- Graphically, operations are listed in a compartment just below the class attributes
- You can specify an operation by stating its signature, covering the name, type, and default value of all parameters and a return type




## **Organizing Attributes and Operations**

To better organize long lists of attributes and operations, you can also prefix each group with a descriptive category by using stereotypes



## **Responsibilities**

- A Responsibility is a contract or an obligation of a class
- When you model classes, a good starting point is to specify the responsibilities of the things in your vocabulary.
- A class may have any number of responsibilities, although, in practice, every well-structured class has at least one responsibility and at most just a handful.
- Graphically, responsibilities can be drawn in a separate compartment at the bottom of the class icon



## **Common Modeling Techniques**

### **Modeling the Vocabulary of a System**

- You'll use classes most commonly to model abstractions that are drawn from the problem you are trying to solve or from the technology you are using to implement a solution to that problem.
- They represent the things that are important to users and to implementers



- To model the vocabulary of a system
  - Identify those things that users or implementers use to describe the problem or solution.
  - Use CRC cards and use case-based analysis to help find these abstractions.
  - For each abstraction, identify a set of responsibilities.
  - Provide the attributes and operations that are needed to carry out these responsibilities for each class.

### **Modeling the Distribution of Responsibilities in a System**

- Once you start modeling more than just a handful of classes, you will want to be sure that your abstractions provide a balanced set of responsibilities.
- To model the distribution of responsibilities in a system
  - Identify a set of classes that work together closely to carry out some behavior.
  - Identify a set of responsibilities for each of these classes.
  - Look at this set of classes as a whole, split classes that have too many responsibilities into smaller abstractions, collapse tiny classes that have trivial responsibilities into larger ones, and reallocate responsibilities so that each abstraction reasonably stands on its own.
  - Consider the ways in which those classes collaborate with one another, and redistribute their responsibilities accordingly so that no class within a collaboration does too much or too little.

### **Modeling Nonsoftware Things**

- Sometimes, the things you model may never have an analog in software
- Your application might not have any software that represents them
- To model nonsoftware things
  - Model the thing you are abstracting as a class.
  - If you want to distinguish these things from the UML's defined building blocks, create a new building block by using stereotypes to specify these new semantics and to give a distinctive visual cue.
  - If the thing you are modeling is some kind of hardware that itself contains software, consider modeling it as a kind of node, as well, so that you can further expand on its structure.

### **Modeling Primitive Types**

At the other extreme, the things you model may be drawn directly from the programming language you are using to implement a solution.

Typically, these abstractions involve primitive types, such as integers, characters, strings, and even enumeration types

To model primitive types

Model the thing you are abstracting as a type or an enumeration, which is rendered using class

notation with the appropriate stereotype.

If you need to specify the range of values associated with this type, use constraints.

## **3.5 Relationships**

In the UML, the ways that things can connect to one another, either logically or physically, are modeled as relationships.

Graphically, a relationship is rendered as a path, with different kinds of lines used to distinguish the kinds of relationships

In object-oriented modeling, there are three kinds of relationships that are most important:

Dependencies

Generalizations


Associations

### **Dependency**

A dependency is a using relationship that states that a change in specification of one thing may affect another thing that uses it but not necessarily the reverse.

Graphically dependency is rendered as a dashed directed line, directed to the thing being depended on.

Most often, you will use dependencies in the context of classes to show that one class uses another class as an argument in the signature of an operation




Dependencies

### **Generalization**

- A generalization is a relationship between a general thing (called the super class or parent) and a more specific kind of that thing (called the subclass or child).
- generalization means that the child is substitutable for the parent. A child inherits the properties of its parents, especially their attributes and operations

- An operation of a child that has the same signature as an operation in a parent overrides the operation of the parent; this is known as polymorphism.
- Graphically generalization is rendered as a solid directed line with a large open arrowhead, pointing to the parent




Generalization

## **Association**

- An association is a structural relationship that specifies that objects of one thing are connected to objects of another
- An association that connects exactly two classes is called a binary association
- An associations that connect more than two classes; these are called n-ary associations.
- Graphically, an association is rendered as a solid line connecting the same or different classes.
- Beyond this basic form, there are four adornments that apply to association

## **Name**


- An association can have a name, and you use that name to describe the nature of the relationship



Association Names

## **Role**


- When a class participates in an association, it has a specific role that it plays in that relationship;
- The same class can play the same or different roles in other associations.
- An instance of an association is called a link



## **Role Names**

### **Multiplicity**


- In many modeling situations, it's important for you to state how many objects may be connected across an instance of an association
- This "how many" is called the multiplicity of an association's role
- You can show a multiplicity of exactly one (1), zero or one (0..1), many (0..\*), or one or more (1..\*). You can even state an exact number (for example, 3).



## **Multiplicity**

### **Aggregation**

- Sometimes, you will want to model a "whole/part" relationship, in which one class represents a larger thing (the "whole"), which consists of smaller things (the "parts").
- This kind of relationship is called aggregation, which represents a "has-a" relationship, meaning that an object of the whole has objects of the part
- Aggregation is really just a special kind of association and is specified by adorning a plain association with an open diamond at the whole end



## **Aggregation**

## **Common Modeling Techniques**

## **Modeling Simple Dependencies**

The most common kind of dependency relationship is the connection between a class that only uses another class as a parameter to an operation.


To model this using relationship

Create a dependency pointing from the class with the operation to the class used as a parameter in the operation.

The following figure shows a set of classes drawn from a system that manages the assignment of students and instructors to courses in a university.

This figure shows a dependency from CourseSchedule to Course, because Course is used in both the add and remove operations of CourseSchedule.

The dependency from Iterator shows that the Iterator uses the CourseSchedule; the CourseSchedule knows nothing about the Iterator. The dependency is marked with a stereotype, which specifies that this is not a plain dependency, but, rather, it represents a friend, as in C++.




## Dependency Relationships

### Modeling Single Inheritance

To model inheritance relationships

- Given a set of classes, look for responsibilities, attributes, and operations that are common to two or more classes.
- Elevate these common responsibilities, attributes, and operations to a more general class. If necessary, create a new class to which you can assign these
- Specify that the more-specific classes inherit from the more-general class by placing a generalization relationship that is drawn from each specialized class to its more-general parent.




## **Inheritance Relationships**

### **Modeling Structural Relationships**

- When you model with dependencies or generalization relationships, you are modeling classes that represent different levels of importance or different levels of abstraction
- Given a generalization relationship between two classes, the child inherits from its parent but the parent has no specific knowledge of its children.
- Dependency and generalization relationships are one-sided.
- Associations are, by default, bidirectional; you can limit their direction
- Given an association between two classes, both rely on the other in some way, and you can navigate in either direction
- An association specifies a structural path across which objects of the classes interact.

### **To model structural relationships**

- For each pair of classes, if you need to navigate from objects of one to objects of another, specify an association between the two. This is a data-driven view of associations.
- For each pair of classes, if objects of one class need to interact with objects of the other class other than as parameters to an operation, specify an association between the two. This is more of a behavior-driven view of associations.
- For each of these associations, specify a multiplicity (especially when the multiplicity is not \*, which is the default), as well as role names (especially if it helps to explain the model).
- If one of the classes in an association is structurally or organizationally a whole compared with the classes at the other end that look like parts, mark this as an aggregation by adorning the association at the end near the whole



Structural Relationships


## 3.6 Common Mechanisms

### Note

A note is a graphical symbol for rendering constraints or comments attached to an element or a collection of elements

Graphically, a note is rendered as a rectangle with a dog-eared corner, together with a textual or graphical comment.

A note may contain any combination of text or graphics



notes


### Stereotypes

A stereotype is an extension of the vocabulary of the UML, allowing you to create new kinds of building blocks similar to existing ones but specific to your problem.

Graphically, a stereotype is rendered as a name enclosed by guillemets and placed above the name of another element

## **Tagged Values**

- Every thing in the UML has its own set of properties: classes have names, attributes, and operations; associations have names and two or more ends (each with its own properties); and so on.
- With stereotypes, you can add new things to the UML; with tagged values, you can add new properties.
- A tagged value is not the same as a class attribute. Rather, you can think of a tagged value as metadata because its value applies to the element itself, not its instances.
- A tagged value is an extension of the properties of a UML element, allowing you to create new information in that element's specification.
- Graphically, a tagged value is rendered as a string enclosed by brackets and placed below the name of another element.
- In its simplest form, a tagged value is rendered as a string enclosed by brackets and placed below the name of another element.
- That string includes a name (the tag), a separator (the symbol =), and a value (of the tag).






## **Constraints**

A constraint specifies conditions that must be held true for the model to be well-formed.

A constraint is rendered as a string enclosed by brackets and placed near the associated element

Graphically, a constraint is rendered as a string enclosed by brackets and placed near the associated element or connected to that element or elements by dependency relationships.



## **3.7 Class Diagrams**

- A class diagram shows a set of classes, interfaces, and collaborations and their relationships.
- Graphically, a class diagram is a collection of vertices and arcs.

### **Common Properties**

#### **Contents**

- Class diagrams commonly contain the following things:
  - Classes
  - Interfaces
  - Collaborations
  - Dependency, generalization, and association relationships
- Like all other diagrams, class diagrams may contain notes and constraints
- Class diagrams may also contain packages or subsystems

Note: Component diagrams and deployment diagrams are similar to class diagrams, except that instead of containing classes, they contain components and nodes

## **Common Uses**

- You use class diagrams to model the static design view of a system. This view primarily supports the functional requirements of a system
- We'll typically use class diagrams in one of three ways:
  1. To model the vocabulary of a system
  2. To model simple collaborations
  3. To model a logical database schema

## **Modeling the vocabulary of a system**

- Modeling the vocabulary of a system involves making a decision about which abstractions are a part of the system under consideration and which fall outside its boundaries

## **Modeling simple collaborations**

- A collaboration is a society of classes, interfaces, and other elements that work together to provide some cooperative behavior that's bigger than the sum of all the elements.


### **Modeling logical database schema**

- We can model schemas for these databases using class diagrams.

### **Common Modeling Techniques**


#### **Modeling Simple Collaborations**

- When you create a class diagram, you just model a part of the things and relationships that make up your system's design view. For this reason, each class diagram should focus on one collaboration at a time.
- To model a collaboration
  - Identify the mechanism you'd like to model. A mechanism represents some function or behavior of the part of the system you are modeling that results from the interaction of a society of classes, interfaces, and other things.
  - For each mechanism, identify the classes, interfaces, and other collaborations that participate in this collaboration. Identify the relationships among these things, as well.
  - Use scenarios to walk through these things. Along the way, you'll discover parts of your model that were missing and parts that were just plain semantically wrong.
  - Be sure to populate these elements with their contents. For classes, start with getting a good balance of responsibilities. Then, over time, turn these into concrete attributes and operations.



### **Modeling a Logical Database Schema**

- The UML is well-suited to modeling logical database schemas, as well as physical databases themselves.
- The UML's class diagrams are a superset of entity-relationship (E-R) diagrams, Whereas classical E-R diagrams focus only on data, class diagrams go a step further by permitting the modeling of behavior, as well. In the physical database these logical operations are generally turned into triggers or stored procedures.
- To model a schema,
  - Identify those classes in your model whose state must transcend the lifetime of their applications.
  - Create a class diagram that contains these classes and mark them as persistent (a standard tagged value). You can define your own set of tagged values to address database-specific details.
  - Expand the structural details of these classes. In general, this means specifying the details of their attributes and focusing on the associations and their cardinalities that structure these classes.
  - Watch for common patterns that complicate physical database design, such as cyclic associations, one-to-one associations, and n-ary associations. Where necessary, create intermediate abstractions to simplify your logical structure.
  - Consider also the behavior of these classes by expanding operations that are important for data access and data integrity. In general, to provide a better separation of concerns, business rules concerned with the manipulation of sets of these objects should be encapsulated in a layer above these persistent classes.
  - Where possible, use tools to help you transform your logical design into a physical design.



## Modeling a Schema

### 3.8 Object Diagram

- An object diagram is a diagram that shows a set of objects and their relationships at a point in time.
- Graphically, an object diagram is a collection of vertices and arcs

- An object diagram is a special kind of diagram and shares the same common properties as all other diagrams—that is, a name and graphical contents that are a projection into a model

### **Contents**

- Object diagrams commonly contain
  - Objects
  - Links
- Like all other diagrams, object diagrams may contain notes and constraints.
- Object diagrams may also contain packages or subsystems

### **Common Uses**

- You use object diagrams to model the static design view or static process view of a system just as you do with class diagrams
- When you model the static design view or static process view of a system, you typically use object diagrams in one way:
  - To model object structures

### **Modeling Object Structures**

- Modeling object structures involves taking a snapshot of the objects in a system at a given moment in time.
- An object diagram represents one static frame in the dynamic storyboard represented by an interaction diagram

### **Common Modeling Techniques**

#### **Modeling Object Structures**

- An object diagram shows one set of objects in relation to one another at one moment in time.
- To model an object structure,

# Class to Object Diagram Example – Order System

