Signal to Noise Ratio[1]

$$\overline{e^2}(t) = \int_{-\Delta v/2}^{\Delta v/2} v^2 \frac{1}{\Delta v} dv = \frac{1}{\Delta v}\left[\frac{v^3}{3}\right]_{-\Delta v/2}^{\Delta v/2}$$

$$= \frac{1}{3\Delta v}\left[\frac{\Delta v^3}{8} + \frac{\Delta v^3}{8}\right]$$

$$= \frac{\Delta v^2}{12}$$

$$SNR\big|_Q = \frac{\overline{f^2}(t)}{\overline{e^2}(t)} = \frac{12}{\Delta v^2}\overline{f^2}(t) \qquad ;\Delta v = \frac{2V}{M}$$

$$= \frac{12}{4V^2} M^2 \overline{f^2}(t)$$

$$= \frac{3M^2 \overline{f^2}(t)}{V^2} = \frac{3M^2}{\alpha}$$

where $\alpha = \dfrac{V^2}{\overline{f^2}(t)} = \dfrac{PeakPower}{AvgPower}$

Signal to Noise Ratio[2]

$$SNR\big|_Q = \frac{3M^2}{\alpha}$$

In dB

$$SNR\big|_Q = 10\log_{10} 3 + 20\log_{10} M - 10\log_{10} \alpha(dB)$$

$$= 4.77 + 20\log_{10} M - 10\log_{10} \alpha(dB)$$

Encoding : each quantization level is encoded into N binary digit

$$\log_b a = \frac{\log_{10} a}{\log_{10} b}$$

$$\therefore M = 2^N$$

$$N = \log_2 M \longleftarrow \text{No.of level}$$

No.of binary digit per code word

QUANTISER NON-UNIFORM





NonUniform / Nonlinear Quantizer

QUANTISER NON-UNIFORM

- μ - law

$$|v| = \frac{\log(1+\mu|m|)}{\log(1+\mu)} \quad \text{where } \mu > 0$$

- if μ = 0→ Uniform Quantizer



Standard
Amerika Utara

QUANTISER NON-UNIFORM

A - law

$$|v| = \begin{cases} \dfrac{A|m|}{1+\log A}, & 0 \le |m| \le \dfrac{1}{A} \\ \dfrac{1+\log(A|m|)}{1+\log A}, & \dfrac{1}{A} \le |m| \le 1 \end{cases}$$

- A = 1 → Uniform Quantizer
- Practical value of A ⇒ A ≅ 100
- Reciprocal slope



Standard Eropa
(digunakan di Indonesia)

Multiplexing TDM

- Multiplexing merupakan proses penggabungan beberapa kanal sinyal informasi kedalam satu kanal informasi dengan tujuan agar sinyal informasi dapat dikirimkan secara simultan dalam satu kanal

- Time Division Multiplexing merupakan proses multiplexing dengan cara membagi waktu menjadi slot-slot waktu yang menyatakan informasi dari tiap kanal

- TDM – PCM (Time Division Multiplexing – Pulse Code Modulation) merupakan proses multiplexing sinyal yang menggunakan teknik pengkodean PCM



Multiplexing TDM (cont)



Standar TDM yang digunakan Indonesia adalah PCM-30 (E1) yang mampu menggabungkan 30 kanal (masing-masing 64 kbps) menjadi sebuah sinyal multiplek TDM PCM dengan laju 2,048 Mbps

PCM-30 (E-1, Standar Eropa)

1 - 15 dan 17 - 30 adalah sinyal
telephon yang dikodekan/ data digital



- 1 TS = 8 bit
- Terdiri dari 32 TS = 30 kanal suara + 1 sinkronisasi + 1 signaling

  Sinkronisasi : TS 0

  Signaling : TS 16

  Voice : TS 1 – 15 + TS 17 – 31
- Dalam 1 detik tdp 8000 sample, sehingga :

  Bit rate = (8 x 8000) x 32 = 2048 kbps

Multiframe PCM-30



A = 0
U = 1 Tidak ada Alarm

A = 1
U = 0 urgent alarm
non urgent alarm

- 1 MF = 16 frame
- Signaling lengkap untuk 30 kanal voice (1 TS 16 untuk signaling 2 kanal voice)
- TS-16 untuk frame ke-0 digunakan untuk alignment / sinkronisasi multiframe

PCM-24 (T-1, Standar Amerika)



- **T1 (DS-0) System**
  - 24 voice channels are time-division multiplexed
  - Each voice signal is sampled at a rate of 8000 samples/sec. (sample duration = 125 µsec)
  - Each sample is quantized in amplitude into one of 256 levels (8 bits are used to represent each level)
  - T1 rate = (24*8 + 1)/125 µsec = 1.544 Mbps

PCM-24 (T-1, Standar Amerika)



- 1 TS = 8 bit
- Terdiri dari 24 TS = 24 kanal suara Dalam 1 detik tdp 8000 sample
- Sinkronisasi menggunakan 1 bit tambahan (=BF)
- Signaling diambil pada bit ke-8 tiap TS pada frame ke-6 dan kelipatannya
- Bit Rate = ((24 x 8) + 1) x 8000 = 193 x 8000 = 1544 kbps
- 1 MF = 12 frame

Perbandingan 3 standar (Amerika, Eropa, Jepang)

Level	Eropa	Amerika Utara	Jepang
	Bit Rate (Mbps)		
1	2.048	1.544	1544
1C	-	3.152	-
2	8.448	6.312	6.312
3	34.368	44.736	32.064
4	139.264	274.176	97.728
5	564.992		400.352

- 1.544 Mbps = T1 = PCM-24 (Amerika)
- 2.048 Mbps = E-1 = PCM-30 (Eropa)
- Standar Jepang kurang populer
- Indonesia menggunakan sistem Eropa
- Internasional menggunakan Standard **PCM-30**

Encoder (Konverter) Line coding

	Two wire BW kecil (misal kabel telepon)	Two wire BW sedang (misal kabel 2 Mbps)	Coaxial
Output Line coding	Rate kecil : bipolar , AMI , HDB-3 , B6ZS	Rate kecil / sedang : bipolar , AMI , HDB-3 , B6ZS	bilpolar , AMI , HDB-3 , B6ZS
	Rate sedang / besar : Sinyal multi level	Rate besar : sinyal multi level	

-output ADC

- sinyal TDM

-Sinyal data text

-Output scrambler

-Output FEC



Line coding


1 0 1 0 1 1 1 0 0
Unipolar NRZ
Polar NRZ
NRZ-Inverted (Differential Encoding)
Bipolar Encoding
Manchester Encoding
Differential Manchester Encoding

Line Coding:Bipolar-AMI vs HDB3 dan B8ZS

- Deretan panjang nol dikodekan sbg ketidakadaan sinyal yg panjang. Clock receiver dpt kehilangan sync.
- Deretan nol yg panjang diganti dg pelanggaran (violation) transisi sinyal yang
  - Menghasilkan transisi sinyal yg cukup utk clock resynchronization,
  - Mengkodekan jumlah nol muncul



End of Module 9