DRAFT — UNOFFICIAL — NOT FOR OPERATIONAL USE

LESSON PLANS

TM-20

USAREUR-AF

LESSON PLAN OUTLINES — TM-20 BUILDER

Maven Smart System (MSS) Training Program

HEADQUARTERS
UNITED STATES ARMY EUROPE AND AFRICA
(USAREUR-AF)
Wiesbaden, Germany

DRAFT — NOT FOR OFFICIAL USE. FOR TRAINING PLANNING PURPOSES ONLY.

12 MARCH 2026

DRAFT — UNOFFICIAL — NOT FOR OPERATIONAL USE

LESSON PLAN OUTLINES — TM-20 BUILDER

MAVEN SMART SYSTEM (MSS) TRAINING PROGRAM

USAREUR-AF Operational Data Team — C2DAO

NOTE

These are lesson plan outlines — abbreviated LP format for instructor preparation. Use the full LP template (`LP_TEMPLATE.md`) to expand any block into a complete lesson plan. For complete lesson plan examples see `TM10/TM10_LESSON_PLANS.md` .

Course: TM-20 Builder | **Duration:** 5 days (40 hours) | **Version:** 1.0 — March 2026

DAY 1 — PROJECT FUNDAMENTALS AND FILE INGESTION

BLOCK 1 — Project Creation

Hours: 1.5 | **Method:** Lab | **Time:** 0830–1000

Purpose: Establishes the C2DAO naming and structure standard before any data is touched. A project created incorrectly will fail data steward promotion review — trainees must internalize the standard before building anything else.

TLO: Given C2DAO naming conventions, the trainee will create a correctly named, marked, and structured Foundry project — to standard, independently.

Key Delivery Notes: - Walk through the naming convention standard from TM-20 Ch 2: `[UNIT]_[DESCRIPTION]_[ENV]` format. Write it on the board for the whole day. - Show a badly-named project (example) before showing a correctly-named one. Make the contrast memorable. - Folder structure: Datasets, Pipelines, Ontology, Applications. Create all four folders — even if they're empty. This prevents chaos later. - Classification marking: show where to set it on project creation. UNCLASSIFIED in training; trainees must know where to set it for production. - Demo, then students create their own. Confirm naming before moving on — fix non-compliant names now, not on Day 4.

Student Activity: Create a Foundry project following C2DAO naming conventions. Create all four required folders. Screenshot the folder structure for self-review.

Common Errors: - Using spaces or special characters in project name (Foundry accepts them but C2DAO convention does not) — catch this before trainee creates datasets inside it - Missing classification marking — evaluator will check; fix before moving on - Skipping folder structure ("I'll add them later") — ensure folders are created in this block

Assessment: Evaluated in Practical Exercise Task 1. Evaluator checks naming convention, classification marking, and folder structure.

BLOCK 2 — File Ingestion

Hours: 0.75 | **Method:** Lab | **Time:** 1015–1100

Purpose: Ingestion is the entry point for all data in Foundry. Trainees must be able to upload a file, inspect the inferred schema, and identify data quality issues before building any pipeline.

TLO: Given a CSV file, the trainee will ingest it into a Foundry project, confirm row count matches the source, and identify at least one type mismatch or null pattern in the schema.

Key Delivery Notes: - Upload a provided CSV file via drag-and-drop or file browser. Show both methods. - After upload, the schema preview appears — walk through it: column names, inferred types, sample values. - Foundry infers types — it may get them wrong. A date column stored as text, a numeric column with trailing spaces. Trainees need to see this, not just upload and move on. - Confirm row count: source file row count should match the ingested dataset row count minus the header. Students verify this.

Student Activity: Upload the provided CSV file. Verify row count. Identify at least one column where the inferred type appears incorrect.

Common Errors: - Not verifying row count after ingestion — make it a habit - Accepting inferred types without checking — particularly date columns stored as strings

Assessment: Evaluated in Practical Exercise Task 2. Row count verification is a tested step.

BLOCK 3 — Dataset Explorer: Column Profiling

Hours: 1.0 | **Method:** Lab | **Time:** 1100–1200

Purpose: QC habits built before the pipeline prevents errors that are much harder to diagnose after. This block teaches trainees to profile data before building — null detection, distribution, type confirmation.

TLO: Given an ingested Foundry dataset, the trainee will use the Dataset Explorer to profile column distributions, identify null rates, and document at least two data quality observations.

DRAFT

Key Delivery Notes: - Open the Dataset Explorer for the ingested dataset. Walk through: column list, null percentage bar, distinct values count, distribution histogram (numeric columns). - Key habit: check null rate for every column you plan to use in a pipeline. A null rate of 20% on `c_rating` means 20% of your downstream objects will have empty ratings — you need a plan for that before the pipeline runs. - Show the "preview" of top 10 rows alongside the column profile — the two views complement each other. - Have trainees document their findings before moving to Block 4. "I observed that column X has 15% nulls and column Y has an incorrect date format." Written, not just mental.

Student Activity: Profile all columns in the ingested dataset. Document: null rate for each, type anomalies, any unexpected distinct values.

Assessment: Supports pipeline quality in Practical Exercise Task 3. Evaluator may ask how the trainee verified data quality before building.

BLOCK 4 — Pipeline Builder Orientation

Hours: 2.0 | **Method:** Lab | **Time:** 1300–1500

Purpose: Trainees need a mental model of the Pipeline Builder canvas before they start adding steps. This block is orientation — not a complete pipeline build. The goal is "I know what the canvas is, where the step library is, and how input/output datasets work."

TLO: Given the Pipeline Builder canvas, the trainee will identify the step library, configure input and output dataset nodes, add a single step, and describe the data flow from input through step to output.

Key Delivery Notes: - Open Pipeline Builder from inside the Foundry project. Canvas orientation: input node (left), step nodes (center), output node (right). - Step library: show how to search for a step by type. Common steps used this week: Filter, Rename, Cast, Calculated Column, Join, Group By, Ontology Write. - Connect input dataset to a Filter step to output dataset — just to demonstrate the connection mechanic. Do not configure the filter yet — that is Day 2. - Run the pipeline with zero transformation (pass-through) and confirm output dataset populates. This validates the canvas is connected.

Student Activity: Build a pass-through pipeline (input → no-op filter → output). Run it. Verify output row count equals input row count. This is "pipeline canvas works" verification.

Common Errors: - Disconnected nodes (step not wired to both input and output) — pipeline won't run; check connections - Output dataset path not set — pipeline runs but output is lost; always configure the output path

Assessment: Foundation for all subsequent labs. Not directly evaluated but a prerequisite for every other pipeline task.

BLOCK 5 — C2DAO Naming Conventions Discussion

Hours: 0.5 | **Method:** Discussion | **Time:** 1500–1530

Purpose: Naming convention is the governance standard that makes data products maintainable. Trainees who deviate from it will fail data steward promotion review. This discussion anchors the standard as a professional expectation, not a bureaucratic requirement.

Key Delivery Notes: - Reference `NAMING_AND_GOVERNANCE_STANDARDS.md`. Walk through naming patterns for: datasets, pipelines, Object Types, Workshop applications. - The naming convention exists because every data product in MSS must be discoverable and interpretable by someone who didn't build it. - Have trainees look at their Block 1 project names and Block 2 datasets — do they follow the convention?

Student Activity: Review their own Block 1 project and Block 2 dataset names against the standard. Correct any deviations now.

BLOCK 6 — Individual Practice

Hours: 1.5 | **Method:** Lab | **Time:** 1530–1700

Purpose: Reinforce Blocks 1–4 with a second independent repetition. Trainees who struggle on the first pass have another chance to get it right before Day 2.

TLO: The trainee will independently create a second project, ingest a provided dataset, and confirm naming compliance — without instructor assistance.

Key Delivery Notes: - Different dataset than Block 2. Instructor circulates and observes; does not assist unless there is a system error. - Trainees who are confident may help each other on the naming convention question — but not on the system steps.

Assessment: Self-assessed. Instructor notes who needed assistance for awareness of Day 2 support needs.

DAY 2 — PIPELINE BUILDER: CLEAN AND TRANSFORM

BLOCK 7 — Pipeline: Filter, Rename, CAST

Hours: 2.0 | **Method:** Lab | **Time:** 0830–1030

DRAFT

Purpose: The three most-used cleaning steps. Every pipeline starts here. Filter removes unwanted rows; Rename makes column names human-readable; CAST corrects type errors caught in Day 1 profiling.

TLO: Given a raw dataset with rows to exclude and columns to rename and type-cast, the trainee will build a pipeline with Filter, Rename, and CAST steps that produces a correctly typed, correctly named output.

Key Delivery Notes: - Filter: condition syntax. Walk through: `column_name IS NOT NULL`, `c_rating IN ('C1', 'C2')`, `date_col >= DATE('2025-01-01')`. Add multiple conditions with AND/OR. - Rename: simple column renames. The output column name is what appears in all downstream steps and the Ontology. Get it right here. - CAST: explicitly type `string_date_col` as DATE. If Foundry inferred wrong type (Day 1 finding), fix it here. Show what happens when CAST fails (type mismatch error in pipeline logs). - Run after each step: don't add 5 steps and then run. Run incrementally — know which step introduced an error.

Student Activity: Build a 3-step pipeline (Filter → Rename → CAST) on the Day 1 dataset. Run after each step. Verify final output has correct types and only filtered rows.

Common Errors: - Filter condition on a NULL-containing column using `!=` instead of `IS NOT NULL` — `NULL != 'C1'` does NOT return nulls; must explicitly filter nulls separately - CAST on a column that contains non-castable values — pipeline error; review source data for anomalies before casting

Assessment: Foundation for Practical Exercise Task 3. Evaluator verifies pipeline runs to completion without error.

BLOCK 8 — Pipeline: Calculated Columns

Hours: 1.25 | **Method:** Lab | **Time:** 1045–1200

Purpose: Calculated columns derive new data from existing columns — string manipulation, conditional logic, null handling. This is where raw data becomes operationally meaningful.

TLO: Given a dataset, the trainee will add calculated columns using string functions, conditional IF/CASE logic, and COALESCE for null handling — producing a typed output column.

Key Delivery Notes: - String functions: `UPPER(col)`, `CONCAT(col1, ' - ', col2)`, `SUBSTRING(col, start, length)`. Use real column names from the training data. - Conditional logic: `IF(c_rating IN ('C3', 'C4'), 'NOT_READY', 'READY')` — creates a boolean readiness flag. CASE WHEN for multi-condition logic. - COALESCE: `COALESCE(last_maintenance_date, DATE('2000-01-01'))` — replace nulls with a default. Essential for columns used in downstream joins. - Always name the calculated column with a descriptive name following the naming convention. `calc_1` is not acceptable.

Student Activity: Add three calculated columns: (1) a string concatenation field, (2) a CASE WHEN readiness flag, (3) a COALESCE null-fill on a date column.

Common Errors: - Referencing a renamed column by its original name in a calculated column — use the post-Rename column name - Forgetting to name the output column — unnamed calculated columns use a default that violates naming conventions

Assessment: Evaluated in Practical Exercise Task 3 (computed columns in the clean pipeline).

BLOCK 9 — Pipeline: Date and Time Functions

Hours: 2.0 | **Method:** Lab | **Time:** 1300–1500

Purpose: Date arithmetic is the most failure-prone area in Pipeline Builder. DATEDIFF behavior is different from Excel. Incorrect date types cause downstream failures. Mastery of this block prevents the most common practical exercise failure mode.

TLO: Given a dataset with date columns, the trainee will build pipeline steps using DATEDIFF, DATE_TRUNC, and CURRENT_DATE — testing results against known-answer records to validate output.

Key Delivery Notes: - Date column types must be DATE or TIMESTAMP — not STRING. If the source has string dates, CAST before using date functions (reinforce Day 2 Block 7). - DATEDIFF: `DATEDIFF('day', start_date, end_date)` — result is number of days between dates. Note: argument order matters and varies by Foundry version. Test with a known record before relying on it. - DATE_TRUNC: `DATE_TRUNC('month', date_col)` — useful for monthly aggregations. - CURRENT_DATE: `DATEDIFF('day', last_maintenance_date, CURRENT_DATE())` — days since last maintenance. This is a live calculation — it changes every day the pipeline runs. - Known-answer test: provide trainees a record with known dates. They calculate DATEDIFF manually, then verify the pipeline output matches.

Student Activity: Build a calculated column for "days_since_last_update" using DATEDIFF. Test against 3 provided known-answer records. All 3 must match.

Common Errors: - Argument order in DATEDIFF reversed — produces negative numbers; easy to catch with known-answer test - Date column is STRING type — DATEDIFF returns an error or null; fix CAST before this step

Assessment: Evaluated in Practical Exercise Task 3. Any pipeline using dates that produces incorrect output will fail.

BLOCK 10 — End-to-End Pipeline Practice

Hours: 1.75 | **Method:** Lab | **Time:** 1515–1700

Purpose: Trainees apply Blocks 7–9 in a complete pipeline, from raw input to typed, filtered, named output. This practice run identifies gaps before Day 3's more complex pipeline work.

TLO: The trainee will independently build a complete clean-and-transform pipeline from raw input to a typed, named, filtered output dataset — without instructor assistance.

Key Delivery Notes: - New dataset provided (not the one from earlier in the day). Trainee builds the full pipeline end to end. - Instructor circulates and observes. Notes who is still struggling with CAST or calculated columns for Day 3 awareness. - Emphasize: run after each step. Check row counts. Verify output schema matches expectation.

Assessment: Not directly evaluated in Practical Exercise (the PE uses a different dataset), but directly builds the skill.

DAY 3 — PIPELINE BUILDER: JOINS; ONTOLOGY MANAGER

BLOCK 11 — Pipeline: Join Step

Hours: 2.0 | **Method:** Lab | **Time:** 0830–1030

Purpose: Joins are the most common multi-source operation and the most common source of silent data errors. Trainees must understand join types and fan-out behavior before using joins in production.

TLO: Given two datasets with a shared key, the trainee will build an inner join and a left join pipeline, identify the row count difference, handle fan-out from a many-to-one join, and produce a correct output.

Key Delivery Notes: - Join types: inner join (only rows where key exists in both), left join (all rows from left dataset; nulls for unmatched right-side columns). Show row counts for both on the training datasets. - Key selection: both datasets must have the join key. If the key column names differ, rename one before joining. - Fan-out: if the right-side dataset has multiple rows per key (e.g., unit_id appears 3 times in the lookup table), the join multiplies rows on the left. This is usually a data error. Always check row counts after a join. - Column selection post-join: only keep columns you need. A join of two 20-column datasets produces a 40-column output — trim it.

Student Activity: Join equipment dataset to a provided unit lookup table on `unit_id`. Check row count before and after. Identify whether fan-out occurred and correct it if so.

Common Errors: - Fan-out ignored — "it worked" when the row count tripled (silent fan-out) - Both datasets must be accessible from the same Foundry project — cross-project reference required if datasets live in different projects

Assessment: Evaluated in Practical Exercise Task 3. The join step is explicitly tested.

BLOCK 12 — Pipeline: Group-By, Union, Output Mode

Hours: 1.25 | **Method:** Lab | **Time:** 1045–1200

Purpose: Aggregations and union operations complete the pipeline toolkit. Output mode configuration (Overwrite vs. Append) is a governance decision that must be made intentionally.

Key Delivery Notes: - Group-By: `GROUP BY unit_id`, aggregate `COUNT(equipment_id) AS unit_equipment_count`, `SUM(c_rating_numeric) AS total_c_score`. Only columns in GROUP BY or aggregation functions appear in output. - Union: combines two datasets with compatible schema. Handle schema mismatches with a renamed/CAST step before the union. - Output mode: **Overwrite** — pipeline replaces the output dataset on every run (point-in-time snapshot). **Append** — pipeline adds rows on every run (historical record). Most pipelines use Overwrite. The GFEBS obligation history pipeline uses Append. Choosing wrong mode is a data governance error.

Assessment: Output mode is tested in Practical Exercise Task 3 (snapshot pipeline in Append mode, run twice, verify two records).

BLOCK 13 — Ontology Manager: Create Object Type

Hours: 2.0 | **Method:** Lab | **Time:** 1300–1500

Purpose: The Ontology is the semantic layer — the pivot point between raw data and MSS applications. Object Types must be correctly designed before being built. Property type decisions are permanent.

TLO: Given a described data entity, the trainee will create a Foundry Object Type with correctly typed properties, a Primary Key, and a display name expression — to standard.

Key Delivery Notes: - CRITICAL: Property types are immutable after objects are created. If you define `c_rating` as STRING when it should be an ENUM or INTEGER, you must delete the Object Type and all data, then recreate. Read the property type table in TM-20 Ch 4 before this block. - Property types: STRING, INTEGER, LONG, DOUBLE, BOOLEAN, DATE, TIMESTAMP. Pick the most restrictive correct type — don't default everything to STRING. - Primary Key: the property that uniquely identifies each Object. Must be unique per Object. Cannot be null. Choose carefully. - Display name expression: what humans see when the Object appears in Quiver or Workshop. Usually a concatenation: `[unit] - [equipment_id]`.

Student Activity: Create an `Equipment` Object Type with at least 5 correctly typed properties, a Primary Key, and a display name expression. Document property types in writing before creating them in the tool.

Common Errors: - Not documenting property types before building — leads to type correction rework - Using STRING for everything to "play it safe" — correct for small projects, but creates query performance issues at scale and violates the TM-20 standard

Assessment: Evaluated in Practical Exercise Task 4.

BLOCK 14 — Ontology Manager: Create Link Type

Hours: 0.75 | **Method:** Lab | **Time:** 1515–1600

Purpose: Link Types model relationships between Object Types — Equipment belongs to Unit. The Link enables navigation between Objects in Quiver, Workshop, and OSDK.

TLO: Given two existing Object Types, the trainee will create a Link Type with correct cardinality and directionality — to standard.

Key Delivery Notes: - Link Type connects two Object Types. Direction matters: `Equipment` LINKS TO `Unit` (Equipment points to Unit; a Unit can be linked from many Equipment Objects). - Cardinality: MANY_TO_ONE (many Equipment to one Unit), ONE_TO_ONE, ONE_TO_MANY, MANY_TO_MANY. Determine from the data model, not from the tool. - Cardinality is not automatically enforced by Foundry in all cases — you are declaring the intended relationship.

Student Activity: Create a Link Type from `Equipment` to `Unit`. Verify the Link appears in the Object Type view.

Assessment: Evaluated in Practical Exercise Task 5.

BLOCK 15 — Pipeline: Ontology Write Step

Hours: 1.0 | **Method:** Lab | **Time:** 1600–1700

Purpose: The Ontology write step is the bridge between pipeline output and the Object layer. Until this step, the pipeline produces datasets — after this step, the pipeline creates or updates Objects.

TLO: Given an existing Object Type and a pipeline output dataset, the trainee will configure an Ontology write step with correct property mapping, run the pipeline, and verify Objects are created.

Key Delivery Notes: - Ontology write step configuration: target Object Type, property mapping (pipeline column → Object property), Primary Key mapping. - Property type must match: if the Object property is DATE and the pipeline column is STRING, the write will fail or produce null values. Confirm types align before running. - Run the pipeline. Navigate to the Object Type in Quiver. Verify object count matches expected row count. - The object count in Quiver is the ground truth — not the pipeline "ran without error." Verify objects.

Student Activity: Configure the Ontology write step mapping pipeline output columns to `Equipment` Object Type properties. Run pipeline. Confirm object count in Quiver matches source row count.

Common Errors: - Primary Key column not mapped — all objects will overwrite each other; you end up with 1 object regardless of row count - Type mismatch between pipeline output and Object property — silent nulls; check by opening an Object and confirming properties populated

Assessment: Evaluated in Practical Exercise Task 6.

DAY 4 — ACTIONS AND WORKSHOP APPLICATIONS

BLOCK 16 — Actions: Create Basic Action

Hours: 1.5 | **Method:** Lab | **Time:** 0830–1000

Purpose: Actions are the write-back mechanism — how authorized users update Object properties from Workshop applications. Every TM-20 data product needs at least one Action.

TLO: Given an Object Type, the trainee will create an Action with a named parameter, a write rule targeting an Object property, and an access restriction — test the Action from Ontology Manager.

Key Delivery Notes: - Action configuration: Name, Description, Parameters (name + type), Write Rules (parameter → Object property mapping), Access Control (who can execute it). - Access control: restrict to Editor role unless there is a specific reason for Viewer access. Most status update Actions should require Editor or a named role group. - Test from Ontology Manager (not Workshop yet — Workshop is Day 4 Block 17). Open an Object, find the Action, execute it with a test parameter, verify the property updated. - Common mistake: no confirmation prompt configured — users can accidentally fire the Action without a review step.

Student Activity: Create an `UpdateCRating` Action with a parameter `new_c_rating` (STRING), a write rule to `Equipment.c_rating`, and Editor-only access restriction. Test from Ontology Manager.

Assessment: Evaluated in Practical Exercise Task 7. Evaluated items: parameter exists, write rule works, access restriction configured correctly (Viewer cannot execute).

BLOCK 17 — Workshop Orientation: Canvas and Table Widget

Hours: 1.75 | **Method:** Lab | **Time:** 1015–1200

Purpose: Workshop is the application layer — the interface users see and interact with. This block establishes the canvas mechanics and the foundational table widget.

TLO: Given a Foundry project with an Object Type, the trainee will create a Workshop application, add a table widget bound to the Object Type, and configure it to display at least 4 properties.

Key Delivery Notes: - Create application: New → Workshop Application. Name it following C2DAO naming convention. - Canvas: drag-and-drop widget placement. Resize widgets. The canvas is freeform. - Table widget: add from widget library. Bind to Object Type (this connects it to live Ontology data). Select properties to display as columns. - Live data: as soon as the table is bound to the Object Type, it shows live Objects. Any Action executed against these Objects will immediately update the table.

Student Activity: Create a Workshop application named per C2DAO convention. Add a table widget bound to the `Equipment` Object Type. Display `equipment_id`, `unit`, `c_rating`, `last_updated`.

Assessment: Foundation for Practical Exercise Task 8.

BLOCK 18 — Workshop: Filter, Metric, and Bar Chart Widgets

Hours: 2.0 | **Method:** Lab | **Time:** 1300–1500

Purpose: A table alone is not a dashboard. Filter, metric, and chart widgets make the application operationally useful — allowing users to slice data, see roll-ups, and visualize trends without exporting.

TLO: The trainee will add a filter widget, metric widget, and bar chart widget to a Workshop application — each correctly bound to the Object Type data source.

Key Delivery Notes: - Filter widget: add a filter on `unit` (dropdown filter based on Object Type property values). The filter must be connected to the table widget — verify that selecting a filter option narrows the table. - Metric widget: count of Equipment Objects where `c_rating` = "C1". Bound to Object Type with a filter condition. The metric is live. - Bar chart widget: X axis = `unit`, Y axis = count of Objects. Add to application alongside the table. - Layout discipline: arrange widgets logically — filter at top, metrics below, table below that. This is a professional product, not a test canvas.

Student Activity: Add all three widget types. Verify filter narrows the table. Verify metric updates when Objects change. Verify bar chart displays correct unit distribution.

Common Errors: - Filter widget not connected to table — visual filter appears but table doesn't respond; check widget connections - Metric widget counting all Objects instead of filtered Objects — connection missing

Assessment: Evaluated in Practical Exercise Task 8.

BLOCK 19 — Workshop: Connecting an Action Button

Hours: 1.25 | **Method:** Lab | **Time:** 1515–1630

Purpose: Action buttons close the loop — users can view data and update it without leaving the application. This block is the final component of a functional TM-20 data product.

TLO: The trainee will add an Action button to a Workshop application, trigger the Action from a selected table row, verify execution confirmation, and confirm the table refreshes to show the updated value.

Key Delivery Notes: - Add a Button widget to the canvas. Configure: Action = `UpdateCRating`, Object source = selected row in the Equipment table. - The button should only activate when a row is selected. If no row is selected, the button should be grayed out or show a tooltip. - After execution: the confirmation toast appears (if configured); the table should auto-refresh to show the updated `c_rating`. If the table

does not refresh, check the application refresh settings. - Test with a Viewer-role account: the button should be disabled or absent for a Viewer. If Viewer can execute the Action, the access restriction is misconfigured.

Student Activity: Add the Action button. Select a row, click the button, confirm execution, verify the `c_rating` updated in the table. Then switch to a test Viewer account and confirm the button is unavailable.

Assessment: Evaluated in Practical Exercise Task 9. Hard No-Go: Viewer account can execute the Action.

BLOCK 20 — Access Control: Viewer vs. Editor

Hours: 0.5 | **Method:** Discussion | **Time:** 1630–1700

Purpose: Access control is a governance requirement, not an option. Trainees must understand what each role can and cannot do before they publish anything.

Key Delivery Notes: - Viewer: can view data, navigate applications, export if export is not restricted. Cannot edit, create, or execute Editor-only Actions. - Editor: can modify data products, execute all Actions. Should be limited to personnel who need write capability. - Granting access: Project settings → Access → add user/group with role. - The principle: least privilege. Grant Viewer unless there is a specific requirement for Editor.

Assessment: Evaluated in Practical Exercise Task 10. Evaluator tests Viewer-role account.

DAY 5 — PUBLISHING, GOVERNANCE, AND PRACTICAL EXERCISE

BLOCK 21 — Workshop Publishing and Viewer Access

Hours: 1.0 | **Method:** Lab | **Time:** 0800–0900

Purpose: An application that only you can see is not a data product. Publishing and access control are the final steps before a Workshop application becomes operational.

TLO: The trainee will configure Workshop application visibility, grant a Viewer-role test account access, and confirm the test account can view the application but cannot modify data.

Key Delivery Notes: - Application visibility: set from the Workshop application settings → Visibility. Options typically: Project members, Named users/groups, or Published (wider access). - Grant the test Viewer account access. Confirm access via logging in as the test account. - Verification: test account

should see the application, see the data, but not be able to execute the Action button. This is the standard the evaluator will check.

Assessment: Evaluated in Practical Exercise Task 10.

BLOCK 22 — Branching

Hours: 1.0 | **Method:** Lab | **Time:** 0900–1000

Purpose: All production changes must be made on a branch, not on main. This is non-negotiable in C2DAO governance. A change made directly to main is already in production.

TLO: The trainee will create a Foundry branch, make a change on the branch, verify the change exists on the branch but not on main.

Key Delivery Notes: - Branch from within the Foundry project: Branch Manager → New Branch. Name the branch following C2DAO naming: `[unit]_[change-description]_[date]`. - Make a change on the branch: a visible change (application header text change, pipeline step description update). This change should be visible on the branch but not on main. - Verify: switch between branch and main — the change should appear and disappear depending on which branch is active. - The most common error: making the change BEFORE creating the branch. Once a change is on main, you cannot retroactively branch around it.

Assessment: Evaluated in Practical Exercise Task 11. Branch must exist with the change visible.

BLOCK 23 — Promotion Workflow

Hours: 0.75 | **Method:** Lab | **Time:** 1015–1100

Purpose: Branch changes are promoted to production through the C2DAO data steward review process. Submitting a complete, well-described promotion request is a professional skill.

TLO: The trainee will submit a promotion request from a branch with a complete change description, simulate a steward rejection, and respond to the rejection comment.

Key Delivery Notes: - Promotion request: Branch Manager → Submit for Promotion. The description field is required. The evaluator (as data steward) will reject any submission with an empty or generic description. - What a good description includes: what changed, why, and what the downstream impact is. - BAD: "Updated application" - GOOD: "Added unit filter to Workshop application per S3 request (12MAR26); filters Equipment table by unit; no impact to Ontology or pipeline" - Rejection workflow: the evaluator responds with a comment requiring clarification. Trainees must respond to the comment and resubmit or revise.

Assessment: Evaluated in Practical Exercise Task 11.

BLOCK 24 — Full-Stack Review

Hours: 1.0 | **Method:** Review | **Time:** 1100–1200

Purpose: Before the evaluation, trainees trace their own data product end-to-end to identify gaps. This is self-assessment, not more instruction.

Key Delivery Notes: - Have trainees walk through their own product: raw file → ingestion → pipeline steps (filter, clean, join, Ontology write) → Object Type → Link Type → Action → Workshop application → access control → branch. - Checklist: does everything connect? Does the pipeline produce the correct output? Does the Quiver Object count match source row count? Does the Viewer test account have correct access? - This is not instructor-led — trainees do this independently. Instructor circulates and answers system questions (not task completion guidance).

BLOCK 25 — Practical Exercise (Evaluated)

Hours: 4.0 | **Method:** Evaluation | **Time:** 1300–1700

Scenario: S4 officer needs an equipment readiness tracker. Two provided files: equipment spreadsheet and unit location CSV. Build the full stack from scratch.

Tasks evaluated: 1. Create Foundry project with correct naming, markings, folder structure 2. Ingest both files; confirm row counts 3. Build pipeline: validate, clean, cast, join on `unit_id`; output clean equipment-with-location dataset 4. Create `Equipment` Object Type with 5 correctly typed properties 5. Create `Unit` Object Type and Link Type from Equipment to Unit 6. Configure pipeline Ontology write step populating Equipment Objects 7. Configure `UpdateCRating` Action with parameter, write rule, Editor-only access 8. Build Workshop application: table, unit/c_rating filter, C1 count metric, equipment-by-C-rating bar chart 9. Connect Action button; execute; verify table refreshes 10. Grant Viewer test account access; confirm Viewer cannot trigger Action 11. Create branch; change application header; submit promotion with complete description

Go standard: All 11 tasks without instructor assistance. Hard No-Go: Viewer account can trigger Action.

USAREUR-AF Operational Data Team — UNCLASSIFIED TM-20 Lesson Plan Outlines | Version 1.0 | March 2026

DRAFT