DRAFT — UNOFFICIAL — NOT FOR OPERATIONAL USE

QUICK REFERENCE

ODT-REF

USAREUR-AF

DoctrineElement → Palantir Foundry Mapping

Quick Reference

HEADQUARTERS
UNITED STATES ARMY EUROPE AND AFRICA
(USAREUR-AF)
Wiesbaden, Germany

DRAFT — NOT FOR OFFICIAL USE. FOR TRAINING PLANNING PURPOSES ONLY.

19 MARCH 2026

DRAFT — UNOFFICIAL — NOT FOR OPERATIONAL USE

DOCTRINEELEMENT → PALANTIR FOUNDRY MAPPING

Authoritative mapping between the GDAP `DoctrineElement` Python schema and the Palantir Foundry Object Type representation, including TypeScript property names, OSDK types, and bi-temporal semantics.

Last updated: 2026-03-12

1. OBJECT TYPE IDENTITY

Attribute	Value
Foundry API name	`DoctrineElement`
Foundry namespace	`gdap`
OSDK interface	`Osdk.Instance<DoctrineElement>`
Primary key property	`id` (string)
Primary key source	`DoctrineElement.unique_id`

2. PRIMARY KEY PATTERN

The `unique_id` field encodes five hierarchical coordinates:

```
{nation}:{document}:{section}:{paragraph}:{version}
```

Example: `US:ADP 3-0:Chapter 2:2-14:v2.0`

This value maps directly to the OSDK `id` property:

```
const element = await client.objects.DoctrineElement.get("US:ADP 3-0:Chapter 2:2-14:v2.0");
```

Rule: The separator is `:`. Each segment must be non-empty. The validator enforces at least 5 segments (split on `:`).

3. PROPERTY MAPPING TABLE

Core Identity

Python Field	Foundry Property	TypeScript Type	Notes
`unique_id`	`id`	`string`	Primary key; 5-segment colon-separated path
`source_nation`	`sourceNation`	`string`	`SourceNation` enum value (e.g., `"US"`, `"NATO"`)
`source_document`	`sourceDocument`	`string`	Document identifier (e.g., `"ADP 3-0"`)
`source_section`	`sourceSection`	`string`	Section reference string
`version`	`version`	`string`	Document version string

Content

Python Field	Foundry Property	TypeScript Type	Notes
`content_type`	`contentType`	`string`	`ContentType` enum value (e.g., `"definition"`)
`content_text`	`contentText`	`string`	Minimum 1 character; the doctrine text atom
`related_concepts`	`relatedConcepts`	`string[]`	Array of concept strings
`related_tasks`	`relatedTasks`	`string[]`	Array of task strings
`data_implications`	`dataImplications`	`string[]`	Array of data implication strings
`warfighting_function`	`warfightingFunction`	`string | undefined`	`WarfightingFunction` enum value

DRAFT

Structural Provenance

Python Field	Foundry Property	TypeScript Type	Notes
`parent_document_id`	`parentDocumentId`	`string`	References `DoctrineDocument.document_id`
`parent_section_id`	`parentSectionId`	`string | undefined`	References `DoctrineSection.section_id`

Extraction Metadata

Python Field	Foundry Property	TypeScript Type	Notes
`confidence_score`	`confidenceScore`	`double`	Range [0.0, 1.0]
`extraction_method`	`extractionMethod`	`string`	`ExtractionMethod` enum (e.g., `"llm_assisted"`)

DRAFT

DVEE Extensions

Python Field	Foundry Property	TypeScript Type	Notes
`authority_level`	`authorityLevel`	`string | undefined`	Command authority tier
`escalation_required`	`escalationRequired`	`boolean | undefined`	Whether escalation is mandated
`escalation_tier`	`escalationTier`	`string | undefined`	Tier label for escalation
`time_sensitivity`	`timeSensitivity`	`string | undefined`	Decision latency category
`risk_acceptance_level`	`riskAcceptanceLevel`	`string | undefined`	Risk tolerance label
`legal_trigger`	`legalTrigger`	`boolean | undefined`	Whether element triggers legal review
`cross_domain_dependency`	`crossDomainDependency`	`string | undefined`	Cross-domain dependency identifier
`decision_latency_estimate`	`decisionLatencyEstimate`	`string | undefined`	Human-readable latency estimate

4. BI-TEMPORAL FIELDS

GDAP uses a bi-temporal model with two independent time axes:

Transaction Time (when the record was created)

Python Field	Foundry Property	TypeScript Type	Notes
`extracted_at`	`extractedAtTimestamp`	`timestamp`	ISO 8601 UTC; auto-populated at extraction time

Valid Time (when the doctrine is in effect)

Python Field	Foundry Property	TypeScript Type	Notes
`effective_date`	`effectiveDate`	`date`	ISO 8601 date; from the source document
`valid_from`	`validFrom`	`date | undefined`	Start of doctrinal validity window
`valid_to`	`validTo`	`date | undefined`	End of doctrinal validity window (`null` = still valid)
`superseded_at`	`supersededAt`	`timestamp | undefined`	When this element was replaced by a newer version

Bi-temporal semantics:

- A record is **currently valid** when `valid_from <= today <= valid_to` (or `valid_to` is null) and `superseded_at` is null.
- A record is **historically accurate** as of transaction time `T` when `extracted_at <= T`.
- To reconstruct doctrine as-of a past date `D`, filter: `effective_date <= D` and `superseded_at > D` (or null).

5. NAMING CONVENTION

All Python `snake_case` field names are converted to Foundry `camelCase` property API names:

```
snake_case        → camelCase
effective_date    → effectiveDate
extracted_at      → extractedAtTimestamp  (suffix added to clarify it is a timestamp)
```

Object type API names use `PascalCase`:

```
DoctrineElement  →  DoctrineElement
DoctrineDocument →  DoctrineDocument
DoctrineSection  →  DoctrineSection
```

6. FOUNDRY TYPESCRIPT INTERFACE

```
import { defineObjectType } from "@osdk/maker";

export const DoctrineElement = defineObjectType({
  apiName: "DoctrineElement",
  displayName: "Doctrine Element",
  description: "Atomic unit of doctrine extracted from a publication.",
  primaryKey: "id",
  properties: {
    id: { type: "string", displayName: "Unique ID" },
    sourceNation: { type: "string", displayName: "Source Nation" },
    sourceDocument: { type: "string", displayName: "Source Document" },
    sourceSection: { type: "string", displayName: "Source Section" },
    version: { type: "string", displayName: "Version" },
    contentType: { type: "string", displayName: "Content Type" },
    contentText: { type: "string", displayName: "Content Text" },
    relatedConcepts: { type: "string", array: true, displayName: "Related Concepts" },
    relatedTasks: { type: "string", array: true, displayName: "Related Tasks" },
    dataImplications: { type: "string", array: true, displayName: "Data Implications"
},
    warfightingFunction: { type: "string", displayName: "Warfighting Function" },
    parentDocumentId: { type: "string", displayName: "Parent Document ID" },
    parentSectionId: { type: "string", displayName: "Parent Section ID" },
    confidenceScore: { type: "double", displayName: "Confidence Score" },
    extractionMethod: { type: "string", displayName: "Extraction Method" },
    effectiveDate: { type: "date", displayName: "Effective Date" },
    extractedAtTimestamp: { type: "timestamp", displayName: "Extracted At" },
    validFrom: { type: "date", displayName: "Valid From" },
    validTo: { type: "date", displayName: "Valid To" },
    supersededAt: { type: "timestamp", displayName: "Superseded At" },
    authorityLevel: { type: "string", displayName: "Authority Level" },
    escalationRequired: { type: "boolean", displayName: "Escalation Required" },
    escalationTier: { type: "string", displayName: "Escalation Tier" },
    timeSensitivity: { type: "string", displayName: "Time Sensitivity" },
    riskAcceptanceLevel: { type: "string", displayName: "Risk Acceptance Level" },
    legalTrigger: { type: "boolean", displayName: "Legal Trigger" },
    crossDomainDependency: { type: "string", displayName: "Cross Domain Dependency" },
    decisionLatencyEstimate: { type: "string", displayName: "Decision Latency
Estimate" },
  },
});
```

7. OSDK QUERY PATTERNS

Get a single element by ID

```
const elem = await client.objects.DoctrineElement.get(
  "US:ADP 3-0:Chapter 2:2-14:v2.0"
);
```

Query by nation and document

```
const usElements = await client.objects.DoctrineElement
  .where({ sourceNation: { eq: "US" }, sourceDocument: { eq: "ADP 3-0" } })
  .fetchPage({ pageSize: 100 });
```

Query currently valid elements (bi-temporal)

```
const today = new Date().toISOString().slice(0, 10);

const validNow = await client.objects.DoctrineElement
  .where({
    effectiveDate: { lte: today },
    supersededAt: { isNull: true },
  })
  .fetchPage({ pageSize: 200 });
```

Query by warfighting function

```
const firesElements = await client.objects.DoctrineElement
  .where({ warfightingFunction: { eq: "fires" } })
  .fetchPage({ pageSize: 50 });
```

DRAFT

8. LINK TYPES

Link Name	Source	Target	Cardinality	Notes
containedBy	DoctrineElement	DoctrineDocument	many-to-one	Via parentDocumentId
inSection	DoctrineElement	DoctrineSection	many-to-one	Via parentSectionId
alignedTo	DoctrineElement	DoctrineElement	many-to-many	Via AlignmentPair join

9. ENUM REFERENCE

SourceNation

Python Value	Foundry String
SourceNation.US	"US"
SourceNation.GB	"GB"
SourceNation.NATO	"NATO"
SourceNation.CA	"CA"
SourceNation.AU	"AU"
SourceNation.DE	"DE"
SourceNation.FR	"FR"
SourceNation.NL	"NL"

DRAFT

ContentType

Python Value	Foundry String
`ContentType.definition`	`"definition"`
`ContentType.task`	`"task"`
`ContentType.authority`	`"authority"`
`ContentType.process`	`"process"`
`ContentType.information_requirement`	`"information_requirement"`
`ContentType.concept`	`"concept"`
`ContentType.constraint`	`"constraint"`

WarfightingFunction

Python Value	Foundry String
`WarfightingFunction.movement_maneuver`	`"movement_maneuver"`
`WarfightingFunction.fires`	`"fires"`
`WarfightingFunction.intelligence`	`"intelligence"`
`WarfightingFunction.sustainment`	`"sustainment"`
`WarfightingFunction.protection`	`"protection"`
`WarfightingFunction.command_control`	`"command_control"`
`WarfightingFunction.information`	`"information"`

DRAFT