Liste des produits de peinture

MARQUE	Nom de rpoduit	Réf FDS
PPG	SIGMAFAST 278 BASE RAL 7035	fds sigmafast 278
PPG	SIGMAZINC 102 HS BASE GREY	fds sigmazinc 102 hs
PPG	SIGMADUR 550 BAS WHITE	FDS sigmadur 550

SAFETY DATA SHEET

Date of issue/Date of revision : 25 August 2025 **Version** : 1.05

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : SIGMADUR 550 BAS WHITE

Product code : 40550-C7000

Product type : Liquid.

Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications, Used by spraying.

Use of the substance/ mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

PPG France Business Support SAS, 3, ZAE "Les Dix Muids", B.P. 89, 59583 Marly Cedex, France, 33 (0)3 27 19 35 00

- Technical contact : Product Compliance EMEA
- Tel : +33 (0)3 27 19 35 00

e-mail address of person responsible for this SDS : Product.Stewardship.EMEA@ppg.com

National contact

PPG Architectural Coatings UK Ltd, Huddersfield Road, Birstall, West Yorkshire WF17 9XA, Tel: +44 (0) 1924 354000

1.4 Emergency telephone number

Supplier

+33 (0)3 27 19 35 00 (0800-1700)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Flam. Liq. 3, H226
Skin Sens. 1, H317
Carc. 1B, H350
STOT SE 3, H335
STOT SE 3, H336
Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :

Signal word : Danger

SECTION 2: Hazards identification

Hazard statements : Flammable liquid and vapour.
May cause an allergic skin reaction.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause cancer.
Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment.

Response : IF exposed or concerned: Get medical advice or attention.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.
P202, P280, P210, P273, P308 + P313, P501

Supplemental label elements : Repeated exposure may cause skin dryness or cracking.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Restricted to professional users.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate, ethenylbenzene, 1,2-propanediol mono(2-methyl-2-propenoate) and 2-propenoic acid	CAS: 37237-99-3	≥25 - ≤50	Skin Sens. 1, H317	[1]
Hydrocarbons, C9, aromatics > 0.1% cumene	REACH #: 01-2119455851-35 EC: 918-668-5 CAS: 128601-23-0	≥10 - ≤21	Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1] [2]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7	≥5.0 - <10	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332	[1] [2]

SECTION 3: Composition/information on ingredients

	CAS: 1330-20-7		Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	
n-butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥5.0 - ≤10	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	[1] [2]
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	REACH #: 01-2119962189-26 CAS: 911674-82-3 Index: 616-198-00-2	<1.0	Skin Sens. 1, H317 Aquatic Chronic 4, H413	[1]
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	REACH #: 01-2119491304-40 EC: 915-687-0 CAS: 1065336-91-5	≤0.37	Skin Sens. 1A, H317 Repr. 2, H361f Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
propylidynetrimethanol	REACH #: 01-2119486799-10 EC: 201-074-9 CAS: 77-99-6	≤0.30	Repr. 2, H361fd	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Xylene: Several REACH registrations cover the REACH registered substance with xylene isomers, ethylbenzene (and toluene). The other REACH Registrations include: 01-2119555267-33 reaction mass of ethylbenzene and m-xylene and p-xylene, 01-2119486136-34 Aromatic hydrocarbons, C8, 01-2119539452-40 reaction mass of ethylbenzene and xylene.

Type

[1] Substance classified with a health or environmental hazard
[2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

SECTION 4: First aid measures

Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.

Ingestion : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO_2, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
sulfur oxides
metal oxide/oxides

SECTION 5: Firefighting measures

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

SECTION 7: Handling and storage

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Occupational exposure limits

Product/ingredient name	Exposure limit values
Hydrocarbons, C9, aromatics > 0.1% cumene	**EU OEL (Europe)** TWA: 19 ppm. TWA: 100 mg/m³.
xylene	**EH40/2005 WELs (United Kingdom (UK), 1/2020) [xylene, o-,m-,p- or mixed isomers]** Absorbed through skin. STEL 15 minutes: 441 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m³. STEL 15 minutes: 100 ppm.
n-butyl acetate	**EH40/2005 WELs (United Kingdom (UK), 1/2020)** STEL 15 minutes: 966 mg/m³. STEL 15 minutes: 200 ppm. TWA 8 hours: 724 mg/m³. TWA 8 hours: 150 ppm.
ethylbenzene	**EH40/2005 WELs (United Kingdom (UK), 1/2020)** Absorbed through skin. STEL 15 minutes: 552 mg/m³.

SECTION 8: Exposure controls/personal protection

	STEL 15 minutes: 125 ppm. TWA 8 hours: 100 ppm. TWA 8 hours: 441 mg/m³.

Biological exposure indices

Product/ingredient name	Exposure indices
xylene	**EH40/2005 BMGVs (United Kingdom (UK), 1/2020) [Xylene, o-, m-, p- or mixed isomers]** BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hydrocarbons, C9, aromatics > 0.1% cumene	DNEL	Long term Inhalation	150 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	25 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	32 mg/m³	General population	Systemic
	DNEL	Long term Dermal	11 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	11 mg/kg bw/day	General population	Systemic
xylene	DNEL	Long term Oral	5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	65.3 mg/m³	General population	Local
	DNEL	Long term Inhalation	65.3 mg/m³	General population	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m³	Workers	Local
	DNEL	Long term Inhalation	221 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	260 mg/m³	General population	Local
	DNEL	Short term Inhalation	260 mg/m³	General population	Systemic
	DNEL	Short term Inhalation	442 mg/m³	Workers	Local
	DNEL	Short term Inhalation	442 mg/m³	Workers	Systemic
n-butyl acetate	DNEL	Long term Inhalation	300 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	11 mg/m³	Workers	Systemic
	DNEL	Long term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	3.4 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	7 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	11 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	12 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	35.7 mg/m³	General population	Local
	DNEL	Long term Inhalation	48 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	300 mg/m³	General population	Local
	DNEL	Short term Inhalation	300 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	300 mg/m³	Workers	Local
	DNEL	Short term Inhalation	600 mg/m³	Workers	Local
	DNEL	Short term Inhalation	600 mg/m³	Workers	Systemic
ethylbenzene	DMEL	Long term Inhalation	442 mg/m³	Workers	Local
	DMEL	Short term Inhalation	884 mg/m³	Workers	Systemic
	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	15 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	77 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic

SECTION 8: Exposure controls/personal protection

	DNEL	Short term Inhalation	293 mg/m³	Workers	Local
propylidynetrimethanol	DNEL	Long term Oral	0.34 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.34 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.58 mg/m³	General population	Systemic
	DNEL	Long term Dermal	0.94 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	3.3 mg/m³	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
xylene	Fresh water	0.327 mg/l	-
	Marine water	0.327 mg/l	-
	Sewage Treatment Plant	6.58 mg/l	-
	Fresh water sediment	12.46 mg/kg dwt	-
	Marine water sediment	12.46 mg/kg dwt	-
	Soil	2.31 mg/kg	-
n-butyl acetate	Fresh water	0.18 mg/l	-
	Marine water	0.018 mg/l	-
	Fresh water sediment	0.981 mg/kg	-
	Marine water sediment	0.0981 mg/kg	-
	Sewage Treatment Plant	35.6 mg/l	-
	Soil	0.0903 mg/kg	-
ethylbenzene	Fresh water	0.1 mg/l	Assessment Factors
	Marine water	0.01 mg/l	Assessment Factors
	Sewage Treatment Plant	9.6 mg/l	Assessment Factors
	Fresh water sediment	13.7 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	1.37 mg/kg dwt	Equilibrium Partitioning
	Soil	2.68 mg/kg dwt	Equilibrium Partitioning
	Secondary Poisoning	20 mg/kg	-

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

butyl rubber

SECTION 8: Exposure controls/personal protection

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour : White.

Odour : Not available.

Odour threshold : Not available.

Melting point/freezing point :

Initial boiling point and boiling range : >37.78°C (>100°F)

Flammability (solid, gas) : liquid

Upper/lower flammability or explosive limits : Not available.

Flash point : Closed cup: 25°C (77°F)

Auto-ignition temperature :

Ingredient name	°C	°F	Method
n-butyl acetate	415	779	EU A.15

pH : Not applicable.
Not applicable. insoluble in water.

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): >21 mm^2/s

Solubility(ies) :

Media	Result
cold water	Not soluble

Miscible with water : No.

Partition coefficient: n-octanol/water : Not applicable.

Vapour pressure :

SECTION 9: Physical and chemical properties

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
n-butyl acetate	11.25096	1.5	DIN EN 13016-2			

Relative density : 1.34

Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties : Product does not present an oxidizing hazard.

Particle characteristics

Median particle size : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides sulfur oxides metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate, ethenylbenzene, 1,2-propanediol mono (2-methyl-2-propenoate) and 2-propenoic acid	LD50 Oral	Rat	>5000 mg/kg	-
Hydrocarbons, C9, aromatics > 0.1% cumene	LD50 Dermal	Rabbit	>3160 mg/kg	-
xylene	LD50 Oral	Rat - Female	3492 mg/kg	-
	LD50 Dermal	Rabbit	1.7 g/kg	-
	LD50 Oral	Rat	4.3 g/kg	-
n-butyl acetate	LC50 Inhalation Vapour	Rat	>21.1 mg/l	4 hours
	LC50 Inhalation Vapour	Rat	2000 ppm	4 hours
	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10.768 g/kg	-
ethylbenzene	LC50 Inhalation Vapour	Rat	17.8 mg/l	4 hours
	LD50 Dermal	Rabbit	17.8 g/kg	-
	LD50 Oral	Rat	3.5 g/kg	-
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	LC50 Inhalation Dusts and mists	Rat	>5.08 mg/l	4 hours

SECTION 11: Toxicological information

Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 Dermal	Rat	>3170 mg/kg	-
	LD50 Oral	Rat - Male, Female	3230 mg/kg	-
propylidynetrimethanol	LD50 Dermal	Rabbit	10 g/kg	-
	LD50 Oral	Rat	14000 mg/kg	-

Conclusion/Summary : There are no data available on the mixture itself.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
SIGMADUR 550 BAS WHITE	N/A	18190.7	N/A	106.0	N/A
Hydrocarbons, C9, aromatics > 0.1% cumene	3492	N/A	N/A	N/A	N/A
xylene	4300	1700	N/A	11	N/A
n-butyl acetate	10768	N/A	N/A	N/A	N/A
ethylbenzene	3500	17800	N/A	17.8	N/A
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	3230	N/A	N/A	N/A	N/A
propylidynetrimethanol	14000	10000	N/A	N/A	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Conclusion/Summary : Not available.

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
2-Propenoic acid, 2-methyl-, methyl ester, polymer with butyl 2-propenoate, ethenylbenzene, 1,2-propanediol mono (2-methyl-2-propenoate) and 2-propenoic acid	skin	Mouse	Sensitising

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary : There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary : There are no data available on the mixture itself.

SECTION 11: Toxicological information

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9, aromatics > 0.1% cumene	Category 3	-	Respiratory tract irritation
-	Category 3	-	Narcotic effects
xylene	Category 3	-	Respiratory tract irritation
n-butyl acetate	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9, aromatics > 0.1% cumene	ASPIRATION HAZARD - Category 1
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.

Ingestion : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

SECTION 11: Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Hydrocarbons, C9, aromatics > 0.1% cumene	EC50 3.2 mg/l	Daphnia	48 hours
	LC50 9.2 mg/l	Fish	96 hours
n-butyl acetate	Acute LC50 18 mg/l	Fish	96 hours
ethylbenzene	Acute EC50 1.8 mg/l Fresh water	Daphnia	48 hours
	Chronic NOEC 1 mg/l Fresh water	Daphnia - *Ceriodaphnia dubia*	-
1,3-bis[12-hydroxy-octadecamide-N-methylene]-benzene	Acute LC50 >100 mg/l	Fish	96 hours
Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	EC50 1.68 mg/l	Algae	72 hours
	LC50 0.9 mg/l	Fish	96 hours
propylidynetrimethanol	Acute LC50 >1000 mg/l	Fish	96 hours

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Hydrocarbons, C9, aromatics > 0.1% cumene	-	75 % - Readily - 28 days	-	-
n-butyl acetate	TEPA and OECD 301D	83 % - Readily - 28 days	-	-
ethylbenzene	-	79 % - Readily - 10 days	-	-

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hydrocarbons, C9, aromatics > 0.1% cumene	-	-	Readily
xylene	-	-	Readily
n-butyl acetate	-	-	Readily
ethylbenzene	-	-	Readily

12.3 Bioaccumulative potential

SECTION 12: Ecological information

Product/ingredient name	$LogP_{ow}$	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
n-butyl acetate	2.3	-	Low
ethylbenzene	3.6	79.43	Low
propylidynetrimethanol	-0.47	-	Low

12.4 Mobility in soil

Soil/water partition coefficient : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

Waste catalogue

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	Yes.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Additional information

ADR/RID : None identified.

Tunnel code : (D/E)

ADN : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.

IMDG : None identified.

IATA : None identified.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Explosive precursors : Not applicable.

Ozone depleting substances

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	Entry Number (REACH)
SIGMADUR 550 BAS WHITE	3 28
Hydrocarbons, C9, aromatics > 0.1% cumene	28

Labelling : Restricted to professional users.

Seveso Directive

This product is controlled under the Seveso Directive.

SECTION 15: Regulatory information

Danger criteria

Category
P5c

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = GB CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Flam. Liq. 3, H226	On basis of test data
Skin Sens. 1, H317	Calculation method
Carc. 1B, H350	Calculation method
STOT SE 3, H335	Calculation method
STOT SE 3, H336	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H361f	Suspected of damaging fertility.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications

SECTION 16: Other information

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Aquatic Chronic 4	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 1B	CARCINOGENICITY - Category 1B
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision : 25 August 2025

Date of previous issue : 16 January 2025

Prepared by : EHS

Version : 1.05

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

SAFETY DATA SHEET

Date of issue/Date of revision : 19 November 2025 **Version** : 1

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : SIGMAFAST 278 BASE RAL 7035

Product code : 000010026401

Other means of identification

30014387

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications, Used by spraying.

Use of the substance/ mixture : Coating.

Uses advised against : Product is not intended, labelled or packaged for consumer use.

1.3 Details of the supplier of the safety data sheet

Sigma Paint Saudi Arabia Ltd.
PO Box 7509
Dammam 31472
Saudi Arabia
Tel: 00966 138 47 31 00
Fax: 00966 138 47 17 34

e-mail address of person responsible for this SDS : ndpic@sfda.gov.sa

1.4 Emergency telephone number : 00966 138473100 extn 1001

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226
Skin Irrit. 2, H315
Eye Irrit. 2, H319
Skin Sens. 1, H317
Repr. 1B, H360F
Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :

: Danger

SECTION 2: Hazards identification

Hazard statements : Flammable liquid and vapour.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May damage fertility.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment.

Response : Collect spillage. IF exposed or concerned: Get medical advice or attention.

Storage : Not applicable.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.
P280, P210, P273, P391, P308 + P313, P501

Hazardous ingredients : bis-[4-(2,3-epoxipropoxi)phenyl]propane; benzyl alcohol; Phenol, styrenated and oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Supplemental label elements : Contains epoxy constituents. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Restricted to professional users.

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
bis-[4-(2,3-epoxipropoxi) phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7	≥5.0 - ≤10	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Dermal] = 1700 mg/kg ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≥1.0 - ≤5.0	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317	ATE [Oral] = 1200 mg/kg	[1]
Phenol, styrenated	EC: 262-975-0 CAS: 61788-44-1	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	-	[1]
1-methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≥1.0 - ≤5.0	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ATE [Inhalation (vapours)] = 17.8 mg/l	[1] [2]
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	REACH #: 01-2119485289-22 EC: 271-846-8 CAS: 68609-97-2 Index: 603-103-00-4	≥1.0 - ≤5.0	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Repr. 1B, H360F	-	[1]
trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	≤1.0	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 **See Section 16 for the full text of the H statements declared above.**	M [Acute] = 1 M [Chronic] = 1	[1]

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard
[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 4: First aid measures

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO_2, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : Decomposition products may include the following materials:
carbon oxides
halogenated compounds
metal oxide/oxides

5.3 Advice for firefighters

Special precautions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

SECTION 6: Accidental release measures

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities : Store between the following temperatures: 0 to 35°C (32 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Talc , not containing asbestiform fibres	**Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016)** A4. TWA 8 hours: 2 mg/m³. Form: measured as respirable fraction of the aerosol. **Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)** TWA 8 hours: 2 mg/m³. **ACGIH TLV (United States, 1/2025)** A4. TWA 8 hours: 2 mg/m³. Form: Respirable fraction.
calcium carbonate	**ACGIH TLV (United States)** TWA: 10 mg/m³. Form: Total dust. TWA: 3 mg/m³. Form: Respirable.
xylene	**Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016) [xylene (o, m & p isomers)]** A4. STEL 15 minutes: 651 mg/m³. STEL 15 minutes: 150 ppm. TWA 8 hours: 434 mg/m³. TWA 8 hours: 100 ppm. **Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006) [xylene (all isomers)]** STEL 15 minutes: 150 ppm. TWA 8 hours: 434 mg/m³. STEL 15 minutes: 651 mg/m³. TWA 8 hours: 100 ppm. **ACGIH TLV (United States, 1/2025) [p-xylene and mixtures containing p-xylene]** A4. Ototoxicant. TWA 8 hours: 20 ppm.
titanium dioxide	**Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016)** A4. TWA 8 hours: 10 mg/m³. **Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)** TWA 8 hours: 10 mg/m³. **ACGIH TLV (United States, 1/2025)** A3. TWA 8 hours: 2.5 mg/m³. Form: respirable fraction, finescale particles.
1-methoxy-2-propanol	**Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016)** TWA 8 hours: 369 mg/m³. TWA 8 hours: 100 ppm. STEL 15 minutes: 553 mg/m³. STEL 15 minutes: 150 ppm. **Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)** STEL 15 minutes: 150 ppm. TWA 8 hours: 369 mg/m³. STEL 15 minutes: 553 mg/m³. TWA 8 hours: 100 ppm.

SECTION 8: Exposure controls/personal protection

	ACGIH TLV (United States, 1/2025) A4. TWA 8 hours: 50 ppm. TWA 8 hours: 184 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 369 mg/m³.
magnesium carbonate	**Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016)** TWA 8 hours: 10 mg/m³. **Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)** TWA 8 hours: 10 mg/m³.
ethylbenzene	**Abu Dhabi - OSHAD - Occupational air quality threshold limit values (United Arab Emirates, 7/2016)** A3. STEL 15 minutes: 543 mg/m³. STEL 15 minutes: 125 ppm. TWA 8 hours: 100 ppm. TWA 8 hours: 434 mg/m³. **Cabinet Decree (12) of 2006 Regarding Regulation Concerning Protection of Air from Pollution (United Arab Emirates, 5/2006)** STEL 15 minutes: 125 ppm. TWA 8 hours: 434 mg/m³. STEL 15 minutes: 543 mg/m³. TWA 8 hours: 100 ppm. **ACGIH TLV (United States, 1/2025)** A3. Ototoxicant. TWA 8 hours: 20 ppm.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Chemical splash goggles.

Skin protection

Hand protection :

SECTION 8: Exposure controls/personal protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Gloves : butyl rubber

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection :

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.

Colour : Grey.

Odour : Aromatic. [Slight]

Odour threshold : Not available.

Melting point/freezing point : Not determined.

Initial boiling point and boiling range : >37.78°C

Flammability : Not determined. There are no data available on the mixture itself.

Upper/lower flammability or explosive limits : Not available.

Flash point : Closed cup: 38°C

Auto-ignition temperature :

Ingredient name	°C	°F	Method
1-methoxy-2-propanol	270	518	

Decomposition temperature : Stable under recommended storage and handling conditions (see Section 7).

pH : Not applicable.

SECTION 9: Physical and chemical properties

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): >21 mm^2/s

Solubility(ies) :

Media	Result
cold water	Not soluble

Partition coefficient: n-octanol/water : Not applicable.

Vapour pressure :

Ingredient name	Vapour Pressure at 20˚C			Vapour pressure at 50˚C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
ethylbenzene	9.30076	1.2				

Relative density : 1.71

Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties : Product does not present an oxidizing hazard.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

Explosive properties : The product itself is not explosive, but the formation of an explosible mixture of vapour or dust with air is possible.

Oxidising properties : Product does not present an oxidizing hazard.

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides

SECTION 11: Toxicological information

11.1 Information on toxicological effects

The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly.

Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.
May damage fertility.

Acute toxicity

Product/ingredient name	Result	Dose / Exposure
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit - Dermal - LD50	23000 mg/kg
	Rat - Oral - LD50	15000 mg/kg
XYLENES	Rat - Oral - LD50	4.3 g/kg
	Rabbit - Dermal - LD50	1.7 g/kg
benzyl alcohol	Rabbit - Dermal - LD50	>2000 mg/kg
	Rat - Oral - LD50	1200 mg/kg
	Rat - Inhalation - LC50 Dusts and mists	>5 mg/l [4 hours]
PHENOLIC RESIN	Rabbit - Dermal - LD50	>5010 mg/kg
	Toxic effects: Gastrointestinal - Gastritis Liver - Other changes Kidney, Ureter, and Bladder - Other changes	
	Rat - Oral - LD50	3550 mg/kg
	Toxic effects: Behavioral - Food intake (animal) Gastrointestinal - Gastritis Liver - Other changes	
1-methoxy-2-propanol	Rabbit - Dermal - LD50	13 g/kg
	Rat - Oral - LD50	5.2 g/kg
	Rat - Inhalation - LC50 Vapour	>7000 ppm [6 hours]
ethylbenzene	Rat - Oral - LD50	3.5 g/kg
	Rabbit - Dermal - LD50	17.8 g/kg
	Rat - Inhalation - LC50 Vapour	17.8 mg/l [4 hours]
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Rat - Oral - LD50	17100 mg/kg
	Rabbit - Dermal - LD50	>4000 mg/kg
trizinc bis(orthophosphate)	Rat - Oral - LD50	>5000 mg/kg
	Rat - Inhalation - LC50 Dusts and mists	>5.7 mg/l [4 hours]

Acute toxicity estimates

Route	ATE value
Oral	48241.21 mg/kg
Dermal	29860.09 mg/kg
Inhalation (vapours)	173.96 mg/l

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/ingredient name	Result
bis-[4-(2,3-epoxipropoxi)phenyl] propane	Rabbit - Eyes - Redness of the conjunctivae Duration of treatment/exposure: 24 hours Irritation score: 0.4
-	Rabbit - Eyes - Mild irritant Duration of treatment/exposure: 24 hours Fully reversible in 7 days or less
-	Rabbit - Skin - Erythema/Eschar Duration of treatment/exposure: 4 hours Irritation score: 0.8
-	Rabbit - Skin - Oedema

SECTION 11: Toxicological information

	Duration of treatment/exposure: 4 hours Irritation score: 0.5
-	Rabbit - Skin - Mild irritant Duration of treatment/exposure: 4 hours
xylene	Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 mg Duration of treatment/exposure: 24 hours

Conclusion/Summary

Skin : Causes skin irritation.

Eyes : Causes serious eye irritation.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Product/ingredient name	Test	Result
bis-[4-(2,3-epoxipropoxi)phenyl] propane	Mouse - skin	Sensitising
Phenol, styrenated	Mouse - skin OECD 429	Sensitising

Conclusion/Summary

Skin : May cause an allergic skin reaction.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

May damage fertility.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
xylene	Category 3	-	Respiratory tract irritation
1-methoxy-2-propanol	Category 3	-	Narcotic effects

Conclusion/Summary (Product) :

Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
ethylbenzene	Category 2	-	hearing organs

Conclusion/Summary (Product) :

Based on available data, the classification criteria are not met.

Aspiration hazard

Product/ingredient name	Result
xylene	ASPIRATION HAZARD - Category 1
ethylbenzene	ASPIRATION HAZARD - Category 1

Conclusion/Summary (Product) : Based on available data, the classification criteria are not met.

SECTION 11: Toxicological information

Information on likely routes of exposure : Not available.

Potential acute health effects

Inhalation : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Skin contact : Causes skin irritation. Defatting to the skin. May cause an allergic skin reaction.

Eye contact : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced foetal weight
increase in foetal deaths
skeletal malformations

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate effects : No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : May damage fertility.

Other information : Not available.

Prolonged or repeated contact may dry skin and cause irritation. Sanding and grinding dusts may be harmful if inhaled. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Inhalation of vapour/aerosol concentrations above the recommended exposure limits causes headaches, drowsiness and nausea and may lead to unconsciousness or death. Avoid contact with skin and clothing.

SECTION 11: Toxicological information

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Dose / Exposure
bis-[4-(2,3-epoxipropoxi) phenyl]propane	Chronic - NOEC	Daphnia	0.3 mg/l [21 days]
	Acute - LC50 - Fresh water	Daphnia - *daphnia magna*	1.8 mg/l [48 hours]
Phenol, styrenated	Acute - EC50	Daphnia	3.8 mg/l [48 hours]
1-methoxy-2-propanol	Acute - LC50 - Fresh water	Fish - Goldfish	>4500 mg/l [96 hours]
	Acute - LC50	Daphnia - Daphnia	23300 mg/l [48 hours]
ethylbenzene	Acute - EC50 - Fresh water	Daphnia	1.8 mg/l [48 hours]
	Chronic - NOEC - Fresh water	Daphnia - *Ceriodaphnia dubia*	1 mg/l
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	LC50	Fish	>1.8 mg/l [96 hours]
	EC50	Daphnia	7.2 mg/l [48 hours]
	EC50	Algae	844 mg/l [72 hours]
trizinc bis(orthophosphate)	Acute - LC50	Fish	0.112 mg/l [96 hours]
	Chronic - NOEC	Fish	0.026 mg/l [30 days]

Conclusion/Summary : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Phenol, styrenated	OECD 301F	7% [28 days] - Not readily		
ethylbenzene	-	79% [10 days] - Readily		
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	OECD [Ready Biodegradability - Manometric Respirometry Test]	87% [28 days] - Readily		

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily
xylene	-	-	Readily
benzyl alcohol	-	-	Readily
Phenol, styrenated	-	-	Not readily
ethylbenzene	-	-	Readily
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	$LogP_{ow}$	BCF	Potential
xylene	3.12	7.4 to 18.5	Low
benzyl alcohol	0.87	-	Low
1-methoxy-2-propanol	<1	-	Low
ethylbenzene	3.6	79.43	Low
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	3.77	160 to 263	Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
bis-[4-(2,3-epoxipropoxi)phenyl]propane	4	10465.7
benzyl alcohol	1.1	12.6442
1-methoxy-2-propanol	1	10.447
ethylbenzene	2.2	170.406

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

SECTION 13: Disposal considerations

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 06 mixed packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Marine pollutant substances	Not applicable.	(bis-[4-(2,3-epoxipropoxi) phenyl]propane)	Not applicable.

Additional information

ADR/RID : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

Tunnel code : (D/E)

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Restricted to professional users.

Other national and international regulations.

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

15.2 Chemical safety assessment : No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms :
ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number

Full text of abbreviated H statements :

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360F	May damage fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

SECTION 16: Other information

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

History

Date of issue/ Date of revision : 19 November 2025

Date of previous issue : No previous validation

Prepared by : EHS

Version : 1

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

FICHE DE DONNÉES DE SÉCURITÉ

Date d'édition/Date de révision : 24 Octobre 2025 **Version** : 1.04

RUBRIQUE 1: Identification de la substance/du mélange et de la société/de l'entreprise

1.1 Identificateur de produit

Nom du produit : SIGMAZINC 102 HS BASE GREY

Code du produit : 000010022770

Autres moyens d'identification

00282840; 00463885

1.2 Utilisations identifiées pertinentes de la substance ou du mélange et utilisations déconseillées

Utilisation du produit : Applications professionnelles, Utilisé par pulvérisation.

Utilisation de la substance/du mélange : Revêtement.

Utilisations non recommandées : Le produit n'est pas destiné, étiqueté ou emballé pour l'usage du consommateur.

1.3 Renseignements concernant le fournisseur de la fiche de données de sécurité

PPG Coatings Belgium BV/SRL
Tweemontstraat 104
B-2100 Deurne
Belgium
Telephone +32-33606311
Fax +32-33606435

Adresse email de la personne responsable pour cette FDS : Product.Stewardship.EMEA@ppg.com

1.4 Numéro d'appel d'urgence

Organisme de conseil/centre antipoison national

Numéro de téléphone : Centre Anti-Poisons/Antigifcentrum + 32 70 245 245

RUBRIQUE 2: Identification des dangers

2.1 Classification de la substance ou du mélange

Définition du produit : Mélange

Classification selon le Règlement (CE) n° 1272/2008 [CLP/SGH]

Flam. Liq. 3, H226
Skin Irrit. 2, H315
Eye Irrit. 2, H319
Skin Sens. 1, H317
Aquatic Acute 1, H400
Aquatic Chronic 1, H410

Ce produit est classé comme dangereux conformément au règlement (CE) n° 1272/2008 et ses modifications.

RUBRIQUE 2: Identification des dangers

Voir la rubrique 16 pour le texte intégral des mentions H déclarées ci-dessus.

Pour plus de détails sur les conséquences en termes de santé et les symptômes, reportez-vous à la rubrique 11.

2.2 Éléments d'étiquetage

Pictogrammes de danger :

Mention d'avertissement : Attention

Mentions de danger : Liquide et vapeurs inflammables.
Provoque une irritation cutanée.
Peut provoquer une allergie cutanée.
Provoque une sévère irritation des yeux.
Très toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.

Prévention : Porter des gants de protection. Porter un équipement de protection des yeux ou du visage. Tenir à l'écart de la chaleur, des surfaces chaudes, des étincelles, des flammes nues et de toute autre source d'inflammation. Ne pas fumer. Éviter le rejet dans l'environnement. Éviter de respirer les vapeurs.

Intervention : Recueillir le produit répandu.

Stockage : Non applicable.

Élimination : Éliminer le contenu et le récipient en conformité avec toutes réglementations locales, régionales, nationales, et internationales.

P280, P210, P273, P261, P391, P501

Ingrédients dangereux : résines époxydiques (700<MW<=1100); bis-[4-(2,3-époxypropoxy)phényl]propane et N, N'-Hexane-1,6-diylbis(12-hydroxystéaramide)

Éléments d'étiquetage supplémentaires : Contient des composés époxydiques. Peut produire une réaction allergique.

Annexe XVII - Restrictions applicables à la fabrication, à la mise sur le marché et à l'utilisation de certaines substances et préparations dangereuses et de certains articles dangereux : Non applicable.

Exigences d'emballages spéciaux

Récipients devant être pourvus d'une fermeture de sécurité pour les enfants : Non applicable.

Avertissement tactile de danger : Non applicable.

2.3 Autres dangers

Le produit répond aux critères de PBT ou de vPvB conformément au règlement (CE) N° 1907/2006, Annexe XIII : Ce mélange ne contient aucune substance évaluée comme étant un PBT ou un vPvB.

RUBRIQUE 2: Identification des dangers

Le produit répond aux critères de propriétés perturbatrices endocriniennes conformément au Règlement (CE) n° 1907/2006. : D'après les données disponibles, les critères de classification ne sont pas satisfaits.

Autres dangers qui ne donnent pas lieu à une classification : Un contact prolongé ou répété peut éventuellement sécher la peau et provoquer une irritation.

RUBRIQUE 3: Composition/informations sur les composants

3.2 Mélanges : Mélange

Nom du produit/ composant	Identifiants	% en poids	Classification	Concentration spécifique limites, facteurs M et ETA	Type
poudre de zinc poussière de zinc (stabilisé)	REACH #: 01-2119467174-37 CE: 231-175-3 CAS: 7440-66-6 Indice: 030-001-01-9	≥50 - ≤75	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [aigu] = 1 M [chronique] = 1	[1]
résines époxydiques (700<MW<=1100)	CAS: 25036-25-3	≥5.0 - ≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	-	[1]
bis-[4-(2,3-époxypropoxy) phényl]propane	REACH #: 01-2119456619-26 CE: 216-823-5 CAS: 1675-54-3 Indice: 603-073-00-2	≥5.0 - ≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
oxyde de zinc	REACH #: 01-2119463881-32 CE: 215-222-5 CAS: 1314-13-2 Indice: 030-013-00-7	≥1.0 - ≤5.0	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [aigu] = 1 M [chronique] = 1	[1]
Hydrocarbures, C9, substances aromatiques > 0.1% cumène	REACH #: 01-2119455851-35 CE: 918-668-5 CAS: 128601-23-0	≥1.0 - ≤5.0	Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	Carc. 1B, H350: C ≥ 10%	[1] [2]
xylène	REACH #: 01-2119488216-32 CE: 215-535-7 CAS: 1330-20-7	≥1.0 - ≤5.0	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ETA [dermique] = 1700 mg/kg ETA [inhalation (vapeurs)] = 11 mg/l	[1] [2]

RUBRIQUE 3: Composition/informations sur les composants

1-méthoxy-2-propanol	REACH #: 01-2119457435-35 CE: 203-539-1 CAS: 107-98-2 Indice: 603-064-00-3	≥1.0 - ≤5.0	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
éthylbenzène	REACH #: 01-2119489370-35 CE: 202-849-4 CAS: 100-41-4 Indice: 601-023-00-4	≥1.0 - ≤5.0	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (organes de l'audition) Asp. Tox. 1, H304 Aquatic Chronic 3, H412	ETA [inhalation (vapeurs)] = 17.8 mg/l	[1] [2]
N,N'-Hexane-1,6-diylbis (12-hydroxystéaramide)	CAS: 55349-01-4	<1.0	Skin Sens. 1, H317 Aquatic Chronic 4, H413 **Voir la rubrique 16 pour le texte intégral des mentions H déclarées ci-dessus.**	-	[1]

Dans l'état actuel des connaissances du fournisseur et dans les concentrations d'application, aucun autre ingrédient présent n'est classé comme dangereux pour la santé ou l'environnement, ni comme PTB ou vPvB, ni comme substance de degré de préoccupation équivalent, ni soumis à une limite d'exposition professionnelle et donc nécessiterait de figurer dans cette rubrique.

Type

[1] Substance classée avec un danger pour la santé ou l'environnement

[2] Substance avec une limite d'exposition au poste de travail

Les limites d'exposition professionnelle, quand elles sont disponibles, sont énumérées à la rubrique 8.

RUBRIQUE 4: Premiers secours

4.1 Description des mesures de premiers secours

Contact avec les yeux : Enlever les lentilles de contact. Laver abondamment avec de l'eau douce et propre en maintenant les paupières écartées pendant au moins 10 minutes et faire appel immédiatement à un médecin.

Inhalation : Emmener à l'air frais. Garder la personne au chaud et au repos. S'il ne respire pas, en cas de respiration irrégulière ou d'arrêt respiratoire, que le personnel qualifié pratique la respiration artificielle ou administre de l'oxygène.

Contact avec la peau : Retirer les vêtements et les chaussures contaminés. Laver soigneusement la peau au savon et à l'eau ou utiliser un nettoyant cutané reconnu. NE PAS UTILISER de solvants ni de diluants.

Ingestion : En cas d'ingestion, consulter immédiatement un médecin et lui montrer l'emballage ou l'étiquette. Garder la personne au chaud et au repos. NE PAS faire vomir.

Protection des sauveteurs : Aucune initiative ne doit être prise qui implique un risque individuel ou en l'absence de formation appropriée. Il peut être dangereux pour la personne assistant une victime de pratiquer le bouche à bouche. Laver abondamment à l'eau les vêtements contaminés avant de les retirer, ou porter des gants.

4.2 Principaux symptômes et effets, aigus et différés

Effets aigus potentiels sur la santé

Contact avec les yeux : Provoque une sévère irritation des yeux.

Inhalation : Aucun effet important ou danger critique connu.

RUBRIQUE 4: Premiers secours

Contact avec la peau : Provoque une irritation cutanée. Dégraisse la peau. Peut provoquer une allergie cutanée.

Ingestion : Aucun effet important ou danger critique connu.

Signes/symptômes de surexposition

Contact avec les yeux : Les symptômes néfastes peuvent éventuellement comprendre ce qui suit:
douleur ou irritation
larmoiement
rougeur

Inhalation : Aucune donnée spécifique.

Contact avec la peau : Les symptômes néfastes peuvent éventuellement comprendre ce qui suit:
irritation
rougeur
sécheresse
gerçure

Ingestion : Aucune donnée spécifique.

4.3 Indication des éventuels soins médicaux immédiats et traitements particuliers nécessaires

Note au médecin traitant : Traitement symptomatique requis. Contacter immédiatement un spécialiste pour le traitement des intoxications, si de grandes quantités ont été ingérées ou inhalées.

Traitements spécifiques : Pas de traitement particulier.

RUBRIQUE 5: Mesures de lutte contre l'incendie

5.1 Moyens d'extinction

Moyens d'extinction appropriés : Utiliser de la poudre chimique sèche, du CO_2, de l'eau pulvérisée ou de la mousse.

Moyens d'extinction inappropriés : Ne pas utiliser de jet d'eau.

5.2 Dangers particuliers résultant de la substance ou du mélange

Dangers dus à la substance ou au mélange : Liquide et vapeurs inflammables. Les écoulements dans les égouts peuvent créer des risques de feu ou d'explosion. L'augmentation de pression résultant d'un incendie ou d'une exposition à des températures élevées peut provoquer l'explosion du conteneur, ce qui risque d'entraîner une nouvelle explosion. Cette substance est très toxique pour les organismes aquatiques avec des effets néfastes à long terme. L'eau du réseau d'extinction d'incendie qui a été contaminée par ce produit doit être conservée en milieu fermé et ne doit être déversée ni dans le milieu aquatique, ni aucun égout ou conduit d'évacuation.

Produits de combustion dangereux : Les produits de décomposition peuvent éventuellement comprendre les substances suivantes:
oxydes de carbone
oxyde/oxydes de métal

5.3 Conseils aux pompiers

Précautions spéciales pour les pompiers : En présence d'incendie, circonscrire rapidement le site en évacuant toute personne se trouvant près des lieux de l'accident. Aucune initiative ne doit être prise qui implique un risque individuel ou en l'absence de formation appropriée. Déplacer les contenants à l'écart de la zone d'incendie si cela ne présente aucun risque. Refroidir les conteneurs exposés aux flammes avec un jet d'eau pulvérisée.

RUBRIQUE 5: Mesures de lutte contre l'incendie

Équipement de protection spécial pour le personnel préposé à la lutte contre l'incendie : Les pompiers devront porter un équipement de protection approprié ainsi qu'un appareil de protection respiratoire autonome avec masque intégral fonctionnant en mode pression positive. Les vêtements pour sapeurs-pompiers (y compris casques, bottes de protection et gants) conformes à la Norme européenne EN 469 procurent un niveau de protection de base contre les accidents chimiques.

RUBRIQUE 6: Mesures à prendre en cas de dispersion accidentelle

6.1 Précautions individuelles, équipement de protection et procédures d'urgence

Pour les non-secouristes : Aucune initiative ne doit être prise qui implique un risque individuel ou en l'absence de formation appropriée. Évacuer les environs. Empêcher l'accès aux personnes non requises et ne portant pas de vêtements de protection. Ne pas toucher ni marcher dans le produit répandu. Éteindre toutes les sources d'inflammation. La zone de danger doit être exempte de cigarettes ou flammes. Éviter de respirer les vapeurs ou le brouillard. Assurer une ventilation adéquate. Porter un appareil de protection respiratoire approprié lorsque le système de ventilation est inadéquat. Porter un équipement de protection individuelle adapté.

Pour les secouristes : Si des vêtements spécifiques sont nécessaires pour traiter le déversement, consulter la section 8 pour les matériaux appropriés et inappropriés. Voir également les informations contenues dans « Pour les non-secouristes ».

6.2 Précautions pour la protection de l'environnement : Évitez la dispersion des matériaux déversés, ainsi que leur écoulement et tout contact avec le sol, les cours d'eau, les égouts et conduits d'évacuation. Informez les autorités compétentes en cas de pollution de l'environnement (égouts, voies d'eau, sol et air) par le produit. Matière propre à polluer l'eau. Peut-être nocif pour l'environnement en cas de déversement de grandes quantités. Recueillir le produit répandu.

6.3 Méthodes et matériel de confinement et de nettoyage

Petit déversement accidentel : Arrêter la fuite si cela ne présente aucun risque. Écarter les conteneurs de la zone de déversement accidentel. Utilisez des outils anti-étincelles ou du matériel anti-déflagrant. Diluer avec de l'eau et éponger si la matière est soluble dans l'eau. Sinon, ou si la matière est insoluble dans l'eau, absorber avec un matériau sec inerte et placer dans un conteneur à déchets approprié. Élimination par une entreprise autorisée de collecte des déchets.

Grand déversement accidentel : Arrêter la fuite si cela ne présente aucun risque. Écarter les conteneurs de la zone de déversement accidentel. Utilisez des outils anti-étincelles ou du matériel anti-déflagrant. S'approcher des émanations dans la même direction que le vent. Bloquer toute pénétration possible dans les égouts, les cours d'eau, les caves ou les zones confinées. Laver le produit répandu dans une installation de traitement des effluents ou procéder comme suit. Contenir les fuites et les ramasser à l'aide de matières absorbantes non combustibles telles que le sable, la terre, la vermiculite, la terre à diatomées. Les placer ensuite dans un récipient pour élimination conformément à la réglementation locale. Élimination par une entreprise autorisée de collecte des déchets. Les matériaux absorbants contaminés peuvent présenter les mêmes risques que le produit répandu.

6.4 Référence à d'autres rubriques : Voir la rubrique 1 pour les coordonnées d'urgence.
Voir la rubrique 8 pour toute information sur les équipements de protection individuelle adaptés.
Voir la rubrique 13 pour toute information supplémentaire sur le traitement des déchets.

RUBRIQUE 7: Manipulation et stockage

Les informations de cette rubrique contiennent des directives et des conseils généraux. Consulter la liste des Utilisations Identifiées de la rubrique 1 pour toute information spécifique aux usages disponible dans le(s) scénario(s) d'exposition.

7.1 Précautions à prendre pour une manipulation sans danger

Mesures de protection : Revêtir un équipement de protection individuelle approprié (voir Section 8). Les personnes ayant des antécédents de sensibilisation cutanée ne doivent pas intervenir dans les processus utilisant ce produit. Ne pas mettre en contact avec les yeux, la peau ou les vêtements. Ne pas avaler. Éviter de respirer les vapeurs ou le brouillard. Éviter le rejet dans l'environnement. Utiliser uniquement dans un environnement bien aéré. Porter un appareil de protection respiratoire approprié lorsque le système de ventilation est inadéquat. Ne pas pénétrer dans les lieux de stockage et dans des espaces confinés à moins qu'il y ait une ventilation adéquate. Garder dans le conteneur d'origine ou dans un autre conteneur de substitution homologué fabriqué à partir d'un matériau compatible et tenu hermétiquement clos lorsqu'il n'est pas utilisé. Tenir éloigné de la chaleur, des étincelles, de la flamme nue, ou de toute autre source d'inflammation. Utiliser un équipement électrique (de ventilation, d'éclairage et de manipulation) anti-déflagrant. Ne pas utiliser d'outils produisant des étincelles. Prendre les mesures nécessaires contre les décharges électrostatiques. Les conteneurs vides retiennent des résidus de produit et peuvent présenter un danger. Ne pas réutiliser ce conteneur.

Conseils sur l'hygiène professionnelle en général : Il est interdit de manger, boire ou fumer dans les endroits où ce produit est manipulé, entreposé ou mis en oeuvre. Il est recommandé au personnel de se laver les mains et la figure avant de manger, boire ou fumer. Retirer les vêtements contaminés et les équipements de protection avant d'entrer dans un lieu de restauration. Voir également la section 8 pour plus d'informations sur les mesures d'hygiène.

7.2 Conditions d'un stockage sûr, y compris les éventuelles incompatibilités : Stocker entre les températures suivantes: 0 à 35°C (32 à 95°F). Stocker conformément à la réglementation locale. Entreposer dans un endroit isolé et approuvé. Stocker dans le récipient d'origine à l'abri de la lumière directe du soleil dans un endroit sec, frais et bien ventilé à l'écart des matériaux incompatibles (cf. la Section 10). Éliminer toutes les sources d'inflammation. Séparer des matières comburantes. Garder le récipient hermétiquement fermé lorsque le produit n'est pas utilisé. Les récipients ayant été ouverts doivent être refermés avec soin et maintenus en position verticale afin d'éviter les fuites. Ne pas stocker dans des conteneurs non étiquetés. Utiliser un récipient approprié pour éviter toute contamination du milieu ambiant. Voir la section 10 concernant les matériaux incompatibles avant manipulation ou utilisation.

7.3 Utilisation(s) finale(s) particulière(s)

Consulter la section 1.2 pour utilisations identifiées.

RUBRIQUE 8: Contrôles de l'exposition/protection individuelle

Les informations de cette rubrique contiennent des directives et des conseils généraux. Consulter la liste des Utilisations Identifiées de la rubrique 1 pour toute information spécifique aux usages disponible dans le(s) scénario(s) d'exposition.

8.1 Paramètres de contrôle

Limites d'exposition professionnelle

RUBRIQUE 8: Contrôles de l'exposition/protection individuelle

Nom du produit/composant	Valeurs limites d'exposition
Hydrocarbures, C9, substances aromatiques > 0.1% cumène	**UE Valeurs limites d'exposition professionnelle (Europe)** MPT: 19 ppm. MPT: 100 mg/m³.
xylène	**Valeurs Limites (Belgique, 12/2023) [Xylène]** Absorbé par la peau. Valeur limite 8 heures: 50 ppm. Valeur limite 8 heures: 221 mg/m³. Valeur de courte durée 15 minutes: 100 ppm. Valeur de courte durée 15 minutes: 442 mg/m³.
1-méthoxy-2-propanol	**Valeurs Limites (Belgique, 12/2023)** Absorbé par la peau. Valeur limite 8 heures: 50 ppm. Valeur limite 8 heures: 184 mg/m³. Valeur de courte durée 15 minutes: 100 ppm. Valeur de courte durée 15 minutes: 369 mg/m³.
éthylbenzène	**Valeurs Limites (Belgique, 12/2023)** Absorbé par la peau. Valeur limite 8 heures: 20 ppm. Valeur limite 8 heures: 87 mg/m³. Valeur de courte durée 15 minutes: 125 ppm. Valeur de courte durée 15 minutes: 551 mg/m³.

Procédures de surveillance recommandées : Il doit être fait référence à des normes de surveillance, comme les suivantes : Norme européenne EN 689 (Atmosphères des lieux de travail - Conseils pour l'évaluation de l'exposition aux agents chimiques aux fins de comparaison avec des valeurs limites et stratégie de mesurage) Norme européenne EN 14042 (Atmosphères des lieux de travail - Guide pour l'application et l'utilisation de procédures et de dispositifs permettant d'évaluer l'exposition aux agents chimiques et biologiques) Norme européenne EN 482 (Atmosphères des lieux de travail - Exigences générales concernant les performances des modes opératoires de mesurage des agents chimiques) Il est également exigé de faire référence aux guides techniques nationaux concernant les méthodes de détermination des substances dangereuses.

DNEL/DMEL

Nom du produit/ composant	Exposition		Valeur
bis-[4-(2,3-époxypropoxy) phényl]propane	DNEL - Opérateurs - Long terme - Inhalation	*Systémique*	12.25 mg/m³
	DNEL - Opérateurs - Court terme - Inhalation	*Systémique*	12.25 mg/m³
	DNEL - Opérateurs - Long terme - Voie cutanée	*Systémique*	8.33 mg/kg bw/jour
	DNEL - Opérateurs - Court terme - Voie cutanée	*Systémique*	8.33 mg/kg bw/jour
	DNEL - Population générale - Consommateurs - Long terme - Voie cutanée	*Systémique*	3.571 mg/kg bw/jour
	DNEL - Population générale - Consommateurs - Court terme - Voie cutanée	*Systémique*	3.571 mg/kg bw/jour
	DNEL - Population générale - Consommateurs - Long terme - Voie orale	*Systémique*	0.75 mg/kg bw/jour
	DNEL - Population générale - Consommateurs - Court terme - Voie orale	*Systémique*	0.75 mg/kg bw/jour
	DNEL - Population générale - Long terme - Voie cutanée	*Systémique*	89.3 µg/kg bw/jour
	DNEL - Population générale - Long terme - Voie orale	*Systémique*	0.5 mg/kg bw/jour
	DNEL - Opérateurs - Long terme - Voie cutanée	*Systémique*	0.75 mg/kg bw/jour
	DNEL - Population générale - Long terme - Inhalation	*Systémique*	0.87 mg/m³
	DNEL - Opérateurs - Long terme - Inhalation	*Systémique*	4.93 mg/m³
Hydrocarbures, C9,	DNEL - Opérateurs - Long terme - Inhalation	*Systémique*	150 mg/m³

RUBRIQUE 8: Contrôles de l'exposition/protection individuelle

substances aromatiques > 0.1% cumène			
	DNEL - Opérateurs - Long terme - Voie cutanée	*Systémique*	25 mg/kg bw/jour
	DNEL - Population générale - Long terme - Inhalation	*Systémique*	32 mg/m³
	DNEL - Population générale - Long terme - Voie cutanée	*Systémique*	11 mg/kg bw/jour
	DNEL - Population générale - Long terme - Voie orale	*Systémique*	11 mg/kg bw/jour
xylène	DNEL - Population générale - Long terme - Voie orale	*Systémique*	5 mg/kg bw/jour
	DNEL - Population générale - Long terme - Inhalation	*Local*	65.3 mg/m³
	DNEL - Population générale - Long terme - Inhalation	*Systémique*	65.3 mg/m³
	DNEL - Population générale - Long terme - Voie cutanée	*Systémique*	125 mg/kg bw/jour
	DNEL - Opérateurs - Long terme - Voie cutanée	*Systémique*	212 mg/kg bw/jour
	DNEL - Opérateurs - Long terme - Inhalation	*Local*	221 mg/m³
	DNEL - Opérateurs - Long terme - Inhalation	*Systémique*	221 mg/m³
	DNEL - Population générale - Court terme - Inhalation	*Local*	260 mg/m³
	DNEL - Population générale - Court terme - Inhalation	*Systémique*	260 mg/m³
	DNEL - Opérateurs - Court terme - Inhalation	*Local*	442 mg/m³
	DNEL - Opérateurs - Court terme - Inhalation	*Systémique*	442 mg/m³
1-méthoxy-2-propanol	DNEL - Population générale - Long terme - Voie orale	*Systémique*	33 mg/kg bw/jour
	DNEL - Population générale - Long terme - Inhalation	*Systémique*	43.9 mg/m³
	DNEL - Population générale - Long terme - Voie cutanée	*Systémique*	78 mg/kg bw/jour
	DNEL - Opérateurs - Long terme - Voie cutanée	*Systémique*	183 mg/kg bw/jour
	DNEL - Opérateurs - Long terme - Inhalation	*Systémique*	369 mg/m³
	DNEL - Opérateurs - Court terme - Inhalation	*Local*	553.5 mg/m³
	DNEL - Opérateurs - Court terme - Inhalation	*Systémique*	553.5 mg/m³
éthylbenzène	DMEL - Opérateurs - Long terme - Inhalation	*Local*	442 mg/m³
	DMEL - Opérateurs - Court terme - Inhalation	*Systémique*	884 mg/m³
	DNEL - Population générale - Long terme - Voie orale	*Systémique*	1.6 mg/kg bw/jour
	DNEL - Population générale - Long terme - Inhalation	*Systémique*	15 mg/m³
	DNEL - Opérateurs - Long terme - Inhalation	*Systémique*	77 mg/m³
	DNEL - Opérateurs - Long terme - Voie cutanée	*Systémique*	180 mg/kg bw/jour
	DNEL - Opérateurs - Court terme - Inhalation	*Local*	293 mg/m³

PNEC

Nom du produit/composant	Description du milieu - Méthode	Valeur
poudre de zinc poussière de zinc (stabilisé)	Eau douce - Distribution de la Sensibilité	20.6 µg/l
	Eau de mer - Distribution de la Sensibilité	6.1 µg/l
	Usine de Traitement d'Eaux Usées - Facteurs d'Évaluation	100 µg/l
	Sédiment d'eau douce - Distribution de la Sensibilité	118 mg/kg dwt
	Sédiment d'eau de mer - Partage à l'Équilibre	56.5 mg/kg dwt
	Sol - Distribution de la Sensibilité	35.6 mg/kg dwt
bis-[4-(2,3-époxypropoxy)phényl]	Eau douce - Facteurs d'Évaluation	0.006 mg/l

RUBRIQUE 8: Contrôles de l'exposition/protection individuelle

propane		
	Eau de mer - Facteurs d'Évaluation	0.001 mg/l
	Sédiment d'eau douce - Partage à l'Équilibre	0.996 mg/kg dwt
	Sédiment d'eau de mer - Partage à l'Équilibre	0.1 mg/kg dwt
	Sol - Partage à l'Équilibre	0.196 mg/kg dwt
	Usine de Traitement d'Eaux Usées - Facteurs d'Évaluation	10 mg/l
	Empoisonnement Secondaire - Facteurs d'Évaluation	11 mg/kg
oxyde de zinc	Eau douce - Distribution de la Sensibilité	20.6 µg/l
	Eau de mer - Distribution de la Sensibilité	6.1 µg/l
	Sédiment d'eau douce - Distribution de la Sensibilité	117 mg/kg dwt
	Usine de Traitement d'Eaux Usées - Facteurs d'Évaluation	52 µg/l
	Sédiment d'eau de mer - Facteurs d'Évaluation	56.5 mg/kg dwt
	Sol - Distribution de la Sensibilité	35.6 mg/kg dwt
xylène	Eau douce	0.327 mg/l
	Eau de mer	0.327 mg/l
	Usine de Traitement d'Eaux Usées	6.58 mg/l
	Sédiment d'eau douce	12.46 mg/kg dwt
	Sédiment d'eau de mer	12.46 mg/kg dwt
	Sol	2.31 mg/kg
1-méthoxy-2-propanol	Eau douce - Facteurs d'Évaluation	10 mg/l
	Eau de mer - Facteurs d'Évaluation	1 mg/l
	Usine de Traitement d'Eaux Usées - Facteurs d'Évaluation	100 mg/l
	Sédiment d'eau douce - Partage à l'Équilibre	41.6 mg/kg
	Sédiment d'eau de mer - Partage à l'Équilibre	4.17 mg/kg
	Sol - Partage à l'Équilibre	2.47 mg/kg
éthylbenzène	Eau douce - Facteurs d'Évaluation	0.1 mg/l
	Eau de mer - Facteurs d'Évaluation	0.01 mg/l
	Usine de Traitement d'Eaux Usées - Facteurs d'Évaluation	9.6 mg/l
	Sédiment d'eau douce - Partage à l'Équilibre	13.7 mg/kg dwt
	Sédiment d'eau de mer - Partage à l'Équilibre	1.37 mg/kg dwt
	Sol - Partage à l'Équilibre	2.68 mg/kg dwt
	Empoisonnement Secondaire	20 mg/kg

8.2 Contrôles de l'exposition

Contrôles techniques appropriés : Utiliser uniquement dans un environnement bien aéré. Utiliser des enceintes fermées, une ventilation par aspiration à la source, ou d'autres systèmes de contrôle automatique intégrés afin de maintenir le seuil d'exposition du technicien aux contaminants en suspension dans l'air inférieur aux limites recommandées ou légales. Les moyens de contrôle automatiques intégrés devront permettre de maintenir les concentrations en gaz, en vapeur ou en poussière en dessous de tout seuil d'explosion. Utiliser un équipement de ventilation antidéflagrant.

Mesures de protection individuelle

Mesures d'hygiène : Se laver abondamment les mains, les avant-bras et le visage après avoir manipulé des produits chimiques, avant de manger, de fumer et d'aller aux toilettes ainsi qu'à la fin de la journée de travail. Il est recommandé d'utiliser les techniques appropriées pour retirer les vêtements potentiellement contaminés. Les vêtements de travail contaminés ne devraient pas sortir du lieu de travail. Laver les vêtements contaminés avant de les réutiliser. S'assurer que les dispositifs rince-œil automatiques et les douches de sécurité se trouvent à proximité de l'emplacement des postes de travail.

Protection des yeux/du visage : Lunettes anti-éclaboussures. Utiliser une protection oculaire homologuée EN 166.

Protection de la peau

RUBRIQUE 8: Contrôles de l'exposition/protection individuelle

Protection des mains : Le port de gants imperméables et résistants aux produits chimiques conformes à une norme approuvée, est obligatoire en tout temps lors de la manutention de produits chimiques si une évaluation des risques le préconise. En prenant en compte les paramètres indiqués par le fabricant de gants, vérifier pendant l'utilisation que les gants conservent leurs propriétés protectrices. Il est noté que le temps de claquage des gants peut différer d'un fabricant à l'autre. En cas de mélanges constitués de plusieurs substances, il est impossible d'estimer de façon précise le délai de sécurité des gants. Gants recommandés sont basé sur le solvant le plus commun dans ce produit. Pour un contact prolongé ou fréquement répété, des gants de classe de protection 6 (temps de rupture supérieur à 480 minutes selon la norme EM 374) sont recommandés. Pour un contact bref, des gants de classe de protection 2 ou classe supérieure (temps de rupture supérieur à 30 minutes selon la norme EN 374) sont recommandés. L'utilisateur doit vérifier que les types de gants qu'il choisit de porter pour la manipulation de ce produit est le plus approprié et prend en compte les conditions d'utilisation particulières, conformément aux indications stipulées dans l'évaluation des risques de l'utilisateur.

Gants : caoutchouc butyle

Protection corporelle : L'équipement de protection personnel pour le corps devra être choisi en fonction de la tâche à réaliser ainsi que des risques encourus, et il est recommandé de le faire valider par un spécialiste avant de procéder à la manipulation du produit. En cas de risque d'inflammation lié à l'électricité statique, porter des vêtements de protection antistatiques. Pour une protection maximale contre les décharges d'électricité statique, les vêtements doivent inclure une combinaison, des chaussures et des gants antistatiques. Pour plus d'informations sur les exigences et les méthodes d'essais des matières et des modèles, consulter la norme européenne EN 1149.

Autre protection cutanée Des chaussures adéquates et toutes mesures de protection corporelle devraient être déterminées en fonction de l'opération effectuée et des risques impliqués, et devraient être approuvées par un spécialiste avant toute manipulation de ce produit.

Protection respiratoire : Le choix de l'appareil de protection respiratoire doit être fondé sur les niveaux d'expositions prévus ou connus, les dangers du produit et les limites d'utilisation sans danger de l'appareil de protection respiratoire retenu. Les ouvriers exposés à des concentrations supérieures à la limite d'exposition doivent porter des appareils de protection respiratoire appropriés et homologués. Porter un appareil de protection respiratoire muni d'un purificateur d'air ou à adduction d' air, parfaitement ajusté et conforme à une norme en vigueur si une évaluation du risque indique que cela est nécessaire. Porter un masque respiratoire conformément à la norme EN140. Type de filtre : filtre de vapeurs organiques (Type A) et à particules P3

Contrôles d'exposition liés à la protection de l'environnement : Il importe de tester les émissions provenant des systèmes de ventilation ou du matériel de fabrication pour vous assurer qu'elles sont conformes aux exigences de la législation sur la protection de l'environnement. Dans certains cas, il sera nécessaire d'équiper le matériel de fabrication d'un épurateur de gaz ou d'un filtre ou de le modifier techniquement afin de réduire les émissions à des niveaux acceptables.

RUBRIQUE 9: Propriétés physiques et chimiques

Les conditions de mesure de toutes les propriétés sont celles de la température et de la pression normales, sauf indication contraire.

9.1 Informations sur les propriétés physiques et chimiques essentielles

Aspect

État physique : Liquide.

Couleur : Gris.

Odeur : Aromatique.

Point de fusion/point de congélation : Indéterminé.

RUBRIQUE 9: Propriétés physiques et chimiques

Point d'ébullition, point d'ébullition initial et intervalle d'ébullition : >37.78°C

Inflammabilité : Indéterminé. Il n'existe aucune donnée disponible pour le mélange lui-même.

Limites inférieure et supérieure d'explosion : Non disponible.

Point d'éclair : Vase clos: 28.5°C

Température d'auto-inflammabilité :

Nom des composants	°C	°F	Méthode
1-méthoxy-2-propanol	270	518	

Température de décomposition : Stable dans les conditions de stockage et de manipulation recommandées (voir Section 7).

pH : Non applicable.

Viscosité : Dynamique (température ambiante): Non disponible.
Cinématique (température ambiante): Non disponible.
Cinématique (40°C): >21 mm^2/s

Solubilité :

Support	Résultat
l'eau froide	Non soluble

Coefficient de partition n-octanol/eau (log Pow) : Non applicable.

Pression de vapeur :

Nom des composants	Pression de vapeur à 20 °C			Pression de vapeur à 50 °C		
	mm Hg	kPa	Méthode	mm Hg	kPa	Méthode
éthylbenzène	9.30076	1.2				

Densité relative : 2.7

Caractéristiques particulaires

Taille des particules moyenne : Non applicable.

9.2 Autres informations

9.2.1 Informations concernant les classes de danger physique

Propriétés explosives : Le produit lui-même n'est pas explosif, mais la formation d'un mélange de vapeur ou de poussière avec l'air est possible.

Propriétés comburantes : Le produit ne présente pas de danger d'oxydation.

Aucune information additionnelle.

RUBRIQUE 10: Stabilité et réactivité

10.1 Réactivité : Aucune donnée d'essai spécifique relative à la réactivité n'est disponible pour ce produit ou ses composants.

10.2 Stabilité chimique : Le produit est stable.

10.3 Possibilité de réactions dangereuses : Dans des conditions normales de stockage et d'utilisation, aucune réaction dangereuse ne se produit.

RUBRIQUE 10: Stabilité et réactivité

10.4 Conditions à éviter : Risque de formation de produits de décomposition dangereux lors d'une exposition à des températures élevées.

Voir les mesures de protection décrites aux sections 7 et 8.

10.5 Matières incompatibles : Tenir éloigné des matières suivantes afin d'éviter des réactions fortement exothermiques : agents oxydants, alcalins forts, acides forts.

10.6 Produits de décomposition dangereux : Dégage de l'hydrogène au contact de l'eau. Selon les conditions, les produits de décomposition peuvent inclure les matières suivantes : oxydes de carbone oxyde/oxydes de métal

RUBRIQUE 11: Informations toxicologiques

11.1 Informations sur les classes de danger telles que définies dans le règlement (CE) no 1272/2008

Le mélange a été évalué selon la méthode traditionnelle de la réglementation du CLP (CE) N° 1272/2008 et est conformément classé pour ses propriétés toxicologiques.

Provoque une sévère irritation des yeux.
Provoque une irritation cutanée.
Peut provoquer une allergie cutanée.

Toxicité aiguë

Nom du produit/composant	Résultat	Dosage / Exposition
poudre de zinc poussière de zinc (stabilisé)	Rat - Voie orale - DL50	>2000 mg/kg
	Rat - Inhalation - CL50 Poussière et brouillards	>5.4 mg/l [4 heures]
résines époxydiques (700<MW <=1100)	Rat - Voie orale - DL50	>2000 mg/kg
	Rat - Voie cutanée - DL50	>2000 mg/kg
bis-[4-(2,3-époxypropoxy)phényl] propane	Lapin - Voie cutanée - DL50	23000 mg/kg
	Rat - Voie orale - DL50	15000 mg/kg
oxyde de zinc	Rat - Voie orale - DL50	>5000 mg/kg
	Rat - Voie cutanée - DL50	>2000 mg/kg
	Rat - Inhalation - CL50 Poussière et brouillards	>5700 mg/m³ [4 heures]
Hydrocarbures, C9, substances aromatiques > 0.1% cumène	Rat - Femelle - Voie orale - DL50	3492 mg/kg
	Lapin - Voie cutanée - DL50	>3160 mg/kg
xylène	Rat - Voie orale - DL50	4.3 g/kg
	Lapin - Voie cutanée - DL50	1.7 g/kg
1-méthoxy-2-propanol	Lapin - Voie cutanée - DL50	13 g/kg
	Rat - Voie orale - DL50	5.2 g/kg
	Rat - Inhalation - CL50 Vapeurs	>7000 ppm [6 heures]
éthylbenzène	Rat - Voie orale - DL50	3.5 g/kg
	Lapin - Voie cutanée - DL50	17.8 g/kg
	Rat - Inhalation - CL50 Vapeurs	17.8 mg/l [4 heures]

Estimations de la toxicité aiguë

Voie	Valeur ETA
Voie cutanée	61193.01 mg/kg
Inhalation (vapeurs)	269.85 mg/l

Conclusion/Résumé : D'après les données disponibles, les critères de classification ne sont pas satisfaits.

Irritation/Corrosion

RUBRIQUE 11: Informations toxicologiques

Nom du produit/composant	Résultat
bis-[4-(2,3-époxypropoxy)phényl] propane	Lapin - Yeux - Rougeur des conjonctives Durée du traitement/de l'exposition: 24 heures Potentiel d'irritation: 0.4
-	Lapin - Yeux - Faiblement irritant Durée du traitement/de l'exposition: 24 heures Entièrement réversible en 7 jours ou moins
-	Lapin - Peau - Érythème/Escarre Durée du traitement/de l'exposition: 4 heures Potentiel d'irritation: 0.8
-	Lapin - Peau - Œdème Durée du traitement/de l'exposition: 4 heures Potentiel d'irritation: 0.5
-	Lapin - Peau - Faiblement irritant Durée du traitement/de l'exposition: 4 heures
xylène	Lapin - Peau - Irritant moyen Quantité/concentration appliquée: 500 mg Durée du traitement/de l'exposition: 24 heures

Conclusion/Résumé

Peau : Provoque une irritation de la peau.

Yeux : Provoque une sévère irritation des yeux.

Respiratoire : D'après les données disponibles, les critères de classification ne sont pas satisfaits.

Sensibilisation respiratoire ou cutanée

Nom du produit/composant	Test	Résultat
bis-[4-(2,3-époxypropoxy)phényl] propane	Souris - peau	Sensibilisant

Conclusion/Résumé

Peau : Peut provoquer une allergie cutanée.

Respiratoire : D'après les données disponibles, les critères de classification ne sont pas satisfaits.

Mutagénicité

D'après les données disponibles, les critères de classification ne sont pas satisfaits.

Cancérogénicité

D'après les données disponibles, les critères de classification ne sont pas satisfaits.

Toxicité pour la reproduction

D'après les données disponibles, les critères de classification ne sont pas satisfaits.

Toxicité spécifique pour certains organes cibles — exposition unique

Nom du produit/composant	Catégorie	Voie d'exposition	Organes cibles
Hydrocarbures, C9, substances aromatiques > 0.1%	Catégorie 3	-	Irritation des voies respiratoires
cumène	Catégorie 3	-	Effets narcotiques
-	Catégorie 3	-	Irritation des voies respiratoires
xylène	Catégorie 3	-	Effets narcotiques
1-méthoxy-2-propanol			

Conclusion/Résumé :

D'après les données disponibles, les critères de classification ne sont pas satisfaits.

RUBRIQUE 11: Informations toxicologiques

Toxicité spécifique pour certains organes cibles – exposition répétée

Nom du produit/composant	Catégorie	Voie d'exposition	Organes cibles
éthylbenzène	Catégorie 2	-	organes de l'audition

Conclusion/Résumé :

D'après les données disponibles, les critères de classification ne sont pas satisfaits.

Danger par aspiration

Nom du produit/composant	Résultat
Hydrocarbures, C9, substances aromatiques > 0.1% cumène xylène éthylbenzène	DANGER PAR ASPIRATION - Catégorie 1 DANGER PAR ASPIRATION - Catégorie 1 DANGER PAR ASPIRATION - Catégorie 1

Conclusion/Résumé :

D'après les données disponibles, les critères de classification ne sont pas satisfaits.

Informations sur les voies d'exposition probables : Non disponible.

Effets aigus potentiels sur la santé

Inhalation : Aucun effet important ou danger critique connu.

Ingestion : Aucun effet important ou danger critique connu.

Contact avec la peau : Provoque une irritation cutanée. Dégraisse la peau. Peut provoquer une allergie cutanée.

Contact avec les yeux : Provoque une sévère irritation des yeux.

Symptômes liés aux caractéristiques physiques, chimiques et toxicologiques

Inhalation : Aucune donnée spécifique.

Ingestion : Aucune donnée spécifique.

Contact avec la peau : Les symptômes néfastes peuvent éventuellement comprendre ce qui suit:
irritation
rougeur
sécheresse
gerçure

Contact avec les yeux : Les symptômes néfastes peuvent éventuellement comprendre ce qui suit:
douleur ou irritation
larmoiement
rougeur

Effets différés et immédiats, et effets chroniques d'une exposition de courte et de longue durée

Exposition de courte durée

Effets potentiels immédiats : Aucun effet important ou danger critique connu.

Effets potentiels différés : Aucun effet important ou danger critique connu.

Exposition prolongée

Effets potentiels immédiats : Aucun effet important ou danger critique connu.

Effets potentiels différés : Aucun effet important ou danger critique connu.

Effets chroniques potentiels pour la santé

Généralités : Un contact prolongé ou répété peut dégraisser la peau et entraîner une irritation, des gerçures et/ou une dermatite. Une fois sensibilisé, une vive réaction allergique peut éventuellement se déclencher lors d'une exposition ultérieure à de très faibles niveaux.

Cancérogénicité : Aucun effet important ou danger critique connu.

RUBRIQUE 11: Informations toxicologiques

Mutagénicité : Aucun effet important ou danger critique connu.

Toxicité pour la reproduction : Aucun effet important ou danger critique connu.

Autres informations : Un contact prolongé ou répété peut éventuellement sécher la peau et provoquer une irritation. Les poussières de ponçage et de meulage peuvent être nocives si inhalées. L'exposition répétée à des concentrations élevées de vapeurs peut provoquer une irritation du système respiratoire et des lésions permanentes au cerveau et au système nerveux. L'inhalation de vapeurs ou d'aérosols à des concentrations supérieures aux limites d'exposition préconisées provoque des maux de tête, des états de somnolence, des nausées et peut aboutir à une perte de connaissance ou à la mort. Éviter le contact avec la peau et les vêtements.

11.2 Informations sur les autres dangers

11.2.1 Propriétés perturbant le système endocrinien

Le produit ne répond pas aux critères pour être considéré comme ayant des propriétés perturbatrices endocriniennes selon les critères énoncés dans le Règlement (CE) n° 1907/2006 ou le Règlement (CE) n° 1272/2008.

11.2.2 Autres informations

Non disponible.

RUBRIQUE 12: Informations écologiques

Il n'existe aucune donnée disponible pour le mélange lui-même.
Ne pas laisser pénétrer dans les égouts ni les cours d'eau.

Le mélange a été évalué selon la méthode de la somme de la réglementation du CLP (CE) N° 1272/2008 et est conformément classé pour ses propriétés éco-toxicologiques. Voir Rubriques 2 et 3 pour plus de détails.

12.1 Toxicité

Nom du produit/composant	Résultat	Espèces	Dosage / Exposition
poudre de zinc poussière de zinc (stabilisé)	Aiguë - CE50 - Eau douce	Algues - *Pseudokirchneriella subcapitata*	0.106 mg/l [72 heures]
	Chronique - CE10	Daphnie - Water flea - *Daphnia magna* - Nouveau-né	6.3 µg/l [21 jours]
	Aiguë - CE50 - Eau douce	Daphnie - Water flea - *Daphnia magna*	354 µg/l [48 heures]
	Chronique - CL10 - Eau douce	Poisson - Rainbow trout, donaldson trout - *Oncorhynchus mykiss* - Juvenile (oiselet, couvée, sevrage)	185 µg/l [30 jours]
	Chronique - CE10 - Eau douce	Algues - Green algae - *Raphidocelis subcapitata* - Phase de Croissance Exponentielle	27.3 µg/l [72 heures]
bis-[4-(2,3-époxypropoxy) phényl]propane	Chronique - NOEC	Daphnie	0.3 mg/l [21 jours]
	Aiguë - CL50 - Eau douce	Daphnie - *daphnia magna*	1.8 mg/l [48 heures]
oxyde de zinc	Aiguë - CE50 - Eau douce	Daphnie - Water flea - *Daphnia magna* - Nouveau-né	0.481 mg/l [48 heures]
	Aiguë - CE50	Algues	0.17 mg/l [72 heures]
	Chronique - NOEC - Eau douce	Algues	0.017 mg/l [72 heures]
Hydrocarbures, C9, substances aromatiques > 0.1% cumène	CE50	Daphnie	3.2 mg/l [48 heures]

RUBRIQUE 12: Informations écologiques

	CL50	Poisson	9.2 mg/l [96 heures]
1-méthoxy-2-propanol	Aiguë - CL50 - Eau douce	Poisson - Poisson rouge	>4500 mg/l [96 heures]
	Aiguë - CL50	Daphnie - Daphnie	23300 mg/l [48 heures]
éthylbenzène	Aiguë - CE50 - Eau douce	Daphnie	1.8 mg/l [48 heures]
	Chronique - NOEC - Eau douce	Daphnie - *Ceriodaphnia dubia*	1 mg/l

Conclusion/Résumé : Très toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.

12.2 Persistance et dégradabilité

Nom du produit/composant	Test	Résultat	Dosage / Inoculum
Hydrocarbures, C9, substances aromatiques > 0.1% cumène	-	75% [28 jours] - Facilement	
éthylbenzène	-	79% [10 jours] - Facilement	

Nom du produit/composant	Demi-vie aquatique	Photolyse	Biodégradabilité
bis-[4-(2,3-époxypropoxy) phényl]propane	-	-	Non facilement
Hydrocarbures, C9, substances aromatiques > 0.1% cumène	-	-	Facilement
xylène	-	-	Facilement
éthylbenzène	-	-	Facilement

12.3 Potentiel de bioaccumulation

Nom du produit/composant	LogKoe	FBC	Potentiel
xylène	3.12	7.4 à 18.5	Faible
1-méthoxy-2-propanol	<1	-	Faible
éthylbenzène	3.6	79.43	Faible

12.4 Mobilité dans le sol

Coefficient de répartition sol/eau

Nom du produit/composant	logKoc	Koc
bis-[4-(2,3-époxypropoxy)phényl]propane	4	10465.7
1-méthoxy-2-propanol	1	10.447
éthylbenzène	2.2	170.406
N,N'-Hexane-1,6-diylbis(12-hydroxystéaramide)	4.3	20556.9

12.5 Résultats des évaluations PBT et vPvB

Ce mélange ne contient aucune substance évaluée comme étant un PBT ou un vPvB.

12.6 Propriétés perturbant le système endocrinien

Le produit ne répond pas aux critères pour être considéré comme ayant des propriétés perturbatrices endocriniennes selon les critères énoncés dans le Règlement (CE) n° 1907/2006 ou le Règlement (CE) n° 1272/2008.

RUBRIQUE 12: Informations écologiques

12.7 Autres effets néfastes

Aucun effet important ou danger critique connu.

RUBRIQUE 13: Considérations relatives à l'élimination

Les informations de cette rubrique contiennent des directives et des conseils généraux. Consulter la liste des Utilisations Identifiées de la rubrique 1 pour toute information spécifique aux usages disponible dans le(s) scénario(s) d'exposition.

13.1 Méthodes de traitement des déchets

Produit

Méthodes d'élimination des déchets : Il est recommandé d'éviter ou réduire autant que possible la production de déchets. La mise au rebut de ce produit, des solutions et des sous-produits devra en permanence respecter les exigences légales en matière de protection de l'environnement et de mise au rebut des déchets ainsi que les exigences de toutes les autorités locales. Élimination des produits excédentaires et non recyclables par une entreprise autorisée de collecte des déchets. Ne pas rejeter les déchets non traités dans les égouts, à moins que ce soit en conformité avec les exigences de toutes les autorités compétentes.

Déchets Dangereux :

Catalogue Européen des Déchets

Code de déchets	Désignation du déchet
08 01 11*	déchets de peintures et vernis contenant des solvants organiques ou d'autres substances dangereuses

Emballage

Méthodes d'élimination des déchets : Il est recommandé d'éviter ou réduire autant que possible la production de déchets. Recycler les déchets d'emballage. Envisager l'incinération ou la mise en décharge uniquement si le recyclage est impossible.

Type d'emballage	Catalogue Européen des Déchets
Récipient	15 01 06 emballages en mélange

Précautions particulières : Ne se débarrasser de ce produit et de son récipient qu'en prenant toutes précautions d'usage. Manipuler avec prudence les récipients vides non nettoyés ni rincés. Les conteneurs vides ou les saches internes peuvent retenir des restes de produit. Les vapeurs des résidus de produits peuvent former une atmosphère très inflammable ou explosive à l'intérieur du récipient. Ne pas couper, souder ou broyer les récipients usagés si l'intérieur n'a pas été soigneusement nettoyé. Évitez la dispersion des matériaux déversés, ainsi que leur écoulement et tout contact avec le sol, les cours d'eau, les égouts et conduits d'évacuation.

RUBRIQUE 14: Informations relatives au transport

	ADR/RID	ADN	IMDG	IATA
14.1 Numéro ONU ou numéro d'identification	UN1263	UN1263	UN1263	UN1263
14.2 Désignation officielle de transport de l'ONU	PEINTURES	PEINTURES	PAINT	PAINT
14.3 Classe(s) de danger pour le transport	3	3	3	3
14.4 Groupe d'emballage	III	III	III	III

RUBRIQUE 14: Informations relatives au transport

14.5 Dangers pour l'environnement	Oui.	Oui.	Yes.	Yes. The environmentally hazardous substance mark is not required.
Substances polluantes de l'environnement marin	Non applicable.	Non applicable.	(Zinc powder - zinc dust (stabilized))	Not applicable.

Informations complémentaires

ADR/RID : Le marquage relatif à une substance dangereuse pour l'environnement n'est pas exigé en cas de transport dans des quantités inférieures ou égales à 5 L ou 5 kg.

Code tunnel : (D/E)

ADN : Le marquage relatif à une substance dangereuse pour l'environnement n'est pas exigé en cas de transport dans des quantités inférieures ou égales à 5 L ou 5 kg.

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA : Le marquage relatif à une substance dangereuse pour l'environnement peut être affiché s'il est exigé par d'autres réglementations sur le transport.

14.6 Précautions particulières à prendre par l'utilisateur : **Transport avec les utilisateurs locaux :** toujours transporter dans des conditionnements qui sont corrects et sécurisés. S'assurer que les personnes transportant le produit connaissent les mesures à prendre en cas d'accident ou de déversement accidentel.

14.7 Transport maritime en vrac conformément aux instruments de l'OMI : Non applicable.

RUBRIQUE 15: Informations relatives à la réglementation

15.1 Réglementations/législation particulières à la substance ou au mélange en matière de sécurité, de santé et d'environnement

Règlement UE (CE) n° 1907/2006 (REACH)

Annexe XIV - Liste des substances soumises à autorisation

Annexe XIV

Aucun des composants n'est répertorié.

Substances extrêmement préoccupantes

Aucun des composants n'est répertorié.

Annexe XVII - Restrictions applicables à la fabrication, à la mise sur le marché et à l'utilisation de certaines substances et préparations dangereuses et de certains articles dangereux

Nom du produit/composant	Entrée n° (REACH)
SIGMAZINC 102 HS BASE GREY	3

Étiquetage : Non applicable.

Autres Réglementations UE

Précurseurs d'explosifs : Non applicable.

Substances qui appauvrissent la couche d'ozone (UE 2024/590)

Non inscrit.

les polluants organiques persistants

RUBRIQUE 15: Informations relatives à la réglementation

Non inscrit.

Directive Seveso

Ce produit est contrôlé selon la directive Seveso.

Critères de danger

Catégorie
P5c E1

15.2 Évaluation de la sécurité chimique : Aucune évaluation de la sécurité chimique n'a été mise en œuvre.

RUBRIQUE 16: Autres informations

Indique quels renseignements ont été modifiés depuis la version précédente.

Abréviations et acronymes

ETA = Estimation de la Toxicité Aiguë
CLP = Règlement 1272/2008/CE relatif à la classification, à l'étiquetage et à l'emballage des substances et des mélanges
DNEL = Dose dérivée sans effet
Mention EUH = mention de danger spécifique CLP
PNEC = concentration prédite sans effet
RRN = Numéro d'enregistrement REACH
PBT = Persistantes, Bioaccumulables et Toxiques
vPvB = Très persistant et très bioaccumulable
ADR = L'Accord européen relatif au transport international des marchandises Dangereuses par Route
ADN = Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation intérieure
code IMDG = code maritime international des marchandises dangereuses
IATA = Association international du transport aérien

Procédure employée pour déterminer la classification selon le Règlement (CE) n° 1272/2008 [CLP/SGH]

Classification	Justification
Flam. Liq. 3, H226	D'après les données d'essai
Skin Irrit. 2, H315	Méthode de calcul
Eye Irrit. 2, H319	Méthode de calcul
Skin Sens. 1, H317	Méthode de calcul
Aquatic Acute 1, H400	Méthode de calcul
Aquatic Chronic 1, H410	Méthode de calcul

Texte intégral des mentions H abrégées

H225	Liquide et vapeurs très inflammables.
H226	Liquide et vapeurs inflammables.
H304	Peut être mortel en cas d'ingestion et de pénétration dans les voies respiratoires.
H312	Nocif par contact cutané.
H315	Provoque une irritation cutanée.
H317	Peut provoquer une allergie cutanée.
H319	Provoque une sévère irritation des yeux.
H332	Nocif par inhalation.
H335	Peut irriter les voies respiratoires.
H336	Peut provoquer somnolence ou vertiges.
H350	Peut provoquer le cancer.
H373	Risque présumé d'effets graves pour les organes à la suite d'expositions répétées ou d'une exposition prolongée.
H400	Très toxique pour les organismes aquatiques.
H410	Très toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.

RUBRIQUE 16: Autres informations

H411	Toxique pour les organismes aquatiques, entraîne des effets néfastes à long terme.
H412	Nocif pour les organismes aquatiques, entraîne des effets néfastes à long terme.
H413	Peut être nocif à long terme pour les organismes aquatiques.
EUH066	L'exposition répétée peut provoquer dessèchement ou gerçures de la peau.

Texte intégral des classifications [CLP/SGH]

Acute Tox. 4	TOXICITÉ AIGUË - Catégorie 4
Aquatic Acute 1	TOXICITÉ À COURT TERME (AIGUË) POUR LE MILIEU AQUATIQUE - Catégorie 1
Aquatic Chronic 1	TOXICITÉ À LONG TERME (CHRONIQUE) POUR LE MILIEU AQUATIQUE - Catégorie 1
Aquatic Chronic 2	TOXICITÉ À LONG TERME (CHRONIQUE) POUR LE MILIEU AQUATIQUE - Catégorie 2
Aquatic Chronic 3	TOXICITÉ À LONG TERME (CHRONIQUE) POUR LE MILIEU AQUATIQUE - Catégorie 3
Aquatic Chronic 4	TOXICITÉ À LONG TERME (CHRONIQUE) POUR LE MILIEU AQUATIQUE - Catégorie 4
Asp. Tox. 1	DANGER PAR ASPIRATION - Catégorie 1
Carc. 1B	CANCÉROGÉNICITÉ - Catégorie 1B
Eye Irrit. 2	LÉSIONS OCULAIRES GRAVES/IRRITATION OCULAIRE - Catégorie 2
Flam. Liq. 2	LIQUIDES INFLAMMABLES - Catégorie 2
Flam. Liq. 3	LIQUIDES INFLAMMABLES - Catégorie 3
Skin Irrit. 2	CORROSION CUTANÉE/IRRITATION CUTANÉE - Catégorie 2
Skin Sens. 1	SENSIBILISATION CUTANÉE - Catégorie 1
STOT RE 2	TOXICITÉ SPÉCIFIQUE POUR CERTAINS ORGANES CIBLES - EXPOSITION RÉPÉTÉE - Catégorie 2
STOT SE 3	TOXICITÉ SPÉCIFIQUE POUR CERTAINS ORGANES CIBLES - EXPOSITION UNIQUE - Catégorie 3

Historique

Date d'édition/ Date de révision : 24 Octobre 2025

Date de la précédente édition : 12 Septembre 2025

Élaborée par : EHS

Version : 1.04

Renonciation

Les informations qui se trouvent dans cette fiche sont fondées sur l'état actuel des informations scientifiques et techniques. L'objet de ces informations est d'attirer l'attention sur l'aspect hygiène et sécurité en ce qui concerne les produits fournis par nous, et de suggérer des mesures de précaution pour l'emmagasinage et l'utilisation des produits. Aucune justification ni garantie n'est donnée en ce qui concerne les propriétés des produits. Notre responsabilité ne pourra être recherchée en cas de non observation des mesures de précaution décrites dans cette fiche technique ou d'utilisation inhabituelle des produits.