

CS 6110 Software Correctness, Spring 2022

Lec5

Ganesh Gopalakrishnan
School of Computing
University of Utah
Salt Lake City, UT 84112

URL: bit.ly/cs6110s22



Slides for Lec5 : Agenda

- Bugs matter (loss of lives, property, wasted time, poor user experience..)
 - Therac incident <https://en.wikipedia.org/wiki/Therac-25>
 - Patients killed
 - Heartbleed <https://d Wheeler.com/essays/heartbleed.html>
 - A huge mistake
- Protocols baked into code are inscrutably complex (hard to debug at that level)
 - Build models (like executable blueprints – or like scale model of an airplane in a wind tunnel)
 - Error-prone but can be gotten right - readable rigorous specification!
 - You'll see the styles that matter + the extras (checks in SPIN) that help
 - Murphi's rule-style shines! - will later show the power of Table-based transition systems! (like Excel sheets)
 - Then auto-generate C or protocols – have MULTIPLE models (so we can check all vantage-points)
 - After tuning/tweaking, switch to C-level verification
- Asg-2 is to take you through these paths
 - We will experience typing a model
 - We will sow a bug in Distributed Termination (work channel slack)
 - And experience how verification goes

Take it from the experts!

- Paul E. McKenney
 - Top Linux Developer at IBM (now works for Facebook)
 - Has authored a free book on parallel programming that he maintains
 - A fantastic collection on (shared memory) parallel programming
 - <https://mirrors.edge.kernel.org/pub/linux/kernel/people/paulmck/perfbook/perfbook.2021.12.22a.pdf>
- Look at its table of contents (next slide)

Take it from the experts!

mirrors.edge.kernel.org/pub/linux/kernel/people/paulmck/perfbook/perfbook.2021.12.22a.pdf

c.2021.12.22a.pdf

1 / 630 | — 119% + | [] []

Is Parallel Programming Hard, And, If So, What Can You Do About It?

Edited by:

Paul E. McKenney
Facebook
paulmck@kernel.org

December 22, 2021
Release v2021.12.22a

11.8 Summary 225

12 Formal Verification 227

12.1 State-Space Search 227

12.1.1 Promela and Spin 227

12.1.2 How to Use Promela 229

12.1.3 Promela Example: Locking 232

12.1.4 Promela Example: QRCU 234

12.1.5 Promela Parable: dynticks and Preemptible RCU 239

12.1.6 Validating Preemptible RCU and dynticks 242

12.2 Special-Purpose State-Space Search 254

12.2.1 Anatomy of a Litmus Test 255

12.2.2 What Does This Litmus Test Mean? 256

12.2.3 Running a Litmus Test 256

12.2.4 PPCMEM Discussion 257

12.3 Axiomatic Approaches 258

12.3.1 Axiomatic Approaches and Locking 259

12.3.2 Axiomatic Approaches and RCU 259

12.4 SAT Solvers 261

12.5 Stateless Model Checkers 262

12.6 Summary 262

12.7 Choosing a Validation Plan 264

Dist Term

```
/*---
// Upstream of i is j with j > i. Node numbering clockwise i
// Everything is upstream of root which is 0.
// Node assigning work upstream turns itself B and becomes P
// But that node (that assigns work upstream and turns itself
// C/E means false or true (C is color, which is W or B)
// State Vector: <NP:I, NS:A, NC:W, HasT: W/B/E, NI: 0..N-1>
// NP=node PC, NS=node state, NC=node color,

R01: <NP:I, NS:A, NC:W, HasT:E, NI: ==0> : tokout! ~~>
      <NP:M, NS:A, NC:W, HasT:E, NI: ==0>

R02: <NP:I, NS:A, NC:W, HasT:E, NI: !=0> :           ~~>
      <NP:M, NS:A, NC:W, HasT:E, NI: !=0>

===

A -> P without work assignment for C color node.
R03: <NP:M, NS:A, NC:C1, HasT:C2, NI: any> : silently ~~>
      <NP:M, NS:P, NC:C1, HasT:C2, NI: any>

A -> P with work assignment, upstream
R04: <NP:M, NS:A, NC:C1, HasT:C2, NI: any> : workupst! ~~>
      <NP:M, NS:P, NC:B, HasT:C2, NI: any>

A -> P with work assignment, downstream
R05: <NP:M, NS:A, NC:C1, HasT:C2, NI: any> : workdnst! ~~>
      <NP:M, NS:P, NC:C1, HasT:C2, NI: any>
```

Dist Term

```
A -> token being ingested : HasT acquires token color
R06: <NP:M, NS:A, NC:C1, HasT:C2, NI: any> : tokin?C3 ~~>
      <NP:M, NS:A, NC:C1, HasT:C3, NI: any>

A -> does not accept work!
A -> can absorb token but does not send it out till it goes P!

===

P -> A by absorbing work
R07: <NP:M, NS:P, NC:C1, HasT:C2, NI: any> : work? ~~>
      <NP:M, NS:A, NC:C1, HasT:C2, NI: any>

P -> Can circulate token if needed, and the token color depends on node
color is B
R08: <NP:M, NS:P, NC:B, HasT:C2, NI: any> : C2 != E / tokout!B ~~>
      <NP:M, NS:P, NC:W, HasT:E, NI: any>

Do this if node color is W and NI is not 0
R09: <NP:M, NS:P, NC:W, HasT:C2, NI: any> : C2 != E / tokout!C2 ~~>
      <NP:M, NS:P, NC:W, HasT:E, NI: any>

Do this if node color is W and NI is 0 and local token is B
R10: <NP:M, NS:P, NC:W, HasT:B, NI: 0> : tokout!W ~~>
      <NP:M, NS:P, NC:W, HasT:E, NI: 0>

Do this if node color is W and NI is 0 and local token is W
R11: <NP:M, NS:P, NC:W, HasT:W, NI: 0> ~~> Termination

Do this if P and HasT == E
R11: <NP:M, NS:P, NC:C1, HasT:E, NI: any> : tokin?C2 ~~>
```

Dist Term

```
Do this if node color is W and NI is 0 and local token is W
R11: <NP:M, NS:P, NC:W,  HasT:W, NI: 0> ~~> Termination
```

```
Do this if P and HasT == E
```

```
R11: <NP:M, NS:P, NC:C1, HasT:E,  NI: any> :  token?C2 ~~>
      <NP:M, NS:P, NC:C1, HasT:C2, NI: any>
```

```
---*/
```

```
#define Ns      3      /* nr of processes (use 5 for demos) */
```

```
#define WORK    1      /* does not matter what this is */
```

```
mtype = { B, W, E, A, P }; // B,W are for token and node color
```

```
chan workqArray[Ns] = [0] of { bit }; /* rendezvous channels
```

```
chan tokqArray[Ns]  = [1] of { mtype }; // really only B,W ;
```

```
mtype ns[Ns]; // really only A,P
```

```
bit terminated = 0;
```

```
proctype node (chan tokIn, tokOut, workIn; byte myid)
```

```
{ mtype nc    = W;
```

```
  mtype HasT = E; /* These xr/xs will throw a false viol
```

```
                  /* Suppress this error by turning off
```

```
  xr tokIn;  xs tokOut;  byte pick = 0;
```

```
  if :: myid == 0 -> tokOut!W :: myid != 0 fi; //--R01
```

```
  do
```

```
    :: ns[myid] == A ->
```

```
    ...fill...
```

```
    :: ns[myid] == P ->
```

```
    ...fill...
```

```
  od;
```


Dist Term

```
od;
end:
//terminated is true here
  assert (...what...)
}

init {
byte i = Ns-1;
  atomic {
    do
      :: i > 0 ->      //--covered by first ND asg-->
        ns[i] = ...figure out...
        run node(tokqArray[i], tokqArray[i-1], workqArray[i], i);
        i--
      :: i == 0 ->
        ns[i] = ...figure out...
        run node(tokqArray[0], tokqArray[Ns-1], workqArray[i], i);
        break
    od
  }
}

//--comment out when doing invalid end-state safety first
never {
do
:: skip
:: terminated &&
  (...what...)
  -> break
od
accept: 1 -> goto accept
```