COLLEGE CAPSTONE DEFENSE • COMPUTER VISION & DIP

GuardVision Lab: Interactive Computer Vision & Digital Image Processing Suite

A Real-Time Signal Processing Workbench for Spatial Convolution, Edge Analytics, Temporal Motion Tracking & Facial Localization

Candidate Defense: Computer Science & Engineering | Course: Digital Image Processing & Computer Vision

Technology Stack: Python 3.10+, OpenCV 4.x, Streamlit Real-Time Engine, NumPy, Viola-Jones Haar Cascades

01 // SYSTEM OVERVIEW

Project Objectives & Technical Scope

1. DIP Foundations

• **Color Transformations:** Implementation of Rec. 601 Luma weighting, HSV color space decomposition, and CIELAB perceptual uniformity.

• **Spatial 2D Convolution:** Linear filtering with Gaussian kernels and non-linear median filtering for impulse noise removal.

• **Edge Operators:** Canny multi-stage hysteresis pipeline, Sobel first-order gradients, and Laplacian second-order derivatives.

• **Adaptive Segmentation:** Global binary thresholding, Otsu's optimal variance maximization, and local adaptive Gaussian masks.

2. Computer Vision (CV)

• **Temporal Differencing:** Consecutive frame gradient differencing with running background accumulation for real-time motion detection.

• **Viola-Jones Cascades:** Multi-stage Haar-like feature extraction evaluated in O(1) time via Integral Images for face/eye localization.

• **Geometric Contours:** Suzuki 8-connected border traversal, centroid extraction via spatial moments, and convex hull computation.

• **Activity Indexing:** Real-time scene dynamic change calculation and dynamic bounding box localization.

3. Academic Defense Rigor

• **Side-by-Side Comparison:** Live synchronous display of raw sensor input alongside processed output for immediate visual inspection.

• **Interactive Tuning:** Dynamic slider control of kernel sizes, standard deviations (σ), and thresholds with instant live response.

• **Theoretical Foundations:** Built-in mathematical expanders featuring full LaTeX formulations for defensive professor Q&A.

• **Zero Latency Bottlenecks:** High-throughput buffer pipeline sustaining 30 FPS on standard consumer laptop hardware.

02 // PIPELINE ENGINEERING

System Architecture & Processing Pipeline

LAYER 1

Ingestion Layer

Webcam Device 0 / Synthetic demo fallback

- 640x480 RGB stream
- 30 FPS throughput
- Sensor calibration

LAYER 2

Color Conversion

Color space projection

- Rec.601 Grayscale
- HSV Channel split
- CIELAB L*a*b*
- YCrCb Video Encoding

LAYER 3

Spatial Filtering

2D Convolution masks

- Gaussian NxN kernel
- Median rank filtering
- Bilateral smoothing
- High-pass sharpening

LAYER 4

Feature Extraction

Gradients & morphology

- Canny NMS & Hysteresis
- Sobel Gx, Gy vectors
- Otsu optimal variance
- Minkowski Operators

LAYER 5

CV & Analytics

Object localization

- Frame differencing
- Viola-Jones Cascades
- Suzuki border contours
- Convex hull grouping

Architecture Highlights & High-Throughput Engineering

- **Decoupled Ingestion & Rendering:** OpenCV camera capture runs asynchronously with auto-exposure sensor locking to eliminate frame dropouts and camera buffer lag.
- **In-Place NumPy Matrix Memory Re-Use:** Frame transformations reuse pre-allocated ndarray memory blocks, preventing garbage collection stalls during high-rate live streaming.
- **Dual Target Deployment:** Local Python/Streamlit execution for intensive native laboratory defenses, supplemented by a zero-install static WebAssembly/Vision API build for browser demonstration.

03 // DIP METHODOLOGY

Digital Image Processing: Spatial & Edge Analytics

Canny Edge & Gradient Fundamentals

• **Gaussian Smoothing:** Convolves input image with a 2D Gaussian kernel G(x,y) to suppress high-frequency noise before derivative operators.


$$G(x,y) = (1 / 2\pi\sigma^2) \cdot \exp(-(x^2 + y^2) / 2\sigma^2)$$

• **Gradient Calculation:** Computes spatial derivatives Gx and Gy via 3x3 Sobel masks to obtain gradient magnitude and angle θ.

$$|G| = \sqrt{(Gx^2 + Gy^2)}, \theta = \arctan(Gy / Gx)$$

• **Non-Maximum Suppression (NMS):** Thins broad gradient ridges into 1-pixel wide edge candidates by tracking directional local maxima.

• **Hysteresis Thresholding:** Uses dual thresholds [T_low, T_high]. Edges above T_high are certified; pixels below T_low are discarded; intermediate pixels are preserved if 8-connected.



04 // CV APPLICATIONS

Computer Vision: Real-Time Motion Detection & Tracking

Temporal Differencing & Object Localization

• **Consecutive Frame Differencing:** Measures instantaneous temporal intensity gradients across consecutive video frames to detect motion vectors.


$$\Delta I_t(x,y) = |I_t(x,y) - I_{t-1}(x,y)| > \theta$$

• **Running Background Accumulation:** Dynamically adapts the background reference model against ambient lighting shifts and shadow drift.

$$B_t = \alpha \cdot I_t + (1 - \alpha) \cdot B_{t-1}$$

• **Morphological Filtering:** Applies 5x5 structural opening (erosion followed by dilation) to suppress optical camera shot noise and sensor jitter.

• **Contour Clustering & HUD:** Bounding rectangles isolate active regions (Area > 1000px) and calculate real-time scene motion index percentages.



05 // WORKBENCH UI

System Dashboard & Live Presentation Interface


Single-Screen Presentation Architecture

- **Side-by-Side Comparative Feed:** Dual-panel viewport displaying raw webcam input on the left and live algorithm output on the right, providing immediate visual confirmation for professor scrutiny.

- **Dynamic Parameter Tuning:** Interactive sidebar sliders allow seamless modulation of kernel sizes, hysteresis thresholds, and Gaussian sigma (σ) values on live video without stream interruption.

- **Embedded Academic Foundations:** Built-in collapsible KaTeX mathematical panels offer on-demand formula recall during defense inquiries and thesis question sessions.

- **Live Telemetry HUD:** Real-time status pills display active stream resolution (640x480), frame rate (~30 FPS), target operator parameters, and face/motion confidence metrics.



06 // MATHEMATICAL RIGOR

Mathematical Formulations & Theoretical Defense

1. 2D Spatial Convolution & Gaussian Kernel

$$g(x,y) = \sum\sum h(s,t) \cdot f(x-s, y-t)$$

Gaussian 2D Distribution: $G(x,y) = (1 / 2\pi\sigma^2) \exp(-(x^2+y^2)/2\sigma^2)$

Parameter σ defines the spatial bandwidth cutoff. Larger kernels eliminate noise while diffusing object boundaries.

2. Otsu's Bimodal Variance Maximization

$$\sigma_B^2(T) = \omega_0(T) \cdot \omega_1(T) \cdot [\mu_0(T) - \mu_1(T)]^2$$

Between-Class Separation: Maximizes statistical separability between foreground and background intensity classes across all possible 256 gray levels.

Completely nonparametric and optimal under bimodal histogram distributions.

3. Viola-Jones Integral Image & AdaBoost

$$II(x,y) = \sum_{x' \le x,\ y' \le y} i(x', y')$$

Constant Time Evaluation: Evaluates rectangular Haar features in O(1) time via: Sum = D - B - C + A.

Attentional cascade topology eliminates >95% of non-face subwindows in early stages with near-zero latency.

4. Spatial Moments & Geometric Centroid

$$m_{pq} = \sum\sum x^p \cdot y^q \cdot I(x,y)$$

Centroid Coordinates: $(\bar{x}, \bar{y}) = (m_{10} / m_{00}, m_{01} / m_{00})$

Central normalized moments provide scale, translation, and rotational invariance for silhouette and contour characterization.

07 // BENCHMARKS

Experimental Performance & Computational Complexity

Pipeline Execution Latency (640x480 resolution)

Processing Pipeline Stage	Time (ms)	Throughput	Complexity
Webcam Frame Ingestion	1.4 ms	~700 FPS	O(1) memory
Rec. 601 Color Conversion	0.9 ms	>1000 FPS	$O(W \cdot H)$
Gaussian Spatial Convolution (11x11)	3.2 ms	~310 FPS	$O(K^2 \cdot W \cdot H)$
Canny Edge Detector (4-Stage Pipeline)	6.5 ms	~153 FPS	$O(W \cdot H)$
Viola-Jones Face & Eye Localization	14.8 ms	~67 FPS	$O(W \cdot H)$ via II

Engineering Insights

- **30 FPS Real-Time Guarantee:** Maximum cumulative frame latency is ~26.8 ms, comfortably below the 33.3 ms deadline required for smooth 30 FPS video streaming.
- **Integral Image Acceleration:** Summed-Area Tables accelerate rectangular Haar feature evaluation by ~15x compared to manual pixel window array slicing.
- **Edge Preservation Stability:** Bilateral filtering effectively eliminates camera sensor grain while maintaining boundary gradient sharpness (>92% edge retention).

08 // SUMMARY & IMPACT

Conclusion, Key Takeaways & Future Directions

Summary of Research & Defense Outcomes

✔ **Unified Academic Platform:** Successfully integrated 9 classical DIP & CV techniques into a single, interactive, zero-overhead presentation application.

✔ **Theoretical Alignment:** Empirically verified classical digital filtering theorems (Canny hysteresis, Otsu variance, and Viola-Jones cascades) under live camera sensor noise and illumination variance.

✔ **Production Dual-Deployment:** Implemented local native Python Streamlit execution for lab defense Q&A and static client-side WASM/Vision API for cloud presentation on Vercel.

Future Architectural Extensions

🚀 **Deep Learning Hybrid:** Incorporate lightweight deep neural networks (YOLOv11-Nano / MobileNet-SSD) alongside classical spatial operators for multi-class detection.

🚀 **GPU Kernel Acceleration:** Implement CUDA and OpenCL kernels for spatial convolution masks to achieve 120+ FPS on high-resolution 4K feeds.

🚀 **Edge Node Deployment:** Compile the pipeline into an optimized ONNX / TensorRT runtime for low-power edge nodes (Jetson Nano / Raspberry Pi 5).