

Lab-10 Ex4 - `fgets` and `scanf` (II)

Repeat Ex2 but with `fgets()` instead of `scanf()` this time:

Create a char array `inputArray` of size 20 and set all elements to 0
Prompt "User input: "
Use `fgets` to get a string from user into `inputArray`
Print the 20 elements of `inputArray` one by one, as a number (i.e. ASCII
Print `inputArray` to the screen, as a string

Do you see the difference in behavior? How does `fgets()` differ from `scanf()`?

(If you forgot syntax of `fgets()`, please check your lecture notes)

User input is ***bold and italic*** in the following sample runs.

Sample run #1

User input: ***HELLO WORLD***

72 69 76 76 79 32 87 79 82 76 68 10 0 0 0 0 0 0 0 0

HELLO WORLD

Reflection: In the sample above, the code of the last character of the string before null character is 10. What is the character with ASCII code 10? Why is it there?

Sample run #2

User input: ***I want Christmas***

73 32 119 97 110 116 32 67 104 114 105 115 116 109 97 115 10 0 0 0 0

I want Christmas

Sample run #3

User input: ***HELLO I AM A SUPERSTAR!***

72 69 76 76 79 32 73 32 65 77 32 65 32 83 85 80 69 82 83 0

HELLO I AM A SUPERS

Reflection: In this example, we have an input over 19 characters. What do you observe?