

Lab-10 Ex2 - `fgets` and `scanf` (PreLab*)

In the lecture notes we have covered two ways to get a string from user - `fgets()` and `scanf()`. Do you know the difference between these two methods? In this exercise, let's try them out!

Let's try our old friend, `scanf()` first? Please follow the pseudocode below:

```
Create a char array inputArray of size 20 and set all elements to 0
Prompt "User input: "
Use scanf to get a string from user into inputArray
Print the 20 elements of inputArray one by one, as a number (i.e. ASCII)
Print inputArray to the screen, as a string
```

You will be able to observe the behavior of `scanf()` as in the sample runs below. Can you see how `scanf()` handles input strings with spaces?

User input is ***bold and italic*** in the following sample runs.

Sample run #1

User input: ***HELLO***

72 69 76 76 79 0 0 0 0 0 0 0 0 0 0 0 0 0 0

HELLO

Sample run #2

User input: ***HELLO WORLD***

72 69 76 76 79 0 0 0 0 0 0 0 0 0 0 0 0 0 0

HELLO

Sample run #3

User input: ***HELLO-WORLD***

72 69 76 76 79 45 87 79 82 76 68 0 0 0 0 0 0 0 0

HELLO-WORLD

You may assume user input is always 19 characters (Why 19?).

Reflection: Have you tried inputting a string of more than 19 characters long? Do you see the null terminating character? (You will learn the concept of "Buffer Overflow" in future courses.)