

Lab Course
Efficient Programming of Multicore Processors
and Supercomputers

Michael Gerndt, Josef Weidendorfer
Lehrstuhl für Rechnertechnik und
Rechnerorganisation/Parallelrechnerarchitektur

Schedule Today

- Introduction
- Heat equation code
- SuperMUC at LRZ
- Groups/Accounts

Goals

- Overview of parallel architectures
- Understand sequential tuning
- Learn programming in MPI and OpenMP
- Know parallelization strategies
 - Domain decomposition
 - Task decomposition

Program

- Presentation
- Discussion of tasks and of your solutions
- Group meetings

Tasks

- Tasks
 - Sequential optimization of solver for heat distribution
 - OpenMP parallelization
 - MPI parallelization
 - Parallelization of Abalone
- Groups of three people

Grading


- Criteria

- Stick to deadlines
- Design and implementation
- Readability of codes
- Reports
- Additional points for additional features
- Presentation of your solution

- To do

- Implement the solution
- Write a small report.
- Submit Report on Tuesday before the next meeting.
- We will look at the report and select presenters for certain parts. You will be informed on Wednesday to prepare a presentation. Presentation could take us through the part of the report if you cannot do slides.

Heat Distribution in a Solid Body



Model

- The heat distribution in a 2d solid body can be modeled by the following partial differential equation (Poisson equation)

$$-\frac{\partial^2 u}{\partial x^2} - \frac{\partial^2 u}{\partial y^2} = k * \frac{\partial u}{\partial t}$$

where $u(x,y,t)$ is the temperature at point (x,y) at time t .


- In a stable state the change is 0 over time.

$$-\frac{\partial^2 u}{\partial x^2} - \frac{\partial^2 u}{\partial y^2} = 0$$

- We solve the equation on the discretized unit square $(0,1) \times (0,1)$ with Dirichlet boundary conditions: fixed temperature on the boundary.

Solver Kernel

- Solver kernel for a simple partial differential equation.
- Grid $(n+2) \times (n+2)$
- Fixed boundaries
- Interior points are recomputed
- Simple iterative solver
 - Mean value of four neighbor points (“4 point stencil”) until allover residuum is below threshold
 - Jacobi method
 - values from previous iteration
 - Gauss-Seidel method
 - new values of upper and left point
 - old values of lower and right point



Application Source

- On the home page of the lab course
- Configuration via input file

```
100      # iterations (0: until residuum < threshold)
300      # initial resolution of x/y discretization
3100     # max resolution
200      # resolution step size
0        # Algorithm 0=Jacobi 1=Gauss
2                # number of heat sources
0.0  0.0  1.0  1.0      # (x,y), size, temperature
1.0  1.0  1.0  0.5
```

- Result
 - Residuum after specified number of iterations
 - Visualization via ppm file

Application Source

- Download and extract (tar xzf heat.tgz)
- check Makefile
- Build and run
 - make
 - ./heat test.dat