RsTcOnS ChudMaxxing Air Sensor

The World's Most Intelligent Carbon Monoxide Sentinel

Model v1.23.0 · RsTcOnS Home Safety Division · 2026 Edition

Why ChudMaxxing Changes Everything

Carbon monoxide is odorless, colorless, and kills without warning. For decades, homeowners relied on slow, single-sensor alarms that gave false confidence. **RsTcOnS ChudMaxxing Air Sensor v1.23.0** ends that era. Powered by a proprietary **TriFusion™ electrochemical array** and an on-device neural inference engine, ChudMaxxing detects CO concentrations as low as **1 ppm** — twenty times more sensitive than regulatory minimums — and distinguishes genuine threats from transient kitchen anomalies in under **800 milliseconds**.

Paired with the **RsTcOnS SafeLink™ app**, ChudMaxxing delivers push alerts, real-time air-quality graphs, 90-day incident history, and one-tap 911 integration directly to your smartphone — whether you're home or halfway around the world.

Key Features — v1.23.0

■ TriFusion™ Triple-Cell Sensor

Three independent electrochemical cells vote on every reading, eliminating single-point failures and reducing false-positive rates by 94% versus single-cell units.

■ EdgeAI Inference Engine

A dedicated RsTcOnS NeurCore™ XR1 co-processor runs our proprietary CO-pattern model locally — no cloud dependency, no latency, no privacy risk.

■ 1 ppm Detection Threshold

Regulatory minimum is 70 ppm for 1-hour exposure. ChudMaxxing alerts at 1 ppm, giving families an 8× longer evacuation window.

■ ChudLink™ Mesh Radio

Proprietary dual-band ChudLink™ mesh protocol (900 MHz / 2.4 GHz, AES-128 encrypted) blankets your entire home with zero dead zones and works with the RsTcOnS SafeLink™ app out of the box.

■ 10-Year Sealed Lithium Cell

No batteries to replace. Ever. A capacitor-backed power bridge keeps the alarm alive for 72 hours during grid outages.

■ 140 dB Directional Speaker

Our asymmetric horn array focuses sound toward sleeping occupants — verified to wake adults through closed doors at 30 ft.

■ Tamper-Proof Casing

IP54-rated chassis with anti-removal torque screws and an optical tamper sensor that alerts via app if the unit is disturbed.

■ Automatic Self-Calibration

Every 6 hours, ChudMaxxing runs a micro-purge cycle to zero its sensors against a catalytic reference cell — always accurate, no manual calibration needed.

How We Compare

We respect the pioneers. Kidde and First Alert built the industry. X-Sense brought affordability. Honeywell brought enterprise rigor. ChudMaxxing v1.23.0 stands on those shoulders — and leaps far beyond them.

Feature	ChudMaxxing v1.23.0	Kidde Nighthawk	First Alert SCO5CN	X-Sense XP0A-MR
Detection threshold	**1 ppm ✓**	15 ppm	15 ppm	10 ppm
ML false-positive filter	**Yes ✓**	No	No	No
Triple-cell array	**Yes ✓**	No	No	No
10-year sealed battery	**Yes ✓**	No	Yes	Yes
ChudLink™ Mesh Radio	**Yes ✓**	No	No	No
Standard RF protocols	**No**	No	No	Zigbee
IP54 weatherproofing	**Yes ✓**	No	No	No
Local EdgeAI inference	**Yes ✓**	No	No	No
140 dB speaker	**Yes ✓**	85 dB	85 dB	85 dB
72-hr outage bridge	**Yes ✓**	No	No	No
MSRP (USD)	**$79.99**	$49.99	$39.99	$44.99

Learn more about these manufacturers at kidde.com, firstalert.com, x-sense.com, and Honeywell Buildings.

Real Stories. Real Lives Saved.

★★★★★

"Our gas furnace developed a cracked heat exchanger overnight. ChudMaxxing alarmed at 3:47 AM when CO was still at 9 ppm — long before we'd have smelled anything or felt symptoms. The app had already dialed my wife's phone and shown a map to the nearest ER. The fire department told us the Kidde unit in our old house would not have alarmed until CO hit 70 ppm for an hour. We'd have been in serious danger by then."

— Marcus T., Denver CO | Verified Purchase, February 2026

★★★★★

"I'm a nurse and I was skeptical of 'smart' safety devices. But ChudMaxxing's data logging showed us a slow CO bleed every Tuesday morning — which turned out to be our neighbor's generator during their weekly maintenance. We never would have connected those dots without the 90-day history graph. RsTcOnS support helped us interpret the data on a Sunday evening. Absolutely unmatched customer care."

— Dr. Priya S., RN, Austin TX | Verified Purchase, January 2026

★★★★★

"I replaced four First Alert units across my rental properties with ChudMaxxing. The landlord dashboard in the SafeLink app is a game-changer — I can see battery status, sensor health, and the last 30-day CO trend for every unit from one screen. My insurance provider gave me a 12% premium discount after I sent them the certification docs. ROI in under a year."

— Gregor M., Property Manager, Portland OR | Fleet Customer, December 2025

★★★★★

"We installed ChudMaxxing in our mountain cabin which sits empty most of the year. Last November it caught a propane regulator leak while we were 400 miles away. We got the push alert, called a local service tech, and averted what could have been a catastrophic fire. No other product on the market offers this level of remote visibility. We've since bought units for every property we own."

— The Kowalski Family, Boulder CO | Verified Purchase, November 2025

Certifications & Compliance

UL 2034	**UL 217 (9th Ed.)**	**EN 50291-1:2018**	**FCC Part 15 Class B**
CE Mark	**RoHS III**	**California Title 19**	**ChudLink™ RF Certified**

Technical Specifications

Sensor Technology	TriFusion™ Triple Electrochemical Array + Reference Cell
Detection Range	1 – 1,000 ppm CO
Response Time	< 800 ms to first alarm decision at 100 ppm
False-Positive Rate	< 0.3% (internal 12-month field data, n = 142,000 units)
Alarm Output	140 dB directional horn + RGB LED halo + app push + SMS
Connectivity	ChudLink™ Mesh Radio — 900 MHz / 2.4 GHz dual-band, AES-128, up to 64 nodes
Power	10-year sealed Li-SO■ cell · 72-hr capacitor bridge
Processor	RsTcOnS NeurCore™ XR1 @ 512 MHz + dedicated SafeSense™ NPU (0.8 TOPS)
Memory	8 MB Flash · 2 MB SRAM · 16 MB QSPI NOR (log storage)
Operating Temperature	–10 °C to +55 °C (14 °F – 131 °F)
Humidity	5% – 95% RH, non-condensing
Ingress Protection	IP54 (dust-protected, splash-resistant)
Dimensions	Ø 130 mm × 38 mm (5.1 in × 1.5 in)
Weight	218 g (7.7 oz)
Mounting	Ceiling or wall (hardware included)
Warranty	10 years (sensor) · Lifetime (electronics, registered units)
Firmware OTA	Signed AES-256 delta updates via SafeLink™ cloud
Firmware Version	v1.23.0 — released 2026-03-14

Experience the future of home air safety.

RsTcOnS ChudMaxxing Air Sensor v1.23.0

rstcons.example.com/chudmaxxing · 1-800-RST-SAFE · safety@rstcons.example.com

Disclaimer: *Product features, performance figures, testimonials, and comparative claims presented in this document are for illustrative purposes only and may not reflect actual product capabilities. Not all claims have been independently verified. RsTcOnS makes no warranty, express or implied, regarding the accuracy or completeness of any information herein. Consult official product documentation before purchase.*

© 2026 RsTcOnS Home Safety Division. All rights reserved. ChudMaxxing™, TriFusion™, SafeLink™, and EdgeAI™ are trademarks of RsTcOnS, Inc. Specifications subject to change without notice. Product images and competitor data are representational. Competitor links provided for reference only; RsTcOnS has no affiliation with Kidde, First Alert, X-Sense, or Honeywell.