

Theory of Computation
CSC 339 – Spring 2021

Chapter-4: part1
Decidability

King Saud University
Department of Computer Science
Dr. Azzam Alsudais

Introduction

- **Turing-recognizable languages**

- **A language L is called Turing-recognizable if there is a TM that recognizes it.**

Introduction

➤ Turing-recognizable languages

- A language L is called Turing-recognizable if there is a TM that recognizes it.
- The TM may or may not halt on strings $\notin L$.

Introduction

‣ Turing-recognizable languages

- A language L is called Turing-recognizable if there is a TM that recognizes it.
- The TM may or may not halt on strings $\notin L$.
- Also called Turing-acceptable or recursively-enumerable

‣ Turing-decidable languages

- A language L is called Turing-decidable if there is a TM that decides it.

Introduction

‣ Turing-recognizable languages

- A language L is called Turing-recognizable if there is a TM that recognizes it.
- The TM may or may not halt on strings $\notin L$.
- Also called Turing-acceptable or recursively-enumerable

‣ Turing-decidable languages

- A language L is called Turing-decidable if there is a TM that decides it.
- The TM always halts on every input.

Introduction

‣ Turing-recognizable languages

- A language L is called Turing-recognizable if there is a TM that recognizes it.
- The TM may or may not halt on strings $\notin L$.
- Also called Turing-acceptable or recursively-enumerable

‣ Turing-decidable languages

- A language L is called Turing-decidable if there is a TM that decides it.
- The TM always halts on every input.
- Also called recursive languages

Decidability

‣ **Problem: is X a prime number?**

Decidability

- **Problem: is X a prime number?**
- **Corresponding language: PRIMES = $\{1, 2, 3, 5, 7, \dots\}$**

Decidability

- **Problem: is X a prime number?**
- **Corresponding language: PRIMES = $\{1, 2, 3, 5, 7, \dots\}$**
- **Can we decide (solve) this problem?**

Decidability

- **Problem: is X a prime number?**
- **Corresponding language: PRIMES = $\{1, 2, 3, 5, 7, \dots\}$**
- **Can we decide (solve) this problem?**
 - **If we can devise a TM (or an algorithm) that decides whether a given number is prime, then the language is decidable.**

Decidability

‣ **Problem:** is X a prime number?

‣ **Suggested Algorithm:**

On input x :

- Divide x by all possible numbers between 2 and \sqrt{x}

Decidability

‣ **Problem:** is X a prime number?

‣ **Suggested Algorithm:**

On input x :

- *Divide x by all possible numbers between 2 and \sqrt{x}*
- *If any of those numbers can divide x , then **reject***

Decidability

‣ **Problem:** is X a prime number?

‣ **Suggested Algorithm:**

On input x :

- *Divide x by all possible numbers between 2 and \sqrt{x}*
- *If any of those numbers can divide x , then **reject***
- *Else, **accept***

Decidability



› If L is decidable so is L^c .

L^c or L 's complement is the set of elements that are not in L

Decidability

› If L is decidable so is L^c .

L^c or L 's complement is the set of elements that are not in L




Decidability

- › If L is decidable so is L^c .
- › Given a TM M that decides L , how can we build TM M' that decides L^c ?

Decidability

- › If L is decidable so is L^c .
- › Given a TM M that decides L , how can we build TM M' that decides L^c ?



Replace every
accept state
with a reject
state, and
vice versa

Decidability

Classes of languages

