



Theory of Computation

CSC 339 – Spring 2021

Chapter-7: part4

NP-Completeness

King Saud University
Department of Computer Science
Dr. Azzam Alsudais

Introduction

➤ Recall that problems in NP are decision problems that can be solved in polynomial time on nondeterministic TMs.

Introduction

- Recall that problems in NP are decision problems that can be solved in polynomial time on nondeterministic TMs.
- A polynomial time solution to some problems in NP can be used to solve all problems in NP.
- These problems are called NP-complete.

Introduction

- Recall that problems in NP are decision problems that can be solved in polynomial time on nondeterministic TMs.
- On the other hand, problems in P are decision problems that can be solved in polynomial time on deterministic TMs.

Introduction

› **Late 1960's and early 1970's, the Cook-Levin theorem was introduced:**

Introduction

➤ **Late 1960's and early 1970's, the Cook-Levin theorem was introduced:**

➤ **NP-completeness: the complexity of some problems in NP is related to that of the entire class.**

Introduction

- **Late 1960's and early 1970's, the Cook-Levin theorem was introduced:**
 - **NP-completeness: the complexity of some problems in NP is related to that of the entire class.**
 - **SAT: The Boolean Satisfiability problem is NP-complete.**

Introduction

- **Late 1960's and early 1970's, the Cook-Levin theorem was introduced:**
 - **NP-completeness: the complexity of some problems in NP is related to that of the entire class.**
 - **SAT: The Boolean Satisfiability problem is NP-complete.**
- **What does it mean for a problem L to be NP-complete?**

Introduction

- **Late 1960's and early 1970's, the Cook-Levin theorem was introduced:**
 - **NP-completeness: the complexity of some problems in NP is related to that of the entire class.**
 - **SAT: The Boolean Satisfiability problem is NP-complete.**
- **What does it mean for a problem L to be NP-complete?**
 - **If a polynomial time algorithm solves an NP-complete problem, then all other problems in NP can be solved in polynomial time.**

NP-Completeness

› What does it mean for a problem L to be NP-complete?

NP-Completeness

- What does it mean for a problem L to be NP-complete?
 - L is in NP, and

NP-Completeness

- **What does it mean for a problem L to be NP-complete?**
 - L is in NP, and
 - **All problems in NP are reducible to L in polynomial time.**

NP-Completeness

- **What does it mean for a problem L to be NP-complete?**
 - L is in NP, and
 - **All problems in NP are reducible to L in polynomial time.**
- **Why is NP-complete important?**

NP-Completeness

- **What does it mean for a problem L to be NP-complete?**
 - L is in NP, and
 - All problems in NP are reducible to L in polynomial time.
- **Why is NP-complete important?**
 - To show that $P = NP$, all we need to do is find a polynomial time algorithm to an NP-complete problem.

NP-Completeness

- **What does it mean for a problem L to be NP-complete?**
 - L is in NP, and
 - All problems in NP are reducible to L in polynomial time.
- **Why is NP-complete important?**
 - To show that $P = NP$, all we need to do is find a polynomial time algorithm to an NP-complete problem.
 - To show that $P \neq NP$, if a problem in NP requires more than polynomial time, an NP-complete one does.

NP-Completeness: Satisfiability Problem (SAT)

➤ A boolean formula is an expression involving boolean variables and operations.

NP-Completeness: Satisfiability Problem (SAT)

- A boolean formula is an expression involving boolean variables and operations.
- A boolean formula is satisfiable if some assignment of 0's and 1's makes the formula evaluate to 1.

NP-Completeness: Satisfiability Problem (SAT)

- A boolean formula is an expression involving boolean variables and operations.
- A boolean formula is satisfiable if some assignment of 0's and 1's makes the formula evaluate to 1.
- Take the following formula
 - $\varphi = (\bar{x} \wedge y) \vee (x \wedge \bar{z})$
 - To satisfy φ , we may assign these values
 - $x = 0$
 - $y = 1$
 - $z = 0$

NP-Completeness: Satisfiability Problem (SAT)

- A boolean formula is an expression involving boolean variables and operations.
- A boolean formula is satisfiable if some assignment of 0's and 1's makes the formula evaluate to 1.

➤ Take the following formula

$$\varphi = (\bar{x} \wedge y) \vee (x \wedge \bar{z})$$

➤ To satisfy φ , we may assign these values

$$x = 0$$

$$y = 1$$

$$z = 0$$

Theorem 7.27

SAT \in P iff P = NP.

NP-Completeness: Polynomial Time Reducibility

Definition 7.28

A function $f: \Sigma^* \rightarrow \Sigma^*$ is a polynomial time computable function if some polynomial time Turing machine M exists that halts with just $f(w)$ on its tape, when started on any input w .

NP-Completeness: Polynomial Time Reducibility

Definition 7.28

A function $f: \Sigma^* \rightarrow \Sigma^*$ is a polynomial time computable function if some polynomial time Turing machine M exists that halts with just $f(w)$ on its tape, when started on any input w .

Definition 7.29

Language A is *polynomial time reducible*, to language B , written $A \leq_P B$, if a polynomial time computable function $f: \Sigma^* \rightarrow \Sigma^*$ exists, where for every w ,

$$w \in A \iff f(w) \in B.$$

The function f is called the *polynomial time reduction* of A to B .

NP-Completeness: Polynomial Time Reducibility

Definition 7.28

A function $f: \Sigma^* \rightarrow \Sigma^*$ is a polynomial time computable function if some polynomial time Turing machine M exists that halts with just $f(w)$ on its tape when started on any input w .

***The main idea is to use
one problem to solve another!***

written $A \leq_P B$, if a polynomial time computable function $f: \Sigma^* \rightarrow \Sigma^*$ exists, where for every w ,

$$w \in A \iff f(w) \in B.$$

The function f is called the *polynomial time reduction* of A to B .

NP-Completeness: Polynomial Time Reducibility

Theorem 7.31

If $A \leq_p B$ and $B \in P$, then $A \in P$.

NP-Completeness: Polynomial Time Reducibility

› Let M be a polynomial time algorithm deciding B and f be the polynomial time reduction from A to B . We describe a polynomial time algorithm N deciding A as follows.

NP-Completeness: Polynomial Time Reducibility

► **Let M be a polynomial time algorithm deciding B and f be the polynomial time reduction from A to B . We describe a polynomial time algorithm N deciding A as follows.**

$N =$ “On input w :

1. Compute $f(w)$.
2. Run M on input $f(w)$ and output whatever M outputs.”

NP-Completeness: Polynomial Time Reducibility

› **Let M be a polynomial time algorithm deciding B and f be the polynomial time reduction from A to B . We describe a polynomial time algorithm N deciding A as follows.**

$N =$ “On input w :

1. Compute $f(w)$.

2. Run M on input $f(w)$ and output whatever M outputs.”

› **We have $w \in A$ whenever $f(w) \in B$ because f is a reduction from A to B .**

› **M accepts $f(w)$ whenever $w \in A$.**

NP-Completeness: 3SAT

➤ *3SAT* is *SAT* where all formulas are in a special format.

NP-Completeness: 3SAT

➤ *3SAT* is *SAT* where all formulas are in a special format.

➤ **A literal is a boolean variable (x or $\neg x$)**

NP-Completeness: 3SAT

- **3SAT is SAT where all formulas are in a special format.**
- **A literal is a boolean variable (x or $\neg x$)**
- **A clause is several literals connected with \vee s.**

NP-Completeness: 3SAT

- **3SAT is SAT where all formulas are in a special format.**
- **A literal is a boolean variable (x or $\neg x$)**
- **A clause is several literals connected with \vee s.**
- **A Boolean formula in conjunctive normal form (called a *cnf-formula*) connects multiple clauses with \wedge s.**

NP-Completeness: 3SAT

- **3SAT is SAT where all formulas are in a special format.**
 - **A literal is a boolean variable (x or $\neg x$)**
 - **A clause is several literals connected with \vee s.**
 - **A Boolean formula in conjunctive normal form (called a *cnf-formula*) connects multiple clauses with \wedge s.**
 - **3cnf-formula is when all clauses contain exactly 3 literals.**
- **$3SAT = \{\langle \varphi \rangle \mid \varphi \text{ is a satisfiable 3cnf-formula}\}$**

$$(x_1 \vee \overline{x_2} \vee \overline{x_3}) \wedge (x_3 \vee \overline{x_5} \vee x_6) \wedge (x_3 \vee \overline{x_6} \vee x_4) \wedge (x_4 \vee x_5 \vee x_6).$$

NP-Completeness: Polynomial Time Reduction (3SAT)

Theorem 7.32

3SAT is polynomial time reducible to CLIQUE.

NP-Completeness: Polynomial Time Reduction (3SAT)

Theorem 7.32

3SAT is polynomial time reducible to CLIQUE.


This requires converting boolean formulas to graphs

NP-Completeness: Polynomial Time Reduction (3SAT)

➤ The reduction function f generates the string $\langle G, k \rangle$, where G is an undirected graph with k nodes.


NP-Completeness: Polynomial Time Reduction (3SAT)

› The reduction function f generates the string $\langle G, k \rangle$, where G is an undirected graph with k nodes.



NP-Completeness: Polynomial Time Reduction (3SAT)


➤ The reduction function f generates the string $\langle G, k \rangle$, where G is an undirected graph with k nodes.



➤ The nodes in G are organized into k groups of three nodes each called the triples, t_1, \dots, t_k .

NP-Completeness: Polynomial Time Reduction (3SAT)

› The reduction function f generates the string $\langle G, k \rangle$, where G is an undirected graph with k nodes.




› The nodes in G are organized into k groups of three nodes each called the triples, t_1, \dots, t_k .

› Each triple corresponds to one of the clauses in φ .

NP-Completeness: Polynomial Time Reduction (3SAT)

› The reduction function f generates the string $\langle G, k \rangle$, where G is an undirected graph with k nodes.



› The nodes in G are organized into k groups of three nodes each called the triples, t_1, \dots, t_k .

› Each triple corresponds to one of the clauses in φ .

› Each node in a triple corresponds to a literal in the associated clause.

NP-Completeness: Polynomial Time Reduction (3SAT)

- › The edges of G connect to all but two types of pairs of nodes in G .

NP-Completeness: Polynomial Time Reduction (3SAT)

- The edges of G connect to all but two types of pairs of nodes in G .
- No edge is present between nodes in the same triple, and


NP-Completeness: Polynomial Time Reduction (3SAT)

- The edges of G connect to all but two types of pairs of nodes in G .
 - No edge is present between nodes in the same triple, and
 - no edge is present between two contradictory labels (e.g., x and $\neg x$).

NP-Completeness: Polynomial Time Reduction (3SAT)

- The edges of G connect to all but two types of pairs of nodes in G .
 - No edge is present between nodes in the same triple, and
 - no edge is present between two contradictory labels (e.g., x and $\neg x$).

➤ Example




$$\phi = (x_1 \vee x_1 \vee x_2) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee x_2).$$

NP-Completeness: Polynomial Time Reduction (3SAT)

- The edges of G connect to all but two types of pairs of nodes in G .
 - No edge is present between nodes in the same triple, and
 - no edge is present between two contradictory labels (e.g., x and $\neg x$).

➤ Example




ϕ is satisfiable iff
 G has a k -clique

$$\phi = (x_1 \vee x_1 \vee x_2) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee x_2).$$

NP-Completeness: Polynomial Time Reduction (3SAT)

- The edges of G connect to all but two types of pairs of nodes in G .
 - No edge is present between nodes in the same triple, and
 - no edge is present between two contradictory labels (e.g., x and $\neg x$).

➤ **Example**



ϕ is satisfiable iff
 G has a k -clique

How?

$$\phi = (x_1 \vee x_1 \vee x_2) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee x_2).$$

NP-Completeness: Polynomial Time Reduction (3SAT)

➤ Suppose that φ has a satisfying assignment.

3SAT	CLIQUE
At least one literal must be true in every clause	Select one node corresponding to a true literal in the satisfying assignment

NP-Completeness: Polynomial Time Reduction (3SAT)


➤ Suppose that φ has a satisfying assignment.

3SAT	CLIQUE
At least one literal must be true in every clause	Select one node corresponding to a true literal in the satisfying assignment
If more than one literal is true in a particular clause, choose one arbitrarily	The nodes we select form a <i>k-clique</i>

NP-Completeness: Polynomial Time Reduction (3SAT)

➤ Suppose that ϕ has a satisfying assignment.

At least one literal must be true in every clause. Selecting one true literal from each clause will form a k -clique in the graph. k nodes were selected because we only chose one from each triple. Each pair is joined with an edge because it does not meet the exception given earlier. Therefore, G contains a k -clique.



$$\phi = (x_1 \vee x_1 \vee x_2) \wedge (\bar{x}_1 \vee \bar{x}_2 \vee \bar{x}_2) \wedge (\bar{x}_1 \vee x_2 \vee x_2).$$


Transform formula to graph.

Example:


$$(x_1 \vee x_2 \vee \overline{x_4}) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_4}) \wedge (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \overline{x_3} \vee \overline{x_4})$$

Create Nodes:


Clause 1




Clause 2




Clause 3



Clause 4




$$(x_1 \vee x_2 \vee \overline{x_4}) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_4}) \wedge (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \overline{x_3} \vee \overline{x_4})$$



Add link from a literal \S to a literal in every other clause, except the complement \S


$$(\overline{x_1} \vee x_2 \vee \overline{x_4}) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_4}) \wedge (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \overline{x_3} \vee \overline{x_4})$$



Resulting Graph

$$(x_1 \vee x_2 \vee \overline{x_4}) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_4}) \wedge (x_1 \vee x_2 \vee x_3) \wedge (x_2 \vee \overline{x_3} \vee \overline{x_4}) = 1$$

$x_1 = 1$
 $x_2 = 0$
 $x_3 = 0$
 $x_4 = 1$



The formula is satisfied if and only if the Graph has a 4-clique

End of Proof

NP-Completeness: Definition

Definition 7.34

A language B is *NP-complete* if it satisfies two conditions:

1. B is in NP, and
2. every A in NP is polynomial time reducible to B .

NP-Completeness: Definition

Definition 7.34

A language B is *NP-complete* if it satisfies two conditions:

1. B is in NP, and
2. every A in NP is polynomial time reducible to B .

Theorem 7.35

If B is NP-complete and $B \in P$, then $P = NP$.

NP-Completeness

Theorem 7.36

If B is NP-complete and $B \leq_p C$ for C in NP,
then C is NP-complete.

NP-Completeness

Theorem 7.36

If B is NP-complete and $B \leq_p C$ for C in NP,
then C is NP-complete.

Check page 304 for proof

NP-Completeness: Cook-Levin Theorem

Cook-Levin Theorem (7.37)

SAT is NP-complete.

NP-Completeness: Cook-Levin Theorem

Cook-Levin Theorem (7.37)

SAT is NP-complete.

Proof

Part-1: Need to show that SAT is in NP.

A nondeterministic TM can find the assignment to a given formula and accept if the assignment satisfies that formula.

NP-Completeness: Cook-Levin Theorem

Cook-Levin Theorem (7.37)

SAT is NP-complete.

Proof

Part-1: Need to show that SAT is in NP.

A nondeterministic TM can find the assignment to a given formula and accept if the assignment satisfies that formula.

Part-2: Need to show that every problem in NP is polynomial reducible to SAT.