My Karpled Sduff for ze ropodica armz brochect

Reuben Stick
Email :   Reuben@5t1x.Tech
Web :   5t1x.Tech

August 5, 2022

1 Raw Python

1.1 The Torques Applied onto the Wrist Joint

```
Tr_W = (M_W * 9.81) * L_W
```
!!Need To Redo/Update!!

1.2 The Torques Applied onto the Elbow Joint

```
Tr_E = ((M_W * 9.81) * (math.sqrt(L_W^2 +L_E^2 -(((2) * (L_W) * (L_E)) * (math.cos
(A_W))))))+ ((M_E * 9.81) * L_E)
```
!!Need To Redo/Update!!

1.3 The Torques Applied onto the Shoulder Joint

```
Tr_S = (M_W * 9.81) * (math.sqrt((math.sqrt(L_W^2 +L_E^2 -(((2)* (L_W) * (L_E)) *
 (math.cos(A_W)))))^2 +L_S^2 -(((2) * ((math.sqrt(L_W^2 +L_E^2 -(((2) * (L_W) * (L_E
)) * (math.cos(A_W))))))* (L_S)) * (math.cos((A_E -(math.acos(((math.sqrt(L_W^2 +L_E
^2 -(((2)* (L_W) * (L_E)) * (math.cos(A_W)))))^2 +L_E^2 - L_W^2)/((2)((math.sqrt(L_W
^2 +L_E^2 -(((2) * (L_W) * (L_E)) * (math.cos(A_W))))))(L_E))))))))))+((M_E * 9.81)
 * (math.sqrt(L_E^2 +L_S^2 -(((2) * (L_E) * (L_S)) * (math.cos(A_E))))))+ ((M_S * 9
.81) * L_S)
```
!!Need To Redo/Update!!

2 Formulae

2.1 The Torques Applied onto the Wrist Joint

$$Tr_W = (9.81 \times M_W) \times (\frac{L_W}{2}) \tag{1}$$

2.2 The Torques Applied onto the Elbow Joint

$$Tr_E = ((9.81 \times M_W) \times (\frac{((\sqrt{L_W{}^2 + L_E{}^2 - (2 \times L_W \times L_E \times \cos(A_W)))) - L_E)}{2} + L_E) + ((9.81 \times M_E) \times (\frac{L_E}{2}) \tag{2}$$

2.3 The Torques Applied onto the Shoulder Joint

$$Tr_S = ((9.81 \times M_W) \times ((\frac{R_{WS} - R_{ES}}{2}) + R_{ES})) + ((9.81 \times M_E) \times ((\frac{R_{ES} - L_S}{2}) + R_{WE})) + ((9.81 \times M_S) \times (\frac{L_S}{2})) \tag{3}$$

$$R_{WS} = \sqrt{R_{WE}^2 + L_S^2 - (2 \times R_{WE} \times L_S \times \cos(A_{E2}))} \tag{4}$$

$$R_{WE} = \sqrt{L_W^2 + L_E^2 - (2 \times L_W \times L_E \times \cos(A_W))} \tag{5}$$

$$R_{ES} = \sqrt{L_S^2 + L_E^2 - (2 \times L_S \times L_E \times \cos(A_E))} \tag{6}$$

$$A_{E1} = \cos^{-1}(\frac{R_{WE}^2 + L_E^2 - L_W^2}{2 \times R_{WE} \times L_E}) \tag{7}$$

$$A_{E2} = A_E - A_{E1} \tag{8}$$

3 Inverse Kinematics for Robotic Arm

3.1 Inverse Kinematics Modelling in Octave

Lengths:

$$L1 = 10 \text{ Length Of First Arm}$$
$$L2 = 7 \text{ Length of Second arm}$$
$$L3 = 4 \text{ Length of Third arm}$$

All possible θ values:

$$\theta1 = 0 : 0.1 : \pi \text{ all possible theta1 values}$$
$$\theta2 = 0 : 0.1 : 1.5 * \pi \text{ all possible theta2 values}$$
$$\theta3 = 0 : 0.1 : \pi/2 \text{ all possible theta3 values}$$

Meshgrid:

$$[\theta1, \theta2, \theta3] = \text{meshgrid}$$
$$(\theta1, \theta2, \theta3) \text{ generate grid of angle values}$$

Compute Coordinates:

$$X = l1 * cos(\theta1) + l2 * cos(\theta1 + \theta2) + l3 * cos(\theta1 + \theta2 + \theta3) \text{ compute } x \text{ coordinates}$$
$$Y = l1 * sin(\theta1) + l2 * sin(\theta1 + \theta2) + l3 * sin(\theta1 + \theta2 + \theta3) \text{ compute } y \text{ coordinates}$$

Create datasets:

$$\text{data } 1 = [X(:)Y(:)\theta1(:)] \text{ create } x\text{-}y\text{-}\theta1 \text{ dataset}$$
$$\text{data } 2 = [X(:)Y(:)\theta2(:)] \text{ create } x\text{-}y\text{-}\theta2 \text{ dataset}$$
$$\text{data } 3 = [X(:)Y(:)\theta3(:)] \text{ create } x\text{-}y\text{-}\theta3 \text{ dataset}$$

Plot:

$$\text{plot}(X(:), Y(:),'r.')$$

Figure 1: $X - Y$ coordinates for all $\theta 1$, $\theta 2$, and $\theta 3$ combinations

X-Y coordinates for all theta1, theta2, and theta3 combinations