

In-EVM Mina State Verification

Technical Reference

Alisa Cherniaeva

a.cherniaeva@nil.foundation

=nil; Crypto3 (<https://crypto3.nil.foundation>)

Ilia Shirobokov

i.shirobokov@nil.foundation

=nil; Crypto3 (<https://crypto3.nil.foundation>)

Mikhail Komarov

nemo@nil.foundation

=nil; Foundation (<https://nil.foundation>)

March 24, 2022

Contents

1	Introduction	2
1.1	Overview	2
2	State Proof Generator	3
2.1	Introduction	3
2.2	Optimizations	3
2.2.1	Batched FRI	3
2.2.2	Hash By Column	3
2.2.3	Hash By Subset	4
2.3	RedShift Protocol	4
2.3.1	Prover View	4
2.3.2	Verifier View	6
2.4	Mina Verification Algorithm	6
2.4.1	Pasta Curves	6
2.4.2	Verification Algorithm	7
2.5	Elliptic Curve Arithmetic	11
2.5.1	Unified Incomplete Addition and Doubling	11
2.5.2	Variable Base Scalar Multiplication	12
2.5.3	Variable Base Endo-Scalar Multiplication	13
2.5.4	Fixed-base scalar multiplication circuit	14
2.6	Multi-Scalar Multiplication Circuit	15
2.6.1	Naive Algorithm	15
2.6.2	Simultaneous Doubling	16
2.7	Poseidon Circuit	17
2.8	Other Circuits	17
2.8.1	Combined Inner Product	18
2.8.2	Endo-Scalar Computation	18
3	In-EVM State Proof Verifier	20
3.1	Verification Logic Architecture	20
3.2	Verification Logic API Reference	20
3.3	Input Data Structures	20
	Bibliography	20

Chapter 1

Introduction

This document is a technical reference to the in-EVM Mina state verification project.

1.1 Overview

The project's purpose is to provide Ethereum users with reliable Mina Protocol's state proof. The project UX consists of several steps:

1. Retrieve Mina Protocol's state proof.
2. Preprocess it by generating an auxiliary proof.
3. Submit the preprocessed proof to EVM-enabled cluster.
4. Verify the proof with EVM.

Such a UX defines projects parts:

1. Mina Protocol's state retriever (O(1) Labs' or Chainsafe's protocol implementation).
2. State proof generator.
3. Ethereum RPC proof submitter.
4. EVM-based proof verifier.

The overall architecture diagram is as follows:
Each of these parts will be considered independently.

Chapter 2

State Proof Generator

This introduces a description for Mina Protocol’s state auxiliary proof generator. Crucial components which define this part design and performance are:

1. Input data format (Pickles proof data structure: [2.4.2](#))
2. Proof system used for the proof generation.
3. Circuit definition used for the proof system.

2.1 Introduction

WIP

To prove Mina blockchain’s state on the Ethereum Virtual Machine, we use Redshift SNARK[[1](#)]. RedShift is a transparent SNARK that uses PLONK[[2](#)] proof system but replaces the commitment scheme. The authors utilize FRI[[3](#)] protocol to obtain transparency for the PLONK system.

However, FRI cannot be straightforwardly used with the PLONK system. To achieve the required security level without huge overheads, the authors introduce *list polynomial commitment* scheme as a part of the protocol. For more details, we refer the reader to [[1](#)].

The original RedShift protocol utilizes the classic PLONK[[2](#)] system. To provide better performance, we generalize the original protocol for use with PLONK with custom gates [[4](#)], [[5](#)] and lookup arguments [[6](#)], [[7](#)].

2.2 Optimizations

WIP

2.2.1 Batched FRI

Instead of checking each commitment individually, it is possible to aggregate them for FRI. For polynomials f_0, \dots, f_k :

1. Get θ from transcript
2. $f = f_0 \cdot \theta^{k-1} + \dots + f_k$
3. Run FRI over f , using oracles to f_0, \dots, f_k

Thus, we can run only one FRI instance for all committed polynomials. See [[1](#)] for details.

2.2.2 Hash By Column

Instead of committing each of the polynomials, it is possible to use the same Merkle tree for several polynomials. This leads to the decrease of the number of Merkle tree paths which are required to be provided by the prover.

See [[8](#)], [[1](#)] for details.

2.2.3 Hash By Subset

Each $i + 1$ FRI round supposes the prover to send all elements from a coset $H \in D^{(i)}$. Each Merkle leaf is able to contain the whole coset instead of separate values.

See [8] for details. Similar approach is described in [1]. However, the authors of [1] use more values per leaf, that leads to better performance.

2.3 RedShift Protocol

WIP

Notations:

N_{wires}	Number of wires ('advice columns')
N_{perm}	Number of wires that are included in the permutation argument
N_{sel}	Number of selectors used in the circuit
N_{const}	Number of constant columns
\mathbf{f}_i	Witness polynomials, $0 \leq i < N_{\text{wires}}$
\mathbf{f}_{c_i}	Constant-related polynomials, $0 \leq i < N_{\text{const}}$
\mathbf{gate}_i	Gate polynomials, $0 \leq i < N_{\text{sel}}$
$\sigma(\text{col} : i, \text{row} : j) = (\text{col} : i', \text{row} : j')$	Permutation over the table

For details on polynomial commitment scheme and polynomial evaluation scheme, we refer the reader to [1].

-
1. $\mathcal{L}' = (\mathbf{q}_0, \dots, \mathbf{q}_{N_{\text{sel}}})$
 2. Let ω be a 2^k root of unity
 3. Let δ be a T root of unity, where $T \cdot 2^S + 1 = p$ with T odd and $k \leq S$
 4. Compute N_{perm} permutation polynomials $S_{\sigma_i}(X)$ such that $S_{\sigma_i}(\omega^j) = \delta^{i'} \cdot \omega^{j'}$
 5. Compute N_{perm} identity permutation polynomials: $S_{id_i}(X)$ such that $S_{id_i}(\omega^j) = \delta^i \cdot \omega^j$
 6. Let $H = \{\omega^0, \dots, \omega^n\}$ be a cyclic subgroup of \mathbb{F}^*
 7. Let $Z(X) = \prod a \in H^*(X - a)$
-

Preprocessing:

2.3.1 Prover View

1. Choose masking polynomials:

$$h_i(X) \leftarrow \mathbb{F}_{<k}[X] \text{ for } 0 \leq i < N_{\text{wires}}$$

Remark: For details on choice of k , we refer the reader to [1].

2. Define new witness polynomials:

$$f_i(X) = \mathbf{f}_i(X) + h_i(X)Z(X) \text{ for } 0 \leq i < N_{\text{wires}}$$

3. Add commitments to f_i to transcript
4. Get $\beta, \gamma \in \mathbb{F}$ from $\text{hash}(\text{transcript})$
5. For $0 \leq i < N_{\text{perm}}$

$$\begin{aligned} p_i &= f_i + \beta \cdot S_{id_i} + \gamma \\ q_i &= f_i + \beta \cdot S_{\sigma_i} + \gamma \end{aligned}$$

6. Define:

$$\begin{aligned} p'(X) &= \prod_{0 \leq i < N_{\text{perm}}} p_i(X) \in \mathbb{F}_{<N_{\text{perm}} \cdot n}[X] \\ q'(X) &= \prod_{0 \leq i < N_{\text{perm}}} q_i(X) \in \mathbb{F}_{<N_{\text{perm}} \cdot n}[X] \end{aligned}$$

7. Compute $P(X), Q(X) \in \mathbb{F}_{<n+1}[X]$, such that:

$$\begin{aligned} P(\omega) &= Q(\omega) = 1 \\ P(\omega^i) &= \prod_{1 \leq j < i} p'(\omega^j) \text{ for } i \in 2, \dots, n+1 \\ Q(\omega^i) &= \prod_{1 \leq j < i} q'(\omega^j) \text{ for } i \in 2, \dots, n+1 \end{aligned}$$

8. Compute commitments to P, Q and add them to transcript.

9. Get $\alpha_0, \dots, \alpha_5 \in \mathbb{F}$ from $\text{hash}(\text{transcript})$

10. Get τ from $\text{hash}(\text{transcript})$

11. Define polynomials (F_0, \dots, F_4 - copy-satisfiability, \mathbf{gate}_0 is PI -constraining gate)):

$$\begin{aligned} F_0(X) &= L_1(X)(P(X) - 1) \\ F_1(X) &= L_1(X)(Q(X) - 1) \\ F_2(X) &= P(X)p'(X) - P(X\omega) \\ F_3(X) &= Q(X)q'(X) - Q(X\omega) \\ F_4(X) &= L_n(X)(P(X\omega) - Q(X\omega)) \\ F_5(X) &= \sum_{0 \leq i < N_{\text{sel}}} (\tau^i \cdot \mathbf{q}_i(X) \cdot \mathbf{gate}_i(X)) + PI(X) \end{aligned}$$

12. Compute:

$$\begin{aligned} F(X) &= \sum_{i=0}^5 \alpha_i F_i(X) \\ T(X) &= \frac{F(X)}{Z(X)} \end{aligned}$$

13. $N_T := \max(N_{\text{perm}}, \mathbf{deg}_{\text{gates}} - 1)$, where $\mathbf{deg}_{\text{gates}}$ is the highest degree of the degrees of gate polynomials.

14. Split $T(X)$ into separate polynomials $T_0(X), \dots, T_{N_T-1}(X)$ ¹

15. Add commitments to $T_0(X), \dots, T_{N_T-1}(X)$ to transcript.

16. Get $y \in \mathbb{F}/H$ from $\text{hash}(\text{transcript})$

17. Run evaluation scheme with the committed polynomials and y .

Remark: Depending on the circuit, evaluation can be done also on $y\omega, y\omega^{-1}$.

18. The proof is π_{comm} and π_{eval} , where:

- $\pi_{\text{comm}} = \{f_{0,\text{comm}}, \dots, f_{N_{\text{wires}}-1,\text{comm}}, P_{\text{comm}}, Q_{\text{comm}}, T_{0,\text{comm}}, \dots, T_{N_T-1,\text{comm}}\}$
- π_{eval} is evaluation proofs for $f_0(y), \dots, f_{N_{\text{wires}}-1}(y), P(y), P(y\omega), Q(y), Q(y\omega), T_0(y), \dots, T_{N_T-1}(y)$

¹Commit scheme supposes that polynomials should be degree $\leq n$

2.3.2 Verifier View

1. Let $f_{0,\text{comm}}, \dots, f_{N_{\text{wires}}-1,\text{comm}}$ be commitments to $f_0(X), \dots, f_{N_{\text{wires}}-1}(X)$
2. $\text{transcript} = \text{setup_values} || f_{0,\text{comm}} || \dots || f_{N_{\text{wires}}-1,\text{comm}}$
3. $\beta, \gamma = \text{hash}(\text{transcript})$
4. Let $P_{\text{comm}}, Q_{\text{comm}}$ be commitments to $P(X), Q(X)$
5. $\text{transcript} = \text{transcript} || P_{\text{comm}} || Q_{\text{comm}}$
6. $\alpha_0, \dots, \alpha_5 = \text{hash}(\text{transcript})$
7. $\tau = \text{hash}(\text{transcript})$
8. $N_T := \max(N_{\text{perm}}, \deg_{\text{gates}} - 1)$, where \deg_{gates} is the highest degree of the degrees of gate polynomials.
9. Let $T_{0,\text{comm}}, \dots, T_{N_T-1,\text{comm}}$ be commitments to $T_0(X), \dots, T_{N_T-1}(X)$
10. $\text{transcript} = \text{transcript} || T_{0,\text{comm}} || \dots || T_{N_T-1,\text{comm}}$
11. $y = \text{hash}_{\mathbb{F}/H}(\text{transcript})$
12. Run evaluation scheme verification with the committed polynomials and y to check values $f_i(y), P(y), P(y\omega), Q(y), Q(y\omega), T_j(y)$.
Remark: Depending on the circuit, evaluation can be done also on $f_i(y\omega), f_i(y\omega^{-1})$ for some i .
13. Calculate:

$$\begin{aligned}
F_0(y) &= L_1(y)(P(y) - 1) \\
F_1(y) &= L_1(y)(Q(y) - 1) \\
p'(y) &= \prod p_i(y) = \prod f_i(y) + \beta \cdot S_{id_i}(y) + \gamma \\
F_2(y) &= P(y)p'(y) - P(y\omega) \\
q'(y) &= \prod q_i(y) = \prod f_i(y) + \beta \cdot S_{\sigma_i}(y) + \gamma \\
F_3(y) &= Q(y)q'(y) - Q(y\omega) \\
F_4(y) &= L_n(y)(P(y\omega) - Q(y\omega)) \\
F_5(y) &= \sum_{0 \leq i < N_{\text{sel}}} (\tau^i \cdot \mathbf{q}_i(y) \cdot \text{gate}_i(y)) + PI(y) \\
T(y) &= \sum_{0 \leq j < N_T} y^{n \cdot j} T_j(y)
\end{aligned}$$

14. Check the identity:

$$\sum_{i=0}^5 \alpha_i F_i(y) = Z(y)T(y)$$

2.4 Mina Verification Algorithm

WIP

2.4.1 Pasta Curves

Let $n_1 = 17, n_2 = 16$. Pasta curves parameters:

- $p = 2^{254} + 45560315531419706090280762371685220353$
- $q = 2^{254} + 45560315531506369815346746415080538113$
- Pallas:

$$\begin{aligned}
\mathbb{G}_1 &= \{(x, y) \in \mathbb{F}_p | y^2 = x^3 + 5\} \\
|\mathbb{G}_1| &= q
\end{aligned}$$

- Vesta:

$$\begin{aligned}
\mathbb{G}_2 &= \{(x, y) \in \mathbb{F}_q | y^2 = x^3 + 5\} \\
|\mathbb{G}_2| &= p
\end{aligned}$$

2.4.2 Verification Algorithm

Notations

N_{wires}	Number of wires ('advice columns')
N_{perm}	Number of wires that are included in the permutation argument
N_{prev}	Number of previous challenges
$S_{\sigma_i}(X)$	Permutation polynomials for $0 \leq i < N_{\text{perm}}$
$\text{pub}(X)$	Public input polynomial
$w_i(X)$	Witness polynomials for $0 \leq i < N_{\text{wires}}$
$\eta_i(X)$	Previous challenges polynomials for $0 \leq i < N_{\text{prev}}$
ω	n -th root of unity

Denote multi-scalar multiplication $\sum_{s_i \in \mathbf{s}, G_i \in \mathbf{G}} [s_i]G_i$ by $\text{MSM}(\mathbf{s}, \mathbf{G})$ for $l_{\mathbf{s}} = l_{\mathbf{G}}$ where $l_{\mathbf{s}} = |\mathbf{s}|$, $l_{\mathbf{G}} = |\mathbf{G}|$. If $l_{\mathbf{s}} < l_{\mathbf{G}}$, then we use only first $l_{\mathbf{s}}$ elements of \mathbf{G}

Proof π contains (here \mathbb{F}_r is a scalar field of \mathbb{G}):

- Commitments:
 - Witness polynomials: $w_{0,\text{comm}}, \dots, w_{N_{\text{wires}},\text{comm}} \in \mathbb{G}$
 - Permutation polynomial: $z_{\text{comm}} \in \mathbb{G}$
 - Quotient polynomial: $t_{\text{comm}} = (t_{1,\text{comm}}, t_{2,\text{comm}}, \dots, t_{N_{\text{perm}},\text{comm}}) \in (\mathbb{G}^{N_{\text{perm}}} \times \mathbb{G})$
- Evaluations:
 - $w_0(\zeta), \dots, w_{N_{\text{wires}}}(\zeta) \in \mathbb{F}_r$
 - $w_0(\zeta\omega), \dots, w_{N_{\text{wires}}}(\zeta\omega) \in \mathbb{F}_r$
 - $z(\zeta), z(\zeta\omega) \in \mathbb{F}_r$
 - $S_{\sigma_0}(\zeta), \dots, S_{\sigma_{N_{\text{perm}}}}(\zeta) \in \mathbb{F}_r$
 - $S_{\sigma_0}(\zeta\omega), \dots, S_{\sigma_{N_{\text{perm}}}}(\zeta\omega) \in \mathbb{F}_r$
 - $\bar{L}(\zeta\omega) \in \mathbb{F}_r$ ²
- Opening proof o_{π} for inner product argument:
 - $(L_i, R_i) \in \mathbb{G} \times \mathbb{G}$ for $0 \leq i < \text{lr_rounds}$
 - $\delta, \hat{G} \in \mathbb{G}$
 - $z_1, z_2 \in \mathbb{F}_r$
- previous challenges:
 - $\{\eta_i(\xi_j)\}_j, \eta_{i,\text{comm}}$, for $0 \leq i < \text{prev}$

Remark: For simplicity, we do not use distinct proofs index i for each element in the algorithm below. For instance, we write pub_{comm} instead of $\text{pub}_{i,\text{comm}}$.

²See https://o1-labs.github.io/mina-book/crypto/plonk/maller_15.html

1. for each π_i :
 - 1.1 **random_oracle**(p_{comm}, π_i):
 - 1.1.1 Copy limbs of **joint_combiner** from PI
 - 1.1.2 **joint_combiner** = **from_limbs**(**joint_combiner_limbs**)
 - 1.1.3 Copy limbs of β, γ from PI
 - 1.1.4 β = **from_limbs**(β_limbs)
 - 1.1.5 γ = **from_limbs**(γ_limbs)
 - 1.1.6 Copy limbs of α from PI
 - 1.1.7 α_c = **from_limbs**(α_limbs)
 - 1.1.8 $\alpha = \phi(\alpha_c)$
 - 1.1.9 Copy limbs of ζ from PI
 - 1.1.10 ζ_c = **from_limbs**(ζ_limbs)
 - 1.1.11 $\zeta = \phi(\zeta_c)$
 - 1.1.12 Initialize $H_{\mathbb{F}_r}$
 - 1.1.13 Copy $H_{\mathbb{F}_q}.\text{digest}$ from PI
 - 1.1.14 $H_{\mathbb{F}_r}.\text{absorb}(H_{\mathbb{F}_q}.\text{digest})$
 - 1.1.15 $\zeta_1 = \zeta^n$
 - 1.1.16 $\zeta_w = \zeta \cdot \omega$
 - 1.1.17 **all_alphas** = $[1, \alpha, \dots, \alpha^{\text{next_power}}]$
 - 1.1.18 **lagrange** = $[\zeta - \text{domain}.w, \dots, \zeta_w - \text{domain}.w]$ L195
 - 1.1.19 **lagrange** = $[1/\text{lagrange}[0], \dots]$
 - 1.1.20 **p_eval**[0] = $(\sum(\text{pub}[i] \cdot \text{domain}[i] \cdot (-\text{lagrange}[i])) \cdot (\zeta_1 - 1) \cdot \text{frac1}|\text{domain}|$
 - 1.1.21 **p_eval**[1] = $(\sum(\text{pub}[i] \cdot \text{domain}[i] \cdot (-\text{lagrange}[\text{pub}.len + i])) \cdot (\zeta_w^n - 1) \cdot \text{frac1}|\text{domain}|$
 - 1.1.22 $H_{\mathbb{F}_r}.\text{absorb}(\text{p_eval}[0])$
 - 1.1.23 $H_{\mathbb{F}_r}.\text{absorb}(\text{evals}[0])$ <- PI src -> plonk_sponge.rs L41
 - 1.1.24 $H_{\mathbb{F}_r}.\text{absorb}(\text{p_eval}[1])$
 - 1.1.25 $H_{\mathbb{F}_r}.\text{absorb}(\text{evals}[1])$ <- PI
 - 1.1.26 Copy $\bar{L}(\zeta\omega)$ from PI
 - 1.1.27 $H_{\mathbb{F}_r}.\text{absorb}(\bar{L}(\zeta\omega))$
 - 1.1.28 $v = \phi(H_{\mathbb{F}_r}.\text{squeeze}())$
 - 1.1.29 $u = \phi(H_{\mathbb{F}_r}.\text{squeeze}())$
 - 1.1.30 Compute evaluation of $\eta_i(\zeta), \eta_i(\zeta\omega)$ for $0 \leq i < N_{\text{prev}}$:
 - 1.1.30.1 $\text{powers_of_evals} = [\zeta^{\text{max_poly_size}}, \zeta_w^{\text{max_poly_size}}]$
 - 1.1.30.2 ...
 - 1.1.31 Compute evaluation of $\bar{L}(\zeta)$:
 - 1.1.31.1 ...
 - 1.2 Combine evals (ploynomial evals) L412
 - 1.3 **f**_{base} := $\{S_{\sigma_{N_{\text{perm}}}-1, \text{comm}}, \text{gate}_{\text{mult}, \text{comm}}, w_{0, \text{comm}}, w_{1, \text{comm}}, w_{2, \text{comm}}, q_{\text{const}, \text{comm}}, \text{gate}_{\text{psdn}, \text{comm}}, \text{gate}_{\text{rc}, \text{comm}}, \text{gate}_{\text{ec_add}, \text{comm}}, \text{gate}_{\text{ec_dbl}, \text{comm}}, \text{gate}_{\text{ec_endo}, \text{comm}}, \text{gate}_{\text{ec_vbase}, \text{comm}}\}$
 - 1.4 $s_{\text{perm}} := (w_0(\zeta) + \gamma + \beta \cdot S_{\sigma_0}(\zeta)) \cdot \dots \cdot (w_5(\zeta) + \gamma + \beta \cdot S_{\sigma_{N_{\text{perm}}}}(\zeta))$
 - 1.5 **f**_{scalars} := $\{-z(\zeta\omega) \cdot \beta \cdot \alpha_0 \cdot \text{zkp}(\zeta) \cdot s_{\text{perm}}, w_0(\zeta) \cdot w_1(\zeta), w_0(\zeta), w_1(\zeta), 1, s_{\text{psdn}}, s_{\text{rc}}, s_{\text{ec_add}}, s_{\text{ec_dbl}}, s_{\text{ec_endo}}, s_{\text{ec_vbase}}\}$
 - 1.6 **PE** is a set of elements of the form $(f_{\text{comm}}, f(\zeta), f(\zeta\omega))$ for the following polynomials:
 $\eta_0, \dots, \eta_{N_{\text{prev}}}, \text{pub}, w_0, \dots, w_{N_{\text{wires}}}, z, S_{\sigma_0}, \dots, S_{\sigma_{N_{\text{perm}}}}, \bar{L}$
 - 1.7 $\mathcal{P}_i = \{H_{\mathbb{F}_q}, \zeta, v, u, \mathbf{PE}, o_{\pi_i}\}$
 2. **final_check_scalar_field**($\mathcal{P}_0, \dots, \mathcal{P}_{\text{batch_size}}$)
-

1. for each π_i :
 - 1.1 $pub_{\text{comm}} = -\text{MSM}(\mathbf{L}, \text{pub}) \in \mathbb{G}$, where \mathbf{L} is Lagrange bases vector
 - 1.2 **random_oracle**(p_{comm}, π_i):
 - 1.2.1 $H_{\mathbb{F}_q}.\text{absorb}(pub_{\text{comm}} || w_{0,\text{comm}} || \dots || w_{N_{\text{wires}},\text{comm}})$
 - 1.2.2 $\text{joint_combiner} = H_{\mathbb{F}_q}.\text{squeeze}() <-$ PI check
 - 1.2.3 $H_{\mathbb{F}_q}.\text{absorb}(\text{LOOKUP})$ L146, commitments sorted
 - 1.2.4 $\beta, \gamma = H_{\mathbb{F}_q}.\text{squeeze}() <-$ PI check
 - 1.2.5 $H_{\mathbb{F}_q}.\text{absorb}(\text{LOOKUP2})$ L156m commitments aggregated
 - 1.2.6 $H_{\mathbb{F}_q}.\text{absorb}(z_{\text{comm}})$
 - 1.2.7 $\alpha = H_{\mathbb{F}_q}.\text{squeeze}() <-$ PI check
 - 1.2.8 $H_{\mathbb{F}_q}.\text{absorb}(t_{1,\text{comm}} || \dots || t_{N_{\text{perm}},\text{comm}} || \dots || \infty ||)$
 - 1.2.9 $\zeta = H_{\mathbb{F}_q}.\text{squeeze}() <-$ PI check
 - 1.2.10 Get digest from $H_{\mathbb{F}_q} <-$ PI check
 - 1.3 $\mathbf{f}_{\text{base}} := \{S_{\sigma_{N_{\text{perm}}-1},\text{comm}}, \text{gate}_{\text{mult},\text{comm}}, w_{0,\text{comm}}, w_{1,\text{comm}}, w_{2,\text{comm}}, q_{\text{const},\text{comm}}, \text{gate}_{\text{psdn},\text{comm}}, \text{gate}_{\text{rc},\text{comm}}, \text{gate}_{\text{ec_add},\text{comm}}, \text{gate}_{\text{ec_dbl},\text{comm}}, \text{gate}_{\text{ec_endo},\text{comm}}, \text{gate}_{\text{ec_vbase},\text{comm}}\}$
 - 1.4 $s_{\text{perm}} := (w_0(\zeta) + \gamma + \beta \cdot S_{\sigma_0}(\zeta)) \cdot \dots \cdot (w_5(\zeta) + \gamma + \beta \cdot S_{\sigma_{N_{\text{perm}}}}(\zeta))$
 - 1.5 $\mathbf{f}_{\text{scalars}} := \{-z(\zeta\omega) \cdot \beta \cdot \alpha_0 \cdot \text{zkp}(\zeta) \cdot s_{\text{perm}}, w_0(\zeta) \cdot w_1(\zeta), w_0(\zeta), w_1(\zeta), 1, s_{\text{psdn}}, s_{\text{rc}}, s_{\text{ec_add}}, s_{\text{ec_dbl}}, s_{\text{ec_endo}}, s_{\text{ec_vbase}}\}$
 - 1.6 $f_{\text{comm}} = \text{MSM}(\mathbf{f}_{\text{base}}, \mathbf{f}_{\text{scalars}})$
 - 1.7 Copy from PI ($\zeta^n - 1$)
 - 1.8 $\bar{L}_{\text{comm}} = f_{\text{comm}} - t_{\text{comm}} \cdot (\zeta^n - 1)$
 - 1.9 **PE** is a set of elements of the form $(f_{\text{comm}}, f(\zeta), f(\zeta\omega))$ for the following polynomials:
 $\eta_0, \dots, \eta_{N_{\text{prev}}}, \text{pub}, w_0, \dots, w_{N_{\text{wires}}}, z, S_{\sigma_0}, \dots, S_{\sigma_{N_{\text{perm}}}}, \bar{L}$
 - 1.10 $\mathcal{P}_i = \{H_{\mathbb{F}_q}, \zeta, v, u, \mathbf{PE}, o_{\pi_i}\}$
 2. **final_check_base_field**($\mathcal{P}_0, \dots, \mathcal{P}_{\text{batch_size}}$)
-

Algorithm 3 Final Check - Scalar Field

Input: $\pi_0, \dots, \pi_{\text{batch_size}}$, where $\pi_i = \{H_{i, \mathbb{F}_q}, \zeta_i, \zeta_i \omega, v_i, u_i, \mathbf{PE}_i, o_{\pi_i}\}$

Output: acc or rej

1. $\rho_1 \rightarrow \mathbb{F}_r \leftarrow$ should be calculated as poseidon from H_{i, \mathbb{F}_q} state
 2. $\rho_2 \rightarrow \mathbb{F}_r$
 3. $r_0 = r'_0 = 1$
 4. for $0 \leq i < \text{batch_size}$:
 - 4.1 $cip_i = \text{combined_inner_product}(\zeta_i, \zeta_i \omega, v_i, u_i, \mathbf{PE}_i) \leftarrow$ PI check
 - 4.2 Calculate opening challenges $\xi_{i,j}$ from limbs in $o_{\pi_i} \leftarrow$ PI?
 - 4.3 Calculate inversion from $\xi_{i,j}$
 - 4.4 Copy limbs c_i_limbs from PI
 - 4.5 $c_i = \phi(c_i_limbs)$
 - 4.6 $h_i(X) := \prod_{k=0}^{\log(d+1)-1} (1 + \xi_{\log(d+1)-k} X^{2^k})$, where $d = \text{lr_rounds}$
 - 4.7 $b_i = h_i(\zeta) + u_i \cdot h_i(\zeta \omega)$
 - 4.8 $sg = -r_i \cdot \text{opening.z1} - r'_i$
 - 4.9 $r_i = r_{i-1} \cdot \rho_1$
 - 4.10 $r'_i = r'_{i-1} \cdot \rho_2$
-

Algorithm 4 Final Check - Base Field

Input: $\pi_0, \dots, \pi_{\text{batch_size}}$, where $\pi_i = \{H_{i, \mathbb{F}_q}, \zeta_i, \zeta_i \omega, v_i, u_i, \mathbf{PE}_i, o_{\pi_i}\}$

Output: acc or rej

1. for $0 \leq i < \text{batch_size}$:
 - 1.1 Get limbs cip_i from PI
 - 1.2 $H_{i, \mathbb{F}_q}.\text{absorb}(cip_i - 2^{255})$
 - 1.3 $U_i = (H_{i, \mathbb{F}_q}.\text{squeeze}()).\text{to_group}()$
 - 1.4 Calculate opening challenges $\xi_{i,j}$ from $o_{\pi_i} \leftarrow$ PI output as limbs:
 - 1.4.1 ?????
 - 1.5 $H_{i, \mathbb{F}_q}.\text{absorb}(\text{openings}.\delta)$ L791
 - 1.6 $h_i(X) := \prod_{k=0}^{\log(d+1)-1} (1 + \xi_{\log(d+1)-k} X^{2^k})$, where $d = \text{lr_rounds}$
 - 1.7 $C_i = \sum_j v_i^j (\sum_k r_i^k f_{j, \text{comm}})$, where $f_{j, \text{comm}}$ from \mathbf{PE}_i .
 - 1.8 $Q_i = \sum (\xi_{i,j} \cdot L_{i,j} + \xi_{i,j}^{-1} \cdot R_j) + cip_i \cdot U_i + C_i$
 - 1.9 $c_i = H_{i, \mathbb{F}_q}.\text{squeeze}() \leftarrow$ PI
 - 1.10 Check $\hat{G}_i = \langle s, G \rangle$, where s is set of $h(X)$ coefficients.
Remark: This check can be done inside the MSM below using r'_i .
 2. Fq: $\text{res} = \sum_i r^i (c_i Q_i + \text{delta}_i - (z_{i,1}(\hat{G}_i + b_i U_i) + z_{i,2} H))$
 3. Fq: **return** $\text{res} == 0$
-

Algorithm 5 Combined Inner Product

Input: $\xi, r, f_0(\zeta_1), \dots, f_k(\zeta_1), f_0(\zeta_2), \dots, f_k(\zeta_2)$ **Output:** s

1. Fr: $s = \sum_{i=0}^k \xi^i \cdot (f_i(\zeta_1) + r \cdot f_i(\zeta_2))$
-

We use the same 15-wires PLONK circuits that are designed for Mina.³

2.5 Elliptic Curve Arithmetic

WIP

2.5.1 Unified Incomplete Addition and Doubling

Row	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
i	x_1	y_1	x_2	y_2	x_3	y_3	inf	same_x	s	inv_y	inv_x

Evaluations:

- Addition case:
 - $(x_3, y_3) = (x_1, y_1) + (x_2, y_2)$
 - **inf** = 1 if (x_3, y_3) is a point-at-infinity, **inf** = 0 otherwise
 - **same_x** = 1 if $x_1 = x_2$, **same_x** = 0 otherwise
 - $s = \frac{y_1 - y_2}{x_1 - x_2}$ if $x_1 \neq x_2$, $s = 0$ otherwise
 - **inv_y** = $\frac{1}{y_2 - y_1}$ if $y_2 \neq y_1$, **inv_y** = 0 otherwise
 - **inv_x** = $\frac{1}{x_2 - x_1}$ if $x_2 \neq x_1$, **inv_x** = 0 otherwise
- Doubling case:
 - $(x_3, y_3) = 2(x_1, y_1)$
 - $x_2 = x_1, y_2 = y_1$
 - **inf** = 1 if (x_3, y_3) is a point-at-infinity, **inf** = 0 otherwise
 - **same_x** = 1
 - $s = \frac{3x_1^2}{2y_1}$ if $y_1 \neq 0$, $s = 0$ otherwise
 - **inv_y** = 0
 - **inv_x** = 0

Constraints (**max degree** = 3):

1. $w_7 \cdot (w_2 - w_0) = 0$
2. $(w_2 - w_0) \cdot w_{10} - (1 - w_7) = 0$
3. $w_7 \cdot (2w_8 \cdot w_1 - 3w_0^2) + (1 - w_7) \cdot ((w_2 - w_0) \cdot w_8 - (w_3 - w_1))$
4. $w_8^2 = w_0 + w_2 + w_4$
5. $w_5 = w_8 \cdot (w_0 - w_4) - w_1$
6. $(w_3 - w_1) \cdot (w_7 - w_6) = 0$
7. $(w_3 - w_1) \cdot w_9 - w_6 = 0$

Copy constraints:

1. $w_6 = 0$

³https://o1-labs.github.io/mina-book/specs/15_wires/15_wires.html

Details. The gate uses basic group law formulae. Let $P = (x_1, y_1), Q = (x_2, y_2), R = (x_3, y_3)$ and $R = P + Q$. Then:

- $(x_2 - x_1) \cdot s = y_2 - y_1$
- $s^2 = x_1 + x_2 + x_3$
- $y_3 = s \cdot (x_1 - x_3) - y_1$

For point doubling $R = P + P = 2P$:

- $2s \cdot y_1 = 3x_1^2$
- $s^2 = 2x_1 + x_3$
- $y_3 = s \cdot (x_1 - x_3) - y_1$

The gate does not handle cases $\mathcal{O} + P$ or $\mathcal{O} + \mathcal{O}$. To ensure that operations with point-at-infinity are not included in the circuit's trace, copy constraint $w_6 = 0$ ($\mathbf{inf} = 0$) was introduced.

Constraints details:

- $x_2 - x_1$ zero check:
 1. $w_7 \cdot (w_2 - w_0) = 0 \longleftrightarrow \mathbf{same_x} \cdot (x_2 - x_1)$
If $x_1 \neq x_2$, then $\mathbf{same_x} = 0$
 2. $(w_2 - w_0) \cdot w_{10} - (1 - w_7) = 0 \longleftrightarrow (x_2 - x_1) \cdot \mathbf{inv}_x - (1 - \mathbf{same_x})$
If $x_1 \neq x_2$, then $\mathbf{inv}_x = (x_2 - x_1)^{-1}$
- Group law constraints:
 1. $w_7 \cdot (2w_8 \cdot w_1 - 3w_0^2) + (1 - w_7) \cdot ((w_2 - w_0 \cdot w_8 - (w_3 - w_1)) \longleftrightarrow \mathbf{same_x} \cdot (2s \cdot y_1 - 3x_1^2) + (1 - \mathbf{same_x}) \cdot (x_2 - x_1 \cdot s - (y_2 - y_1)))$
If $x_1 = x_2$ then use doubling $2s \cdot y_1 = 3x_1^2$. Otherwise use addition $(x_2 - x_1) \cdot s = y_2 - y_1$.
 2. $w_8^2 = w_0 + w_2 + w_4 \longleftrightarrow s^2 = x_1 + x_2 + x_3$
Constrains x_3 . It does not depend on x_1, x_2 equality.
 3. $w_5 = w_8 \cdot (w_0 - w_4) - w_1 \longleftrightarrow y_3 = s \cdot (x_1 - x_3) - y_1$
Constrains y_3 . It does not depend on x_1, x_2 equality.
- $P + (-P)$ constraints:
 1. $(w_3 - w_1) \cdot (w_7 - w_6) = 0 \longleftrightarrow (y_2 - y_1) \cdot (\mathbf{same_x} - \mathbf{inf}) = 0$
We can get infinity point iff $x_1 = x_2$ and $y_1 \neq y_2$.
If $y_1 \neq y_2$ then $\mathbf{inf} = \mathbf{same_x}$.
 2. $(w_3 - w_1) \cdot w_9 - w_6 = 0 \longleftrightarrow (y_2 - y_1) \cdot \mathbf{inv}_y - \mathbf{inf}$
The prover sets $\mathbf{inv}_y = 0$ for $y_1 = y_2$.
If $y_1 \neq y_2$ then $\mathbf{inv}_y = (y_2 - y_1)^{-1}$

2.5.2 Variable Base Scalar Multiplication

For $R = [r]T$, where $r = 2^n + k$ and $k = [k_n \dots k_0]$, $k_i \in \{0, 1\}$:⁴

1. $P = [2]T$
2. for i from $n - 1$ to 0:
 - 2.1 $Q = k_{i+1} ? T : -T$
 - 2.2 $R = P + Q + P$
3. $R = k_0 ? R - T : R$

The first and last steps of the algorithm are verified by the unified addition and doubling circuit.

Row	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
i	x_T	y_T	x_0	y_0	$n = 0$	n'	—	x_1	y_1	x_2	y_2	x_3	y_3	x_4	y_4
$i + 1$	x_5	y_5	b_0	b_1	b_2	b_3	b_4	s_0	s_1	s_2	s_3	s_4	—	—	—
\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots
$i + 100$	x_T	y_T	x_0	y_0	n	n'	—	x_1	y_1	x_2	y_2	x_3	y_3	x_4	y_4
$i + 101$	x_5	y_5	b_0	b_1	b_2	b_3	b_4	s_0	s_1	s_2	s_3	s_4	—	—	—

⁴Using the results from <https://arxiv.org/pdf/math/0208038.pdf>

Two gates are used in the circuit. Call them VBSM_1 and VBSM_2 . VBSM_1 is applied to even rows and VBSM_2 is used with odd rows. Each two rows perform calculations with five bits of the scalar.

Evaluations:

- b_i are bits of the k , first b_1 is the most significant bit of k , n is an accumulator of b_i .
- $(x_1, y_1) - (x_0, y_0) = (x_0, y_0) + (x_T, (2b_1 - 1)y_T)$
- $(x_2, y_2) - (x_1, y_1) = (x_1, y_1) + (x_T, (2b_1 - 1)y_T)$
- $(x_3, y_3) - (x_2, y_2) = (x_2, y_2) + (x_T, (2b_1 - 1)y_T)$
- $(x_4, y_4) - (x_3, y_3) = (x_3, y_3) + (x_T, (2b_1 - 1)y_T)$
- $(x_5, y_5) - (x_4, y_4) = (x_4, y_4) + (x_T, (2b_1 - 1)y_T)$
- $s_0 = \frac{y_0 - (2b_0 - 1) \cdot y_T}{x_0 - x_T}$
- $s_1 = \frac{y_1 - (2b_1 - 1) \cdot y_T}{x_1 - x_T}$
- $s_2 = \frac{y_2 - (2b_2 - 1) \cdot y_T}{x_2 - x_T}$
- $s_3 = \frac{y_3 - (2b_3 - 1) \cdot y_T}{x_3 - x_T}$
- $s_4 = \frac{y_4 - (2b_4 - 1) \cdot y_T}{x_4 - x_T}$

Constraints:

- $\text{next}(w_2) \cdot (w_2 - 1) = 0$
- $\text{next}(w_3) \cdot (w_3 - 1) = 0$
- $\text{next}(w_4) \cdot (w_4 - 1) = 0$
- $\text{next}(w_5) \cdot (w_5 - 1) = 0$
- $\text{next}(w_6) \cdot (w_6 - 1) = 0$
- $(w_2 - w_0) \cdot \text{next}(w_7) = w_3 - (2\text{next}(w_2) - 1) \cdot w_1$
- $(w_7 - w_0) \cdot \text{next}(w_8) = w_8 - (2\text{next}(w_3) - 1) \cdot w_1$
- $(w_{10} - w_0) \cdot \text{next}(w_9) = w_{11} - (2\text{next}(w_4) - 1) \cdot w_1$
- $(w_{12} - w_0) \cdot \text{next}(w_{10}) = w_{13} - (2\text{next}(w_5) - 1) \cdot w_1$
- $(\text{next}(w_0) - w_0) \cdot \text{next}(w_{11}) = \text{next}(w_1) - (2\text{next}(w_6) - 1) \cdot w_1$
- $(2 \cdot w_3 - \text{next}(w_7) \cdot (2 \cdot w_2 - \text{next}(w_7)^2 + w_0))^2 = (2 \cdot w_2 - \text{next}(w_7)^2 + w_0)^2 \cdot (w_7 - w_0 + \text{next}(w_7)^2)$
- $(2 \cdot w_8 - \text{next}(w_8) \cdot (2 \cdot w_7 - \text{next}(w_8)^2 + w_0))^2 = (2 \cdot w_7 - \text{next}(w_8)^2 + w_0)^2 \cdot (w_9 - w_0 + \text{next}(w_8)^2)$
- $(2 \cdot w_{10} - \text{next}(w_9) \cdot (2 \cdot w_9 - \text{next}(w_9)^2 + w_0))^2 = (2 \cdot w_9 - \text{next}(w_9)^2 + w_0)^2 \cdot (w_{11} - w_0 + \text{next}(w_9)^2)$
- $(2 \cdot w_{12} - \text{next}(w_{10}) \cdot (2 \cdot w_{11} - \text{next}(w_{10})^2 + w_0))^2 = (2 \cdot w_{11} - \text{next}(w_{10})^2 + w_0)^2 \cdot (w_{13} - w_0 + \text{next}(w_{10})^2)$
- $(2 \cdot w_{14} - \text{next}(w_{11}) \cdot (2 \cdot w_{13} - \text{next}(w_{11})^2 + w_0))^2 = (2 \cdot w_{13} - \text{next}(w_{11})^2 + w_0)^2 \cdot (\text{next}(w_0) - w_0 + \text{next}(w_{11})^2)$
- $(w_8 + w_3) \cdot (2 \cdot w_2 - \text{next}(w_7)^2 + w_0) = (w_2 - w_7) \cdot (2 \cdot w_3 - \text{next}(w_7) \cdot (2 \cdot w_2 - \text{next}(w_7)^2 + w_0))$
- $(w_{10} + w_8) \cdot (2 \cdot w_7 - \text{next}(w_8)^2 + w_0) = (w_7 - w_9) \cdot (2 \cdot w_8 - \text{next}(w_8) \cdot (2 \cdot w_7 - \text{next}(w_8)^2 + w_0))$
- $(w_{12} + w_{10}) \cdot (2 \cdot w_9 - \text{next}(w_9)^2 + w_0) = (w_9 - w_{11}) \cdot (2 \cdot w_{10} - \text{next}(w_9) \cdot (2 \cdot w_9 - \text{next}(w_9)^2 + w_0))$
- $(w_{14} + w_{10}) \cdot (2 \cdot w_{11} - \text{next}(w_{10})^2 + w_0) = (w_{11} - w_{13}) \cdot (2 \cdot w_{12} - \text{next}(w_{10}) \cdot (2 \cdot w_{11} - \text{next}(w_{10})^2 + w_0))$
- $(\text{next}(w_1) + w_{14}) \cdot (2 \cdot w_{13} - \text{next}(w_{11})^2 + w_0) = (w_{13} - \text{next}(w_0) \cdot (2 \cdot w_{14} - \text{next}(w_{11}) \cdot (2 \cdot w_{13} - \text{next}(w_{11})^2 + w_0)))$
- $w_5 = 32 \cdot (w_4) + 16 \cdot \text{next}(w_2) + 8 \cdot \text{next}(w_3) + 4 \cdot \text{next}(w_4) + 2 \cdot \text{next}(w_5) + \text{next}(w_6)$

Copy constraints:

- (x_T, y_T) in row j are copy constrained with (x_T, y_T) in row $j + 2$
- (x_0, y_0) in row i are copy constrained with values from the first doubling circuit
- (x_0, y_0) in row $j, j \neq i$ are copy constrained with (x_5, y_5) in row $j - 1$
- $n = 0$ in row i and n in the row $j, j \neq i$ is copy constrained with n' in the row $j - 2$

2.5.3 Variable Base Endo-Scalar Multiplication

For $R = [b]T$, where $b = [b_n \dots b_0]$ and $b_i \in \{0, 1\}$:⁵

⁵Using the results from <https://eprint.iacr.org/2019/1021.pdf>

1. $P = [2](\phi(T) + T)$
2. for i from $\frac{\lambda}{2} - 1$ to 0:
 - 2.1 $Q = r_{2i+1} ? \phi([2r_{2i} - 1]T) : [2r_{2i} - 1]T$
 - 2.2 $R - P = P + Q$

The first step of the algorithm are verified by the doubling and unified addition circuit.

Row	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
i	x_T	y_T	--	--	x_P	y_P	$n = 0$	x_R	y_R	s_1	s_3	b_1	b_2	b_3	b_4
\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots
$i + 63$	x_T	y_T	--	--	x_P	y_P	n	x_R	y_R	s_1	s_3	b_1	b_2	b_3	b_4
$i + 64$	--	--	--	--	x_P	y_P	n	--	--	--	--	--	--	--	--

Evaluations:

- The first x_P, y_P are equal to $2 \cdot ((x_T, y_T) + ((\text{endo}) \cdot x_T, y_T))$
- b_i are bits of the k , first b_1 is the most significant bit of k , n is an accumulator of b_i .
- $(x_R, y_R) - (x_P, y_P) = (x_P, y_P) + (1 + (\text{endo} - 1) \cdot b_2)x_T, (2b_1 - 1)y_T$
- $(\text{next}(x_P), \text{next}(y_P)) - (x_R, y_R) = (x_R, y_R) + ((\text{endo} - 1) \cdot b_2)x_T, (2b_1 - 1)y_T$
- $s_1 = \frac{(2b_1 - 1) \cdot y_T - y_P}{(1 + (\text{endo} - 1) \cdot b_2)x_T - x_P}$
- $s_3 = \frac{(2b_1 - 1) \cdot y_T - y_R}{(1 + (\text{endo} - 1) \cdot b_2)x_T - x_R}$

Constraints:

- $w_{11} \cdot (w_{11} - 1) = 0$
- $w_{12} \cdot (w_{12} - 1) = 0$
- $w_{13} \cdot (w_{13} - 1) = 0$
- $w_{14} \cdot (w_{14} - 1) = 0$
- $((1 + (\text{endo} - 1) \cdot w_{12}) \cdot w_0 - w_4) \cdot w_9 = (2 \cdot w_{11} - 1) \cdot w_1 - w_5$
- $(2 \cdot w_4 - w_9^2 + (1 + (\text{endo} - 1) \cdot w_{12}) \cdot w_0) \cdot ((w_4 - w_7) \cdot w_9 + w_8 + w_5) = (w_4 - w_7) \cdot 2 \cdot w_5$
- $(w_8 + w_5)^2 = (w_4 - w_7)^2 \cdot (w_9^2 - (1 + (\text{endo} - 1) \cdot w_{12}) \cdot w_0 + w_7)$
- $((1 + (\text{endo} - 1) \cdot w_{12}) \cdot w_0 - w_7) \cdot w_{10} = (2 \cdot w_{13} - 1) \cdot w_1 - w_8$
- $(2 \cdot w_7 - w_{10}^2 + (1 + (\text{endo} - 1) \cdot w_{14}) \cdot w_0) \cdot ((w_7 - \text{next}(w_4)) \cdot w_{10} + \text{next}(w_5) + w_8) = (w_7 - \text{next}(w_4)) \cdot 2 \cdot w_8$
- $(\text{next}(w_4) + w_8)^2 = (w_7 - \text{next}(w_4))^2 \cdot (w_{10}^2 - (1 + (\text{endo} - 1) \cdot w_{14}) \cdot w_0 + \text{next}(w_4))$
- $\text{next}(w_6) = 16 \cdot w_6 + 8 \cdot w_{11} + 4 \cdot w_{12} + 2 \cdot w_{13} + w_{14}$

Copy constraints:

- (x_T, y_T) in row j are copy constrained with (x_T, y_T) in row $j + 1$
- (x_P, y_P) in row i are copy constrained with values from the first doubling circuit

2.5.4 Fixed-base scalar multiplication circuit

We precompute all values $w(B, s, k) = (k_i + 2) \cdot 8^s B$, where $k_i \in \{0, \dots, 7\}$, $s \in \{0, \dots, 83\}$ and $w(B, s, k) = (k_i \cdot 8^s - \sum_{j=0}^{84} 8^{j+1}) \cdot B$, where $k_i \in \{0, \dots, 7\}$, $s = 84$.

Row	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
i	b_0	b_1	b_2	b_3	b_4	b_5	u_0	u_1	v_0	v_1	x_1	y_1	x_2	y_2	acc
\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots
$i + 42$	b_0	b_1	b_2	u_0	v_0	x_w	y_w	α	β	γ	δ	λ	--	--	b

Define the following functions:

1. $\phi_1 : (x_1, x_2, x_3, x_4) \mapsto$
 $x_3 \cdot (-u'_0 \cdot x_2 \cdot x_1 + u'_0 \cdot x_1 + u'_0 \cdot x_2 - u'_0 + u'_2 \cdot x_1 \cdot x_2 - u'_2 \cdot x_2 + u'_4 \cdot x_1 \cdot x_2 - u'_4 \cdot x_2 - u'_6 \cdot x_1 \cdot x_2 +$
 $u'_1 \cdot x_2 \cdot x_1 - u'_1 \cdot x_1 - u'_1 \cdot x_2 + u'_1 - u'_3 \cdot x_1 \cdot x_2 + u'_3 \cdot x_2 - u'_5 \cdot x_1 \cdot x_2 + u'_5 \cdot x_2 + u'_7 \cdot x_1 \cdot x_2) - (x_4 -$
 $u'_0 \cdot x_2 \cdot x_1 + u'_0 \cdot x_1 + u'_0 \cdot x_2 - u'_0 + u'_2 \cdot x_1 \cdot x_2 - u'_2 \cdot x_2 + u'_4 \cdot x_1 \cdot x_2 - u'_4 \cdot x_2 - u'_6 \cdot x_1 \cdot x_2)$
2. $\phi_2 : (x_1, x_2, x_3, x_4) \mapsto$
 $x_3 \cdot (-v'_0 \cdot x_2 \cdot x_1 + v'_0 \cdot x_1 + v'_0 \cdot x_2 - v'_0 + v'_2 \cdot x_1 \cdot x_2 - v'_2 \cdot x_2 + v'_4 \cdot x_1 \cdot x_2 - v'_4 \cdot x_2 - v'_6 \cdot x_1 \cdot x_2 + v'_1 \cdot$
 $x_2 \cdot x_1 - v'_1 \cdot x_1 - v'_1 \cdot x_2 + v'_1 - v'_3 \cdot x_1 \cdot x_2 + v'_3 \cdot x_2 - v'_5 \cdot x_1 \cdot x_2 + v'_5 \cdot x_2 + v'_7 \cdot x_1 \cdot x_2) - (x_4 - v'_0 \cdot$
 $x_2 \cdot x_1 + v'_0 \cdot x_1 + v'_0 \cdot x_2 - v'_0 + v'_2 \cdot x_1 \cdot x_2 - v'_2 \cdot x_2 + v'_4 \cdot x_1 \cdot x_2 - v'_4 \cdot x_2 - v'_6 \cdot x_1 \cdot x_2)$

Constraints:

- For $i + 0$:
 - $b_i \cdot (b_i - 1) = 0$, where $i \in \{0, \dots, 5\}$
 - $\phi_1(b_0, b_1, b_2, u_0) = 0$, where $(u'_i, v'_i) = w(B, 0, i)$
 - $\phi_1(b_3, b_4, b_5, u_1) = 0$, where $(u'_i, v'_i) = w(B, 1, i)$
 - $\phi_2(b_0, b_1, b_2, v_0) = 0$, where $(u'_i, v'_i) = w(B, 0, i)$
 - $\phi_2(b_3, b_4, b_5, v_1) = 0$, where $(u'_i, v'_i) = w(B, 1, i)$
 - $acc = b_0 + b_1 \cdot 2 + b_2 \cdot 2^2 + b_3 \cdot 2^3 + b_4 \cdot 2^4 + b_5 \cdot 2^5$
 - $(x_1, y_1) = (u_0, v_0)$
 - $(x_2, y_2) = (x_1, y_1) + (u_1, v_1)$ incomplete addition, where $x_1 \neq u_1$
- For $i + z$, $z \in 1, \dots, 41$:
 - $b_i \cdot (b_i - 1) = 0$, where $i \in \{0, \dots, 5\}$
 - $\phi_1(b_0, b_1, b_2, u_0) = 0$, where $(u'_i, v'_i) = w(B, z \cdot 2, i)$
 - $\phi_1(b_3, b_4, b_5, u_1) = 0$, where $(u'_i, v'_i) = w(B, z \cdot 2 + 1, i)$
 - $\phi_2(b_0, b_1, b_2, v_0) = 0$, where $(u'_i, v'_i) = w(B, z \cdot 2, i)$
 - $\phi_2(b_3, b_4, b_5, v_1) = 0$, where $(u'_i, v'_i) = w(B, z \cdot 2 + 1, i)$
 - $acc = b_0 + b_1 \cdot 2 + b_2 \cdot 2^2 + b_3 \cdot 2^3 + b_4 \cdot 2^4 + b_5 \cdot 2^5 + acc_{prev} \cdot 2^6$
 - $(x_1, y_1) = (u_0, v_0) + (x_2, y_2)_{prev}$ incomplete addition, where $u_0 \neq x_2$
 - $(x_2, y_2) = (x_1, y_1) + (u_1, v_1)$ incomplete addition, where $x_1 \neq u_1$
- For $i + 42$:
 - $b_i \cdot (b_i - 1) = 0$, where $i \in \{0, \dots, 2\}$
 - $\phi_1(b_0, b_1, b_2, u_0) = 0$, where $(u'_i, v'_i) = w(B, 84, i)$
 - $\phi_2(b_0, b_1, b_2, v_0) = 0$, where $(u'_i, v'_i) = w(B, 84, i)$
 - $b = b_0 + b_1 \cdot 2 + b_2 \cdot 2^2 + acc_{prev} \cdot 2^3$
 - $(x_w, y_w) = (u_0, v_0) + (x_2, y_2)_{prev}$ complete addition from [Orchard](#)

2.6 Multi-Scalar Multiplication Circuit

WIP

Input: $G_0, \dots, G_{k-1} \in \mathbb{G}, s_0, \dots, s_{k-1} \in \mathbb{F}_r$, where \mathbb{F}_r is scalar field of \mathbb{G} .

Output: $S = \sum_{i=0}^k s_i \cdot G_i$

2.6.1 Naive Algorithm

Using endomorphism:

1. $A = \infty$
2. for j from 0 to $k - 1$:
 - 2.1 $r := s_j, T := G_j$
 - 2.2 $S = [2](\phi(T) + T)$
 - 2.3 for i from $\frac{\lambda}{2} - 1$ to 0:
 - 2.3.1 $Q = r_{2i+1} ? \phi([2r_{2i} - 1]T) : [2r_{2i} - 1]T$
 - 2.3.2 $R = S + Q$

$$2.3.3 \ S = R + S$$

$$2.4 \ A = A + S$$

$$\text{rows} \approx k \cdot (\text{sm_rows} + 1 + 2) \approx 67k,$$

where `sm_rows` is the number of rows in the scalar multiplication circuit.

Without endomorphism:

$$1. \ A = \infty$$

$$2. \ \text{for } j \text{ from } 0 \text{ to } k - 1:$$

$$2.1 \ r := s_j, T := G_j$$

$$2.2 \ S = [2]T$$

$$2.3 \ \text{for } i \text{ from } n - 1 \text{ to } 0:$$

$$2.3.1 \ Q = k_{i+1} ? T : -T$$

$$2.3.2 \ R = S + Q$$

$$2.3.3 \ S = R + S$$

$$2.4 \ S = k_0 ? S - T : S$$

$$2.5 \ A = A + S$$

$$\text{rows} \approx k \cdot (\text{sm_rows} + 1 + 1) \approx 105k,$$

where `sm_rows` is the number of rows in the scalar multiplication circuit.

2.6.2 Simultaneous Doubling

Remark: Simultaneous doubling incurs a negligible completeness error for independently chosen random terms of the sum.

Using endomorphism:

$$1. \ A = \sum_{j=0}^k [2](\phi(G_j) + G_j)$$

$$2. \ \text{for } i \text{ from } \frac{\lambda}{2} - 1 \text{ to } 0:$$

$$2.1 \ \text{for } j \text{ from } 0 \text{ to } k - 1:$$

$$2.1.1 \ r := s_j, T := G_j$$

$$2.1.2 \ Q = r_{2i+1} ? \phi([2r_{2i} - 1]T) : [2r_{2i} - 1]T$$

$$2.1.3 \ A = A + Q$$

$$2.2 \ \text{if } i \neq 0:$$

$$2.2.1 \ A = 2 \cdot A$$

$$\text{rows} \approx \frac{\lambda}{2} \cdot (k \cdot \text{add_rows} + \text{dbl_rows}) + 2k \approx 64 \cdot (k + 1) \approx 66k + 64,$$

where

- `add_rows` is the number of rows in the addition circuit.
- `dbl_rows` is the number of rows in the doubling circuit.

Without endomorphism:

1. $A = \sum_{j=0}^k [2]G_j$
2. for i from $n - 1$ to 0:
 - 2.1 for j from 0 to $k - 1$:
 - 2.1.1 $r := s_j, T := G_j$
 - 2.1.2 $Q = k_{i+1} ? T : -T$
 - 2.1.3 $A = A + Q$
 - 2.2 if $i \neq 0$:
 - 2.2.1 $A = 2 \cdot A$
3. $A = A + \sum_{j=0}^k [1 - s_{j,0}]G_j$

$$\text{rows} \approx \frac{2}{3}n \cdot (k \cdot \text{add_rows} + \text{dbl_rows}) + k \approx 103 \cdot (k + 1) + 2k \approx 104k + 103,$$

where

- **add_rows** is the number of rows in the addition circuit.
- **dbl_rows** is the number of rows in the doubling circuit.

2.7 Poseidon Circuit

WIP

Mina uses Poseidon hash with width = 3. Therefore, each permutation state is represented by 3 elements and each row contains 5 states.

Denote i -th permutation state by $T_i = (T_{i,0}, T_{i,1}, T_{i,2})$.

Row	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
i	$T_{0,0}$	$T_{0,1}$	$T_{0,2}$	$T_{4,0}$	$T_{4,1}$	$T_{4,2}$	$T_{1,0}$	$T_{1,1}$	$T_{1,2}$	$T_{2,0}$	$T_{2,1}$	$T_{2,2}$	$T_{3,0}$	$T_{3,1}$	$T_{3,2}$
\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots
$i + 10$	$T_{50,0}$	$T_{50,1}$	$T_{50,2}$	$T_{54,0}$	$T_{54,1}$	$T_{54,2}$	$T_{51,0}$	$T_{51,1}$	$T_{51,2}$	$T_{52,0}$	$T_{52,1}$	$T_{52,2}$	$T_{53,0}$	$T_{53,1}$	$T_{53,2}$
$i + 11$	$T_{55,0}$	$T_{55,1}$	$T_{55,2}$	\dots	\dots	\dots	\dots	\dots	\dots	\dots	\dots	\dots	\dots	\dots	\dots

State change constraints:

$$\text{STATE}(i + 1) = \text{STATE}(i)^\alpha \cdot \text{MDS} + \text{RC}$$

Denote the index of the first state in the row by **start** (e.g. **start** = 50 for 10-th row). We can expand the previous formula to:

- For i from **start** to **start** + 5:
 - $T_{i+1,0} = T_{i,0}^5 \cdot \text{MDS}[0][0] + T_{i,1}^5 \cdot \text{MDS}[0][1] + T_{i,2}^5 \cdot \text{MDS}[0][2] + \text{RC}_{i+1,0}$
 - $T_{i+1,1} = T_{i,0}^5 \cdot \text{MDS}[1][0] + T_{i,1}^5 \cdot \text{MDS}[1][1] + T_{i,2}^5 \cdot \text{MDS}[1][2] + \text{RC}_{i+1,1}$
 - $T_{i+1,2} = T_{i,0}^5 \cdot \text{MDS}[2][0] + T_{i,1}^5 \cdot \text{MDS}[2][1] + T_{i,2}^5 \cdot \text{MDS}[2][2] + \text{RC}_{i+1,2}$

Notice that the constraints above include the state from the next row (**start** + 5).

2.8 Other Circuits

WIP

2.8.1 Combined Inner Product

$$\sum_{i=0}^k \xi^i \cdot (f_i(\zeta_1) + r \cdot f_i(\zeta_2))$$

Row	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
$i + 0$	f_1	f'_1	f_2	f'_2	acc	ξ	ξ_{acc}	s_1	s_2	ξ'_{acc}
$i + 1$	f_3	f'_3	f_4	f'_4	acc	r	ξ_{acc}	s_1	s_2	ξ'_{acc}
\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots
$i + \lceil \frac{k}{2} \rceil - 1$	f_{k-3}	f'_{k-3}	f_{k-2}	f'_{k-2}	acc	ξ	ξ_{acc}	s_1	s_2	ξ'_{acc}
$i + \lceil \frac{k}{2} \rceil$	f_{k-1}	f'_{k-1}	f_k	f'_k	acc	r	ξ_{acc}	s_1	s_2	ξ'_{acc}

Constraints for $i + z$, where $z \bmod 2 = 0$:

- $(w_0 + w_1 \cdot \text{next}(w_5)) \cdot w_6 = w_7$
- $(w_2 + w_3 \cdot \text{next}(w_5)) \cdot w_9 = w_8$
- $w_5 \cdot w_6 = w_9$
- $w_5 \cdot w_9 = \text{next}(w_9)$
- $w_5 \cdot \text{next}(w_9) = \text{next}(w_5)$
- $w_4 + w_7 + w_8 + \text{next}(w_7) + \text{next}(w_8) = \text{next}(w_4)$

Constraints for $i + z$, where $z \bmod 2 = 1$:

- $(w_0 + w_1 \cdot w_5) \cdot w_9 = w_7$
- $(w_2 + w_3 \cdot w_5) \cdot w_6 = w_8$

2.8.2 Endo-Scalar Computation

Let α be equals to $\phi(b)$, where $b \in 0, 1^\lambda$.

Row	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
i	n_0	n_8	a_0	b_0	a_8	b_8	--	x_0	x_1	x_2	x_3	x_4	x_5	x_6	x_7
\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots	\vdots
$i + 7$	n_0	n_8	a_0	b_0	a_8	b_8	res	x_0	x_1	x_2	x_3	x_4	x_5	x_6	x_7

Evaluations:

- In the first row $n_0 = 0$, $a_0 = 2$, $b_0 = 2$.
- x_i are 2-bits chunks of the b , first x_0 is the most significant bit of b , n is an accumulator of x_i .
- The values (a_8, b_8) are 8 iterations of the following computations:

$$(a_i, b_i) = (2 \cdot a_{i-1} + c_f(x_{i-1}), 2 \cdot b_{i-1} + d_f(x_{i-1})), \text{ where } c_f(x) = 2/3 \cdot x^3 - 5/2 \cdot x^2 + 11/6 \cdot x \text{ and } d_f(x) = 2/3 \cdot x^3 - 7/2 \cdot x^2 + 29/6 \cdot x - 1.$$

Constraints:

- $w_7 \cdot (w_7 - 1) \cdot (w_7 - 2) \cdot (w_7 - 3) = 0$
- $w_8 \cdot (w_8 - 1) \cdot (w_8 - 2) \cdot (w_8 - 3) = 0$
- $w_9 \cdot (w_9 - 1) \cdot (w_9 - 2) \cdot (w_9 - 3) = 0$
- $w_{10} \cdot (w_{10} - 1) \cdot (w_{10} - 2) \cdot (w_{10} - 3) = 0$
- $w_{11} \cdot (w_{11} - 1) \cdot (w_{11} - 2) \cdot (w_{11} - 3) = 0$
- $w_{12} \cdot (w_{12} - 1) \cdot (w_{12} - 2) \cdot (w_{12} - 3) = 0$
- $w_{13} \cdot (w_{13} - 1) \cdot (w_{13} - 2) \cdot (w_{13} - 3) = 0$
- $w_{14} \cdot (w_{14} - 1) \cdot (w_{14} - 2) \cdot (w_{14} - 3) = 0$
- $w_4 = 256 \cdot w_2 + 128 \cdot c_f(w_6) + 64 \cdot c_f(w_7) + 32 \cdot c_f(w_8) + 16 \cdot c_f(w_9) + 8 \cdot c_f(w_{10}) + 4 \cdot c_f(w_{11}) + 2 \cdot c_f(w_{12}) + c_f(w_{13})$

- $w_5 = 256 \cdot w_3 + 128 \cdot d_f(w_6) + 64 \cdot d_f(w_7) + 32 \cdot d_f(w_8) + 16 \cdot d_f(w_9) + 8 \cdot d_f(w_{10}) + 4 \cdot d_f(w_{11}) + 2 \cdot d_f(w_{12}) + d_f(w_{13})$
- $w_1 = 2^{16} \cdot w_0 + 2^{14} \cdot w_6 + 2^{12} \cdot w_7 + 2^{10} \cdot w_8 + 2^8 \cdot w_9 + 2^6 \cdot w_{10} + 2^4 \cdot w_{11} + 2^2 \cdot w_{12} + w_{13}$
- for $i + 7$:
 1. $w_6 = \mathbf{endo} \cdot w_4 + \cdot w_5$

Copy constraints:

- n_0, a_0, b_0 in row $j + 1$ are copy constrained with (n_8, a_8, b_8) in row j

Chapter 3

In-EVM State Proof Verifier

This introduces a description for in-EVM Mina Protocol state proof verification mechanism. Crucial components which define this part design are:

1. Verification architecture description.
2. Verification logic API reference.
3. Input data structures description.

3.1 Verification Logic Architecture

The verification logic is split to several parts:

1. Verification Key Definition
2. LPC/FRI auxiliary proof deserialization

3.2 Verification Logic API Reference

3.3 Input Data Structures

Bibliography

1. Kattis A., Panarin K., Vlasov A. RedShift: Transparent SNARKs from List Polynomial Commitment IOPs. Cryptology ePrint Archive, Report 2019/1400. 2019. <https://ia.cr/2019/1400>.
2. Gabizon A., Williamson Z. J., Ciobotaru O. PLONK: Permutations over Lagrange-bases for Oecumenical Noninteractive arguments of Knowledge. Cryptology ePrint Archive, Report 2019/953. 2019. <https://ia.cr/2019/953>.
3. Fast Reed-Solomon interactive oracle proofs of proximity / E. Ben-Sasson, I. Bentov, Y. Horesh et al. // 45th international colloquium on automata, languages, and programming (icalp 2018) / Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik. 2018.
4. Gabizon A., Williamson Z. J. Proposal: The Turbo-PLONK program syntax for specifying SNARK programs. https://docs.zkproof.org/pages/standards/accepted-workshop3/proposal-turbo_plonk.pdf.
5. PLONKish Arithmetization - The halo2 book. <https://zcash.github.io/halo2/concepts/arithmetization.html>.
6. Gabizon A., Williamson Z. J. plookup: A simplified polynomial protocol for lookup tables. Cryptology ePrint Archive, Report 2020/315. 2020. <https://ia.cr/2020/315>.
7. Lookup argument - The halo2 book. <https://zcash.github.io/halo2/design/proving-system/lookup.html>.
8. Chiesa A., Ojha D., Spooner N. Fractal: Post-Quantum and Transparent Recursive Proofs from Holography. Cryptology ePrint Archive, Report 2019/1076. 2019. <https://ia.cr/2019/1076>.