

# README for The Econometrics Journal Data Editor

## ## 1. Package overview

Replication package for:

**\*\*Identification and Bayesian Inference for Synthetic Control Methods with Spillover Effects\*\***

This package is prepared for ECTJ pre-acceptance reproducibility checks.  
Substantive computation is implemented in plain '.R' scripts under 'code/'.

## ## 2. Folder structure

- 'code/': executable replication scripts
- 'data/': bundled input data ('.rda') and documentation
- 'data/nonproprietary/': non-proprietary CSV copies of bundled datasets
- 'output/figures/': generated figures (expected to be created by replicator run)
- 'output/tables/': generated tables and CSV summaries (expected to be created by replicator run)
- 'output/logs/': run logs
- 'RESULTS\_MAPPING.csv': paper outputs to script/output mapping
- 'MANIFEST.csv': submission boundary and file classification record
- 'DEPENDENCY\_LOCK.csv': fixed dependency/version specification used for this package

## ## 3. Data availability statement

Datasets required for replication are bundled in this package:

- 'data/california\_smoking.rda'
- 'data/sudan\_secession.rda'

Non-proprietary copies are bundled as CSV:

- 'data/nonproprietary/california\_panel.csv'
- 'data/nonproprietary/california\_w\_vector.csv'
- 'data/nonproprietary/california\_W\_matrix.csv'
- 'data/nonproprietary/sudan\_panel.csv'
- 'data/nonproprietary/sudan\_w\_vector.csv'
- 'data/nonproprietary/sudan\_W\_matrix.csv'

Variable-level documentation is provided in:

- 'data/VARIABLE\_DICTIONARY.md'

## ## 4. Required rights statements

I certify that the author(s) of the manuscript have legitimate access to and permission to use the data used .

I certify that the author(s) of the manuscript have documented permission to redistribute/publish the data co

## ## 5. Software and dependency requirements

- R: '>= 4.2.0'
- C++ toolchain: required for 'Rcpp' compilation
- Tested platform for this package: macOS (Apple Silicon)

Dependency preflight:

```
'''bash
Rscript code/00_setup.R
'''
```

Optional behaviors:

- Auto-install missing packages from CRAN:

```
'''bash
SCSPILL_INSTALL_MISSING=true Rscript code/00_setup.R
'''
```

- Enforce exact versions from 'DEPENDENCY\_LOCK.csv':

```
'''bash
SCSPILL_ENFORCE_LOCK=true Rscript code/00_setup.R
'''
```

## 6. Execution modes: smoke vs full

### 'smoke' mode

Purpose:

- pipeline integrity check only (script orchestration, file generation, logging)
- not a claim of manuscript-scale numerical reproduction

Command:

```
'''bash
Rscript code/99_run_all.R smoke all
'''
```

Expected outputs in smoke mode:

- all core figure/table file paths listed in 'RESULTS\_MAPPING.csv' are generated
- simulation output is generated with reduced workload (still produces mapping-compatible files)
- logs are written under 'output/logs/'

### 'full' mode

Purpose:

- manuscript-scale reproduction mode for paper tables/figures and reported numbers

Command:

```
'''bash
Rscript code/99_run_all.R full all
'''
```

Expected outputs in full mode:

- full set of mapped outputs in 'RESULTS\_MAPPING.csv'
- full simulation and JDT workload (long runtime)
- logs under 'output/logs/'

Approximate runtime and hardware for full mode:

- recommended hardware:  $\geq$  8GB RAM, multi-core CPU
- 'code/01\_california\_main.R': roughly 30-90 minutes
- 'code/02\_sudan\_main.R': roughly 60-180 minutes
- 'code/03\_simulation\_main.R': several hours
- 'code/04\_geweke\_main.R': several hours

### ## 7. Master execution interface

Preferred command:

```
'''bash
Rscript code/99_run_all.R full all
'''
```

Optional Makefile entrypoint:

```
'''bash
make run SCSPILL_MODE=full SCSPILL_TARGET=all
'''
```

Supported targets in 'code/99\_run\_all.R':

- 'all'
- 'main'
- 'simulation'
- 'geweke'

'code/99\_run\_all.R' validates mode/target, runs dependency and data-export preflight, executes selected scripts, writes 1

### ## 8. Output mapping (RESULTS\_MAPPING)

The authoritative paper-output mapping is stored in:

- 'RESULTS\_MAPPING.csv'

This file maps:

- paper output identifier
- producing script
- expected output path
- smoke/full generation expectations

### ## 9. Submission boundary (frozen)

Submission boundary is defined by:

- 'MANIFEST.csv'

'MANIFEST.csv' classifies each entry as one of:

- 'code'
- 'input\_data'
- 'generated\_output'
- 'documentation'

For generated outputs, it explicitly indicates:

- 'bundled\_at\_submission'

- 'generated\_by\_editor'

Current boundary rule:

- output figures/tables in 'RESULTS\_MAPPING.csv' are \*\*expected to be generated by the editor run\*\* and are marked 'bundled'.
- execution logs in 'output/logs/' are bundled as run evidence.

### ## 10. Logging and environment signals

Each script log written by 'code/99\_run\_all.R' includes:

- run timestamp
- execution mode and target
- mode purpose
- R version
- platform/OS info
- seed contract used by the script
- dependency lock package versions ('DEPENDENCY\_LOCK.csv')

If absolute paths appear in some environments, they are environment artifacts only and are not required for reproduction.

### ## 11. Data citations (copy for manuscript references)

- Abadie, A., Diamond, A., & Hainmueller, J. (2010). Synthetic control methods for comparative case studies: Estimating treatment effects on a time series of US states.
- Cunningham, S. (2021). \*Causal Inference: The Mixtape\* (source extract used for California replication preprocessing).
- World Bank. World Development Indicators (dataset).
- International Monetary Fund. Direction of Trade Statistics (dataset).

### ## 12. Mandatory-requirement cross-reference (M1-M12)

- M1: package completeness -> 'RESULTS\_MAPPING.csv', 'code/99\_run\_all.R'
- M2: README + software versions -> this file, 'README.pdf', 'DEPENDENCY\_LOCK.csv'
- M3: data + variable documentation -> 'data/', 'data/VARIABLE\_DICTIONARY.md'
- M4: full reproducible code -> 'code/01\_\*.R' to 'code/04\_\*.R'
- M5: fixed seeds -> script seed initialization + log seed contracts
- M6: non-proprietary copies -> 'data/nonproprietary/\*.csv'
- M7: data availability statement -> Section 3
- M8: rights statements -> Section 4
- M9: run instructions + output locations -> Sections 6-9
- M10: software/package requirements -> Section 5
- M11: expected runtime/hardware -> Section 6 (full mode)
- M12: data citations -> Section 11

### ## 13. Explicit assumptions

1. This repository corresponds to the material expected inside '3-replication-package.zip'.
2. '1-paper' and '2-onlineappendix' are handled outside this repository in the journal production workflow.
3. No restricted-data exemption workflow is used in this package version.
4. Bundled '.rda' analysis extracts are treated as reproducibility inputs; provider-side raw download bundles are outside this repository.