Plot a life cycle diagram from a matrix model

Owen Jones

2018-02-06

The exercise plots a life cycle with the stages and transitions of a give matrix chosen from the comadre (or compadre) database (or indeed elsewhere). It will use the R function plotLifeCycle from the Rage library. This function works well with matrices of relatively low dimensionality (~< 7), and where not many transitions are depicted.

```
library(Rage)
```

Let's plot the lifecycle described by the A matrix for a species containing the word "lion" in the common name used by the author(s) in the original source publication.

First load the data:

```
load("COMADRE_v.2.0.1.RData")
```

To find the species with the word lion in their common name, we use the function grep.

```
lions <- grep("lion",comadre$metadata$CommonName)
unique(comadre$metadata$CommonName[lions])</pre>
```

- > [1] "Common lionfish"
- > [2] "Red lionfish"
- > [3] "Northern sea lion; Steller sea lion"
- > [4] "New Zealand sea lion"
- > [5] "California sea lion"

Unfortunately, no actual lion (*Panthera leo*) has been included in this version of COMADRE, but there are plenty of other "lions" in it. We will plot the life cycle of the red lionfish (*Pterois volitans*):

```
matNum <- which(comadre$metadata$CommonName == "Red lionfish")
matNum</pre>
```

> [1] 166

```
sp <- gsub("_"," ",comadre$metadata$SpeciesAccepted[matNum])
sp</pre>
```

> [1] "Pterois volitans"

The matrix 'A' and the stages of this study are:

```
matA <- comadre$mat[[matNum]]$matA
matA</pre>
```

```
> A1 A2 A3
```

```
> [1,] 0e+00 0.000 35.315
```

- > [2,] 3e-05 0.777 0.000
- > [3,] 0e+00 0.071 0.949

stages <- comadre\$matrixClass[[matNum]]\$MatrixClassAuthor
stages</pre>

```
> [1] "Larvae" "Juvenile (20 - 174 mm)" 
> [3] "Adult (> 174 mm)"
```

To plot its lifecycle, use the function plotLifeCycle.R from the Rage package.

```
Rage::plotLifeCycle(matA, title = "Red lionfish")
```