

Shell Command Reference



File Commands

ls - directory listing
ls -al - formatted listing with hidden files
cd *dir* - change directory to *dir*
cd - change to home
pwd - show current directory
mkdir *dir* - create a directory *dir*
rm *file* - delete *file*
rm -r *dir* - delete directory *dir*
rm -f *file* - force remove *file*
rm -rf *dir* - force remove directory *dir* *
cp *file1 file2* - copy *file1* to *file2*
cp -r *dir1 dir2* - copy *dir1* to *dir2*; create *dir2* if it doesn't exist
mv *file1 file2* - rename or move *file1* to *file2*
if *file2* is an existing directory, moves *file1* into directory *file2*
ln -s *file link* - create symbolic link *link* to *file*
touch *file* - create or update *file*
cat > *file* - places standard input into *file*
more *file* - output the contents of *file*
head *file* - output the first 10 lines of *file*
tail *file* - output the last 10 lines of *file*
tail -f *file* - output the contents of *file* as it grows, starting with the last 10 lines

Process Management

ps - display your currently active processes
top - display all running processes
kill *pid* - kill process id *pid*
killall *proc* - kill all processes named *proc* *
bg - lists stopped or background jobs; resume a stopped job in the background
fg - brings the most recent job to foreground
fg *n* - brings job *n* to the foreground

File Permissions

chmod *octal file* - change the permissions of *file* to *octal*, which can be found separately for user, group, and world by adding:

- 4 - read(r)
- 2 - write(w)
- 1 - execute(x)

Examples:

chmod 777 - read, write, execute for all
chmod 755 - rwx for owner, rx for group and world
For more options, see **man chmod**.

SSH

ssh *user@host* - connect to *host* as *user*
ssh -p *port user@host* - connect to *host* on port *port* as *user*
ssh-copy-id *user@host* - add your key to *host* for *user* to enable a keyed or passwordless login

Searching

grep *pattern files* - search for *pattern* in *files*
grep -r *pattern dir* - search recursively for *pattern* in *dir*
command* | grep *pattern - search for *pattern* in the output of *command*
locate *file* - find all instances of *file*

System Info

date - show the current date and time
cal - show this month's calendar
uptime - show current uptime
w - display who is online
whoami - who you are logged in as
finger *user* - display information about *user*
uname -a - show kernel information
cat /proc/cpuinfo - cpu information
cat /proc/meminfo - memory information
man *command* - show the manual for *command*
df - show disk usage
du - show directory space usage
free - show memory and swap usage
whereis *app* - show possible locations of *app*
which *app* - show which *app* will be run by default

Network

ping *host* - ping *host* and output results
whois *domain* - get whois information for *domain*
dig *domain* - get DNS information for *domain*
dig -x *host* - reverse lookup *host*
wget *file* - download *file*
wget -c *file* - continue a stopped download

Installation

Install from source:

./configure

make

make install

dpkg -i *pkg.deb* - install a package (Debian)

rpm -Uvh *pkg.rpm* - install a package (RPM)

Shortcuts

Ctrl+C - halts the current command
Ctrl+Z - stops the current command, resume with **fg** in the foreground or **bg** in the background
Ctrl+D - log out of current session, similar to **exit**
Ctrl+W - erases one word in the current line
Ctrl+U - erases the whole line
Ctrl+R - type to bring up a recent command
!! - repeats the last command
exit - log out of current session

* use with extreme caution.