

GRANITE STATE ENVIRONMENTAL LABS

88 Foundry Street · Manchester, NH 03101 · (603) 555-0271 · www.granitestate-envlab.example

NH-ELAP Accredited — Cert. No. NH-2298 | DoD ELAP Recognized

SOIL WASTE CHARACTERIZATION REPORT — EXCESS EXCAVATED MATERIAL

REPORT NO. GSE-26-08814	DATE REPORTED July 22, 2026
CLIENT / CONTRACTOR Colby & Hart Construction Co.	PROJECT / SITE Riverside Mixed-Use Development, Lot 14B, Manchester NH
SAMPLE ID SB-07 (2.0–4.0 ft bgs)	SAMPLE MATRIX Native Soil (Sandy Silt)
DATE COLLECTED July 15, 2026, 13:40 EDT	DATE RECEIVED July 16, 2026, 09:05 EDT
COLLECTED BY R. Desmarais (GeoTech Env. Svcs)	CHAIN OF CUSTODY NO. COC-51309

1. Case Narrative

Composite soil boring samples were collected to characterize excess material generated during foundation excavation, in support of off-site disposal approval. Historical fill and adjacent former filling-station use required screening for petroleum hydrocarbons and RCRA metals. Results below are for the boring showing the highest field PID reading.

2. Petroleum Hydrocarbons

Parameter	Result	Method	Reporting Limit	Flag
TPH — Diesel Range Organics (DRO)	1,240 mg/kg	SW-846 8015D	10 mg/kg	Review
TPH — Gasoline Range Organics (GRO)	88 mg/kg	SW-846 8015D	5 mg/kg	—
Benzene	0.42 mg/kg	SW-846 8260D	0.02 mg/kg	—
Naphthalene	3.1 mg/kg	SW-846 8270E	0.10 mg/kg	—

3. RCRA Metals (Total, SW-846 6010D/7471B)

Analyte	Result (mg/kg)	Regional Screening Level	Reporting Limit	Flag
Arsenic	9.8	23 (residential)	0.5 mg/kg	Pass
Lead	142	400 (residential)	1.0 mg/kg	Pass
Chromium (Total)	18.3	—	0.5 mg/kg	—
Mercury	0.03	—	0.02 mg/kg	Pass

4. TCLP Leachate (Metals) — Disposal Facility Screen

Analyte	Result (mg/L)	RCRA Limit (mg/L)	Flag
Lead	0.089	5.0	Pass
Arsenic	< 0.010	5.0	Pass
Chromium (Total)	0.021	5.0	Pass

TCLP run as a conservative check for landfill acceptance; total metals concentrations were well below the 20x rule threshold.

5. Waste Profile Recommendation

Material is non-hazardous per RCRA characteristic testing. DRO result exceeds the receiving facility's 500 mg/kg petroleum-impacted soil acceptance screen; recommend routing to a facility permitted for petroleum-contaminated soil (PCS) or beneficial reuse under state Brownfields guidance rather than a standard C&D landfill.

I certify that this data package has undergone Level II data validation and meets the QA/QC objectives of the approved sampling and analysis plan for this project.

M. Okafor, QA Officer

Date: July 22, 2026

This report shall not be reproduced except in full, without the written approval of GRANITE STATE ENVIRONMENTAL LABS. Results are illustrative and fictional — for template/reference use only.