CSC248 – Fundamentals of Data Structure Academic Session October 2023 – February 2024 Lab Assignment 4 – Linked List (UDT)

| Course Outcomes (CO) | LO1 | LO2 | LO3 |
|----------------------|-----|-----------|-----|
| CO1 | | | |
| CO2 | V | $\sqrt{}$ | |
| CO3 | | | |

The list using dynamic storage to store computer's information for a computer laboratory. Given the respective classes as follows:

```
public class Computer
private int serialNo; //computer identification
private String brand; //brand name private int
            //year of buying private double price
      //buying price
 //Normal constructor
   //Getter
} public class
ListNode{ private
Object obj;
 private ListNode next;
         :
}
public class List
 private ListNode firstNode; //reference to the first node in the list
private ListNode lastNode; //reference to the last node in the list
private ListNode currNode;
                             //to traversal purpose
         :
   publicList();
   public void insertAtFront(Object);
   public void insertAtBack(Object); public
   void insertAtAtMiddle(Object); public
   Object remove(int);
 public void searchComputer(int);     public
   int countComputer(double);
}
```

(MNOS2023) 1 | Page

- a) Write all definition functions for the above operation to do the following tasks:
 - i. To insert a new node (computer's information) at the front/back/middle of list. The information is given by a parameter. If the information existed in the list, you don't have to insert the node. (NOTE** Every computer has a unique serial number identification)
 - ii. To remove a node from the list based on the serial number of the computer. Computer serial number is given by a parameter.
 - iii. To print the output of computer's information based on the searching index (the serial number). Computer serial number is given by a parameter.
 - iv. To count and return the number of computers which exceed a certain amount price. The amount is given by a parameter. This method also will print the output of brand code and year of buying which computers fulfill the above criteria.
- b) Write an application program by implementing a menu selection to do the following tasks.
 - i. Insert a new node into list. The computer to be inserted can be at the front, at the back and at the middle of the list based on the user selection.
 - ii. To delete any node from a list based on serial number of the computer
 - iii. To print the output of computer's information based on the searching index
 - iv. To count and return the number of computers which exceed a certain amount price

Computer.java

```
public class Computer {
    private int serialNo;
    private String brand;
    private int year;
    private double price;
    public Computer(int serialNo, String brand, int year, double price) {
        this.serialNo = serialNo;
        this.brand = brand;
        this.year = year;
        this.price = price;
    public int getSerialNo() {
        return this.serialNo;
    public void setSerialNo(int serialNo) {
        this.serialNo = serialNo;
    public String getBrand() {
        return this.brand;
    public void setBrand(String brand) {
        this.brand = brand;
    }
    public int getYear() {
        return this.year;
    public void setYear(int year) {
        this.year = year;
    public double getPrice() {
        return this.price;
    public void setPrice(double price) {
        this.price = price;
    public String toString() {
```

List.java

```
public class List {
    private ListNode firstNode;
    private ListNode lastNode;
    private ListNode currNode;
    public List() {
        this.firstNode = null;
        this.lastNode = null;
        this.currNode = null;
    public ListNode getFirstNode() {
        return this.firstNode;
    public void setFirstNode(ListNode firstNode) {
        this.firstNode = firstNode;
    public ListNode getLastNode() {
        return this.lastNode;
    public void setLastNode(ListNode lastNode) {
        this.lastNode = lastNode;
    public ListNode getCurrNode() {
        return this.currNode;
    public void setCurrNode(ListNode currNode) {
        this.currNode = currNode;
    public void insertAtFront(Object obj) {
        ListNode newNode = new ListNode(obj, this.firstNode);
        this.firstNode = newNode;
        if (this.lastNode == null) {
            this.lastNode = newNode;
    public void insertAtBack(Object obj) {
        ListNode newNode = new ListNode(obj, null);
        if (this.lastNode == null) {
```

```
this.firstNode = newNode;
        this.lastNode = newNode;
   } else {
       this.lastNode.setNext(newNode);
        this.lastNode = newNode;
// insert at middle
public void insertAtMiddle(Object obj) {
   ListNode newNode = new ListNode(obj, null);
   if (this.firstNode == null) {
        this.firstNode = newNode;
        this.lastNode = newNode;
   } else {
        // put the new node at the middle and not based on the serial number
        ListNode curr = this.firstNode;
        int count = 0;
        while (curr != null) {
            count++;
            curr = curr.getNext();
        curr = this.firstNode;
        for (int i = 0; i < (count / 2) - 1; i++) {
            curr = curr.getNext();
        newNode.setNext(curr.getNext());
        curr.setNext(newNode);
        if (newNode.getNext() == null) {
            this.lastNode = newNode;
public Object remove(int serialNo) {
    ListNode curr = this.firstNode;
   ListNode prev = null;
   while (curr != null) {
        if (((Computer) curr.getObj()).getSerialNo() == serialNo) {
            break;
        prev = curr;
        curr = curr.getNext();
```

```
if (curr == null) {
        return null;
   if (prev == null) {
        this.firstNode = curr.getNext();
    } else {
        prev.setNext(curr.getNext());
   if (curr.getNext() == null) {
       this.lastNode = prev;
   return curr.getObj();
public void searchComputer(int serialNo) {
    ListNode curr = this.firstNode;
   while (curr != null) {
        if (((Computer) curr.getObj()).getSerialNo() == serialNo) {
            break;
        curr = curr.getNext();
   if (curr == null) {
        System.out.println("Computer not found");
        System.out.println(curr.getObj());
public int countComputer(double price) {
   int count = 0;
   ListNode curr = this.firstNode;
   while (curr != null) {
        if (((Computer) curr.getObj()).getPrice() > price) {
            count++;
            // print out the computer
            System.out.println(curr.getObj() + "\n");
        curr = curr.getNext();
   return count;
public void print() {
   ListNode curr = this.firstNode;
   while (curr != null) {
        System.out.println(curr.getObj() + "\n");
```

```
curr = curr.getNext();
}
}
}
```

ListNode.java

```
public class ListNode {
    private Object obj;
    private ListNode next;
   public ListNode(Object obj, ListNode next) {
        this.obj = obj;
        this.next = next;
   public Object getObj() {
        return this.obj;
   public void setObj(Object obj) {
        this.obj = obj;
    public ListNode getNext() {
        return this.next;
    public void setNext(ListNode next) {
        this.next = next;
    public String toString() {
        return this.obj.toString();
```

```
import java.util.Scanner;
public class Main {
    public static void main(String[] args) {
        Scanner strInput = new Scanner(System.in);
        Scanner intInput = new Scanner(System.in);
        System.out.println("Welcome to Computer List Program\n");
        System.out.print(
                "1. Insert a new node into list\n2. Delete node from list based
on serial number\n3. Print output of computer's information\n4. Count and return
the number of computers which exceed a certain amount price\n5. Display all
lists\n6. Exit\n\nEnter your choice: ");
        int choice = intInput.nextInt();
        List list = new List();
        System.out.println();
        while (choice != 6) {
            if (choice == 1) {
                System.out.print("Enter serial number: ");
                int serialNo = intInput.nextInt();
                // check if theres any computer with the same serial number
                ListNode curr = list.getFirstNode();
                boolean exist = false;
                while (curr != null) {
                    if (((Computer) curr.getObj()).getSerialNo() == serialNo) {
                        System.out.println("Serial number already exist\n");
                        exist = true;
                        break;
                    curr = curr.getNext();
                if (exist) {
                    continue;
                System.out.print("Enter brand: ");
                String brand = strInput.nextLine();
                System.out.print("Enter year: ");
                int year = intInput.nextInt();
                System.out.print("Enter price (RM): ");
                double price = intInput.nextDouble();
```

```
System.out.print(
                        "\n1. Insert at the beginning of the list\n2. Insert at
the end of the list\n3. Insert at middle of the list\n\nEnter your choice: ");
                int choice2 = intInput.nextInt();
                if (choice2 == 1) {
                    list.insertAtFront(new Computer(serialNo, brand, year,
price));
                } else if (choice2 == 2) {
                    list.insertAtBack(new Computer(serialNo, brand, year,
price));
                } else if (choice2 == 3) {
                    list.insertAtMiddle(new Computer(serialNo, brand, year,
price));
                } else {
                    System.out.println("Invalid choice");
            } else if (choice == 2) {
                System.out.print("Enter serial number: ");
                int serialNo = intInput.nextInt();
                if (list.remove(serialNo) == null) {
                    System.out.println("Serial number not found\n");
                } else {
                    System.out.println("Serial number " + serialNo + " has been
deleted\n");
            } else if (choice == 3) {
                System.out.print("Enter serial number: ");
                int serialNo = intInput.nextInt();
                System.out.println();
                list.searchComputer(serialNo);
            } else if (choice == 4) {
                System.out.print("Enter price to print out which computers price
exceed it (RM): ");
                double price = intInput.nextDouble();
                System.out.println("\nThere's " + list.countComputer(price) + "
computers which exceed RM " + price);
            } else if (choice == 5) {
                list.print();
            } else {
                System.out.println("Invalid choice");
            System.out.print(
```

Sample Output

Welcome to Computer List Program 1. Insert a new node into list 2. Delete node from list based on serial number 3. Print output of computer's information 4. Count and return the number of computers which exceed a certain amount price 5. Display all lists 6. Exit Enter your choice: 1 Enter serial number: 1234 Enter brand: Nitro Enter year: 2022 Enter price (RM): 9435 1. Insert at the beginning of the list 2. Insert at the end of the list 3. Insert at middle of the list Enter your choice: 1 1. Insert a new node into list 2. Delete node from list based on serial number 3. Print output of computer's information 4. Count and return the number of computers which exceed a certain amount price 5. Display all lists 6. Exit Enter your choice: 5

Serial number: 1234

Brand: Nitro Year: 2022

Price: RM 9435.0

- 1. Insert a new node into list
- 2. Delete node from list based on serial number
- 3. Print output of computer's information
- 4. Count and return the number of computers which exceed a certain amount price
- 5. Display all lists
- 6. Exit

Enter your choice: 1

Enter serial number: 3213 Enter brand: HP Pavillion

Enter year: 2023

Enter price (RM): 3423

- 1. Insert at the beginning of the list
- 2. Insert at the end of the list
- 3. Insert at middle of the list

Enter your choice: 2

- 1. Insert a new node into list
- 2. Delete node from list based on serial number
- 3. Print output of computer's information
- 4. Count and return the number of computers which exceed a certain amount price
- 5. Display all lists
- 6. Exit

Enter your choice: 5

Serial number: 1234

Brand: Nitro Year: 2022 Price: RM 9435.0

Serial number: 3213 Brand: HP Pavillion

Year: 2023 Price: RM 3423.0

- 1. Insert a new node into list
- 2. Delete node from list based on serial number
- 3. Print output of computer's information
- 4. Count and return the number of computers which exceed a certain amount price
- 5. Display all lists
- 6. Exit

Enter your choice: 1

Enter serial number: 1234 Serial number already exist

Enter serial number: 2343 Enter brand: Asus Tuf Enter year: 2020

Enter price (RM): 4300

- 1. Insert at the beginning of the list
- Insert at the end of the list
 Insert at middle of the list

Enter your choice: 3

- 1. Insert a new node into list
- 2. Delete node from list based on serial number
- 3. Print output of computer's information
- 4. Count and return the number of computers which exceed a certain amount price
- 5. Display all lists
- 6. Exit

Enter your choice: 5

Serial number: 1234

Brand: Nitro Year: 2022

Price: RM 9435.0

Serial number: 2343 Brand: Asus Tuf Year: 2020

Price: RM 4300.0

Serial number: 3213 Brand: HP Pavillion

Year: 2023

Price: RM 3423.0

- 1. Insert a new node into list
- 2. Delete node from list based on serial number
- 3. Print output of computer's information
- 4. Count and return the number of computers which exceed a certain amount price
- 5. Display all lists
- 6. Exit

Enter your choice: 2

Enter serial number: 2111 Serial number not found

- 1. Insert a new node into list
- 2. Delete node from list based on serial number
- 3. Print output of computer's information
- 4. Count and return the number of computers which exceed a certain amount price
- 5. Display all lists
- 6. Exit

Enter your choice: 2

Enter serial number: 2343

Serial number 2343 has been deleted

- 1. Insert a new node into list
- 2. Delete node from list based on serial number
- 3. Print output of computer's information
- 4. Count and return the number of computers which exceed a certain amount price
- 5. Display all lists
- 6. Exit

Enter your choice: 3

Enter serial number: 2343

Computer not found

- 1. Insert a new node into list
- 2. Delete node from list based on serial number
- 3. Print output of computer's information
- 4. Count and return the number of computers which exceed a certain amount price
- 5. Display all lists
- 6. Exit

Enter your choice: 3

Enter serial number: 1234

Serial number: 1234

Brand: Nitro Year: 2022

Price: RM 9435.0

- 1. Insert a new node into list
- 2. Delete node from list based on serial number
- 3. Print output of computer's information
- 4. Count and return the number of computers which exceed a certain amount price
- 5. Display all lists
- 6. Exit

Enter your choice: 4

Enter price to print out which computers price exceed it (RM): 2000

Serial number: 1234

Brand: Nitro Year: 2022 Price: RM 9435.0

Serial number: 3213 Brand: HP Pavillion

Year: 2023

Price: RM 3423.0

There's 2 computers which exceed RM 2000.0

- 1. Insert a new node into list
- 2. Delete node from list based on serial number
- 3. Print output of computer's information
- 4. Count and return the number of computers which exceed a certain amount price
- 5. Display all lists
- 6. Exit

Enter your choice: 6

Program terminating...