

Kitti DataSet localization model.

(Autonomous Vehicle Localization Using Onboard Sensors and HD-Geolocated Maps [MATLAB Project #20] - Spring 2024 Semester).

[Project Link - Our submission](#)

Presented by:

- Hazem Mohsen Abdelaziz
- Yousra Adly Deifallah

Under Supervision of:

- Prof. Dr. Mohamed Ibrahim Awad (Head of Mechatronics department - Faculty of Engineering - Ain Shams University)

Table of Contents

Data Loading, Visualization, And Storing.....	1
Loading Unsync Data.....	10
GPS data conversion (Geodatic to local) and Visualization.....	12
IMU Based Localization.....	13
Synced IMU-Based Localization model, evaluation, and Stored data visualization.....	13
[Unsynchronized] IMU-Based Localization model, evaluation, and Stored data visualization.....	16
Lidar-Based Localization model and evaluation.....	20
Camera-Based Localization model and evaluation.....	23
Sensory Data Fusion.....	26
Average Estimation Model.....	26
Weighted Sum Estimation.....	29
Standard Kalman Filter.....	33
Synced data Kalman Filter.....	33
Unsynced data Kalman Filter.....	37
Extracting Weights for adaptive filters.....	40
Adaptive filters (Weighted Average - KF - unsynced KF).....	41
Adaptive Weighted Average Model.....	41
Adaptive Kalman Filter.....	42
Adaptive Kalman Filter for Unsynced data.....	43
Frame-Based KF.....	44
Evaluating Fusion Techniques on world map using Latitude/Longitude Coordinates.....	46

Data Loading, Visualization, And Storing.

```
%Loading Dataset from extracted folder on our local machine
%Add dataset path below
dataset_path = 'C:\Users\Hazem Abdelaziz\Downloads\GP-
Github\Autonomous-Vehicle-Localization-Using-Onboards-Sensor-and-HD-Geolocated-
Maps-Project-Solution\KITTI\2011_09_29_drive_0071\2011_09_29_drive_0071_sync';
%Start loading UNSYNC OXTS data to perform same for IMU based estimates
unSyncDataset_path = 'C:\Users\Hazem Abdelaziz\Downloads\GP-
Github\Autonomous-Vehicle-Localization-Using-Onboards-Sensor-and-HD-Geolocated-
Maps-Project-Solution\KITTI\2011_09_29_drive_0071\2011_09_29_drive_0071_extract';
```

```

%for GPS data (Where LLA_to_Local function script exists)
mainDirectory = 'C:\Users\Hazem Abdelaziz\Downloads\GP-Github\Autonomous-Vehicle-
Localization-Using-Onboards-Sensor-and-HD-Geolocated-Maps-Project-Solution\KITTI';
%Go to images folder and check for how many images in there to represents
%number of frames
rgbFolderPath = strcat(dataset_path, '\image_02\data');
grayFolderPath = strcat(dataset_path, '\image_00\data');
pngFiles = dir(fullfile(rgbFolderPath, '*.png'));
rgbVector = cell(1, numel(pngFiles));
grayVector = cell(1, numel(pngFiles));
%For Unsynced data
%Go to OXTS folder and check for how many Samples in there to represents
%number of frames
unsyncOxtsFolderPath = strcat(unSyncDataset_path, '\oxts\data');
unsyncOxtsFiles = dir(fullfile(unsyncOxtsFolderPath, '*.txt'));
%Setting number of frames and Sampling time according to certain dataset
framesNum = numel(pngFiles);
Ts = 0.1;
%And for Unsynced Data
unsyncFramesNum = numel(unsyncOxtsFiles);
unsyncIMUTs = 0.01;

```

```

%Store stereo camera first frame (For center cameras 0: Gray & 2: RGB)
gray_image = imread(fullfile(dataset_path, 'image_00\data', '0000000000.png'));
rgb_image = imread(fullfile(dataset_path, 'image_02\data', '0000000000.png'));

```

```

% Display the images
figure;
imshow(gray_image);
title('Gray Scale Image');
figure;
imshow(rgb_image);
title('Colored Image');

```

```

%Store Colored image in an image vector
% !! If the data set contains many frames this might take a while
for i = 1:numel(pngFiles)
    %Construct the full file path
    filePath = fullfile(rgbFolderPath, pngFiles(i).name);
    %Read the image and store it
    rgbVector{i} = imread(filePath);
end

```

```

%Store Gray Colored image in an image vector
camAvI = zeros(framesNum,1);
for i = 1:numel(pngFiles)
    %Construct the full file path
    filePath = fullfile(grayFolderPath, pngFiles(i).name);
    %Read the image and store it
    grayVector{i} = imread(filePath);
    camAvI(i) = mean(mean(grayVector{i}));
end

```

end

```
%This Cell is to save a video consisting of multiple images in a vector
%Each image of type cell
%cd('') %Here you can enter the save location
%{
outputVideo = VideoWriter('output_video.avi');
outputVideo.FrameRate = 10; %Frame rate that the images vector recorded at for a
better display
open(outputVideo);

for i = 1:numel(rgbVector)
    % Convert image from cell to matrix
    frame =rgbVector{i};

    %write the frame to the video
    writeVideo(outputVideo, frame);
end

% Close the video file
close(outputVideo);
%}
```

```
%This cell is to display the sequence of rgb colored image frames
for i = 1:numel(rgbVector)
    % Display the current image
    imshow(rgbVector{i});
    title(['Frame ', num2str(i)]); %Adding frame number as a title
    pause(0.1); %Pausing the video according to recorded frame rate
end
```

```
pcdFolderPath = strcat(dataset_path, '\velodyne_points\data');
pcdFiles = dir(pcdFolderPath);
% || CAUTION || %
%This section is to convert from bin file data to
% !! This section is to be run once to avoid overwriting and saving files
%multiple times, to convert it for the first time uncomment the section
%bellow
%{
cd(pcdFolderPath);
for i = 1:length(pcdFiles)
    filename = pcdFiles(i).name;
    if(length(filename) > 10)
        binOpen = fopen(filename, 'rb'); %Open binary in read mode
        binData = fread(binOpen, [4, inf], 'single'); %Reading data from binary
file
        fclose(binOpen);
        extension_to_remove = '.bin';
        original_str = filename;
        start_idx = strfind(original_str, extension_to_remove);
        end_idx = start_idx + length(extension_to_remove) - 1;
```

```

        modified_str = original_str;
        modified_str(start_idx:end_idx) = '';
        save(strcat(modified_str, '.mat'), 'binData');
    end
end
%}

```

```

%visualize a LiDAR point cloud from a frame
point_cloud = load(fullfile(pcdFolderPath, '0000000000.mat'));
pcdX = point_cloud.binData(:,1);
pcdY = point_cloud.binData(:,2);
pcdZ = point_cloud.binData(:,3);
point_cloud_data = [pcdX, pcdY, pcdZ];
pcshow(point_cloud_data)
xlabel('X');
ylabel('Y');
zlabel('Z');
title('Point Cloud Visualization');

```

```

pcdMat = NaN(5000, 4, framesNum); %This matrix will hold our point cloud
pcdR = zeros(framesNum, 1); %Vector to hold average reflectivity for each frame
matFiles = dir(fullfile(pcdFolderPath, '*.mat'));
for i = 1:numel(matFiles)
    point_cloud = load(fullfile(pcdFolderPath, matFiles(i).name));
    pcdMat(1:size(point_cloud.binData(:,1)),1,i) = point_cloud.binData(:,1);
    pcdMat(1:size(point_cloud.binData(:,2)),2,i) = point_cloud.binData(:,2);
    pcdMat(1:size(point_cloud.binData(:,3)),3,i) = point_cloud.binData(:,3);
    pcdMat(1:size(point_cloud.binData(:,4)),4,i) = point_cloud.binData(:,4) *
255; %Multiplication to get actual value, denormalization
    pcdR(i) = mean(pcdMat(:,4,i));
    if(i==1)
        fprintf('Out of %d frames, Processing point cloud matching on frame
No.',framesNum);
    end
    fprintf('\b\b\b\b\b%d', i);
end
end

```

Out of 1059 frames, Processing point cloud matching on frame No.
1059

```

%Creating point cloud vector to downsample and filter (Preprocessing)
pointCloudObjects = cell(framesNum);
for i = 1:framesNum
    % Convert the array to a pointCloud object
    pointCloudObjects{i} = pointCloud(pcdMat(:,1:3,i));
    pointCloudObjects{i} = pcdownsample(pointCloudObjects{i}, 'gridAverage',
0.5);
    %PCD With outliers removal
    pointCloudObjects{i} = pcdenoise(pointCloudObjects{i}, 'Threshold', 0.5);
    if(i==1)
        fprintf('Out of %d frames, Processing point cloud matching on frame
No.',framesNum);
    end
end

```

```

end
fprintf('\b\b\b\b\b\b%d', i);
end

```

Out of 1059 frames, Processing point cloud matching on frame No.
1059

```

%To display 3D lidar data
xlimits = [-40 40];
ylimits = [-40 40];
zlimits = [ -5 5];
coder.extrinsic('isOpen', 'pcplayer')
player = pcplayer(xlimits, ylimits, zlimits);
for i = 1:numel(matFiles)
    pcdX = pcdMat(:,1,i);
    pcdY = pcdMat(:,2,i);
    pcdZ = pcdMat(:,3,i);
    point_cloud_data = [pcdX, pcdY, pcdZ];
    % Update the plot with the point cloud for the current frame
    view(player, point_cloud_data);
    pause(0.1); % Adjust the pause duration as needed
end

```

```

%To display 3D lidar data (Downsampled)
xlimits = [-40 40];
ylimits = [-40 40];
zlimits = [ -5 5];
coder.extrinsic('isOpen', 'pcplayer')
player = pcplayer(xlimits, ylimits, zlimits);
for i = 1:numel(matFiles)
    % Update the plot with the point cloud for the current frame
    view(player, pointCloudObjects{i});
    pause(0.1); % Adjust the pause duration as needed
end

```

```

%Reading GPS/IMU data from OXTS folder
%Data are stored in the format show at dataformat.txt file
oxtsFolderPath = strcat(dataset_path, '\oxts\data');
oxtsFiles = dir(oxtsFolderPath);
cd(oxtsFolderPath);
OXTS = zeros(framesNum,30);
j = 1;
for i = 3:length(oxtsFiles) % 3 to avoid backward in location
    filename = oxtsFiles(i).name;
    if(length(filename) > 5)
        OXTS(j,:) = importdata(filename);
    end
    j = j +1;
end
%Go back to where the live script located to be used in further processing
%for GPS data (Where LLA_to_Local function script exists)
cd(mainDirectory);

```

```

%Separating OXTS folder to Data vectors needed for further processing
%To Get GPS-Based Position(Ground Truth Position)that will be converted to local
frame:
latitude = OXTS(:,1);
longitude = OXTS(:,2);
altitude = OXTS(:,3);

%To Get (To evaluate integration model and difference):
roll = OXTS(:,4);
pitch = OXTS(:,5);
yaw = OXTS(:,6);

%To get velocity of vehicle (To evaluate integration model and difference):
vn = OXTS(:,7);
ve = OXTS(:,8);

%IMU Readings (To obtain Pose estimation based on IMU data only):
    %Accelerometer reading:
af = OXTS(:,15);
al = OXTS(:,16);
au = OXTS(:,17);
    %Gyroscope reading:
wf = OXTS(:,21);
wl = OXTS(:,22);
wu = OXTS(:,23);

%Loading GPS accuracy and numbers of satellites
posAcc = OXTS(:,24);
numSats = OXTS(:,27);

%Creating time frame starting from Second 0
timeVector = 0:0.1:(framesNum-1)*0.1;

%Get absolute velocity from either derivative of acceleration of
%sqrt(vn^2+ve^2)
vAbs = sqrt(vn.^2 + ve.^2);
%To get the scale factor or abs Dist, that will be used in camera algorithm
%we divide vAbs / camera frequency, which in this case is equals to 10
scaleFactor = vAbs / 10;

```

```

%Creating subplots to visualize IMU data
figure;
figure('Position', [50, 50, 2000, 2000]); % [left bottom width height]

subplot(3,2,1);
plot(timeVector, af);
xlabel('Time (sec)');
ylabel('Af (m/s^2)');
grid("on");

subplot(3,2,2);


```

```
plot(timeVector, al);
xlabel('Time (sec)');
ylabel('A1 (m/s^2)');
grid("on");

subplot(3,2,3);
plot(timeVector, au);
xlabel('Time (sec)');
ylabel('Au (m/s^2)');
grid("on");
subplot(3,2,4);
plot(timeVector, wf);
xlabel('Time (sec)');
ylabel('Wf (rad/s)');
grid("on");

subplot(3,2,5);
plot(timeVector, wl);
xlabel('Time (sec)');
ylabel('Wl (rad/s)');
grid("on");

subplot(3,2,6);
plot(timeVector, wu);
xlabel('Time (sec)');
ylabel('Wu (rad/s)');
grid("on");
```



```
%Now we plot the route using GPS data on a global map
webmap('Open Street Map');
wmmarker(latitude(1), longitude(1), 'FeatureName', 'Start point');
wmline(latitude(2:end-1), longitude(2:end-1));
wmmarker(latitude(end), longitude(end), 'FeatureName', 'End point');
```

```
%Filtering input data, if needed uncomment below section
%{
Fs = 10; %sampling frequency
%cutoff frequency
cutoff_frequency = 1; % Specify the cutoff frequency for filtering high-
frequency noise
```



```

%low-pass filter
[b, a] = butter(4, cutoff_frequency / (Fs / 2), 'low'); %4th-order Butterworth
filter

% Apply the low-pass filter to the data
af = filtfilt(b, a, af);
al = filtfilt(b, a, al);
wu = filtfilt(b, a, wu);
vn = filtfilt(b, a, vn);
ve = filtfilt(b, a, ve);
%}

```

```


%Creating subplots to visualize GPS geodatic frame data
figure;
set(gcf, 'Color', 'white');
figure('Position', [50, 50, 2000, 2000]); % [left bottom width height]

subplot(1,3,1);
plot(timeVector, latitude);
xlabel('Time (sec)');
ylabel('Latitude (deg)');

subplot(1,3,2);
plot(timeVector, longitude);
xlabel('Time (sec)');
ylabel('Longitude (deg)');

subplot(1,3,3);
plot(timeVector, altitude);
xlabel('Time (sec)');
ylabel('Altitude (m)');

```



Loading Unsync Data.

```
%Reading GPS/IMU data from Unsynchronized OXTS folder
cd(unsyncOxtsFolderPath);
UNSYNCOXTS = zeros(framesNum,30);
j = 1;
for i = 1:length(unsyncOxtsFiles)
    filename = unsyncOxtsFiles(i).name;
    if(length(filename) > 5)
        UNSYNCOXTS(j,:) = importdata(filename);
    end
    j = j + 1;
end
```

```

end
%Go back to where the live script located to be used in further processing
%for GPS data (Where LLA_to_Local function script exists)
cd(mainDirectory);

%Seperating OXTS folder to Data vectors needed for further processing
%To Get GPS-Based Position(Ground Truth Position)that will be converted to local
frame:
unsyncLatitude = UNSYNCOXTS(:,1);
unsyncLongitude = UNSYNCOXTS(:,2);
unsyncAltitude = UNSYNCOXTS(:,3);

%To Get (To evaluate integration model and difference):
unsyncRoll = UNSYNCOXTS(:,4);
unsyncPitch = UNSYNCOXTS(:,5);
unsyncYaw = UNSYNCOXTS(:,6);

%To get velocity of vehcile (To evaluate integration model and difference):
unsyncVn = UNSYNCOXTS(:,7);
unsyncVe = UNSYNCOXTS(:,8);

%IMU Readings (To obtain Pose estimation based on IMU data only):
    %Accelerometer reading:
unsyncAf = UNSYNCOXTS(:,15);
unsyncAl = UNSYNCOXTS(:,16);
unsyncAu = UNSYNCOXTS(:,17);
    %Groscope reading:
unsyncWf = UNSYNCOXTS(:,21);
unsyncWl = UNSYNCOXTS(:,22);
unsyncWu = UNSYNCOXTS(:,23);

%Loading GPS accuracy and numbers of satellites
unsyncPosAcc = UNSYNCOXTS(:,24);
unsyncNumSats = UNSYNCOXTS(:,27);

%Creating time frame starting from Second 0 (Assuming Ts is const at 0.01s)
unsyncTimeVector = 0:0.01:(unsyncFramesNum-1)*0.01;

%Creating timeSeries from timestamps text file
uOxtsTsPath = strcat(unSyncDataset_path, '\oxts\ ', 'timestamps.txt');
fid = fopen(uOxtsTsPath, 'r');
timestamps_str = textscan(fid, '%s', 'Delimiter', '\n');
fclose(fid);
timestamps = datetime(timestamps_str{1}, 'InputFormat', 'yyyy-MM-dd
HH:mm:ss.SSSSSSSS', 'Format', 'yyyy-MM-dd HH:mm:ss.SSSSSSSS');
time_diff = diff(timestamps);
time_diff_seconds = seconds(time_diff);
uOxtsTs = zeros(1, unsyncFramesNum);
uOxtsTs(1) = 0.01;
uOxtsTs(2:end) = time_diff_seconds;
usOxtsTsRef = zeros(1, length(uOxtsTs)); %For a vector containing the time
difference in second
for i = 2:length(uOxtsTs)

```

```

usOxtsTsRef(i) = usOxtsTsRef(i-1) + uOxtsTs(i);
end

```

GPS data conversion (Geodatic to local) and Visualization.

```

%Converting LLA coordinate frame position to Local frame position using GPS
%data obtained
GPSn = zeros(framesNum, 1);
GPSe = zeros(framesNum, 1);
unsyncGPSn = zeros(unsyncFramesNum, 1);
unsyncGPSe = zeros(unsyncFramesNum, 1);
%Refrencing motion to first frame readings
for i= 1:framesNum
    [deltaE, deltaN, ~] = lla_to_enu(latitude(1), longitude(1), altitude(1),
latitude(i), longitude(i), altitude(i));
    GPSe(i) = deltaE;
    GPSn(i) = deltaN;
end
for i= 1:unsyncFramesNum
    [deltaE, deltaN, ~] = lla_to_enu(unsynclatitude(1), unsyncLongitude(1),
unsyncAltitude(1), unsyncLatitude(i), unsyncLongitude(i), unsyncAltitude(i));
    unsyncGPSe(i) = deltaE;
    unsyncGPSn(i) = deltaN;
end

```


```

%Graph GPS based position
figure;

plot(GPSe, GPSn, '-o');
hold on;
plot(unsyncGPSe, unsyncGPSn, '-*');

xlabel('East position (m)');
ylabel('North Position (m)');
legend('Synced GPS position', 'UnSynced GPS position');
grid on;

```



IMU Based Localization

Synced IMU-Based Localization model, evaluation, and Stored data visualization.

```
%Convert Acceleration from sensor frame (Vehicle frame) to Global ENU Frame
Avehicle = [af,al];
Aenu = zeros(framesNum,2);
for i= 1:framesNum
    Aenu(i,1) = (cos(yaw(i)) * af(i)) -(sin(yaw(i)) * al(i));
    Aenu(i,2) = (sin(yaw(i)) * af(i)) +(cos(yaw(i)) * al(i));
end
Ae = Aenu(:,1);
An = Aenu(:,2);
```

```
%To get IMU-Based Pose:
IMUYaw = zeros(framesNum, 1);
IMUn= zeros(framesNum,1);
IMUe= zeros(framesNum,1);
IMUVn = zeros(framesNum,1);
IMUVe = zeros(framesNum,1);

%Setting initial data
IMUYaw(1) = yaw(1);
IMUVn(1) = vn(1);
IMUVe(1) = ve(1);

%Assuming zero initial pose.
```

```

for i = 2:(framesNum)
    %Using double integration to get position from acceleration and single
    %step integration to get o
    % rientation from angular velocity
    IMUVn(i) = IMUVn(i-1) + (An(i) * Ts); %Velociy from integration (north
direction)
    IMUVe(i) = IMUVe(i-1) + (Ae(i) * Ts); %Velociy from integration (east
direction)

    IMUn(i) = IMUn(i-1) + (IMUVn(i) * Ts) + (0.5 * (Ts^2) * An(i)); %Position
from integration (north direction)
    IMUe(i) = IMUe(i-1) + (IMUVe(i) * Ts) + (0.5 * (Ts^2) * Ae(i)); %Position
from integration (east direction)

    IMUYaw(i) = IMUYaw(i-1) + (wu(i) * Ts); %orientation from integration (Yaw
angle)
end

```

```

%Evaluating IMU-Based Position based on Ground truth data
figure;

```

```

subplot(2, 1, 1);
plot(GPSe, GPSn, '-o');
hold on;
plot(IMUe, IMUn, '-*');
xlabel('East position (m)');
ylabel('North Position (m)');
legend('Synced GPS route', 'Synceed IMU route');
grid on;


```

```

subplot(2, 1, 2);
plot(timeVector, rad2deg(yaw), 'g');
hold on;
plot(timeVector, rad2deg(IMUYaw), 'r--');
xlabel('Time (s)');
ylabel('Yaw angle (rad)');
legend('Ground-Truth Yaw', 'IMU-Based Yaw');
grid on;
sgtitle('IMU-Based model output');

```

IMU-Based model output




```
%Calculating Error (Difference between IMU and GPS data)
SeDiff = GPSe - IMUe;
SnDiff = GPSn- IMUn;
yawDiff = yaw- IMUYaw;

%Graphing error
figure;
figure('Position', [50, 50, 600, 600]); % [left bottom width height]

subplot(3, 1, 1);
plot(timeVector, SeDiff, 'r');
xlabel('Time (s)');
ylabel('Se difference (m)');
grid on;
subplot(3, 1, 2);
plot(timeVector, SnDiff, 'g');
xlabel('Time (s)');
ylabel('Sn difference (m)');
grid on;
subplot(3, 1, 3);
plot(timeVector, rad2deg(yawDiff), 'b');
xlabel('Time (s)');
ylabel('Yaw angle difference (deg)');
title('Yaw Angle')
grid on;

sgtitle('IMU-Based model Difference to GPS');
```



[Unsynchronized] IMU-Based Localization model, evaluation, and Stored data visualization.

```
%Convert Acceleration from sensor frame (Vehicle frame) to Global ENU Frame
unsyncAvehicle = [unsyncAf,unsyncAl];
unsyncAenu = zeros(unsyncFramesNum,2);
for i= 1:unsyncFramesNum
    unsyncAenu(i,1) = (cos(unsyncYaw(i)) * unsyncAf(i)) -(sin(unsyncYaw(i)) *
unsyncAl(i));
    unsyncAenu(i,2) = (sin(unsyncYaw(i)) * unsyncAf(i)) +(cos(unsyncYaw(i)) *
unsyncAl(i));
end
unsyncAe = unsyncAenu(:,1);
unsyncAn = unsyncAenu(:,2);
```

```
%To get Unsync IMU-Based Pose:
unsyncIMUYaw = zeros(unsyncFramesNum, 1);
unsyncIMUn= zeros(unsyncFramesNum,1);
```



```

unsyncIMUe= zeros(unsyncFramesNum,1);
unsyncIMUVn = zeros(unsyncFramesNum,1);
unsyncIMUve = zeros(unsyncFramesNum,1);

%Setting initial data
unsyncIMUYaw(1) = unsyncYaw(1);
unsyncIMUVn(1) = unsyncVn(1);
unsyncIMUve(1) = unsyncVe(1);

%Assuming zero initial pose.
for i = 2:(unsyncFramesNum)
    %Using double integration to get position from acceleration and single
    %step integration to get o
    %rientation from angular velocity
    unsyncIMUVn(i) = unsyncIMUVn(i-1) + (unsyncAn(i) * unsyncIMUTs); %Velocity
    from integration (north direction)
    unsyncIMUve(i) = unsyncIMUve(i-1) + (unsyncAe(i) * unsyncIMUTs); %Velocity
    from integration (east direction)

    unsyncIMUn(i) = unsyncIMUn(i-1) + (unsyncIMUVn(i) * unsyncIMUTs); %Position
    from integration (north direction)
    unsyncIMUe(i) = unsyncIMUe(i-1) + (unsyncIMUve(i) * unsyncIMUTs); %Position
    from integration (east direction)

    unsyncIMUYaw(i) = unsyncIMUYaw(i-1) + (unsyncWu(i) * unsyncIMUTs);
    %orientation from integration (Yaw angle)
end

```

```

%now using timestamps difference in time to evaluate
%Setting initial data
unsyncIMUYawT = zeros(unsyncFramesNum, 1);
unsyncIMUnT = zeros(unsyncFramesNum,1);
unsyncIMUeT = zeros(unsyncFramesNum,1);
unsyncIMUVnT = zeros(unsyncFramesNum,1);
unsyncIMUveT = zeros(unsyncFramesNum,1);

unsyncIMUYawT(1) = unsyncYaw(1);
unsyncIMUVnT(1) = unsyncVn(1);
unsyncIMUveT(1) = unsyncVe(1);

%Assuming zero initial pose.
for i = 2:(unsyncFramesNum)
    %Using double integration to get position from acceleration and single
    %step integration to get o
    %rientation from angular velocity
    unsyncIMUVnT(i) = unsyncIMUVnT(i-1) + (unsyncAn(i) * u0xtsTs(i)); %Velocity
    from integration (north direction)
    unsyncIMUveT(i) = unsyncIMUveT(i-1) + (unsyncAe(i) * u0xtsTs(i)); %Velocity
    from integration (east direction)

    unsyncIMUnT(i) = unsyncIMUnT(i-1) + (unsyncIMUVnT(i) * u0xtsTs(i));
    %Position from integration (north direction)

```

```

    unsyncIMUeT(i) = unsyncIMUeT(i-1) + (unsyncIMUVeT(i) * uOxtsTs(i));
    %Position from integration (east direction)

    unsyncIMUYawT(i) = unsyncIMUYawT(i-1) + (unsyncWu(i) * uOxtsTs(i));
    %orientation from integration (Yaw angle)
end

```

```

%Evaluating IMU-Based Position based on Ground truth data
figure;

```

```


subplot(2, 1, 1);
plot(unsyncGPSn, unsyncGPSn, '-o');
hold on;
plot(unsyncIMUn, unsyncIMUn, '-*');
xlabel('East position (m)');
ylabel('North Position (m)');
legend('unSynced GPS route', 'unSynceed IMU route');
grid on;

```

```

subplot(2, 1, 2);
plot(unsyncTimeVector, unsyncYaw, 'g');
hold on;
plot(unsyncTimeVector, unsyncIMUYaw, 'r--');
xlabel('Time (s)');
ylabel('Yaw angle (rad)');
legend('Ground-Truth Yaw', 'IMU-Based Yaw');
grid on;
sgtitle('Unsynced IMU-Based model output');

```




```
%Calculating Error (Difference between Unsync IMU and GPS data)
```

```
unsyncSeDiff = unsyncGPSse - unsyncIMUe;  
unsyncSnDiff = unsyncGPSsn - unsyncIMUn;  
unsyncYawDiff = unsyncYaw - unsyncIMUYaw;  
unsyncSeDiffT = unsyncGPSse - unsyncIMUe;  
unsyncSnDiffT = unsyncGPSsn - unsyncIMUn;  
unsyncYawDiffT = unsyncYaw - unsyncIMUYaw;
```

```
%Graphing error
```

```
figure;  
subplot(3, 1, 1);  
plot(unsyncTimeVector, unsyncSeDiff, 'r');  
hold on;  
plot(usOxtsTsRef, unsyncSeDiffT, 'b');  
xlabel('Time (s)');  
ylabel('Unsync Se difference (m)');  
grid on;  
subplot(3, 1, 2);  
plot(unsyncTimeVector, unsyncSnDiff, 'r');  
hold on;  
plot(usOxtsTsRef, unsyncSnDiffT, 'b');  
xlabel('Time (s)');  
ylabel('Unsync Sn difference (m)');  
grid on;  
subplot(3, 1, 3);  
plot(unsyncTimeVector, rad2deg(unsyncYawDiff), 'r');  
hold on;  
plot(usOxtsTsRef, deg2rad(unsyncYawDiffT), 'b');  
xlabel('Time (s)');  
ylabel('Unsync Yaw angle difference (deg)');  
title('Yaw Angle')  
grid on;  
  
sgtitle('Unsynced IMU-Based model Difference to GPS');
```



Lidar-Based Localization model and evaluation.

```
lidarX = zeros(1, framesNum);
lidarY = zeros(1, framesNum);
lidarXBar = zeros(1, framesNum);
lidarYBar = zeros(1, framesNum);
lidarYaw = zeros(1, framesNum);
lidarYaw(1) = rad2deg(yaw(1)); %Setting initial starting angle
lidarSampleNumber = framesNum-1;
for i = 1:lidarSampleNumber %for more accurate (full trajectory results we need
to change from a limited number to total number of frames)
    % Check if each point cloud has at least three unique points
    ptCloudOne= pointCloudObjects{i};
    ptCloudTwo = pointCloudObjects{i+1};
    numptCloudOne = size(ptCloudOne.Location, 1);
    numptCloudTwo = size(ptCloudTwo.Location, 1);
    if numptCloudOne < 3 || numptCloudTwo < 3
        lidarX(i+1) = lidarX(i);
        lidarY(i+1) = lidarY(i);
        lidarXBar(i+1) = lidarXBar(i);
        lidarYBar(i+1) = lidarYBar(i);
        lidarYaw(i+1) = lidarYaw(i);
    else
        [tform, ~, ~] = pcregistericp(ptCloudTwo, ptCloudOne,
Metric="pointToPlane");
        % Extract rotation matrix and translation vector from transformation
matrix
        R = tform.T(1:3, 1:3);
```

```

    eulerAngles = -rotm2eul(R, 'XYZ');
    deltaYaw_vehicle_deg = double(rad2deg(eulerAngles(3)));
    t = tform.T(4, 1:3)';
    deltaY_vehicle_m = (t(1) * sin(deg2rad(lidarYaw(i)))) - (t(2) *
cos(deg2rad(lidarYaw(i)))); %for only lidar data
    deltaX_vehicle_m = - (t(2) * sin(deg2rad(lidarYaw(i)))) + (t(1) *
cos(deg2rad(lidarYaw(i)))); %for only lidar data
    deltaY_vehicle_mBar = (t(1) * sin(IMUYaw(i))) - (t(2) *
cos(IMUYaw(i))); %for Lidar-INS referenced
    deltaX_vehicle_mBar = - (t(2) * sin(IMUYaw(i))) + (t(1) *
cos(IMUYaw(i))); %for Lidar-INS referenced
    lidarY(i+1) = lidarY(i) + deltaY_vehicle_m;
    lidarX(i+1) = lidarX(i) + deltaX_vehicle_m;
    lidarYBar(i+1) = lidarYBar(i) + deltaY_vehicle_mBar;
    lidarXBar(i+1) = lidarXBar(i) + deltaX_vehicle_mBar;
    lidarYaw(i+1) = lidarYaw(i) + deltaYaw_vehicle_deg;
end
%Display number of iteration to see current progress
if(i==1)
    fprintf('Out of %d frames, Processing point cloud matching on frame
No.',framesNum);
end
fprintf('\b\b\b\b\b\b%d', i+1);
end

```

Out of 1059 frames, Processing point cloud matching on frame No.
1059

```

%Evaluating Lidar-Based Position based on Ground truth data
figure;

subplot(2, 1, 1);
plot(unsyncGPS_e, unsyncGPS_n, '-o');
hold on;
plot(lidarX, lidarY, '-*');
plot(lidarXBar, lidarYBar, '-s');

xlabel('East position (m)');
ylabel('North Position (m)');
legend('Synced GPS route', 'Lidar route', 'Lidar INS referenced route');
grid on;

subplot(2, 1, 2);
plot(timeVector, yaw, 'g');
hold on;
plot(timeVector, deg2rad(lidarYaw), 'r--');
xlabel('Time (s)');
ylabel('Yaw angle (rad)');
legend('Ground-Truth Yaw', 'IMU-Based Yaw');
grid on;
sgtitle('Unsynced IMU-Based model output');

sgtitle('Lidar-Based model output');

```

```

%Calculating Error (Difference between Lidar and GPS data)
LidarYDiff = GPSe - (lidarX)';
LidarXDiff = GPSn - (lidarY)';
LidarYBarDiff = GPSe - (lidarXBar)';
LidarXBarDiff = GPSn - (lidarYBar)';
LidaryawDiff = rad2deg(yaw) - (lidarYaw)';

%Graphing error
figure;
figure('Position', [0, 0, 1250, 1250]);

subplot(3,2,1);
plot(timeVector, LidarXDiff);
xlabel('Time (sec)');
ylabel('Lidar-Based X Error (m)');
grid("on");

subplot(3,2,2);
plot(timeVector, LidarXBarDiff);
xlabel('Time (sec)');
ylabel('Lidar-INS referenced X Error (m)');
grid("on");


subplot(3,2,3);
plot(timeVector, LidarYDiff);
xlabel('Time (sec)');
ylabel('Lidar-Based Y Error (m)');
grid("on");

subplot(3,2,4);
plot(timeVector, LidarYBarDiff);
xlabel('Time (sec)');
ylabel('Lidar-INS referenced Y Error (m)');
grid("on");

subplot(3,2,5);
plot(timeVector, LidaryawDiff);
xlabel('Time (sec)');
ylabel('Yaw angle difference (deg)');
grid("on");
sgtitle('Lidar-Based model difference to GPS');

```

Lidar-Based model difference to GPS



Camera-Based Localization model and evaluation.

```
%Creating cameraParams object
%See cam_to_cam_calib file to obtain these values
focalLength = [984 980];
principalPoint = [690 233];
cameraParams = cameraIntrinsics(focalLength, principalPoint, size(grayVector{1}
(:, :, 1)));
```

```
%Loop for saving camera estimates
camX = zeros(1,numel(pngFiles));
```

```

camY = zeros(1,numel(pngFiles));
camYaw = zeros(1,numel(pngFiles));
camYaw(1) = yaw(1);
figure;
for i = 1:numel(pngFiles) - 1

    grayFrame1 = grayVector{i};
    grayFrame2 = grayVector{i+1};

    %Detect and match features
    %For limited number of features
    %points1 = selectStrongest(detectKAZEFeatures(grayFrame1), 500);
    %points2 = selectStrongest(detectKAZEFeatures(grayFrame2), 500);

    %For maximum number of features
    points1 = detectKAZEFeatures(grayFrame1);
    points2 = detectKAZEFeatures(grayFrame2);

    [features1, points1] = extractFeatures(grayFrame1, points1);
    [features2, points2] = extractFeatures(grayFrame2, points2);

    indexPairs = matchFeatures(features1, features2);
    matchedPoints1 = points1(indexPairs(:, 1), :);
    matchedPoints2 = points2(indexPairs(:, 2), :);

    % Estimate Fundamental/Essential matrix
    [eMatrix, inliers] = estimateEssentialMatrix(matchedPoints1, matchedPoints2,
cameraParams);

    % Select inlier points
    inlierPoints1 = matchedPoints1(inliers);
    inlierPoints2 = matchedPoints2(inliers);

    %Estimate relative camera pose
    relPose = estrelpose(eMatrix, cameraParams, inlierPoints1, inlierPoints2);

    Rot = relPose.R;
    t = relPose.Translation;

    eulerAngles = rotm2eul(Rot, 'XYZ');
    camYaw(i+1) = camYaw(i) - eulerAngles(2);
    camX(i+1) = camX(i) + t(3)*cos(yaw(i))*scaleFactor(i) - t(1)*sin((pi/2)-
yaw(i))*scaleFactor(i);
    camY(i+1) = camY(i) + t(3)*sin(yaw(i))*scaleFactor(i) - t(1)*cos((pi/2)-
yaw(i))*scaleFactor(i);

    %Visualize matched features
    %showMatchedFeatures(grayFrame1, grayFrame2, inlierPoints1, inlierPoints2,
'montage');
    if(i==1)
        fprintf('Out of %d frames, Processing point cloud matching on frame
No.',framesNum);
    end
    fprintf('\b\b\b\b\b\b%d', i+1);


```



```
end
```

Out of 1059 frames, Processing point cloud matching on frame No. 1059

```
figure;  
subplot(2, 1, 1);  
plot(GPSe, GPSn, '-o');  
hold on;  
plot(camX, camY, '-*');  
xlabel('East position (m)');  
ylabel('North Position (m)');  
legend('GPS route', 'Camera route');  
grid on;  
  
subplot(2, 1, 2);  
plot(timeVector, yaw, 'g');  
hold on;  
plot(timeVector, camYaw, 'r--');  
xlabel('Time (s)');  
ylabel('Yaw angle (rad)');  
legend('Ground-Truth Yaw', 'Camera-Based Yaw');  
grid on;  
sgtitle('Camera-Based model output');
```



```
%camera based error evaluation  
%Calculating Error (Difference between Camera and GPS data)  
SeDiffCam = GPSe' - camX;  
SnDiffCam = GPSn' - camY;
```


```

yawDiffCam = yaw' - camYaw;

%Graphing error
figure;
subplot(3, 1, 1);
plot(timeVector, SeDiffCam, 'r');
xlabel('Time (s)');
ylabel('Se difference (m)');
grid on;
subplot(3, 1, 2);
plot(timeVector, SnDiffCam, 'g');
xlabel('Time (s)');
ylabel('Sn difference (m)');
grid on;
subplot(3, 1, 3);
plot(timeVector, rad2deg(yawDiffCam), 'b');
xlabel('Time (s)');
ylabel('Yaw angle difference (deg)');
title('Yaw Angle')
grid on;

sgtitle('Camera-Based model Difference to GPS');

```



Sensory Data Fusion

Average Estimation Model

```

XAvg = zeros(framesNum, 1);

```

```

YAvg = zeros(framesNum, 1);
YawAvg = zeros(framesNum, 1);

for i= 1:framesNum
    XAvg(i) = (camX(:,i) + lidarXBar(:,i) + GPSe(i,:) + IMUe(i,:)) / 4;
    YAvg(i) = (camY(:,i) + lidarYBar(:,i) + GPSn(i,:) + IMUn(i,:)) / 4;
    YawAvg(i) = (camYaw(:,i) + deg2rad(lidarYaw(:,i)) + yaw(i,:) +
IMUYaw(i,:)) / 4;
end

```

```

%Graphing Average Estimation output in comparison with GPS data as the ground
truth

```

```


figure;

subplot(2, 1, 1);
plot(GPSe, GPSn, '-o');
hold on;
plot(XAvg, YAvg, '-*');
xlabel('East position (m)');
ylabel('North Position (m)');
legend('GPS route', 'Average Estimation route');
grid on;

subplot(2, 1, 2);
plot(timeVector, yaw, 'g');
hold on;
plot(timeVector, YawAvg, 'r--');
xlabel('Time (s)');
ylabel('Yaw angle (rad)');
legend('Ground-Truth Yaw', 'Average Estimation Yaw');
grid on;
sgtitle('Average Estimation model output');

```

Average Estimation model output



```
%AV Using synced data evaluation
```

```
AEDeltaE = GPSe - XAvg;
```

```
AEDeltaN = GPSn - YAvg;
```

```
AEDeltaYaw = yaw - YawAvg;
```

```
figure;
```

```
subplot(3, 1, 1);
```

```
plot(timeVector, AEDeltaE, 'r');
```

```
xlabel('Time (s)');
```

```
ylabel('Error in East (m)');
```

```
grid on;
```

```
subplot(3, 1, 2);
```

```
plot(timeVector, AEDeltaN, 'g');
```

```
xlabel('Time (s)');
```

```
ylabel('KF_North/GPS North (m)');
```

```
ylabel('Error in North (m)');
```

```
grid on;
```

```
subplot(3, 1, 3);
```


```
plot(timeVector, rad2deg(AEDeltaYaw), 'b');
```

```
xlabel('Time (s)');
```

```
ylabel('Error in Yaw (deg)');
```

```
grid on;
```

```
sgtitle('Average Estimation Model output Difference to GPS');
```



Weighted Sum Estimation

```

XGws = zeros(framesNum, 1);
YGws = zeros(framesNum, 1);
YawGws = zeros(framesNum, 1);
X = [camX', lidarXBar', GPSe, IMUe];
Y = [camY', lidarYBar', GPSn, IMUn];
Yaw = [camYaw', deg2rad(lidarYaw)', yaw, IMUYaw];
WeigthGXY = [5, 10, 20, 20];
WeigthGYaw = [5, 8, 20, 10];

for i= 1:framesNum
    XGws(i,:) = sum(WeigthGXY .* X(i,:)) / sum(WeigthGXY);
    YGws(i,:) = sum(WeigthGXY .* Y(i,:)) / sum(WeigthGXY);
    YawGws(i,:) = sum(WeigthGYaw .* Yaw(i,:)) / sum(WeigthGYaw);
end

```

```

%Graphing Weighted Sum Estimation Including GPS output in comparison with GPS
data as the ground truth
figure;

subplot(2, 1, 1);
plot(GPSe, GPSn, '-o');
hold on;
plot(XGws, YGws, '-*');
xlabel('East position (m)');
ylabel('North Position (m)');


```

```

legend('GPS route', 'Weighted sum route');
grid on;

subplot(2, 1, 2);
plot(timeVector, yaw, 'g');
hold on;
plot(timeVector, YawGWS, 'r--');
xlabel('Time (s)');
ylabel('Yaw angle (rad)');
legend('Ground-Truth Yaw', 'Weighted sum route');
grid on;
sgtitle('Weighted sum model output');

```



```

%GWS data difference
GWSDeltaE = GPSe - XGWs;
GWSDeltaN = GPSn - YGWs;
GWSDeltaYaw = yaw - YawGWS;

figure;

subplot(3, 1, 1);
plot(timeVector, GWSDeltaE, 'r');
xlabel('Time (s)');
ylabel('Error in East (m)');
grid on;

subplot(3, 1, 2);
plot(timeVector, GWSDeltaN, 'g');
xlabel('Time (s)');

```


```

ylabel('Error in North (m)');
grid on;

subplot(3, 1, 3);
plot(timeVector, rad2deg(GWSDeltaYaw), 'b');
xlabel('Time (s)');
ylabel('Error in Yaw (deg)');
grid on;
sgtitle('Weighted Sum Estimation Including GPS output evaluation');

```

Weighted Sum Estimation Including GPS output evaluation



```

XWs = zeros(framesNum, 1);
YWs = zeros(framesNum, 1);
YawWs = zeros(framesNum, 1);
WeigthXY = [5, 10, 0, 20];
WeigthYaw = [5, 8, 0, 10];

for i= 1:framesNum
    XWs(i,:) = sum(WeigthXY .* X(i,:)) / sum(WeigthXY);
    YWs(i,:) = sum(WeigthXY .* Y(i,:)) / sum(WeigthXY);
    YawWs(i,:) = sum(WeigthYaw .* Yaw(i,:)) / sum(WeigthYaw);
end

```

%Graphing Weighted Sum Estimation Without GPS output in comparison with GPS data as the ground truth

figure;

```

subplot(2, 1, 1);
plot(GPSe, GPSn, '-o');

```


```

hold on;
plot(XWs, YWs, '-*');
xlabel('East position (m)');
ylabel('North Position (m)');
legend('GPS route', 'Weighted sum excluding GPS data route');
grid on;

subplot(2, 1, 2);
plot(timeVector, yaw, 'g');
hold on;
plot(timeVector, YawWs, 'r--');
xlabel('Time (s)');
ylabel('Yaw angle (rad)');
legend('Ground-Truth Yaw', 'Weighted sum route');
grid on;

sgtitle('Weighted Sum Estimation Without GPS output');

```



```

%WS data difference
WSDeltaE = GPSe - XWs;
WSDeltaN = GPSn - YWs;
WSDeltaYaw = yaw - YawWs;

figure;

subplot(3, 1, 1);
plot(timeVector, WSDeltaE, 'r');
xlabel('Time (s)');
ylabel('Error in East (m)');

```



```


grid on;

subplot(3, 1, 2);
plot(timeVector, WSDeltaN, 'g');
xlabel('Time (s)');
ylabel('Error in North (m)');
grid on;

subplot(3, 1, 3);
plot(timeVector, rad2deg(WSDeltaYaw), 'b');
xlabel('Time (s)');
ylabel('Error in Yaw (deg)');
grid on;
sgtitle('Weighted Sum Estimation Without GPS difference to GPS');

```

Weighted Sum Estimation Without GPS difference to GPS



Standard Kalman Filter

Synced data Kalman Filter.

%Now with all data stored and set to be used in evaluating different filters estimates.

%Using Kalman Filter as follows (Initializing Parameters and matrices (dt, F, G, H, Q, R) -> Setting Initial estimates -> Main Loop (Prediction -> update))

%1- Initializing Parameters and Matrices (Synced data)

dt = 0.1; %Time step for used synced data approximately.

%Initializing State Transition matrix (F)

F = [1, 0, dt, 0, 0;

```

    0, 1, 0, dt, 0;
    0, 0, 1, 0, 0;
    0, 0, 0, 1, 0;
    0, 0, 0, 0, 1];
%Initializing Control Matrix (G)
G = [(dt^2)/2, 0, 0;
     0, (dt^2)/2, 0;
     dt, 0, 0;
     0, dt, 0;
     0, 0, dt];
%Initializing Measurements matrix (H)
H = [1, 0, 0, 0, 0;
     0, 1, 0, 0, 0;
     0, 0, 0, 0, 1;
     1, 0, 0, 0, 0;
     0, 1, 0, 0, 0;
     0, 0, 0, 0, 1;
     1, 0, 0, 0, 0;
     0, 1, 0, 0, 0;
     0, 0, 0, 0, 1];
%Initializing Process noise covariance matrix (Q)
Q = diag([0.1, 0.1, 0.01, 0.01, 0.1]);
%Initializing Measurement noise covariance matrix (R) for every sensor
R = diag([0.2, 0.2, 0.2, 0.1, 0.1, 0.1, 0.01, 0.01, 0.01]); %CAMERA -> LIDAR ->
GPS
%2-Setting initial estimates
%Initializing variables vector to hold xCheck, xHat, pCheck, pHat
xCheck = zeros(framesNum+1,5,1)';
pCheck = zeros(framesNum+1,5,5);
xHat = zeros(framesNum+1,5,1)'; % (+1) for inital estimates -> xHat(0)
pHat = zeros(framesNum+1,5,5); % (+1) for inital estimates -> pHat(0)
K = zeros(framesNum+1,5,9);
%Initializing state estimates xHat(k-1) -> first prediction iteration
xHat(:,1) = zeros(5,1); %[GPSe(0); GPSn(0); ve(0); vn(0); yaw(0);]; -> are all
assumed to be zero
xHat(5,1) = yaw(1);
%Initializing error covariance estimates pHat(k-1) -> first prediction iteration
pHat(1, :, :) = eye(5);
%Input matrix
u = [Ae An wu]';
%Measurement Matrix y
y = zeros(9, framesNum+1);
y(:,2:end) = [camX' camY' camYaw' lidarXBar' lidarYBar' deg2rad(lidarYaw') GPSe
GPSn yaw]'; %to store input with size with size 9*numFrames

```

%3.0-Main filter loop

```

for i = 2:framesNum +1
%Prediction step
xCheck(:,i) = (F * xHat(:,i-1)) + (G * u(:,i-1));
pCheck(i, :, :) = (F * reshape(pHat(i-1, :, :), 5, 5) * F') + Q;
%Update step -> proceeed update step in 3 stages ->
K(i, :, :) = (reshape(pCheck(i, :, :), 5, 5) * H') * (inv(((H
*reshape(pCheck(i, :, :), 5, 5) * H') + R)));

```

```

xHat(:,i) = xCheck(:,i) + reshape(K(i,:,:), 5, 9)*(y(:,i) - (H * xCheck(:,i)));
pHat(i,:,:)= (eye(5) - (reshape(K(i,:,:), 5, 9) * H)) *
reshape(pCheck(i,:,:),5, 5);
end

```

```

%Seperating 2D Pose from states for visualization

```

```

kfEast = xHat(1, 2:end);

```

```

kfNorth = xHat(2, 2:end);

```

```

kfYaw = xHat(5, 2:end);

```

```

%Graphing Filter output in comparison with GPS data as the ground truth

```

```

figure;

```

```

subplot(2, 1, 1);

```

```

plot(GPSe, GPSe, '-o');

```

```

hold on;

```

```

plot(kfEast, kfNorth, '-*');

```

```

xlabel('East position (m)');

```

```

ylabel('North Position (m)');

```

```

legend('GPS route', 'Kalman Filter route');

```

```

grid on;

```

```

subplot(2, 1, 2);

```

```

plot(timeVector, yaw, 'g');

```

```

hold on;

```

```

plot(timeVector, kfYaw, 'r--');

```

```

xlabel('Time (s)');

```

```

ylabel('Yaw angle (rad)');

```

```

legend('Ground-Truth Yaw', 'Kalman Filter route');

```

```


grid on;

```

```

sgtitle('Synced KF output');

```




```
%KF Using synced data difference
kfDeltaE = GPSe - kfEast';
kfDeltaN = GPSn - kfNorth';
kfDeltaYaw = yaw - kfYaw';

figure;

subplot(3, 1, 1);
plot(timeVector, kfDeltaE, 'r');
xlabel('Time (s)');
ylabel('Error in East (m)');
grid on;

subplot(3, 1, 2);
plot(timeVector, kfDeltaN, 'g');
xlabel('Time (s)');
ylabel('Error in North (m)');
grid on;

subplot(3, 1, 3);
plot(timeVector, rad2deg(kfDeltaYaw), 'b');
xlabel('Time (s)');
ylabel('Error in Yaw (deg)');
grid on;
sgtitle('Synced KF output difference to GPS');
```



Unsynced data Kalman Filter.

%1- Initializing Parameters and Matrices (UnSynced data)

dtU = 0.01; %Time step for used synced data approximately.

%Initializing State Transition matrix (F)

```
FU = [1,    0,    dtU,    0,    0;
      0,    1,    0,    dtU,    0;
      0,    0,    1,    0,    0;
      0,    0,    0,    1,    0;
      0,    0,    0,    0,    1];
```

%Initializing Control Matrix (G)

```
GU = [(dtU^2)/2,    0,    0;
      0,    (dtU^2)/2,    0;
      dtU,    0,    0;
      0,    dtU,    0;
      0,    0,    dtU];
```

%Initializing Measurements matrix (H) -> Including only GPS

```
HUGPS = [1,    0,    0,    0,    0;
          0,    1,    0,    0,    0;
          0,    0,    0,    0,    1];
```

%Initializing Process noise covariance matrix (Q)

```
QU = diag([0.1, 0.1, 0.1, 0.1, 0.1]);
```

%Initializing Measurement noise covariance matrix (R) for every sensor

```
RUGPS = diag([0.1, 0.1, 0.1]); %GPS
```

%1-Setting variables and initial estimates for filter saving the estimates after cam & lidar update

```

%Initializing variables vector to hold xCheck, xHat, pCheck, pHat
xHatU = zeros(framesNum,5,1)'; % (+1) for initial estimates -> xHat(0)
pHatU = zeros(framesNum,5,5); % (+1) for initial estimates -> pHat(0)
%2-Setting variables and initial estimates for filter not including GPS
%Initializing variables vector to hold xCheck, xHat, pCheck, pHat
xCheckUG = zeros(unsyncFramesNum+1,5,1)';
pCheckUG = zeros(unsyncFramesNum+1,5,5);
xHatUG = zeros(unsyncFramesNum+1,5,1)'; % (+1) for initial estimates -> xHat(0)
pHatUG = zeros(unsyncFramesNum+1,5,5); % (+1) for initial estimates -> pHat(0)
%Initializing state estimates xHat(k-1) -> first prediction iteration
xHatUG(5,1) = unsyncYaw(1); %[GPSe(0); GPSn(0); ve(0); vn(0); yaw(0);]; -> are
all assumed to be zero not including yaw
%Initializing error covariance estimates pHat(k-1) -> first prediction iteration
pHatUG(1, :, :) = eye(5);
%Input matrix
uU = [unsyncAe unsyncAn unsyncWu];

```

```

%3-Main filter loop for unsynced data
gpsF = zeros(framesNum, 3); %Corelated frames of synced data in unsynced data
%Providing start point as initial condition
gpsF(1,1) = unsyncGPSe(1);
gpsF(1,2) = unsyncGPSn(1);
gpsF(1,3) = yaw(1);
filterRatio = unsyncFramesNum/framesNum;
for i = 2:unsyncFramesNum
    %Prediction step
    xCheckUG(:,i) = (FU * xHatUG(:,i-1)) + (GU * uU(i-1,:))';
    pCheckUG(i, :, :) = (FU * reshape(pHatUG(i-1, :, :), 5, 5) * FU') + QU;

    %Update step
    %When Camera and lidar data are taken into consideration
    if(floor(mod(i, filterRatio)) == 1)
        frameIndex = ceil(i / filterRatio);
        %Now Set R, H, and Y --> to suit Lidar, Camera, GPS
        Y = [camX(frameIndex) camY(frameIndex) camYaw(frameIndex)
lidarXBar(frameIndex) lidarYBar(frameIndex) deg2rad(lidarYaw(frameIndex))
unsyncGPSe(i-1) unsyncGPSn(i-1) unsyncYaw(i-1)]';
        K = (reshape(pCheckUG(i, :, :), 5, 5) * H') * (inv(((H *
reshape(pCheckUG(i, :, :), 5, 5) * H') + R)));
        xHatUG(:,i) = xCheckUG(:,i) + K*(Y - (H * xCheckUG(:,i)));
        pHatUG(i, :, :) = (eye(5) - K * H) * reshape(pCheckUG(i, :, :), 5, 5);
        xHatU(:,frameIndex+1) = xHatUG(:,i);
        pHatU(frameIndex+1, :, :) = pHatUG(i, :, :);
        gpsF(frameIndex+1, :) = [unsyncGPSe(i-1) unsyncGPSn(i-1)
unsyncYaw(i-1)]';
    else
        Y = [unsyncGPSe(i-1) unsyncGPSn(i-1) unsyncYaw(i-1)]';
        K = (reshape(pCheckUG(i, :, :), 5, 5) * HUGPS') * (inv(((HUGPS *
reshape(pCheckUG(i, :, :), 5, 5) * HUGPS') + RUGPS)));
        xHatUG(:,i) = xCheckUG(:,i) + K*(Y - (HUGPS * xCheckUG(:,i)));
        pHatUG(i, :, :) = (eye(5) - K * HUGPS) * reshape(pCheckUG(i, :, :), 5, 5);
    end
end
end

```


```

%Seperating 2D Pose from states for visualization
kfEastU = xHatU(1,2:end);
kfNorthU = xHatU(2,2:end);
kfYawU = xHatU(5,2:end);
%Graphing Filter output in comparison with GPS data as the ground truth
figure;
subplot(2, 1, 1);
plot(gpsF(:,1), gpsF(:,2), '-o');
hold on;
plot(kfEastU, kfNorthU, '-*');
xlabel('East position (m)');
ylabel('North Position (m)');
legend('GPS route', 'Unsynced Kalman Filter route');
grid on;

subplot(2, 1, 2);
plot(timeVector', gpsF(2:end,3), 'g');
hold on;
plot(timeVector, kfYawU, 'r--');
xlabel('Time (s)');
ylabel('Yaw angle (rad)');
legend('Ground-Truth Yaw', 'Unsynced Kalman Filter route');
grid on;

sgtitle('UnSynced KF output');

```



```

figure;
%KF Using unsynced data

```

```

kfDeltaEU = gpsF(2:end,1) - kfEastU';
kfDeltaNU = gpsF(2:end,2) - kfNorthU';
kfDeltaYawU = gpsF(2:end,3) - kfYawU';


figure;

subplot(3, 1, 1);
plot(timeVector, kfDeltaEU, 'r');
xlabel('Time (s)');
ylabel('Error in East (m)');
grid on;

subplot(3, 1, 2);
plot(timeVector, kfDeltaNU, 'g');
xlabel('Time (s)');
ylabel('KF_North/GPS North (m)');
ylabel('Error in North (m)');
grid on;

subplot(3, 1, 3);
plot(timeVector, rad2deg(kfDeltaYawU), 'b');
xlabel('Time (s)');
ylabel('Error in Yaw (deg)');
grid on;
sgtitle('unSynced data KF error difference to GPS');

```



Extracting Weights for adaptive filters.

```
%First extracting Synced data weights for camera, lidar, and gps
```



```

gpsVar = (gpsWeights_FIS([posAcc numSats])).^2;
unsyncGpsVar = (gpsWeights_FIS([unsyncPosAcc unsyncNumSats])).^2;
camVar = (camWeights_FIS(camAvI)).^2;
lidarVar = (lidarWeights_FIS(pcdR)).^2;
imuVar = (0.15 * ones(framesNum, 1)).^2;%as imu weight and it is constant


```

%Plotting Weights for adaptive filters

```

figure;
plot(timeVector, gpsVar, '-o');
hold on;
plot(unsyncTimeVector, unsyncGpsVar, '-*');
plot(timeVector, camVar, '-x');
plot(timeVector, lidarVar, '-s');
plot(timeVector, imuVar, '-g');
legend('Synced GPS Variance', 'Unsynced GPS Variance', 'Camera Variance', 'Lidar Variance', 'IMU Variance');
title('Different sensors variance based on fuzzy inference systems');
xlabel('Time (s)');
ylabel('Variance');
grid on;
hold off;

```



Adaptive filters (Weighted Average - KF - unsynced KF).

Adaptive Weighted Average Model

```

XAGWs = zeros(framesNum, 1);

```

```

YAGWs = zeros(framesNum, 1);
YawAGWs = zeros(framesNum, 1);
X = [camX', lidarXBar', GPSe, IMUe];
Y = [camY', lidarYBar', GPSn, IMUn];
Yaw = [camYaw', deg2rad(lidarYaw)', yaw, IMUYaw];
WeightsAvModel = [(1 ./ camVar) (1 ./ lidarVar) (1 ./ gpsVar) (1 ./ imuVar)];

for i= 1:framesNum
    XAGWs(i,:) = sum(WeightsAvModel(i,:) .* X(i,:)) / sum(WeightsAvModel(i,:));
    YAGWs(i,:) = sum(WeightsAvModel(i,:) .* Y(i,:)) / sum(WeightsAvModel(i,:));
    YawAGWs(i,:) = sum(WeightsAvModel(i,:) .* Yaw(i,:)) /
sum(WeightsAvModel(i,:));
end

```

Adaptive Kalman Filter

```

%Storing R values
AR = ones(9,9,framesNum);
imuVariance = imuVar(1);
for i = 1:framesNum
    AR(:,:,i) = diag([camVar(i), camVar(i), camVar(i), lidarVar(i), lidarVar(i),
lidarVar(i), gpsVar(i), gpsVar(i), gpsVar(i))]); %Camera - lidar - gps
end
%Initializing parameters.
AQ = diag([imuVariance, imuVariance, imuVariance^0.5, imuVariance^0.5,
imuVariance]);
AxCheck = zeros(framesNum+1,5,1)';
ApCheck = zeros(framesNum+1,5,5);
AxHat = zeros(framesNum+1,5,1)'; % (+1) for initial estimates -> xHat(0)
ApHat = zeros(framesNum+1,5,5); % (+1) for initial estimates -> pHat(0)
AK = zeros(framesNum+1,5,9);
%Initializing state estimates xHat(k-1) -> first prediction iteration
AxHat(:,1) = zeros(5,1); %[GPSe(0); GPSn(0); ve(0); vn(0); yaw(0)]; -> are all
assumed to be zero
AxHat(5,1) = yaw(1);
%Initializing error covariance estimates pHat(k-1) -> first prediction iteration
ApHat(1,:,:) = eye(5);
%applying same Kalman main loop but with adaptive weights
for i = 2:framesNum +1
    %Prediction step
    AxCheck(:,i) = (F * AxHat(:,i-1)) + (G * u(:,i-1));
    ApCheck(i,:,:) = (F * reshape(ApHat(i-1,:,:), 5, 5) * F') + AQ;
    %Update step -> proceed update step in 3 stages ->
    AK(i,:,:) = (reshape(ApCheck(i,:,:), 5, 5) * H') * (inv(((H
*reshape(ApCheck(i,:,:), 5, 5) * H') + reshape(AR(:,:,i-1), 9,9)))));
    AxHat(:,i) = AxCheck(:,i) + reshape(AK(i,:,:), 5, 9)*(y(:,i) - (H *
AxCheck(:,i)));
    ApHat(i,:,:) = (eye(5) - (reshape(AK(i,:,:), 5, 9) * H)) *
reshape(ApCheck(i,:,:),5, 5);
end
AkfEast = AxHat(1, 2:end);
AkfNorth = AxHat(2, 2:end);

```

```
AkfYaw = AxHat(5, 2:end);
```

Adaptive Kalman Filter for Unsynced data

```
%Initializing Process noise covariance matrix (Q)
AQU = diag([imuVariance, imuVariance, imuVariance^0.5, imuVariance^0.5,
imuVariance]);
%Initializing Measurement noise covariance matrix (R) for every sensor
ARUGPS = ones(3,3,unsyncFramesNum);
for i = 1:unsyncFramesNum
    ARUGPS(:, :, i) = diag([unsyncGpsVar(i), unsyncGpsVar(i), unsyncGpsVar(i)]);
%Camera - lidar - gps
end
%Setting variables and initial estimates for filter saving the estimates after
cam & lidar update
%Initializing variables vector to hold xCheck, xHat, pCheck, pHat
AxHatU = zeros(framesNum,5,1)'; % (+1) for inital estimates -> xHat(0)
ApHatU = zeros(framesNum,5,5); % (+1) for inital estimates -> pHat(0)
%2-Setting variables and initial estimates for filter not including GPS
%Initializing variables vector to hold xCheck, xHat, pCheck, pHat
AxCheckUG = zeros(unsyncFramesNum+1,5,1)';
ApCheckUG = zeros(unsyncFramesNum+1,5,5);
AxHatUG = zeros(unsyncFramesNum+1,5,1)'; % (+1) for inital estimates -> xHat(0)
ApHatUG = zeros(unsyncFramesNum+1,5,5); % (+1) for inital estimates -> pHat(0)
%Initializing state estimates xHat(k-1) -> first prediction iteration
AxHatUG(5,1) = unsyncYaw(1); %[GPSe(0); GPSn(0); ve(0); vn(0); yaw(0)]; -> are
all assumed to be zero not including yaw
%Initializing error covariance estimates pHat(k-1) -> first prediction iteration
ApHatUG(1, :, :) = eye(5);
%Main filter loop for unsynced data
AgpsF = zeros(framesNum, 3); %Corelated frames of synced data in unsynced data
AgpsF(1,3) = yaw(1);
filterRatio = unsyncFramesNum/framesNum;

for i = 2:unsyncFramesNum
    %Prediction step
    AxCheckUG(:, i) = (FU * AxHatUG(:, i-1)) + (GU * uU(i-1, :))';
    ApCheckUG(i, :, :) = (FU * reshape(ApHatUG(i-1, :, :), 5, 5) * FU') + AQU;

    %Update step
    %When Camera and lidar data are taken into consideration
    if(floor(mod(i, filterRatio)) == 1)
        frameIndex = ceil(i / filterRatio);
        %Now Set R, H, and Y --> to suit Lidar, Camera, GPS
        Y = [camX(frameIndex) camY(frameIndex) camYaw(frameIndex)
lidarXBar(frameIndex) lidarYBar(frameIndex) deg2rad(lidarYaw(frameIndex))
unsyncGPSe(i-1) unsyncGPSn(i-1) unsyncYaw(i-1)]';
        RAfilter = diag([camVar(frameIndex) camVar(frameIndex)
camVar(frameIndex) lidarVar(frameIndex) lidarVar(frameIndex)
lidarVar(frameIndex) unsyncGpsVar(i-1) unsyncGpsVar(i-1) unsyncGpsVar(i-1)]);
```

```

        K = (reshape(ApCheckUG(i,:,:), 5, 5) * H') * (inv((H *
reshape(ApCheckUG(i,:,:), 5, 5) * H') + RAfilter)));
        AxHatUG(:,i) = AxCheckUG(:,i) + K*(Y - (H * AxCheckUG(:,i)));
        ApHatUG(i,:,:)= (eye(5) - K * H) * reshape(ApCheckUG(i,:,:), 5, 5);
        AxHatU(:,frameIndex) = AxHatUG(:,i);
        ApHatU(frameIndex,:,:)= ApHatUG(i,:,:);
        AgpsF(frameIndex, :) = [unsyncGPSe(i-1) unsyncGPSn(i-1) unsyncYaw(i-1)]];
    else
        Y = [unsyncGPSe(i-1) unsyncGPSn(i-1) unsyncYaw(i-1)]];
        K = (reshape(ApCheckUG(i,:,:), 5, 5) * HUGPS') * (inv((HUGPS *
reshape(ApCheckUG(i,:,:), 5, 5) * HUGPS') + reshape(ARUGPS(:, :, i-1), 3, 3))));
        AxHatUG(:,i) = AxCheckUG(:,i) + K*(Y - (HUGPS * AxCheckUG(:,i)));
        ApHatUG(i,:,:)= (eye(5) - K * HUGPS) * reshape(ApCheckUG(i,:,:), 5, 5);
    end

end

AkfEastU = AxHatU(1,1:end);
AkfNorthU = AxHatU(2,1:end);
AkfYawU = AxHatU(5,1:end);

```

Frame-Based KF

```

%Trying Variations of KF with absolute position different for each frame on its
own.
%Separating Absolute Estimates from each Sensor
AbsIMUX = diff(IMUe);
AbsIMUY = diff(IMUn);
AbsIMUYaw = diff(IMUYaw);
AbsGPSX = diff(GPSe);
AbsGPSY = diff(GPSn);
AbsGPSYaw = diff(yaw);
AbsCamX = diff(camX);
AbsCamY = diff(camY);
AbsCamYaw = diff(camYaw);
AbsLidarX = diff(lidarXBar);
AbsLidarY = diff(lidarYBar);
AbsLidarYaw = diff(lidarYaw);

%Kalman filter
xCheckFrames = zeros(framesNum+1,5,1)';
pCheckFrames = zeros(framesNum+1,5,5);
xHatFrames = zeros(framesNum+1,5,1)'; % (+1) for inital estimates -> xHat(0)
pHatFrames = zeros(framesNum+1,5,5); % (+1) for inital estimates -> pHat(0)
KFrames = zeros(framesNum+1,5,9);
%Initializing state estimates xHat(k-1) -> first prediction iteration
xHatFrames(:,1) = zeros(5,1); %[GPSe(0); GPSn(0); ve(0); vn(0); yaw(0)]; -> are
all assumed to be zero
xHatFrames(5,1) = yaw(1);
%Initializing error covariance estimates pHat(k-1) -> first prediction iteration
pHatFrames(1, :, :) = eye(5);
%Measurement Matrix y
yFrames = zeros(9, framesNum);


```

```
yFrames(:,2:end) = [AbsCamX; AbsCamY; AbsCamYaw; AbsLidarX; AbsLidarY;
deg2rad(AbsLidarYaw); AbsGPSX'; AbsGPSY'; AbsGPSYaw']; %to store input with size
with size 9*numFrames
```

```
for i = 2:framesNum +1
%Prediction step
xCheckFrames(:,i) = (F * zeros(5,1)) + (G * u(:,i-1)); %Replacing initial
estimates with zeros and pInitial with identity matrix due to absolute
referencing
pCheckFrames(i, :, :) = (F * eye(5) * F') + AQ;
%Update step -> proceed update step in 3 stages ->
KFrames(i, :, :) = (reshape(pCheckFrames(i, :, :), 5, 5) * H') * (inv(((H
*reshape(pCheckFrames(i, :, :), 5, 5) * H') + reshape(AR(:, :, i-1), 9,9))));
xHatFrames(:,i) = xCheckFrames(:,i) + reshape(KFrames(i, :, :), 5,
9)*(yFrames(:,i-1) - (H * xCheckFrames(:,i)));
pHatFrames(i, :, :) = (eye(5) - (reshape(KFrames(i, :, :), 5, 9) * H)) *
reshape(pCheckFrames(i, :, :), 5, 5);
end
kfXFrames = cumsum(xHatFrames(1,2:end));
kfYFrames = cumsum(xHatFrames(2,2:end));
kfYawFrames = cumsum(xHatFrames(5,2:end));%Plotting
```

```
figure;
subplot(2, 1, 1);
plot(GPSe, GPSn, '-o');
hold on;
plot(kfXFrames, kfYFrames, '-*');
xlabel('East position (m)');
ylabel('North Position (m)');
legend('GPS route', 'Adaptive Frame-Based Kalman Filter route');
grid on;

subplot(2, 1, 2);
plot(timeVector, yaw, 'g');
hold on;
plot(timeVector, kfYawFrames, 'r--');
xlabel('Time (s)');
ylabel('Yaw angle (rad)');
legend('Ground-Truth Yaw', 'Adaptive Frame-Based Kalman Filter route');
grid on;
sgtitle('Frame-Based KF output');
```



Evaluating Fusion Techniques on world map using Latitude/Longitude Coordinates.

```

LL_Av = zeros(framesNum, 2); %for average estimation
LL_WEG = zeros(framesNum, 2); %for weighted estimation With GPS
LL_WE = zeros(framesNum, 2); %for weighted estimation Without GPS
LL_KFS = zeros(framesNum, 2); %for KF using synced data
LL_KFUS = zeros(framesNum, 2); %for KF using unsynced data
%For adaptive filters
ALL_WEG = zeros(framesNum, 2); %for weighted estimation adaptive
ALL_KFS = zeros(framesNum, 2); %for KF using synced data adaptive
ALL_KFUS = zeros(framesNum, 2); %for KF using unsynced data adaptive
%frame based
LL_KFFrame = zeros(framesNum, 2); %for frame-based kalman filter

for i = 1:framesNum
    LL_Av(i,:) = en_to_ll([XAvg(i), YAvg(i)] , [latitude(1), longitude(1),
altitude(1)]);
    LL_WE(i,:) = en_to_ll([XWs(i), YWs(i)] , [latitude(1), longitude(1),
altitude(1)]);
    LL_WEG(i,:) = en_to_ll([XGWs(i), YGWs(i)] , [latitude(1), longitude(1),
altitude(1)]);
    LL_KFS(i,:) = en_to_ll([kfEast(i), kfNorth(i)] , [latitude(1), longitude(1),
altitude(1)]);
    LL_KFUS(i,:) = en_to_ll([kfEastU(i), kfNorthU(i)] , [unsyncLatitude(1),
unsyncLongitude(1), unsyncAltitude(1)]);
    %For adaptive filters

```

```

    ALL_WEG(i,:) = en_to_ll([XAGWs(i), YAGWs(i)] , [latitude(1), longitude(1),
altitude(1)]);
    ALL_KFS(i,:) = en_to_ll([AkfEast(i), AkfNorth(i)] , [latitude(1),
longitude(1), altitude(1)]);
    ALL_KFUS(i,:) = en_to_ll([AkfEastU(i), AkfNorthU(i)] , [unsyncLatitude(1),
unsyncLongitude(1), unsyncAltitude(1)]);
    %For sensor-based frames kalma
    LL_KFFrame(i,:) = en_to_ll([kfXFrames(i), kfYFrames(i)] ,
[unsyncLatitude(1), unsyncLongitude(1), unsyncAltitude(1)]);
end

```


```

%Plotting East & North Positions of all filters
figure;
figure('Position', [0, 0, 2000, 2000]);

plot(GPSe, GPSn, 'r--');
hold on;
plot(unsyncGPSe, unsyncGPSn, 'g--');
plot(XAvg, YAvg, 'b--');
plot(XWs, YWs, 'c--');
plot(XGWs, YGWs, 'y--');
plot(kfEast, kfNorth, 'm--');
plot(kfEastU, kfNorthU, '-c');
plot(XAGWs, YAGWs, '-b');
plot(AkfEast, AkfNorth, '-r');
plot(AkfEastU, AkfNorthU, '-g');
plot(kfXFrames, kfYFrames, 'g--');

legend('GPS', 'Unsynced GPS', 'Average', 'Weighted Average', 'Weighted Average
Excluding GPS', 'KF', 'Unsynced KF', 'Adaptive Weighted Average', ...
'Adaptive KF', "Adaptive Unsynced KF", "Frame-Based KF");
title('All filters routes');
xlabel('East (m)');
ylabel('North (m)');
grid on;
hold off;

```



```
%Now we plot the route using GPS data on a global map
webmap('Open Street Map');
wmmarker(latitude(1), longitude(1), 'FeatureName', 'Start point actual');
wmline(latitude(2:end-1), longitude(2:end-1), "Color", 'black');
wmmarker(latitude(end), longitude(end), 'FeatureName', 'End point actual');

wmline(LL_Av(2:end-1, 1), LL_Av(2:end-1, 2), "Color", "yellow", "OverlayName",
'Average Estimates path');
wmmarker(LL_Av(end, 1), LL_Av(end, 2), 'FeatureName', 'End point Average
Estimates');
```



```

wmline(LL_WE(2:end-1, 1), LL_WE(2:end-1, 2), "Color", "magenta", "OverlayName",
'Weighted Estimates Including GPS path');
wmmarker(LL_WE(end, 1), LL_WE(end, 2), 'FeatureName', 'End point Weighted
Estimates Excluding GPS');

wmline(LL_WEG(2:end-1, 1), LL_WEG(2:end-1, 2), "Color", "cyan", "OverlayName",
'Weighted Estimates Excluding GPS path');
wmmarker(LL_WEG(end, 1), LL_WEG(end, 2), 'FeatureName', 'End point Weighted
Estimates Including GPS');

wmline(LL_KFS(2:end-1, 1), LL_KFS(2:end-1, 2), "Color", "blue", "OverlayName",
'KF Estimates path');
wmmarker(LL_KFS(end, 1), LL_KFS(end, 2), 'FeatureName', 'End point KF Estimates
using Synced data');

wmline(LL_KFUS(2:end-1, 1), LL_KFUS(2:end-1, 2), "Color", "green",
"OverlayName", 'Unsynced KF path');
wmmarker(LL_KFUS(end, 1), LL_KFUS(end, 2), 'FeatureName', 'End point Unsynced KF
Estimates');

wmline(ALL_WEG(2:end-1, 1), ALL_WEG(2:end-1, 2), "Color", "red", "OverlayName",
'adaptive weighted average estimates path');
wmmarker(ALL_WEG(end, 1), ALL_WEG(end, 2), 'FeatureName', 'End point adaptive
weighted average Estimates');

wmline(ALL_KFS(2:end-1, 1), ALL_KFS(2:end-1, 2), "Color", "yellow",
"OverlayName", 'adaptive KF path');
wmmarker(ALL_KFS(end, 1), ALL_KFS(end, 2), 'FeatureName', 'End point adaptive KF
Estimates');

wmline(ALL_KFUS(2:end-1, 1), ALL_KFUS(2:end-1, 2), "Color", "white",
"OverlayName", 'adaptive Unsynced KF path');
wmmarker(ALL_KFUS(end, 1), ALL_KFUS(end, 2), 'FeatureName', 'End point adaptive
Unsynced KF Estimates');

wmline(LL_KFFrame(2:end-1, 1), LL_KFFrame(2:end-1, 2), "Color", "cyan",
"OverlayName", 'Frame-Based KF path');
wmmarker(LL_KFFrame(end, 1), LL_KFFrame(end, 2), 'FeatureName', 'End point Frame-
Based KF Estimates');

```

%Now we evaluate each filter using gps normalized accuracy score measure

```

AVAccScore = zeros(framesNum,1);
WEAccScore = zeros(framesNum,1);
WEGAccScore = zeros(framesNum,1);
KFSAccScore = zeros(framesNum,1);
KFUSAccScore = zeros(framesNum,1);
AWEGAccScore = zeros(framesNum,1);
AKFSAccScore = zeros(framesNum,1);
AKFUSAccScore = zeros(framesNum,1);
FBKFAccScore = zeros(framesNum,1);

```

```

for i= 1:framesNum

```

```

    [AVAccScore(i), ~, ~] = accuracyScore(GPSe(i), GPSn(i), posAcc(i), XAvg(i),
YAvg(i));
    [WEAccScore(i), ~, ~] = accuracyScore(GPSe(i), GPSn(i), posAcc(i), XWs(i),
YWs(i));
    [WEGAccScore(i), ~, ~] = accuracyScore(GPSe(i), GPSn(i), posAcc(i), XGWs(i),
YGWs(i));
    [KFSAccScore(i), ~, ~] = accuracyScore(GPSe(i), GPSn(i), posAcc(i),
kfEast(i), kfNorth(i));
    [KFUSAccScore(i), ~, ~] = accuracyScore(gpsF(i,1), gpsF(i,2),
unsyncPosAcc(ceil(i*(1/filterRatio))), kfEastU(i), kfNorthU(i));
    [AWEAccScore(i), ~, ~] = accuracyScore(GPSe(i), GPSn(i), posAcc(i),
XAGWs(i), YAGWs(i));
    [AKFSAccScore(i), ~, ~] = accuracyScore(GPSe(i), GPSn(i), posAcc(i),
AkfEast(i), AkfNorth(i));
    [AKFUSAccScore(i), ~, ~] = accuracyScore(AgpsF(i,1), AgpsF(i,2),
unsyncPosAcc(ceil(i*(1/filterRatio))), AkfEastU(i), AkfNorthU(i));
    [FBKFAccScore(i), ~, ~] = accuracyScore(GPSe(i), GPSn(i), posAcc(i),
kfXFrames(i), kfYFrames(i));
end

```


```

%Now we plot change in accuracy measure for different approaches (Low accuracy
filters)
figure;

plot(timeVector, AVAccScore, '-s');
hold on;
plot(timeVector, WEAccScore, '-x');
plot(timeVector, WEGAccScore, '-o');
plot(timeVector, KFSAccScore, '-*');
plot(timeVector, KFUSAccScore, '--');

legend('Average Estimates Score', 'Weighted Estimates Score', 'Weighted
Estimates Score Excluding GPS', 'KF Estimates Score', 'Unsynced KF Estimates
Score');
title('Accuracy Score for Non Adaptive filters');
xlabel('Time (s)');
ylabel('accuracyScore');
grid on;
hold off;

```



%Now we plot change in accuracy measure for different approaches (High accuracy filters)

figure;

```
plot(timeVector, AWEGAccScore, '-x');
```

```
hold on;
```

```
plot(timeVector, AKFSAccScore, '-*');
```

```
plot(timeVector, AKFUSAccScore, '-s');
```

```
plot(timeVector, FBKFAccScore, '-o');
```

```
legend('Adaptive Weighted Estimates Score','Adaptive KF Estimates Score',
```

```
'Adaptive Unsynchronized KF Estimates Score', 'Frame-Based KF');
```


```
title('Accuracy Score for frame-based and adaptive filters');
```

```
xlabel('Time (s)');
```

```
ylabel('accuracyScore');
```

```
grid on;
```

```
hold off;
```



```
%To obtain total distance of travel
totalDist = 0;
for i= 2:framesNum
    deltaEast = GPSe(i) - GPSe(i-1);
    deltaNorth = GPSn(i) - GPSn(i-1);
    dist = sqrt(deltaEast^2 + deltaNorth^2);
    totalDist = totalDist + dist;
end
%Displaying Average accuracy score per path
fprintf(['For a route with length = %f (m)
\n_____ \n\n' ...
    'Average Estimates Average accuracyScore = %f\n\nWeighted Estimates Average
accuracyScore = %f\n\n' ...
    'Weighted Estimates Excluding GPS Average accuracyScore = %f\n\nSynced KF
Estimates Average accuracyScore = %f\n\n' ...
    'Adaptive Weighted Estimates Excluding GPS Average accuracyScore = %f\n\n'
    ...
    'Unsynchronized KF Estimates Average accuracyScore = %f\n\nAdaptive KF Estimates
Average accuracyScore = %f\n\n' ...
    'Adaptive Unsynchronized KF Estimates Average accuracyScore = %f\n\nFrame-Based KF
Average AccuracyScore = %f'], totalDist, mean(AVAccScore), ...
    mean(WEAccScore), mean(WEGAccScore), mean(KFSAccScore), mean(AWEGAccScore),
    mean(KFUSAccScore), mean(AKFSAccScore), mean(AKFUSAccScore), mean(FBKFAccScore));
```

For a route with length = 237.832732 (m)

Average Estimates Average accuracyScore = 1.876649

Weighted Estimates Average accuracyScore = 5.740868

Weighted Estimates Excluding GPS Average accuracyScore = 3.653279

Synced KF Estimates Average accuracyScore = 0.221358

Adaptive Weighted Estimates Excluding GPS Average accuracyScore = 0.799923

Unsynced KF Estimates Average accuracyScore = 1.212436

Adaptive KF Estimates Average accuracyScore = 0.039406

Adaptive Unsynced KF Estimates Average accuracyScore = 0.209377

Frame-Based KF Average AccuracyScore = 0.382453