Bookmarks

CKA

- Static Pods | Kubernetes
- InitContainers
- Kubernetes - Creating Multi-Container Pods
- Secret - mount it on one container from volume
- Secrets - Expose secret data through env variables in pod
- Secret - convert secret data to a base-64 representation
- Secret - create a secret
- Deployment-updates-image-change
- Deployments-Rollout-History
- Deployments-Rollback-to-previous-version
- Deployments-Scaling
- Deployments-rollout-status
- Non Persistent Volumes
- etcd clusters for Kubernetes
- Safely Drain a Node while Respecting Application SLOs | Kubernetes
- DaemonSet | Kubernetes
- Persistent-Volume
- Multi-container Pod communicating using Shared Volume
- Persistent Volume Clain
- Remove Taint from Master
- Troubleshooting kubeadm | Kubernetes
- Access API server using Kubectl Proxy
- Access API server without kubectl proxy

Get a list of running services in a cluster via kubectl cluster-info
DaemonSet	Kubernetes Engine	Google Cloud
kubernetes-the-hard-way
Change the Reclaim Policy of a PersistentVolume
LimitRange - Limit Storage Consumption
StorageQuota to limit PVC count and cumulative storage capacity
Redis Config Map and Pod Yamls
Redis-Pod-With-Volume-Yaml
Test-Whether-Nginx-Pod-Is-Working
Accessing Nginx Service from Busybox Pod
Deployment Create Yaml
Debug Pods and Replication Controllers
Nodes - Check for sufficient memory and capacity