

EE-559: Practical Session 2

François Fleuret

<https://fleuret.org/dlc/>

February 15, 2018

Draft, do not distribute

Introduction

The objective of this session is to continue practicing with tensors, deal with a real data-set, and get a feeling of how good/bad are the k -nearest neighbor rule and the PCA dimension reduction.

You can get an information sheet about the practical sessions and provided helper functions at

<https://fleuret.org/dlc/dlc-info-sheet.tex>

1 Nearest neighbor

Write a function that gets a training set and a test sample and returns the label of the training point the closest to the latter.

More precisely, write:

```
def nearest_classification(train_input, train_target, x):
```

where

- `train_input` is a 2d float tensor of dimension $n \times d$ containing the training vectors,
- `train_target` is a 1d long tensor of dimension n containing the training labels,
- `x` is 1d float tensor of dimension d containing the test vector,

and the returned value is the class of the train sample closest to x for the L^2 norm.

Hint: The function should have no python loop, and use in particular `torch.mean`, `torch.view`, `torch.expand_as`, `torch.pow`, `torch.sum`, and `torch.sort`. My version is 164 characters long.

2 Error estimation

Write a function

```
def compute_nb_errors(train_input, train_target, test_input, test_target,
                      mean = None, proj = None):
```

where

- `train_input` is a 2d float tensor of dimension $n \times d$ containing the train vectors,
- `train_target` is a 1d long tensor of dimension n containing the train labels,
- `test_input` is a 2d float tensor of dimension $m \times d$ containing the test vectors,
- `test_target` is a 1d long tensor of dimension m containing the test labels,
- `mean` is either `None` or a 1d float tensor of dimension d ,
- `proj` is either `None` or a 2d float tensor of dimension $c \times d$,

that subtracts `mean` (if it is not `None`) from the vectors of both `train_input` and `test_input`, apply the operator `proj` (if it is not `None`) to both, and returns the number of classification errors using the 1-nearest-neighbor rule on the resulting data.

Hint: Use in particular `torch.expand_as` and `torch.mm`. My version is 487 characters long, and it has a loop (the horror!)

3 PCA

Write a function

```
def PCA(x):
```

where `x` is a 2d float tensor of dimension $n \times d$, which returns a pair composed of the 1d mean vector of dimension d and the PCA basis, ranked in decreasing order of the eigen-values, as a 2d tensor of dimension $d \times d$.

Hint: The function should have no python loop, and use in particular `torch.expand_as`, `torch.eig`, and `torch.sort`. My version is 275 characters long.

4 Check that all this makes sense

Compare the performance of the 1-nearest neighbor rule on data projected either a 100d random subspace (*i.e.* using a basis generated with a normal) and using the PCA basis for different dimensions (e.g. 3, 10, 50, 100).

Compare also the performance between MNIST and CIFAR.

Does all this make sense?