Robot Mapping

Least Squares Approach to **SLAM**

Cyrill Stachniss



Three Main SLAM Paradigms

Kalman filter

Particle filter

Graphbased



least squares approach to SLAM


Least Squares in General

- Approach for computing a solution for an overdetermined system
- "More equations than unknowns"
- Minimizes the sum of the squared errors in the equations
- Standard approach to a large set of problems

Today: Application to SLAM


Graph-Based SLAM

- Constraints connect the poses of the robot while it is moving
- Constraints are inherently uncertain



Graph-Based SLAM


 Observing previously seen areas generates constraints between nonsuccessive poses



Idea of Graph-Based SLAM


- Use a graph to represent the problem
- Every node in the graph corresponds to a pose of the robot during mapping
- Every edge between two nodes corresponds to a spatial constraint between them
- Graph-Based SLAM: Build the graph and find a node configuration that minimize the error introduced by the constraints

- Every node in the graph corresponds to a robot position and a laser measurement
- An edge between two nodes represents a spatial constraint between the nodes




KUKA Halle 22, courtesy of P. Pfaff

- Every node in the graph corresponds to a robot position and a laser measurement
- An edge between two nodes represents a spatial constraint between the nodes




KUKA Halle 22, courtesy of P. Pfaff

 Once we have the graph, we determine the most likely map by correcting the nodes



 Once we have the graph, we determine the most likely map by correcting the nodes


... like this



 Once we have the graph, we determine the most likely map by correcting the nodes


... like this

 Then, we can render a map based on the known poses



The Overall SLAM System

- Interplay of front-end and back-end
- Map helps to determine constraints by reducing the search space
- Topic today: optimization




The Graph

- It consists of n nodes $x = x_{1:n}$
- Each \mathbf{x}_i is a 2D or 3D transformation (the pose of the robot at time t_i)
- A constraint/edge exists between the nodes \mathbf{x}_i and \mathbf{x}_j if...


Create an Edge If... (1)


- ...the robot moves from x_i to x_{i+1}
- Edge corresponds to ødometry



Create an Edge If... (2)

• ...the robot observes the same part of the environment from \mathbf{x}_i and from \mathbf{x}_j






Measurement from \mathbf{x}_i

Measurement from \mathbf{x}_j

Create an Edge If... (2)

- ...the robot observes the same part of the environment from \mathbf{x}_i and from \mathbf{x}_j
- Construct a <u>virtual measurement</u> about the position of \mathbf{x}_j seen from \mathbf{x}_i



Edge represents the position of x_j seen from x_i based on the **observation**

Transformations

- Transformations can be expressed using homogenous coordinates
- Odometry-Based edge

$$(\mathbf{X}_i^{-1}\mathbf{X}_{i+1})$$

Observation-Based edge

$$(\mathbf{X}_i^{-1}\mathbf{X}_j)$$

How node i sees node j

Homogenous Coordinates

- H.C. are a system of coordinates used in projective geometry
- Projective geometry is an alternative algebraic representation of geometric objects and transformations
- Formulas involving H.C. are often simpler than in the Cartesian world
- A single matrix can represent affine transformations and projective transformations

Homogenous Coordinates

- H.C. are a system of coordinates used in projective geometry
- Projective geometry is an alternative algebraic representation of geometric objects and transformations
- Formulas involving H.C. are often simpler than in the Cartesian world
- A single matrix can represent affine transformations and projective transformations

Homogenous Coordinates

- N-dim space expressed in N+1 dim
- 4 dim. for modeling the 3D space
- To HC: $(x, y, z)^T \to (x, y, z, 1)^T$
- Backwards: $(x,y,z,w)^T \rightarrow (\frac{x}{w},\frac{y}{w},\frac{z}{w})^T$ Vector in HC: $v = (x,y,z,w)^T$
- Translation:

$$T = \begin{pmatrix} 1 & 0 & 0 & t_x \\ 0 & 1 & 0 & t_y \\ 0 & 0 & 1 & t_z \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

Rotation:

$$R = \left(\begin{array}{cc} R^{3D} & 0\\ 0 & 1 \end{array}\right)$$


The Edge Information Matrices

- Observations are affected by noise
- Information matrix Ω_{ij} for each edge to encode its uncertainty
- The "bigger" Ω_{ij} , the more the edge "matters" in the optimization


Questions

- What do the information matrices look like in case of scan-matching vs. odometry?
- What should these matrices look like when moving in a long, featureless corridor?

Pose Graph



Pose Graph



• Goal:
$$\mathbf{x}^* = \underset{\mathbf{x}}{\operatorname{argmin}} \sum_{ij} \mathbf{e}_{ij}^T \mathbf{\Omega}_{ij} \mathbf{e}_{ij}$$

Least Squares SLAM

 This error function looks suitable for least squares error minimization

$$\mathbf{x}^* = \underset{\mathbf{x}}{\operatorname{argmin}} \sum_{ij} \mathbf{e}_{ij}^T(\mathbf{x}_i, \mathbf{x}_j) \Omega_{ij} \mathbf{e}_{ij}(\mathbf{x}_i, \mathbf{x}_j)$$
$$= \underset{\mathbf{x}}{\operatorname{argmin}} \sum_{k} \mathbf{e}_{k}^T(\mathbf{x}) \Omega_k \mathbf{e}_{k}(\mathbf{x})$$

Least Squares SLAM

 This error function looks suitable for least squares error minimization

$$\mathbf{x}^* = \underset{\mathbf{x}}{\operatorname{argmin}} \sum_{\mathbf{k}} \mathbf{e}_k^T(\mathbf{x}) \mathbf{\Omega}_k \mathbf{e}_k(\mathbf{x})$$

Question:

• What is the state vector?

Least Squares SLAM

 This error function looks suitable for least squares error minimization

$$\mathbf{x}^* = \underset{\mathbf{x}}{\operatorname{argmin}} \sum_{k} \mathbf{e}_k^T(\mathbf{x}) \mathbf{\Omega}_k \mathbf{e}_k(\mathbf{x})$$



What is the state vector?

$$\mathbf{x}^T = \begin{pmatrix} \mathbf{x}_1^T & \mathbf{x}_2^T & \cdots & \mathbf{x}_n^T \end{pmatrix}$$

 $\mathbf{x}^T = (\mathbf{x}_1^T \ \mathbf{x}_2^T \ \cdots \ \mathbf{x}_n^T)$ One block for each node of the graph Specify the error function!

The Error Function

Error function for a single constraint

$$\mathbf{e}_{ij}(\mathbf{x}_i, \mathbf{x}_j) = \mathsf{t2v}(\mathbf{Z}_{ij}^{-1}(\mathbf{X}_i^{-1}\mathbf{X}_j))$$

$$\mathsf{measurement}$$

$$\mathbf{x}_i \text{ referenced w.r.t.} \mathbf{x}_i$$

Error as a function of the whole state vector

$$\mathbf{e}_{ij}(\mathbf{x}) = \mathsf{t2v}(\mathbf{Z}_{ij}^{-1}(\mathbf{X}_i^{-1}\mathbf{X}_j))$$

Error takes a value of zero if

$$\mathbf{Z}_{ij} = (\mathbf{X}_i^{-1} \mathbf{X}_j)$$

Gauss-Newton: The Overall Error Minimization Procedure


- Define the error function
- Linearize the error function
- Compute its derivative
- Set the derivative to zero
- Solve the linear system
- Iterate this procedure until convergence

Linearizing the Error Function

 We can approximate the error functions around an initial guess x via Taylor expansion

$$\mathbf{e}_{ij}(\mathbf{x} + \Delta \mathbf{x}) \simeq \mathbf{e}_{ij}(\mathbf{x}) + \mathbf{J}_{ij}\Delta \mathbf{x}$$
 with $\mathbf{J}_{ij} = \frac{\partial \mathbf{e}_{ij}(\mathbf{x})}{\partial \mathbf{x}}$

• Does one error term $e_{ij}(x)$ depend on all state variables?



- Does one error term $e_{ij}(x)$ depend on all state variables?
 - ightharpoonup No, only on \mathbf{x}_i and \mathbf{x}_j

- Does one error term $e_{ij}(x)$ depend on all state variables?
 - ightharpoonup No, only on \mathbf{x}_i and \mathbf{x}_j
- Is there any consequence on the structure of the Jacobian?

- Does one error term $e_{ij}(x)$ depend on all state variables?
 - \rightarrow No, only $on x_i$ and x_j
- Is there any consequence on the structure of the Jacobian?
 - Yes, it will be non-zero only in the rows corresponding to x_i and x_j

$$\frac{\partial \mathbf{e}_{ij}(\mathbf{x})}{\partial \mathbf{x}} = \left(\mathbf{0} \cdots \frac{\partial \mathbf{e}_{ij}(\mathbf{x}_i)}{\partial \mathbf{x}_i} \cdots \frac{\partial \mathbf{e}_{ij}(\mathbf{x}_j)}{\partial \mathbf{x}_j} \cdots \mathbf{0} \right)$$

$$\mathbf{J}_{ij} = \left(\mathbf{0} \cdots \mathbf{A}_{ij} \cdots \mathbf{B}_{ij} \cdots \mathbf{0} \right)$$

Jacobians and Sparsity

• Error $e_{ij}(x)$ depends only on the two parameter blocks x_i and x_j

$$e_{ij}(\mathbf{x}) = e_{ij}(\mathbf{x}_i, \mathbf{x}_j)$$

• The Jacobian will be zero everywhere except in the columns of x_i and x_i

$$\mathbf{J}_{ij} \; = \; \left[egin{array}{c} \mathbf{0} \cdots \mathbf{0} & rac{\partial \mathbf{e}(\mathbf{x}_i)}{\partial \mathbf{x}_i} & \mathbf{0} \cdots \mathbf{0} & rac{\partial \mathbf{e}(\mathbf{x}_j)}{\partial \mathbf{x}_j} & \mathbf{0} \cdots \mathbf{0} \\ & & & & & & & & & & & & & & & \end{array}
ight]$$

Consequences of the Sparsity

• We need to compute the coefficient vector b and matrix H:

$$\mathbf{b}^{T} = \sum_{ij} \mathbf{b}_{ij}^{T} = \sum_{ij} \mathbf{e}_{ij}^{T} \mathbf{\Omega}_{ij} \mathbf{J}_{ij}$$

$$\mathbf{H} = \sum_{ij} \mathbf{H}_{ij} = \sum_{ij} \mathbf{J}_{ij}^{T} \mathbf{\Omega}_{ij} \mathbf{J}_{ij}$$

- The sparse structure of J_{ij} will result in a sparse structure of H
- This structure reflects the adjacency matrix of the graph

Illustration of the Structure




Illustration of the Structure






Illustration of the Structure





38

Illustration of the Structure




$$\mathbf{H} = \sum_{ij} \mathbf{H}_{ij}$$









Consequences of the Sparsity

- An edge contributes to the linear system via \mathbf{b}_{ij} and \mathbf{H}_{ij}
- The coefficient vector is:

$$\mathbf{b}_{ij}^{T} = \mathbf{e}_{ij}^{T} \mathbf{\Omega}_{ij} \mathbf{J}_{ij}$$

$$= \mathbf{e}_{ij}^{T} \mathbf{\Omega}_{ij} \left(\mathbf{0} \cdots \mathbf{A}_{ij} \cdots \mathbf{B}_{ij} \cdots \mathbf{0} \right)$$

$$= \left(\mathbf{0} \cdots \mathbf{e}_{ij}^{T} \mathbf{\Omega}_{ij} \mathbf{A}_{ij} \cdots \mathbf{e}_{ij}^{T} \mathbf{\Omega}_{ij} \mathbf{B}_{ij} \cdots \mathbf{0} \right)$$

• It is non-zero only at the indices corresponding to \mathbf{x}_i and \mathbf{x}_j

Consequences of the Sparsity

• The coefficient matrix of an edge is:

$$egin{array}{lll} \mathbf{H}_{ij} &=& \mathbf{J}_{ij}^T \mathbf{\Omega}_{ij} \mathbf{J}_{ij} \ &=& egin{pmatrix} \vdots \ \mathbf{A}_{ij}^T \ \mathbf{B}_{ij}^T \ \vdots \ \end{bmatrix} \mathbf{\Omega}_{ij} egin{pmatrix} \cdots \mathbf{A}_{ij} \cdots \mathbf{B}_{ij} \cdots \ \mathbf{B}_{ij}^T \mathbf{\Omega}_{ij} \mathbf{A}_{ij} & \mathbf{A}_{ij}^T \mathbf{\Omega}_{ij} \mathbf{B}_{ij} \ \mathbf{B}_{ij}^T \mathbf{\Omega}_{ij} \mathbf{A}_{ij} & \mathbf{B}_{ij}^T \mathbf{\Omega}_{ij} \mathbf{B}_{ij} \end{array}$$

Non-zero only in the blocks relating i,j

Sparsity Summary

- An edge ij contributes only to the
 - ullet ith and the jth block of \mathbf{b}_{ij}
 - ullet to the blocks ii, jj, ij and ji of \mathbf{H}_{ij}
- Resulting system is sparse
- System can be computed by summing up the contribution of each edge
- Efficient solvers can be used
 - Sparse Cholesky decomposition
 - Conjugate gradients
 - ... many others

The Linear System

Vector of the states increments:

$$\Delta \mathbf{x}^T = \begin{pmatrix} \Delta \mathbf{x}_1^T & \Delta \mathbf{x}_2^T & \cdots & \Delta \mathbf{x}_n^T \end{pmatrix}$$

Coefficient vector:

$$\mathbf{b}^T = \left(\mathbf{\bar{b}}_1^T \mathbf{\bar{b}}_2^T \cdots \mathbf{\bar{b}}_n^T \right)$$

System matrix:

$$\mathbf{H} = \begin{pmatrix} \bar{\mathbf{H}}^{11} & \bar{\mathbf{H}}^{12} & \cdots & \bar{\mathbf{H}}^{1n} \\ \bar{\mathbf{H}}^{21} & \bar{\mathbf{H}}^{22} & \cdots & \bar{\mathbf{H}}^{2n} \\ \vdots & \ddots & & \vdots \\ \bar{\mathbf{H}}^{n1} & \bar{\mathbf{H}}^{n2} & \cdots & \bar{\mathbf{H}}^{nn} \end{pmatrix}$$

Building the Linear System

For each constraint:

- Compute error $\langle e_{ij} = t2v(\mathbf{Z}_{ij}^{-1}(\mathbf{X}_i^{-1}\mathbf{X}_j)) \rangle$
- Compute the blocks of the Jacobian:

$$\mathbf{A}_{ij} = \frac{\partial \mathbf{e}(\mathbf{x}_i, \mathbf{x}_j)}{\partial \mathbf{x}_i}$$
 $\mathbf{B}_{ij} = \frac{\partial \mathbf{e}(\mathbf{x}_i, \mathbf{x}_j)}{\partial \mathbf{x}_j}$

Update the coefficient vector:

$$\bar{\mathbf{b}}_{i}^{T} + = \mathbf{e}_{ij}^{T} \mathbf{\Omega}_{ij} \mathbf{A}_{ij} \qquad \bar{\mathbf{b}}_{j}^{T} + = \mathbf{e}_{ij}^{T} \mathbf{\Omega}_{ij} \mathbf{B}_{ij}$$

Update the system matrix:

$$\bar{\mathbf{H}}^{ii} + = \mathbf{A}_{ij}^T \mathbf{\Omega}_{ij} \mathbf{A}_{ij} \qquad \bar{\mathbf{H}}^{ij} + = \mathbf{A}_{ij}^T \mathbf{\Omega}_{ij} \mathbf{B}_{ij}$$


$$\bar{\mathbf{H}}^{ji} + = \mathbf{B}_{ij}^T \mathbf{\Omega}_{ij} \mathbf{A}_{ij} \qquad \bar{\mathbf{H}}^{jj} + = \mathbf{B}_{ij}^T \mathbf{\Omega}_{ij} \mathbf{B}_{ij}$$

Algorithm

```
optimize(x):
           while (!converged)
                      (\mathbf{H}, \mathbf{b}) = \text{buildLinearSystem}(\mathbf{x})
3:
                     \Delta \mathbf{x} = \text{solveSparse}(\mathbf{H}\Delta \mathbf{x} = -\mathbf{b})
4:
5:
                    \mathbf{x} = \mathbf{x} + \mathbf{\Delta}\mathbf{x}
6:
            end
           return x
```

Example on the Blackboard

Trivial 1D Example



Two nodes and one observation

$$\mathbf{x} = (x_1 x_2)^T = (00)$$

$$\mathbf{z}_{12} = 1$$

$$\Omega = 2$$

$$\mathbf{e}_{12} = z_{12} - (x_2 - x_1) = 1 - (0 - 0) = 1$$

$$\mathbf{J}_{12} = (1 - 1)$$

$$\mathbf{b}_{12}^T = \mathbf{e}_{12}^T \Omega_{12} \mathbf{J}_{12} = (2 - 2)$$

$$\mathbf{H}_{12} = \mathbf{J}_{12}^T \Omega \mathbf{J}_{12} = \begin{pmatrix} 2 & -2 \\ -2 & 2 \end{pmatrix}$$

$$\Delta \mathbf{x} = -\mathbf{H}_{12}^{-1} b_{12}$$
BUT $\det(\mathbf{H}) = 0$???

What Went Wrong?

- The constraint specifies a relative constraint between both nodes
- Any poses for the nodes would be fine as long a their relative coordinates fit
- One node needs to be "fixed"

$$\mathbf{H} = \begin{pmatrix} 2 & -2 \\ -2 & 2 \end{pmatrix} + \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix}$$
 constraint that sets
$$\mathbf{dx_1} = \mathbf{0}$$

$$\mathbf{\Delta x} = -\mathbf{H}^{-1}b_{12}$$


$$\mathbf{\Delta x} = (0\ 1)^T$$

Role of the Prior

- We saw that the matrix H has not full rank (after adding the constraints)
- The global frame had not been fixed
- Fixing the global reference frame is strongly related to the prior $p(\mathbf{x}_0)$
- A Gaussian estimate about x₀ results in an additional constraint
- E.g., first pose in the origin:

$$e(\mathbf{x}_0) = t2v(\mathbf{X}_0)$$

Real World Examples





Fixing a Subset of Variables

- Assume that the value of certain variables during the optimization is known a priori
- We may want to optimize all others and keep these fixed
- How?

Fixing a Subset of Variables

- Assume that the value of certain variables during the optimization is known a priori
- We may want to optimize all others and keep these fixed
- How?
- If a variable is not optimized, it should "disappears" from the linear system

Fixing a Subset of Variables

- Assume that the value of certain variables during the optimization is known a priori
- We may want to optimize all others and keep these fixed
- How?
- If a variable is not optimized, it should "disappears" from the linear system
- Construct the full system
- Suppress the rows and the columns corresponding to the variables to fix

Why Can We Simply Suppress the Rows and Columns of the Corresponding Variables?

Uncertainty


- H represents the information matrix given the linearization point
- Inverting H gives the (dense) covariance matrix
- The diagonal blocks of the covariance matrix represent the (absolute) uncertainties of the corresponding variables

Relative Uncertainty

To determine the relative uncertainty between x_i and x_j :

- Construct the full matrix H
- Suppress the rows and the columns of \mathbf{x}_i (= do not optimize/fix this variable)
- Compute the block j,j of the inverse
- This block will contain the covariance matrix of \mathbf{x}_j w.r.t. \mathbf{x}_i , which has been fixed

Example



Conclusions

- The back-end part of the SLAM problem can be effectively solved with Gauss-Newton
- The H matrix is typically sparse
- This sparsity allows for efficiently solving the linear system
- One of the state-of-the-art solutions for computing maps

Literature

Least Squares SLAM

 Grisetti, Kümmerle, Stachniss,
 Burgard: "A Tutorial on Graph-based SLAM", 2010