




Description

For the electronic measurement of currents: DC, AC, pulsed, mixed, with a galvanic isolation between the primary circuit (high power) and the secondary circuit (electronic circuit).

Features

- ◆ Closed loop (compensated) current Transducer using the Hall effect
- ◆ Galvanic isolation between primary and secondary circuit
- ◆ Low power consumption
- ◆ Extended measuring range
- ◆ Insulated plastic case recognized according to UL 94-V0



$$I_{PN} = 500A$$

Advantages

- ◆ Very good linearity
- ◆ Excellent accuracy
- ◆ Low temperature drift
- ◆ Wide frequency bandwidth
- ◆ Optimized response time
- ◆ No insertion losses
- ◆ High immunity against external Interference
- ◆ Excellent performance and price

Industrial applications

- ◆ AC variable speed drives
- ◆ Battery supplied applications
- ◆ Uninterruptible Power Supplies (UPS)
- ◆ Power supplies for welding applications
- ◆ Static converters for DC motor drives
- ◆ Switched-Mode Power Supplies (SMPS)

TYPES OF PRODUCTS				
Type	Primary nominal current r. m. s I_{PN} (A)	Primary current measuring range I_P (A)	Measuring resistance@70°C R_M (Ω)	
BSH-500ICV5M	500	0 ... ± 800	0~60	with $\pm 15V$ @ $\pm 500A_{maxi}$
			0~11	with $\pm 15V$ @ $\pm 800A_{maxi}$
			0~92	with $\pm 18V$ @ $\pm 500A_{maxi}$
			0~30	with $\pm 18V$ @ $\pm 800A_{maxi}$
			5~149	with $\pm 24V$ @ $\pm 500A_{maxi}$
			5~65	with $\pm 24V$ @ $\pm 800A_{maxi}$


Parameters Table

PARAMETERS	SYMBOL	UNIT	VALUE	CONDITIONS
Electrical data				
Supply voltage ($\pm 5\%$)	V_C	V	$\pm 15 \dots 24$	
Current consumption	I_C	mA	$24 + I_s$	@ $\pm 18V$
Secondary nominal current r.m.s	I_{SN}	mA	100	
Conversion ratio	K_N		1:5000	
Accuracy - Dynamic performance data				
Linearity	ε_L	%	$< \pm 0.1$	
Accuracy	X_G	%	$< \pm 0.6$	@ I_{PN} , $T_A = 25^\circ C$
Offset current	I_o	mA	$< \pm 0.40$	@ $I_P = 0, T_A = 25^\circ C$
Thermal drift of I_o	I_{OT}	mA	$< \pm 0.40$	@ $I_P = 0, -40^\circ C \sim +70^\circ C$
Magnetic offset current	I_{OM}	mA	$< \pm 0.20$	@ $I_P = 0$, after an overload of $3 \times I_{PN}$
Response time	t_r	μS	< 1	@ 90% of I_{PN} step
d_i/d_t accurately followed	d_i/d_t	A/ μS	> 100	
Frequency bandwidth ⁽¹⁾	BW	kHz	DC~100	@ -1dB
General data				
Ambient operating temperature	T_A	$^\circ C$	$-40 \sim +70$	
Ambient storage temperature	T_S	$^\circ C$	$-40 \sim +85$	
Secondary coil resistance	R_s	Ω	70	@ $T_A = 70^\circ C$
Mass	m	g	255	
Isolation data				
R. m. s voltage for AC isolation test	V_d	KV	3.8	@ 50Hz, 1 min
Impulse withstand voltage	V_w	KV	12.5	@ 1.2/50 μS
Creepage distance	dCp	mm	> 15.2	
Clearance distance	dCI	mm	> 14.5	
Comparative Tracking Index	CTI		> 175	

Notes:

- (1) Please refer to derating curves in the technical file to avoid excessive core heating at high frequency

Dimensions BSH-500ICV5M (in mm. 1 mm = 0.0394 inch)



◆Instructions of use

1. When the test current passes through the sensor, you can get the size of the output current.
(Warning: wrong connection may lead to sensors damage.)
2. Based on user needs, the sensors output range can be appropriately regulated.
3. According to user needs, different rated input currents and output currents of the sensors can be customized.



RESTRICTIONS ON PRODUCT USE

- The information contained herein is subject to change without notice.
- BYD Semiconductor Co., Ltd. exerts the greatest possible effort to ensure high quality and reliability. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing products, to comply with the standards of safety in making a safe design for the entire system, including redundancy, fire-prevention measures, and malfunction prevention, to prevent any accidents, fires, or community damage that may ensue. In developing your designs, please ensure that products are used within specified operating ranges as set forth in the most recent products specifications.
- The products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of products listed in this document shall be made at the customer's own risk.