

Topics

- Exception vs Interruption
- Common Exception
- Exception Handler
 - Register in coprocessor 0
 - Trap, eret (MIPS32)

Exception vs Interruption

- An exception is an event that disrupts the normal flow of the execution of your code.
 - ➤ When an exception occurs, the CPU will figure out what is wrong by checking its status, see if it can be corrected and then continue the execution of the normal code like nothing happened.
 - ➤ E.g. Accessing to the 0x0 address in user mode will trigger an exception.


- An interruption is an event caused by a device which is external to the CPU.
 - ➤ E.g. 'syscall' is an interruption.

Common Exception

The following exceptions are the most common in the main processor:

- Address error exceptions
 - ➤ Which occur when the machine references a data item that is NOT on its proper memory alignment or when an address is invalid for the executing process.
- Overflow exceptions
 - ➤ Which occur when **arithmetic operations** compute **signed** values and the destination lacks the precision to store the result.
- > Bus exceptions
 - > Which occur when an address is invalid for the executing process.
- > **Divide-by-zero** exceptions
 - > Which occur when a divisor is zero.

Bad Address Exception



Registers	Coproc 1	Coproc 0	
ı	Vame	Number	Value
\$8 (vaddr)		8	0x00000000
\$12 (status)	12	0x0000ff13
\$13 (cause)	(13	0x00000010
\$14 (epc)		14	0x0040000c

Bkpt	Address	Code	Basic		Source	
	0x00400000	0x23bdfffc	addi \$29, \$29, 0xfffffffc	5:	addi \$sp, \$sp, -4	
	0x00400004	0xafa20000	sw \$2,0x00000000(\$29)	6:	sw \$v0, (\$sp)	
	0x00400008	0x24020004	addiu \$2, \$0, 0x00000004	9:	li \$v0, 4	
	0x0040000c	0x0000000c	syscall	10:	syscall	П
	0x00400010	0x8fa20000	lw \$2,0x00000000(\$29)	12:	lw \$v0,(\$sp)	
	0x00400014	0x23bd0004	addi \$29, \$29, 0x00000004	13:	addi \$sp, \$sp, 4	
	0x00400018	0x201fffff	addi \$31, \$0, 0xffffffff	15:	addi \$ra, \$zero, 0xffffffff	
	0x0040001c	0x03e00008	jr \$31	16:	jr \$ra	

Runtime exception at 0x0040000c: address out of range 0x00000000


\$a0's default value is 0x00000000, which is not allowed to access in user mode

The Register in Coprocessor 0

Register name	Register number	Usage
VAddr	8	memory address at which an offending memory reference occurred
Status	12	interrupt mask and enable bits
Cause	13	exception type and pending interrupt bits
EPC	14	address of instruction that caused exception

Registers Coproc 1 C	oproc 0	
Name	Number	Value
\$8 (vaddr)	8	0x00000000
\$12 (status)	12	0x0000ff13
\$13 (cause)	13	0x00000030
\$14 (epc)	14	0x00400010

Exception Control Registers



BD = Branch Delay, UM = User Mode, EL = Exception Level, IE =Interrupt Enable

EXCEPTION CODES

Number	Name	Cause of Exception	Number	Name	Cause of Exception
0	Int	Interrupt (hardware)	9	Bp	Breakpoint Exception
4	AdEL	Address Error Exception (load or instruction fetch)		RI	Reserved Instruction Exception
5	AdES	Address Error Exception (store)	11	CpU	Coprocessor Unimplemented
6	IBE	Bus Error on Instruction Fetch	12	Ov	Arithmetic Overflow Exception
7	DBE	Bus Error on Load or Store	13	Tr	Trap
8	Sys	Syscall Exception cs202 wangw6@sustech.edu.c	15	FPE	Floating Point Exception

Bad Address Exception continued

```
.data
     str: .asciiz "hello"
.text
print_string:
     addi $sp,$sp,-4
     sw $v0,($sp)
     la $a0,str
     li $v0,4
     syscall
     lw $v0,($sp)
     addi $sp,$sp,4
     addi $ra,$zero,0xffffffff
     jr $ra
```

\$ra	31	0xffffffff
рс		0xffffffff

Registers	Coproc 1	Coproc 0	
1	lame	Number	Value
\$8 (vaddr)		8	0xffffffff
\$12 (status)	12	0x0000ff13
\$13 (cause)		13	0x00000010
\$14 (epc)		14	0xffffffff

Error in : invalid program counter value: Oxffffffff

Bad Address Exception continued

Which one will trigger the exception?

Registers	Coproc 1	Coproc 0	
Name	Nu	ımber	Value
\$8 (vaddr)		8	0x10010009
\$12 (status)		12	0x0000ff13
\$13 (cause)		13	0x00000010
\$14 (epc)		14	0x0040001c

```
.include "../macro print str.asm"
.data
     str: .asciiz "data is:"
     bs: .byte 1:10
     ws: .word 2:10
.text
     print string("data is:")
     add $t0,$zero,$zero
     addi $t1,$zero,10
loop out:
     lw $a0,bs
     li $v0,1
     syscall
     add $t0,$t0,1
     bne $t0,$t1,loop out
     end
```

```
.include "../macro print str.asm"
.data
     str: .asciiz "data is:"
         .byte 1:10
     bs:
     ws: .word 2:10
.text
     print_string("data is:")
     add $t0,$zero,$zero
     addi $t1,$zero,10
loop out:
     lw $a0,ws
     li $v0,1
     syscall
     add $t0,$t0,1
     bne $t0,$t1,loop out
     end
```

Runtime exception at 0x0040001c: fetch address not aligned on word boundary 0x10010009

Arithmetic Exception

Will the 'addu' trigger an exception? How about 'sub', 'div'? How about 'addiu \$a0, \$t0, -1'?

.data
addend1: .word 0x7fffffff
addend2: .word 0x7fffffff
.text
print_string:
lw \$t0,addend1
lw \$t1,addend2
add \$a0,\$t0,\$t1
li \$v0,1
syscall
li \$v0,10
syscall

Registers	Coproc 1	Coproc 0	
N	ame	Number	Value
\$8 (vaddr)		8	0x00000000
\$12 (status)		12	0x0000ff13
\$13 (cause)		13	0x00000030
\$14 (epc)		14	0x00400010

Bkpt	Address	Code	Basic		Source
	0x00400000	0x3c011001	lui \$1,0x00001001	6:	lw \$t0, addend1
treat.	0x00400004	0x8c280000	lw \$8,0x00000000(\$1)	12	
	0x00400008	0x3c011001	lui \$1,0x00001001	7:	lw \$t1, addend2
leens .	0x0040000c	0x8c290004	lw \$9,0x00000004(\$1)	10	
	0x00400010	0x01092020	add \$4, \$8, \$9	8:	add \$a0, \$t0, \$t1
11000	0x00400014	0x24020001	addiu \$2, \$0, 0x00000001	10:	li \$v0,1
	0x00400018	0x0000000c	syscall	11:	syscall
11000	0x0040001c	0x2402000a	addiu \$2, \$0, 0x0000000a	13:	li \$v0,10
	0x00400020	0x0000000c	syscall	14:	syscall

Runtime exception at 0x00400010: arithmetic overflow

How MIPS Acts When Taking An Exception?

- > Step1. It sets up the EPC to point to the restart location
- > Step2. CPU changes into kernel mode and disables the interrupts (MIPS does this by setting EXL bit of Status register)
- > Step3. Set up the Cause register to indicate which is wrong so that software can tell the reason for the exception. If it is for address exception, for example, TLB miss and so on, the BadVaddr register is set.
- > Step4. CPU starts fetching instructions from the exception entry point and then goes to the exception handler.

Up to MIPS III, eret instruction is used to return to the original location before falling into the exception. Note that eret behavior is: clear the SR[EXL] bit and return control to the adress stored in EPC.

Exception Related Instructions

> Conditional trap

```
\triangleright teq $s0, $s1 ##trap(jump to the ktext), if s0==s1
```

```
\triangleright tne $s0, $s1 ##trap(jump to the ktext), if s0!=s1
```

```
\triangleright teqi $s0, 1 ##trap(jump to the ktext), if s0==1
```

> mfc0, mtc0

```
>mfc0 $k0,$14 ##Move from coproc0 reg#14(epc) to $k0
```

```
\rightarrow mtc0 $k0,$14 ##Move from $k0 to coproc0 reg#14(epc)
```

> eret

- > Returns from an interrupt, exception or error trap.
- Similar to a branch or jump instruction, eret executes the next instruction before taking effect. Use this on R4000 processor machines in place of rfe.

Demo

```
.data
         dmsg:
                  .asciiz "\ndata over"
.text
         li $v0,5
main:
         syscall
         teqi $v0,0
         la $a0,dmsg
         li $v0,4
         syscall
         li $v0,10
         syscall
```

```
.ktext
          0x80000180
     move $k0,$v0
     move $k1,$a0
     la $a0,msg
     li $v0,4
     syscall
     move $v0,$k0
     move $a0,$k1
     mfc0 $k0,$14
     addi $k0,$k0,4
     mtc0 $k0,$14
     eret
.kdata
msg: .asciiz "\nTrap generated"
```

Q1. How to tigger the trap? Q2. When will the string "\ndata over" be printed out? Q3. Use "break" in text segment and ktext segment seperately, what happens?


Practice


- 1. Implementing a procedure to read a list of number from input, store them into an array and print every item of the array out:
 - 1. The size of the array and its space are determined by user's input
 - 2. The space of array item is determined by user's input
 - 3. While storing the array items into array, if the item exceed the bounday of array, an exception will be triggered and exit the program.
 - 1. For example: the size of array is 10 and its space is 10Bytes, the space of each array item is 4Bytes. Using loop to read the value of array items and write them into the array's space. While processing the 3th array item and write it into array's space, this value will pollute other areas. Your procedure should trigger an exception on this situation, print the warning infomation and exit the program.
 - 4. While all items are stored into the array correctly, print every item out.

The exception handler do the following things:

- 1. stop the program running
- 2. output prompt information, including "runtime exception at $0x_***"$ (the address of the instruction which triggered the exception), the cause of the exception ("Arrayltem pollutes other areas", index is:***) and the index of array item which triggered the exception.
- 3. exit the program.

Tips: usage of '.align'





.data

str: .asciiz "data is:"

bs: .byte 1:10

ws: .word 2:10


.data

str: .asciiz "data is:"

.align 2

bs: .byte 1:10

ws: .word 2:10



Tips

.align Align the next datum on a 2 ⁿ byte boundary.

For example, .align 2 aligns the next value on a word boundary. .align 0 turns off automatic alignment of .half, .word, .float, and .double directives until the next .data or .kdata directive.

.kdata subsequent items are stored in the kernel data segment, If the optional argument addr is present, subsequent items are stored starting at address addr.

.ktext subsequent items are stored in the kernel text segment, In SPIM, these items may only be instructions or words. If the optional argument addr is present, subsequent items are stored starting at address addr.