



Overview

An overview of the architecture, services, and new features of CircleCI Server v3.0.1

docs@circleci.com

Version 3.0.1, 05/05/2021: FINAL

| | |
|--|-----------|
| CircleCI Server v3.x Overview | 1 |
| Introduction | 1 |
| Architecture | 1 |
| Services | 3 |
| What to read next | 8 |
| CircleCI Server v3.x What's New | 9 |
| New Features | 9 |
| Known Issues | 9 |
| Release 3.0.1 | 9 |
| What to read next | 10 |
| CircleCI Server v3.x FAQ | 11 |
| Does Server 3.0 have a data retention policy? | 11 |
| What control is granted over Nomad certificates? | 11 |
| Is the polling time which checks for health status able to be changed or disabled? | 11 |
| What do the Application Status options in KOTS mean? | 11 |

CircleCI Server v3.x Overview

Introduction

CircleCI Server v3.0.1 is a continuous integration and continuous delivery (CI/CD) platform that you can install on your GCP or AWS Kubernetes cluster.

The core of the CircleCI Server application runs inside Kubernetes.

The application exposes five services using load balancers, three of these load balancers are VPC-internal.

| Load Balancer | Type | Ports | Description |
|---------------------|----------|------------|--|
| Front-end GUI Proxy | External | 80 and 443 | Exposes the web application. |
| Front-end API | External | 80 and 443 | Exposes the web application. |
| Nomad Control Plane | Internal | 4647 | Exposes an RPC protocol for Nomad runners. |
| Output Processor | Internal | 8585 | Ingests output from Nomad runners. |
| VM Service | Internal | 3000 | Provisions virtual machines. |

CircleCI Server schedules CI jobs using the [Nomad](#) scheduler. The Nomad control plane runs inside of Kubernetes, while the Nomad clients, which are responsible for running scheduled CircleCI jobs, are provisioned outside the cluster. CircleCI Server can run Docker jobs on the Nomad clients themselves or in a dedicated virtual machine (VM).

Job artifacts and output are sent directly from jobs in Nomad to object storage (S3, GCS, or other supported options). Audit logs and other items from the application are also stored in object storage so both the Kubernetes cluster and the Nomad clients need access to object storage.

[KOTs](#) is used to configure and deploy CircleCI Server 3.0.

Architecture

Below is a diagram describing the architecture of Server 3.x. The available services are described in greater detail in the [Services](#) section.

Services

CircleCI Server 3.0 consists of the following services. Find their descriptions and failure implications below:

| Service | Component | Description | What happens if it fails? | Notes |
|--------------------------|--------------------------------|---|---|-------|
| api-service | App Core | Provides a GraphQL API that provides much of the data to render the web frontend. | Many parts of the UI (e.g. Contexts) will fail completely. | |
| audit-log-service | App Core | Persists audit log events to blob storage for long term storage. | Some events may not be recorded. | |
| builds-service | App Core | Ingests from www-api and sends to plans-service, workflows-conductor, and to orbs-service | | |
| circle-legacy-dispatcher | Execution | Part of Compute Management. Sends to usage Q (mongo) and back to VCS. | | |
| circleci-mongodb | Execution | Primary datastore | | |
| circleci-postgres | Data storage for microservices | | | |
| circleci-rabbitmq | Pipelines and Execution | Queuing for workflow messaging, test-results, usage, crons, output, notifications, and scheduler | | |
| circleci-redis | Execution | Cache data that will not be stored permanently (i.e. build logs), for request caching, and for rate limit calculations. | A failed cache can end up resulting in rate limiting from the VCS if too many calls are made to it. | |

| Service | Component | Description | What happens if it fails? | Notes |
|-------------------|-----------|--|--|-------|
| circleci-telegraf | | Telegraf collects statsd metrics. All white-boxed metrics in our services publish statsd metrics that are sent to telegraf, but can also be configured to be exported to other places (i.e. Datadog or local-observability-stack-prometheus) | | |
| circleci-vault | | HashiCorp Vault to run encryption and decryption as a service for secrets | | |
| config | | | | |
| contexts-service | App Core | Stores and provides encrypted contexts. | All builds using Contexts will fail. | |
| cron-service | Pipelines | Triggers scheduled workflows. | Scheduled workflows will not run. | |
| dispatcher | Execution | Split jobs into tasks and send them to scheduler to run. | No jobs will be sent to Nomad, the run queue will increase in size but there should be no meaningful loss of data. | |
| domain-service | App Core | Stores and provides information about our domain model. Works with permissions and API | Workflows will fail to start and some REST API calls may fail causing 500 errors in the CircleCI UI. If LDAP authentication is in use, all logins will fail. | |

| Service | Component | Description | What happens if it fails? | Notes |
|---------------------|-----------|--|--|---|
| exim | | Will be removed in GA, but users can provide mail submission credentials to an existing MTA | No email notifications will be sent. | |
| federations-service | App Core | Stores user identities (LDAP). API and permissions-service | If LDAP authentication is in use, all logins will fail and some REST API calls might fail. | LDAP integration not available |
| frontend | Frontend | CircleCI web app and www-api proxy. | The UI and REST API will be unavailable and no jobs will be triggered by GitHub/Enterprise. Running builds will be OK but no updates will be seen. | Rate limit of 150 requests per second with a single user instantaneous limit of 300 requests. |
| inject-bottoken | | A Kubernetes job that inserts a "bot token" into MongoDB. Bot tokens are authorization interservice communication. Mainly for www-api | | |
| kotsadm-kots | Licensing | The main Kots application. Runs the Kots admin console where upgrades and configuration of server take place No admin console available. | No upgrades or configuration possible for Server | |
| kotsadm-migrations | Licensing | Performs database migrations to handle updates of Kotsadm | | |

| Service | Component | Description | What happens if it fails? | Notes |
|--------------------------------------|-----------|--|--|-------|
| kotsadm-minio | Licensing | Object storage for Kots licensing | | |
| kotsadm-operator | Licensing | Deploys and controls Kotsadm | | |
| kotsadm-postgres | Licensing | Database for Kots licensing | | |
| legacy-notifier | App Core | Handles notifications to external services (Slack, email, etc.) | | |
| local-observability-stack-grafana | Server | Used for dashboarding and monitoring | | |
| local-observability-stack-loki | Server | Used for log aggregation | | |
| local-observability-stack-prometheus | Server | Used for metrics | | |
| local-observability-stack-promtail | Server | Used to aggregate logs in a Loki instance. | Log aggregation will fail. Loki won't contain any container logs. | |
| orb-service | Pipelines | Handles communication between orb registry and config. | | |
| output-processor | Execution | Receives job output & status updates and writes them to MongoDB. Also provides an API to running jobs to access caches, workspaces, store caches, workspaces, artifacts, & test results. | | |
| permissions-service | App Core | Provides the CircleCI permissions interface. | Workflows will fail to start and some REST API calls may fail, causing 500 errors in the UI. | |

| Service | Component | Description | What happens if it fails? | Notes |
|-----------------------|--------------------|--|--|------------------------------------|
| scheduler | Execution | Runs tasks sent to it. Works with Nomad server. | No jobs will be sent to Nomad, the run queue will increase in size but there should be no meaningful loss of data. | |
| server-troubleshooter | Data | Runs commands inside pods and appends output to support bundles. | | May not be available in GA. |
| slanger | Server | Provides real-time events to the CircleCI app. | Live UI updates will stop but hard refreshes will still work. | |
| test-results | Execution | Parses test result files and stores data. | There will be no test failure or timing data for jobs, but this will be back-filled once the service is restarted. | |
| vm-gc | Compute Management | Periodically check for stale machine and remote Docker instances and request that vm-service remove them. | Old vm-service instances might not be destroyed until this service is restarted. | |
| vm-scaler | Machine | Periodically requests that vm-service provision more instances for running machine and remote Docker jobs. | VM instances for machine and Remote Docker might not be provisioned causing you to run out of capacity to run jobs with these executors. | Different overlay for EKS vs. GKE. |
| vm-service | Machine | Inventory of available vm-service instances, and provisioning of new instances. | Jobs that use machine or remote Docker will fail. | |

| Service | Component | Description | What happens if it fails? | Notes |
|------------------------------------|-----------|---|--|--|
| workflows-conductor-event-consumer | Pipelines | Takes in information from VCS to kick off pipelines. | New Pipelines will not be kicked off when there are changes in the VCS. | |
| workflows-conductor-grpc-handler | Pipelines | Helps translate the information through gRPC. | | |
| web-ui-* | Frontend | Micro Front End (MFE) services used to render the frontend web application GUI. | The respective services page will fail to load. Example: A web-ui-server-admin failure means the Server Admin page will fail to load. | The MFE's are used to render the web application located at app.<my domain here> |

What to read next

- [What's new in 3.x](#)
- [Server 3.x Installation](#)
- [Server 3.x Migration](#)

CircleCI Server v3.x What's New

Server 3.0 is now generally available. The newest version of server offers the ability to scale under heavy workloads, all within your own Kubernetes cluster and private network, while still enjoying the full CircleCI cloud experience.

Server 3.0 includes the latest CircleCI features, such as orbs, scheduled workflows, matrix jobs, and more. For existing customers interested in migrating from 2.19 to 3.x, contact your customer success manager. Server 3.0 will receive monthly patch releases and quarterly feature releases.

New Features

- New UI
- Orbs for Server
- Pipelines
- Config 2.1
- API 2.0
- Scheduled Workflows
- Matrix Jobs
- And much more...

Known Issues

- No support for external data stores (Postgres, Mongo, Vault). This feature will be implemented in a future release.
- It is currently possible for multiple organizations under the same CircleCI server account to have contexts with identical names. This should be avoided as doing so could lead to errors and unexpected behavior. This will be fixed in a future patch release.
- CircleCI 1.0 builds are not supported. If an attempt is made to run a 1.0 build, no feedback will be available in the application to indicate the cause of the issue. If a build is run on your installation and does not show up in the CircleCI application, users should be directed to use the [CircleCI CLI](#) to validate the project configuration and get details of the possible cause of the issue.
- CircleCI currently assigns a public load balancer for the frontend services. For some customers, their infrastructure or security groups won't allow this. We will provide an optional internal local balancer for the frontend services in a future release.
- [Telegraf](#) metrics collection customization is not yet available.

Release 3.0.1

- `build_agent version` value updated, as the previous version was relying on a vulnerable version of PsExec.
- Due to an issue that was causing duplicated checks in GitHub, environment variables for `output-processor` were reconfigured.
- Adjusted deployment configuration for `vm-service` to handle out-of-order database migrations managed

by Flyway.

What to read next

To learn more about Server v3.x, see the following:

- [Server 3.x Overview](#)
- [Server 3.x Installation](#)
- [Server 3.x Migration](#)
- [Server 3.x Operations](#)

CircleCI Server v3.x FAQ

Does Server 3.0 have a data retention policy?

We do not currently support a defined data retention policy. Data is stored indefinitely on server.

What control is granted over Nomad certificates?

Full control of the certificates, all the way down to mTLS for Nomad.

Is the polling time which checks for health status able to be changed or disabled?

No, this is not customizable.

What do the Application Status options in KOTS mean?

Please see the [KOTS documentation](#).