LED and Photodetectors

Table of Contents

| ED | 1 |
|----------------------------|---|
| PhotodetectorPhotodetector | 3 |

Copyright (C) 2022 Miodrag Bolic

This program is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version. This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details https://www.gnu.org/licenses/.


This code was developed by Miodrag Bolic for the book PERVASIVE CARDIOVASCULAR AND RESPIRATORY MONITORING DEVICES

LED


```
clear all
Vin(:,1)=0:0.01:10; %time;
Vin(:,2)=0:0.01/2:5;
% model_name = 'LED2';
% open_system(model_name)
% V = sdo.getParameterFromModel(model_name, 'V');
simOut = sim('LED2', 'CaptureErrors', 'on');

Warning: Matching "Goto" for "From" 'LED2/LED W/From1' not found
Warning: Matching "Goto" for "From" 'LED2/LED W/From3' not found
Warning: Matching "Goto" for "From" 'LED2/LED W/From3' not found
Warning: Matching "Goto" for "From" 'LED2/LED W/From3' not found
Warning: Matching "Goto" for "From" 'LED2/LED W/From3' not found

figure
plot(simOut.current_out.Data*1000,simOut.Power_out.Data*1000)
xlabel('Forward current (mA)', 'FontSize', 10)
ylabel('Radiant power (mW)', 'FontSize', 10)
```



```
figure
plot(simOut.diode_out.Data, simOut.current_out.Data*1000)
ylabel('Forward current (mA)', 'FontSize', 10)
xlabel('Forward voltage (V)', 'FontSize', 10)
```



```
% plot(-simOut.diode_out.Data,-simOut.current_out.Data*le6)
% xlabel(' Reverse Voltage (V)', 'FontSize', 10)
% ylabel('Reverse Light Current (µA)', 'FontSize', 10)
%
% clear all
% Irr1(:,1)=0:0.01:10; %time
% Irr1(:,2)=10; % irradiance
% Vin(:,1)=0:0.01:10; %time;
% Vin(:,2)=-5:0.01:5;
% simOut = sim('photodiode', 'CaptureErrors', 'on');
% hold on
% plot(-simOut.diode_out.Data,-simOut.current_out.Data*le6)
```

Photodetector

```
clear all

Irr1(:,1)=0:0.01:10; %time
Irr1(:,2)=0:0.01:10; % irradiance
Vin(:,1)=0:0.01:10; %time;
Vin(:,2)=5;
simOut = sim('photodiode', 'CaptureErrors', 'on');
figure
loglog(Irr1(:,2),simOut.current_out.Data(1:length(Irr1(:,2)))*1e6)
xlabel('Irradiance (W/m^2)', 'FontSize', 10)
ylabel('Reverse light current (µA)', 'FontSize', 10)
```

```
10<sup>-1</sup>

10<sup>-2</sup>

10<sup>-3</sup>

10<sup>-2</sup>

10<sup>-1</sup>

Irradiance (W/m<sup>2</sup>)
```

```
clear all
Irr1(:,1)=0:0.01:10; %time
Irr1(:,2)=0.1; % irradiance
Vin(:,1)=0:0.01:10; %time;
Vin(:,2)=-5:0.01:5;
simOut = sim('photodiode', 'CaptureErrors', 'on');
figure
al=plot(-simOut.diode_out.Data,-simOut.current_out.Data*1e6)
```

```
Line with properties:
```

```
Color: [0 0.4470 0.7410]
LineStyle: '-'
LineWidth: 0.5000
Marker: 'none'
MarkerSize: 6
MarkerFaceColor: 'none'
XData: [1×9178 double]
YData: [1×9178 double]
ZData: [1×0 double]
Show all properties
```

```
xlabel('Reverse voltage (V)', 'FontSize', 10)
ylabel('Reverse light current (µA)', 'FontSize', 10)
```

```
Irr1(:,1)=0:0.01:10; %time
Irr1(:,2)=5; % irradiance
Vin(:,1)=0:0.01:10; %time;
Vin(:,2)=-5:0.01:5;
simOut = sim('photodiode', 'CaptureErrors', 'on');
hold on
a2=plot(-simOut.diode_out.Data,-simOut.current_out.Data*1e6)
```

a2 =
 Line with properties:

```
Color: [0.8500 0.3250 0.0980]
LineStyle: '-'
LineWidth: 0.5000
Marker: 'none'
MarkerSize: 6

MarkerFaceColor: 'none'
XData: [1×8636 double]
YData: [1×8636 double]
ZData: [1×0 double]
```

Show all properties

```
xlim([-4,1])
legend([a1,a2],["0.1W/m^2","5W/m^2"])
```

