Compensation and Pension Record Interchange (CAPRI)

System Administration and Technical Guide



March 2013 Version 1.1

Department of Veterans Affairs (VA)
Office of Information and Technology (OIT)
Management & Financial Systems

Revision History

Date	Version	Description	Author
7/10/2012	1.0	Initial Publication	Eileen Fairbrother / Mike Jenkins / Donna Sandusky / George Kocis / Susan Koch
3/25/2013	1.1	Updated sections 5 and 7.4 with changing the CLAIMS server FQDN from CLAIMS.FORUM.VA.GOV "to" CLAIMS.MED.VA.GOV as indicated by Michael Shickle 03/25/2013	Gina Johnson

Preface

Purpose of the System Administration and Technical Guide

The System Administration and Technical Guide document describes the handling, functionality and architecture of the CAPRI product. The guide includes detailed information about the technical architecture and components associated with CAPRI.

Reference Numbering System

This document uses a numbering system to organize its topics into sections and show the reader how these topics relate to each other. For example, section 1.3 means this is the main topic for the third section of Chapter 1. If there were two subsections to this topic, they would be numbered 1.3.1 and 1.3.2. A section numbered 2.3.5.4.7 would be the seventh subsection of the fourth subsection of the fifth subsection of the third topic of Chapter 2. This numbering system tool allows the reader to more easily follow the logic of sections that contain several subsections.

Table of Contents

1.	Intro	oduction	1
	1.1	Acronyms	
	1.2	Reference Materials	
	1.3	Helpful CAPRI User Information	
	1.4	CAPRI Technical Support	3
2.	Age	ency Partners	3
		External Clients	3
		2.1.1. Department of Defense (DoD)	3
	2.2	Internal Clients	
		2.2.1. Veterans Health Administration	
		2.2.1.1. Health Information Access (HIA)	4
		2.2.2. Veterans Benefits Administration	
		2.2.2.1. Veteran Service Organization (VSO)	
		2.2.3. National Cemetery Administration	
		2.2.4. VA Office of Inspector General	/
3.	Sys	tems Relationship	8
	3.1	System Architecture Diagram	8
	3.2	Database Integration Agreements (DBIAs)	
		3.2.1. Custodial Agreements	
		3.2.2. Subscriber Agreements	9
4.	Acc	ount Management	9
		Establishing CAPRI Account	
5.	Inst	talling CAPRI	9
		PRI Distribution Files	
Ο.	6.1		
7.		ging onto CAPRI	11
	7.1		11
	7.2	Non-CAPRI Remote Users	
	7.3	Regional Office CAPRI Remote Users	
	7.4	CAPRI Remote Users	
	7.5	VistA Terminal	
	7.6	Terminal Server Users	
	7.7 7.8	CAPRI NewsCAPRI Alerts	
		Audit Kept	
_		•	
8.		PRI Application Maintenance	
	8.1	CAPRI Application Software Maintenance	
	8.2	C&P Worksheet Template Maintenance	19
9.	App	Dications Development Tools and Usage	
	9.1	Delphi 2006 Development Software	19

Table of Contents

10. Code Repository Tool (Version Control)	20
11.CAPRI Source Files for Delphi 2006	20
12. CAPRI Remote Procedure Calls (RPCs) for MUMPS	20
13. Fileman 13.1 Installation Procedures and Usage 13.1.1. Environmental Setup	2323232323242424242424
14. Archiving, Purging, and Frequency	
15. Security	26
15.1 Security Management	
15.2 General Security	26
15.2.1. Remote Systems	
15.2.2. Contingency Planning	26
15.2.3. Interfacing	26
15.2.4. Electronic Signatures	
15.2.5. Security Keys	26
16. CAPRI Troubleshooting and Error Information	27
16.1 CAPRI Not Installed in VistA	
16.2 CAPRI GUI Option Not Assigned to User in VistA	
16.3 VistA Server Down	28
16.4 VistA Limits Ability to See Patient Records	28
16.5 Network Problems	
16.6 Institution File in VistA has Been Locally Modified	
16.7 Too Many Invalid Attempts at Access Code / Verify Code	
16.8 Multiple Sign-Ons	
16.9 General Error Message	30
Annendix A - CAPRI Remote Procedure Calls for MIMPS	Δ_1

1. Introduction

The Compensation and Pension Record Interchange (CAPRI) project is an information technology initiative to improve service to disabled veterans by promoting efficient communication between the Veterans Health Administration (VHA) and Veterans Benefits Administration (VBA). Online access to medical data enhances the timeliness of the benefits determination. Previous attempts to automate this process were hindered by the "roll and scroll" nature of the VHA computer interface of the Automated Medical Information Exchange (AMIE) II. The CAPRI software acts as a bridge between the VBA and VHA information systems. It offers VBA Rating Veteran Service Representatives and Decision Review Officers help in building the rating decision documentation through online access to medical data. It also offers VHA Compensation and Pension (C&P) staff an easy, standardized way of recording C&P Examination reports.

CAPRI provides VBA employees with a standardized, user-friendly method to rapidly access veterans' electronic medical records throughout the Department of Veterans Affairs (VA). CAPRI delivers leading edge "point and click" technology to the users' desktops. In addition, the learning curve for CAPRI is significantly less than that for character-based systems. CAPRI builds upon existing VHA information security approaches. In addition to using established mechanisms to ensure only authorized access to medical data, CAPRI adds a level of security by allowing VBA users to read but not alter electronic medical record information. CAPRI also provides innovative improvements for medical centers by integrating highly detailed (C&P) Rating examination results into the veterans' medical records. Previously, these reports were not retained online in medical center computer systems but were archived onto paper. This procedure precluded the sharing of clinically useful data.

Initially developed specifically for VBA, the utility of CAPRI has been expanded to other user groups that include VHA, Office of the Medical Inspector, Office of Information (OI), Research, and Veteran Service Officers. Recently, most of the newest features of CAPRI are specifically targeted at adding features to be used by VHA C&P providers and staff.

Note: This document has extensive use of URLs to enable the user access to the best, current and specific information available.

1.1 Acronyms

Term	Definition
A&A	Advisory & Assistance
AHLTA	Armed Forces Health Longitudinal Technology Application (formerly CHCS II, US DoD military health system)
AMIE	Automated Medical Information Exchange
AWIV	Advanced Web Image Viewer
C&P	Compensation and Pension
CAPRI	Compensation and Pension Records Interchange
CPRS	Computerized Patient Record System
CPWM	Compensation and Pension Worksheet Module
DBQ	Disability Benefits Questionnaire
DoD	Department of Defense
DVBA	Department of Veterans Benefits Administration
EHR	Electronic Health Record

Term	Definition
FHIE	Federal Health Information Exchange
GUI	Graphical User Interface
HIA	Health Information Access
HTML	HyperText Markup Language
IDE	Interactive Development Environment
IAs	Integration Agreements
IRM	Information Resources Management
IS	Information Systems
IT	Information Technology
MAS	Medical Administration Service
MUMPS / M	Massachusetts General Hospital Utility Multi-Programming System
NCIO	Network Chief Information Officer
NPM	National Patch Module
OI	Office of Information
OIT	Office of Information Technology
RDV	Remote Data View
RO	Regional Office
RPC	Remote Procedure Call
TIU	Text Integration Utilities
URL	Universal Resource Locator (Internet Shortcut – file name extension)
VA	Department of Veterans Affairs
VAMC	VA Medical Center
VBA	Veterans Benefits Administration
VDL	VA (Software) Document Library
VHA	Veterans Health Administration
VISN	Veterans Integrated Service Network
VistA	Veterans Health Information Systems and Technology Architecture

1.2 Reference Materials

This section contains all referenced materials related to this document.

- http://www-01.ibm.com/software/awdtools/clearcase/
- http://vaww.oed.portal.va.gov/development/legacy_product_enhancements/healthcare_manageme_nt_products/CAPRI/CAPRI%20Reference%20Documents/Forms/AllItems.aspx
- http://vbaw.vba.va.gov/bl/21/Systems/capamie.htm
- http://vaww.va.gov/hia/
- http://www.ehealth.va.gov/CAPRI for VSOs.asp
- http://www.ehealth.va.gov/docs/2008_07JUL_IAP_HIA_brchre_WebV.pdf
- http://www.ehealth.va.gov/docs/CAPRIforVSOsWeb.pdf

- http://www.ehealth.va.gov/vadod/
- http://www.hardhats.org/index.html
- http://www.va.gov/oig/52/reports/2007/VAOIG-05-01143-71.pdf
- http://www.va.gov/oig/54/reports/VAOIG-08-03299-217.pdf
- http://www.va.gov/TRM/ToolPage.asp?tid=39
- http://www.va.gov/vdl/
- http://www.va.gov/vdl/application.asp?appid=133
- http://www.va.gov/vdl/application.asp?appid=31
- http://www.va.gov/vdl/application.asp?appid=5
- http://www.va.gov/vdl/application.asp?appid=163
- http://www.va.gov/vdl/documents/Financial_Admin/CAPRI/capri_dbq_push_utility1_0um.pdf
- http://www2.va.gov/directory/guide/division.asp?dnum=1

DISCLAIMER: The appearance of external hyperlink references in the manual does not constitute endorsement by the VA of this Web site or the information, products, or services contained therein. The VA does not exercise any editorial control over the information you may find at these locations. Such links are provided and consistent with the stated purpose of the VA.

1.3 Helpful CAPRI User Information

The following link provides CAPRI specific information regarding obtaining CAPRI access, CAPRI Training, Advanced Web Image Viewer (AWIV) Desk Reference, CAPRI/Virtual VA interactions, and other useful information at: http://vbaw.vba.va.gov/bl/21/Systems/capamie.htm

1.4 **CAPRI Technical Support**

User support questions should be addressed to local IT support staff, Information Resources Management (IRM), or one of the National Service Desks. A Remedy ticket may be submitted for CAPRI related issues to the National Service Desk at 1-888-596-4357.

2. Agency Partners

2.1 External Clients

Non-VA users include external reviewers and researchers obtaining information from various VA administrations for their specific authorized purposes.

2.1.1. Department of Defense (DoD)

The DoD and the VA have been working together, starting in 2002, to share health information between their two Electronic Health Record (EHR) systems. The VA's EHR is Veterans Health Information Systems and Technology Architecture / Computerized Patient Record System (VistA CPRS) and the DoD's is Armed Forces Health Longitudinal Technology Application (AHLTA), formerly CHCS II, US DoD military health system. Transferring information between VistA CPRS and AHLTA was a major undertaking, since both EHRs were created using different types of software applications.

Both the DoD and the VA have been committed to the task and worked together to develop advanced technology to ensure the secure transfer of electronic health information between the two EHR systems. This important work supports the health care provided to active duty service members and veterans.

2.2 Internal Clients

CAPRI is a VHA developed application. The other two administrations within the VA, VBA and the National Cemetery Administration, use CAPRI directly and/or indirectly.

2.2.1. Veterans Health Administration

The following link (URL) provides a complete list of VHA Medical Centers, Outpatient Clinics, Community Based Outpatient Clinics, Vet Centers, and Veterans Integrated Service Network (VISN) locations where the VHA utilizes the CAPRI system.

http://www2.va.gov/directory/guide/division.asp?dnum=1

The level of access granted to users will depend on job function, need to know, and the level of security placed on certain sensitive patient records.

2.2.1.1. Health Information Access (HIA)

This VHA program coordinates access to many of VHA's health information resources that include national databases, EHRs, extracted datasets, and medical record data found in CPRS through CAPRI and VistAWeb.

2.2.2. Veterans Benefits Administration


The following table lists the VBA regional office (RO) locations with each of their VBA system name.

Note: VBA IT continues to use the VA Office of Information Technology (OIT) naming convention method prior to its reorganization. This naming convention is organizational versus geographical in nature. This table reflects that as all VBA IT locations fall under Region 5. VHA IT currently uses the VA OIT current geographical naming convention. Additionally, VBA from a Business Line perspective doesn't use Region 5, but breaks Region 5 down into three separate NCIOs. (See map following this table)

VBA Region 5				
REGIONAL OFFICE LOCATION	SYSTEM_NAME			
	ST. PETERSBURG REGION			
Atlanta, GA	REGION 5 > VBA > St Petersburg Region > VARO Atlanta > LAN			
Baltimore, MD	REGION 5 > VBA > St Petersburg Region > VARO Baltimore > LAN			
Columbia, SC	REGION 5 > VBA > St Petersburg Region > VARO Columbia > LAN			
Huntington, WV	REGION 5 > VBA > St Petersburg Region > VARO Huntington > LAN			
Jackson, MS	REGION 5 > VBA > St Petersburg Region > VARO Jackson > LAN			
Little Rock, AR	REGION 5 > VBA > St Petersburg Region > VARO Little Rock > LAN			
Louisville, KY	REGION 5 > VBA > St Petersburg Region > VARO Louisville > LAN			
Montgomery, AL	REGION 5 > VBA > St Petersburg Region > VARO Montgomery > LAN			
Nashville, TN	REGION 5 > VBA > St Petersburg Region > VARO Nashville > LAN			
New Orleans, LA	REGION 5 > VBA > St Petersburg Region > VARO New Orleans > LAN			
Newark, NJ	REGION 5 > VBA > St Petersburg Region > VARO Newark > LAN			
Roanoke, VA	REGION 5 > VBA > St Petersburg Region > VARO Roanoke > LAN			
St. Louis, MO	REGION 5 > VBA > St Petersburg Region > VARO St. Louis > LAN			
St. Louis RMC, MO	REGION 5 > VBA > St Petersburg Region > VARO St. Louis RMC > LAN			
St. Petersburg, FL	REGION 5 > VBA > St Petersburg Region > VARO St. Petersburg > LAN			
Washington, DC	REGION 5 > VBA > St Petersburg Region > VARO Washington > LAN			

VBA Region 5					
REGIONAL OFFICE LOCATION SYSTEM_NAME					
Winston-Salem, NC	REGION 5 > VBA > St Petersburg Region > VARO Winston-Salem > LAN				
Willston-Salem, NC	St. Paul Region				
Poston MA	REGION 5 > VBA > St Paul Region > VARO Boston > LAN				
Boston, MA Buffalo, NY	REGION 5 > VBA > St Paul Region > VARO Buffalo > LAN				
Chicago, IL	REGION 5 > VBA > St Paul Region > VARO Chicago > LAN				
Cleveland, OH	REGION 5 > VBA > St Paul Region > VARO Clitcago > LAN REGION 5 > VBA > St Paul Region > VARO Cleveland > LAN				
Des Moines, IA	REGION 5 > VBA > St Paul Region > VARO Des Moines > LAN				
Detroit, MI	REGION 5 > VBA > St Paul Region > VARO Detroit > LAN				
Fargo, ND	REGION 5 > VBA > St Paul Region > VARO Fargo > LAN				
Hartford, CT	REGION 5 > VBA > St Paul Region > VARO Hartford > LAN				
Indianapolis, IN	REGION 5 > VBA > St Paul Region > VARO Indianapolis > LAN				
Lincoln, NE	REGION 5 > VBA > St Paul Region > VARO Lincoln > LAN				
Manchester, NH	REGION 5 > VBA > St Paul Region > VARO Manchester > LAN				
Milwaukee, WI	REGION 5 > VBA > St Paul Region > VARO Milwaukee > LAN				
New York, NY	REGION 5 > VBA > St Paul Region > VARO New York > LAN				
•					
Philadelphia, PA	REGION 5 > VBA > St Paul Region > VARO Philadelphia > LAN REGION 5 > VBA > St Paul Region > VARO Pittsburgh > LAN				
Pittsburgh, PA					
Providence, RI	REGION 5 > VBA > St Paul Region > VARO Providence > LAN				
Sioux Falls, SD	REGION 5 > VBA > St Paul Region > VARO Sioux Falls > LAN				
St. Paul, MN REGION 5 > VBA > St Paul Region > VARO St. Paul > LAN					
Togus, ME	REGION 5 > VBA > St Paul Region > VARO Togus > LAN				
White River Jct, VT	REGION 5 > VBA > St Paul Region > VARO White River Jct. > LAN				
Wichita, KS	REGION 5 > VBA > St Paul Region > VARO Wichita > LAN				
Wilmington, DE REGION 5 > VBA > St Paul Region > VARO Wilmington > LAN					
	SAN DIEGO REGION				
Albuquerque, NM	REGION 5 > VBA > San Diego Region > VARO Albuquerque > LAN				
Anchorage, AK	REGION 5 > VBA > San Diego Region > VARO Anchorage > LAN				
Boise, ID	REGION 5 > VBA > San Diego Region > VARO Boise > LAN				
Denver, CO	REGION 5 > VBA > San Diego Region > VARO Denver > LAN				
Cheyenne, WO	REGION 5 > VBA > San Diego Region > VARO Cheyenne > LAN				
Fort Harrison, MT	REGION 5 > VBA > San Diego Region > VARO Fort Harrison > LAN				
Honolulu, HI	REGION 5 > VBA > San Diego Region > VARO Honolulu > LAN				
Houston, TX	REGION 5 > VBA > San Diego Region > VARO Houston > LAN				
Los Angeles, CA	REGION 5 > VBA > San Diego Region > VARO Los Angeles > LAN				
Manila, Pl	REGION 5 > VBA > San Diego Region > VARO Manila > LAN				
Muskogee, OK	REGION 5 > VBA > San Diego Region > VARO Muskogee > LAN				
Oakland, CA	REGION 5 > VBA > San Diego Region > VARO Oakland > LAN				
Phoenix, AZ	REGION 5 > VBA > San Diego Region > VARO Phoenix > LAN				
Portland, OR REGION 5 > VBA > San Diego Region > VARO Portland > LAN					
Reno, NV	REGION 5 > VBA > San Diego Region > VARO Reno > LAN				
Salt Lake City, UT	REGION 5 > VBA > San Diego Region > VARO Salt Lake City > LAN				
San Diego, CA	REGION 5 > VBA > San Diego Region > VARO San Diego > LAN				
San Juan, PR	REGION 5 > VBA > San Diego Region > VARO San Juan > LAN				
Seattle, WA	REGION 5 > VBA > San Diego Region > VARO Seattle > LAN				
Waco, TX	REGION 5 > VBA > San Diego Region > VARO Waco > LAN				

This is the VBA's Region 5 Business Line perspective Network map of CIOs:



2.2.2.1. Veteran Service Organization (VSO)

All VSO offices are co-located with VBA regional offices as shown in the table of the previous Section 2.2.2. The VSO has authorized CAPRI read-only permissions for specific claimant's EHR. This access allows the VSO to help a veteran who is preparing a VA benefit claim.

CAPRI offers VSO users:

- A national user account option with a single access/verify code, from which authorized users can view a Veteran's entire VA health record from any site where the Veteran has been seen
- Customizable reports and health summaries
- C&P exam requests and results
- A search feature that enables users to search progress notes and discharge summaries for text
- Access to current and past AMIE C&P claims activity
- Federal Health Information Exchange (FHIE)/ DoD health data
- Access to VistAWeb for quickly viewing data at remote locations

VistAWeb is an intranet, browser-based application that provides a read-only view into EHR data. It allows the user to view data that is accessible on the reports tab of CPRS. It retrieves data for patients from all sites where the patient has visited if authorized for special user access and mirrors the behavior of the CPRS and Remote Data View (RDV), however imaging is not currently available.

2.2.3. National Cemetery Administration

The National Cemetery Administration does not directly use the CAPRI application, but receives its verified veteran information through VBA. VBA uses CAPRI to acquire this veteran information.

2.2.4. VA Office of Inspector General

The VA Office of Inspector General performs audits and conducts research for reports when directed using CAPRI accessed data.


3. Systems Relationship

3.1 System Architecture Diagram

The diagram associated with the following link is a high-level association of CAPRI and the systems it interfaces to. This diagram, "CAPRI Data Flow Diagram_Updated09May2012" is available at the following URL:

 $\underline{http://vaww.oed.portal.va.gov/development/legacy_product_enhancements/healthcare_management_products/CAPRI/CAPRI/S20Reference% 20Documents/Forms/AllItems.aspx$

CAPRI Data Flow Diagram



- 1. Authorized remote CAPRI User (usually VBA) logs into the VMS Cluster (if VHA local user skip to step 3)
- The VMS Cluster validates the list of VHA facilities the user is authorized to connect to and passes the CAPRI session overto the selected VistA system (CAPRI connection to the VMS Cluster is dropped and user is now connected to that VistA system)
- CAPRI user selects patient from the VistA system; that process initiates the retrieval of the list (through the MPI) of other facilities where that the patient has presented for care; that list will include Station 200 if DoD data is available for the patient
- 4. If DoD data is available on Station 200, a separate DoD tab is enabled in CAPRI; when DoD tab is selected, CAPRI queries Station 200 for the available DoD report types and presents to the user
- User picks the desired DoD report type and date range, then CAPRI queries Station 200; Station 200 queries the BHIE framework for the needed DoD data elements for the selected report type/date range (limited data is held at VA)
- 6. Using authentication established when user connects to CAPRI, the user is connected to VistA.

3.2 Database Integration Agreements (DBIAs)

There is a large amount of data as well as continual changes within the DBIAs. Therefore, it is recommended to follow these steps to obtain the most current and valid DBIAs for the CAPRI/AMIE package.

3.2.1. Custodial Agreements

A list of CAPRI/AMIE current custodial Integration Agreements (IAs) can be created by FORUM users with DBA Menu access by following these steps:

- 1. Log on to FORUM
- 2. DBA Menu
- 3. Integration Control Registrations Menu

- 4. Custodial Package Menu
- 5. Active ICRs by Custodial Package Option
- 6. Select Package Name: AMIE

3.2.2. Subscriber Agreements

A list of CAPRI/AMIE current subscriber IAs can be created by FORUM users with DBA Menu access by following these steps:

- 1. Log on to FORUM
- 2. DBA Menu
- 3. Integration Control Registrations Menu
- 4. Subscriber Package Menu
- 5. Print Active by Subscriber Package Option
- 6. Start with subscribing package: AUTOMATED MED INFO A
- 7. Go to subscribing package: AUTOMATED MED INFO Z

4. Account Management

4.1 Establishing CAPRI Account

CAPRI access for local VHA medical center users is managed by the local IRM/ISO staff at the medical center, just like any other application (i.e. roll-and-scroll VistA, CPRS, BCMA, etc). HIA only manages CAPRI users that authenticate/authorize through the CLAIMS system. To contact the HIA team send email to: hia.vso@va.gov

Once you obtain access and depending on your role you will be able to create additional accounts using CAPRI tools. Refer to the latest version of the <u>CAPRI GUI User Manual</u> in the VA (Software) Document Library (VDL), see section "Edit Remote User Site Access" at the following URL: http://www/va/gov/vdl/application.asp?appid=133

5. **Installing CAPRI**

Note: It is important that all users at your site remain on the same version.

The AMIE package must be installed and maintained at VistA sites with patient data that will be accessed through the CAPRI GUI application. Installation and configuration of the AMIE package is described in the AMIE Installation Guide, Technical Manual, and Release Notes found at: http://www.va.gov/vdl/application.asp?appid=31


The AMIE package is maintained through patches in the Department of Veterans Benefits Administration (DVBA) namespace, issued through the VistA National Patch Module (NPM).

For the VBA, the new version runs when the user starts the application from **Start/Vbapps/CAPRI/CAPRI**. The user can make new Windows desktop shortcuts (see Section 7.1) after starting the new version.

For the VHA, the IRM department will install the CAPRI desktop icon. Please check with them on the specifics of starting CAPRI. Normally, the user should find the CAPRI shortcut in the same place the user would find the Computerized Patient Record System (CPRS).

Local VistA Connection: The CAPRI shortcut can be set to connect to a specific VistA system. CAPRI will accept the command line parameters **s=servername** and **p=portname**, just like CPRS.

CAPRI REMOTE: CAPRI Remote users access CAPRI through the Claims system, which runs on the VHA Forum hardware. The server for those users should be set to **CLAIMS.MED.VA.GOV**, port **9400**. For more details reference the latest version of the <u>CAPRI GUI User Manual</u>, see section "CAPRI Remote Functionality" at the following URL: http://www.va.gov/vdl/application.asp?appid=133



6. CAPRI Distribution Files

6.1 CAPRI GUI Client Software

The CAPRI GUI client software is distributed as a zipped file from which the executable CAPRI.exe is extracted. Information on downloading the installation files for the CAPRI GUI software is included in the FORUM patch announcing a new version of CAPRI. The following is a sample of a FORUM patch section describing the availability of the installation files and other documents pertaining to the GUI distribution.

Release notes are normally provided with each release to provide a list of the updates included in the patch, because not all users have access to the patch description. The user manual is included if it is updated. The distribution of these documents is at the discretion of each installing facility. The updated documents are placed on the VDL site following patch release.


The CAPRI GUI client software and documentation are available using FTP. The preferred method is to FTP the files from:

download.vista.med.va.gov (Files will be in an anonymous.software directory)

This transmits the files from the first available FTP server. Sites may also elect to retrieve software directly from a specific server as follows:

OI&T FIELD OFFICE	FTP ADDRESS	DIRECTORY
Albany	ftp.fo-albany.med.va.gov	[anonymous.software]
Hines	ftp.fo-hines.med.va.gov	[anonymous.software]
Salt Lake City	ftp.fo-slc.med.va.gov	[anonymous.software]

The following files will be available:



Note: The VDL web site is usually updated within 1-3 days of the release date and will contain the "Release Notes" and <u>if</u> updated the "CAPRI GUI User Manual" as shown in the highlighted text above. The VDL's URL is: http://www.va.gov/vdl/applicaiton.asp?appid=133

7. Logging onto CAPRI

The information is this section is a combination from several different sources but most of the information can be found in the latest version of the <u>CAPRI GUI User Manual</u>, see section "Logging On" at the following URL: http://www.va.gov/vdl/application.asp?appid=133

Please check this main source, the latest version of the <u>CAPRI GUI User Manual</u>, for any updated information that may not be found here.

7.1 Desktop Icon Shortcuts Setup

Note: It is important that all users at your site remain on the same version. Additionally, there is no required fixed location for the CAPRI executable. The location is at the discretion of each installing facility. CAPRI is routinely installed in the Program Files/VistA/CAPRI directory of a user's WinXP workstation. Many sites install the GUI on a network share drive and place a shortcut on the user's workstations. Other sites install the GUI on a Citrix server for remote access.

For the VBA, the new version runs when the user starts the application from **Start/Vbapps/CAPRI/CAPRI**. The user can make new Windows desktop shortcuts after starting the new version.


For the VHA, the IRM department will install the CAPRI desktop icon. Please check with them on the specifics of starting CAPRI. Normally, the user should find the CAPRI shortcut in the same place the user would find the CPRS.

Local Vista Connection: The CAPRI shortcut can be set to connect to a specific VistA system. CAPRI will accept the command line parameters **s=servername** and **p=portname**, just like CPRS. See the

"Additional Information" section; subsection "Installation", in the latest version of the <u>CAPRI GUI User</u> Manual, at the following URL: http://www.va.gov/vdl/application.asp?appid=133

7.2 Non-CAPRI Remote Users

- **Step 1** The user starts by double-clicking the CAPRI icon.
- **Step 2 OPTIONAL** If the workstation has been configured with serverlist.exe by IRM, and if there is no server and port information in the CAPRI shortcut, a window will appear asking the user to select an initial server and port (see following screenshot). Selecting the down arrow in the upper right corner displays all the VHA sites the user can access. A scroll bar appears if the list is too long to be displayed. If the user has access to only one VHA facility, then the VistA sign on screen in **Step 5** is displayed immediately.
- **Step 3 OPTIONAL** The user scrolls to the name of the desired VHA facility, if it is not already visible, and clicks it to select it.



Step 4 – OPTIONAL – The user clicks OK



Step 5 – The user enters a VistA Access Code, presses the **Tab** key, and then enters the Verify Code. The user then presses **Enter** or clicks **OK**. This takes the user to the Patient Selector Screen.

Note: New users without access codes should contact local IRM staff to get one.




7.3 Regional Office CAPRI Remote Users


Most VBA users are CAPRI Remote users. Each CAPRI Remote user needs only one Access Code and one Verify Code to connect to authorized VA Medical Center (VAMC) sites.

- Step 1 From the Start/VBAPPS/CAPRI Remote/CAPRI Remote menu, the user clicks the CAPRI icon.
- **Step 2** After entering the VistA Access Code, the user presses the **Tab** key to go to the next field and enters the Verify Code. Then the user presses **Enter** or clicks **OK**


Note: New users without access codes should contact local IRM staff to get one. The first time the user logs into a VistA application, only the Access Code should be entered. CAPRI will then prompt the user to create a Verify Code. Most users should have a valid Access and Verify Code combination by the time they use CAPRI.




OPTIONAL – To change the **Verify Code**, the user selects the **Change Verify Code** checkbox on the sign-on dialog before clicking $\underline{\mathbf{O}}\mathbf{K}$. The user will then be prompted to create a new **Verify Code** as shown in the steps in the following screenshot.



After selecting **OK**, the user is prompted to enter and confirm a **New Verify Code**



Step 3 – The CAPRI Remote site selection screen displays the user's authorized VHA facilities. (These accesses are established when an account is initially created and/or the user request specific facilities along with the proper approvals after the account creation. This facility information is located in the CAPRI file 396.96.) When the user selects a CAPRI Remote site executable it provides the authorized remote sites. If shown, the vertical scrollbar is used to scroll through all authorized sites. The user selects a site and then either double-clicks the site's name or clicks **OK** to access that site. CAPRI has been modified to include the city and state where each facility is located. In addition, the list may now be sorted by State. The following screenshot shows DEV/FEX Test System in Troy, New York as the selected VHA facility.




After CAPRI loads the VHA facility, the user is prompted with the Patient Selector screen. Instructions for use of the Patient Selector screen are found in section "CAPRI – Using the Software" of the latest version of the <u>CAPRI GUI User Manual</u> at the following URL: http://www.va.gov/vdl/application.asp?appid=133



7.4 CAPRI Remote Users

CAPRI Remote users access CAPRI through the Claims system, which runs on the VHA Forum hardware. The server for those users should be set to **CLAIMS.MED.VA.GOV**, port **9400** (see screenshot below).



CAPRI Remote users outside of VBA will normally obtain an access code from the Office of Information (OI) support staff, not from the local field site. Most VBA users are CAPRI Remote users. Most VHA users are local site users. If a user starts CAPRI and does not successfully connect to a VistA system within 90 seconds, CAPRI automatically shuts down.

When users log into CAPRI remotely, CAPRI alerts users when no email account is set up.

For additional information see the <u>CAPRI Remote Functionality</u> section in the <u>CAPRI GUI User Manual</u> at the following URL: http://www.va.gov/vdl/application.asp?appid=133

7.5 **VistA Terminal**

The "Attachmate Reflections Secure Shell" application replaces the telnet window. CAPRI Remote users can launch a VistA Terminal session by selecting the VistA button to log into the local VistA system site they are assigned to. A dialog box is displayed when the VistA button is clicked that provides the user the ability to choose between connecting using the secure shell application or telnet. The default is set to secure shell application.

Note: Local CAPRI users will not have access to the VistA Terminal from CAPRI and the VistA button will not be available.

7.6 **Terminal Server Users**

Step 1 – From the Hines terminal server application, the user double-clicks the **CAPRI** icon.


Step 2 – Follow the instructions in the previous Section 4.3.2, Regional Office CAPRI Remote Users, **Steps 2** and **3**.

7.7 CAPRI News

Before logging on to CAPRI, News alerts are displayed if new items exist. The user can select the **News** item to view the contents.

The user can select **Clear All** to remove all News items.

The user can select **Close** to continue working with CAPRI.



7.8 CAPRI Alerts

When users of the CAPRI C&P Template functionality log into CAPRI, any existing CAPRI Template Alerts are displayed.

CAPRI automatically checks pending Compensation and Pension Worksheet Module (CPWM) Template statuses. Pending templates in the user's queue are displayed on the alert screen. The C&P Alert screen displays alerts according to template status. Alerts for template statuses are: **draft**, **awaiting signature**, **sent back from reviewer**, **requiring review**, **CPRS documents to cosign**, and **cosigned documents ready to transfer to AMIE**

The user clicks the **Resolve This Alert** button to be taken to the section of CAPRI where the alert can be resolved. For example, if the user has unsigned templates, then he or she is taken to the **Unsigned Templates** window.

The user may select **Continue** to bypass the alerts and go to the **Patient Selector** screen.



7.9 Audit Kept

The following instructions are to view your audit log. This is an example only, use your correct information to locate your log.

Example: The log file is named - DVBA_2.7_BuildVersion_dd_mm_yy.TXT

Go to: C:\Documents and Settings\YourVAUserName\Local Settings\Temp\DVBA_2.7_BuildVersion_dd_mm_yy.txt

8. CAPRI Application Maintenance

8.1 **CAPRI Application Software Maintenance**

The National Patch Module currently resides on the FORUM server and is used to release VistA patches nationally.

Updates to the CAPRI application are distributed through the VA FORUM National Patch Module (NPM) under the DVBA namespace. The DVBA namespace is shared with the Automated Medical Information Exchange (AMIE) package. Patch names follow the format "DVBA*Version*PatchNumber".

The patch consists of the patch description and the routines and VistA FileMan components in PackMan format for installation on the VistA server. The patch description consists of an overview description of the patch, a functional overview, a list of the components released by the patch, retrieval instructions for the software and documentation, and installation instructions for the VistA server portion of the patch.

CAPRI executable and documentation associated with the patch are retrieved from an FTP server designated by the VA for software downloads. The software retrieval instructions are always added by the developer in the SOFTWARE AND DOCUMENTATION RETRIEVAL section of the patch description. A separate installation guide is provided with each CAPRI patch that provides instructions for installing the CAPRI GUI. New versions of the CAPRI GUI do not require installation of previous versions.

The Associated Patches section of the Patch Description lists any previous patches that must be installed prior to the new patch. The Functional Overview section of the patch describes the functional and technical changes included in the patch. The Installation Requirements section provides detailed instructions on the installation of all patch components.

When a CAPRI patch includes new GUI, the Software and Documentation Retrieval section indicates the name of the GUI distribution (zip) file, the installed executable version, and the file size. This section also provides primary and alternative FTP download locations of the installation file, any Release Notes, and other updated documentation files. Updated patch documentation is uploaded to the VDL within three days of the patch release at the following URL:

http://www.va.gov/vdl/application.asp?appid=133

When a CAPRI patch contains a new GUI version, users should be aware of any notes regarding the timing of installation of the M components and providing the new GUI to users.

VA staff with access to FORUM can subscribe to receive notification of newly released CAPRI patches by selecting the FORUM "Patch User Menu" option, "Select Packages for Notification" sub-option, then selecting the AMIE package.

8.2 **C&P Worksheet Template Maintenance**

CAPRI template files are in an ever evolving environment. To obtain the latest information available information it is best to retrieve a list each time.

CAPRI examination templates are stored in the CAPRI TEMPLATE DEFINITION file. This file maintains a list of definitions used to generate examination templates in the CAPRI Graphical User Interface (GUI). Entries in the CAPRI TEMPLATE DEFINITION file are used by the CAPRI application to create the examination templates in the CAPRI GUI. Retired template definitions are retained in the file for historical purposes. This file should remain standardized between all sites. No additions, modifications, or editions should be made to this file except through the remote PUSH utility.

Entries in the CAPRI TEMPLATE DEFINITION file are maintained remotely. The Business Engineering Services Team (BEST) team manages the CAPRI TEMPLATE DEFINITION file using the CAPRI Template PUSH utility. Organizationally, the (BEST) falls under Systems Management within the VHA Chief Business Office (CBO). Insight into this utility can be gained from the <u>CAPRI PUSH DBQ Utility User Manual</u> document at the following URL:

http://www.va.gov.vdl/application.asp?appid-133

This utility is used only by BEST staff. PUSH utility users log onto the CLAIMS Server for authentication and verification. The user performing a PUSH operation must be assigned the option DVBA MANAGE CAPRI TMPLTES GUI option. This option exists only on the CLAIMS and TEST CLAIMS systems, since this is where the operator is authenticated and where the initial context is created. The option DVBA CAPRI GUI is used to create the context for connection to sites where the template definitions are actually updated. Questions about and issues with the PUSH utility should be addressed to: VHA CBO BEST Staff.

9. Applications Development Tools and Usage

9.1 **Delphi 2006 Development Software**

This section includes the Delphi 2006 installation procedure, installation of third-party components, and their purpose and usage. This documentation is currently available in draft format in SharePoint at: http://vaww.oed.portal.va.gov/development/legacy_product_enhancements/healthcare_management_products/CAPRI/CAPRI/20Reference%20Documents/Forms/AllItems.aspx

Upon final approval this document will be posted in the VDL at: http://www.va.gov/vdl/application.asp?appid=133

10. Code Repository Tool (Version Control)

The Delphi application utilizes the Rational ClearCase tool for version control. Its VA approval documentation is located at URL: http://www.va.gov/TRM/ToolPage.asp?tid=39

Per this VA URL, it is recommended to go directly to IBM's Rational ClearCase website at URL: http://www-01.ibm.com/software/awdtools/clearcase/

for any additional current application information.

11. CAPRI Source Files for Delphi 2006

The CAPRI application is developed in Delphi 2006. Standard source file name extensions are preserved as required by the development tool. These file name extensions are .dfm, .pas, .res, and .drc

The CAPRI source files are stored on a Rational ClearQuest Server. Your code must be checked into ClearQuest once modifications have passed testing by the developer.

Due to the longevity of the CAPRI project only limited unit description and usage is available. The developer will need to reference the CAPRI GUI User Manual to obtain and understand what logic occurs when executing the application. By using the CAPRI GUI User Manual, adding break points in the Delphi 2006 IDE, the developer will obtain an understanding of the Functions, Procedures, RPCs, input and output file, and parameter list and usage.

Select the latest version of the <u>CAPRI GUI User Manual</u> at the following URL: http://www.va.gov/vdl/application.asp?appid=133

For any additional assistance refer to Section 1.4, CAPRI Technical Support, for contact information.

12. CAPRI Remote Procedure Calls (RPCs) for MUMPS

See Appendix A for a list of detailed RPCs used by the CAPRI Graphical User Interface (GUI) software.

To duplicate the list of RPCs in Appendix <>, do the following:

- 1. Type "D P^DI" to start Fileman.
- 2. At "Select OPTION:", select option 2, "PRINT FILE ENTRIES".
- 3. At "OUTPUT FROM WHAT FILE:", enter "REMOTE PROCEDURE".
- 4. Accept the default for "SORT BY: NAME//" by hitting RETURN.
- 5. At "START WITH NAME: FIRST//", enter "DVBA" to start with the first CAPRI RPC name.
- 6. At "GO TO NAME: LAST//", enter "DVBC" to list all of the CAPRI namespace RPCs.
- 7. Accept the default for "WITHIN NAME, SORT BY:"
- 8. At "FIRST PRINT FIELD:", Enter a "?" and then "Y" for "Do you want the entire nn-Entry FIELD list?". The list will be displayed for you to choose from.
- 9. At "FIRST PRINT FIELD:" prompt, enter ".01" for NAME. At each successive "THEN PRINT FIELD:" prompt, enter the field numbers listed here:
 - .02 TAG
 - .03 ROUTINE

- .04 RETURN VALUE TYPE
- .06 INACTIVE
- 1 DESCRIPTION (word-processing)
- 2 INPUT PARAMETER

At "THEN PRINT INPUT PARAMETER SUB-FIELD:" after entering "2", click RETURN to bypass sub-fields.

- 3 RETURN PARAMETER DESCRIPTION
- 10. At the next "THEN PRINT FIELD:", press RETURN to complete the list of desired fields.
- 11. For the heading, answer "Replace" with "REM...", then answer "With" with RETURN to remove a heading, or enter a heading.
- 12. At the "STORE PRINT LOGIC IN TEMPLATE:" select or create a Print Template, or take the default to bypass creating a print template.
- 13. At "DEVICE:", answer "0;80;99999" to display the RPC listing to your screen.

Copy and paste the results into a word processing application for possible cleanup.

This is an example of the dialog:

```
From the VA FileMan menu, select "Print File Entries"
VA FileMan
   VA FileMan Version 22.0
   Enter or Edit File Entries
   Print File Entries
   Search File Entries
   Modify File Attributes
   Inquire to File Entries
   Utility Functions ...
   Data Dictionary Utilities ...
   Transfer Entries
   Other Options ...
Select VA FileMan Option: PRINT FILE ENTRIES
OUTPUT FROM WHAT FILE: PATIENT// REMOTE PROCEDURE (2998 entries)
SORT BY: NAME//
START WITH NAME: FIRST// DVBA
GO TO NAME: LAST// DVBC
  WITHIN NAME, SORT BY:
FIRST PRINT FIELD: ? (enter "?" to view available fields)
 Answer with FIELD NUMBER, or LABEL
 Do you want the entire 14-Entry FIELD List? Y (Yes)
   Choose from:
   .01
           NAME
   .02
           TAG
   .03
           ROUTINE
   .04
           RETURN VALUE TYPE
   .05
           AVAILABILITY
   .06
           INACTIVE
   .07
           CLIENT MANAGER
   .08
           WORD WRAP ON
   .09
           VERSION
   .1
           SUPPRESS RDV USER SETUP
   .11
           APP PROXY ALLOWED
  1
            DESCRIPTION (word-processing)
  2
           INPUT PARAMETER (multiple)
           RETURN PARAMETER DESCRIPTION (word-processing)
FIRST PRINT FIELD: .01 NAME
THEN PRINT FIELD: .02 TAG
THEN PRINT FIELD:
Heading (S/C): REMOTE PROCEDURE LIST Replace REM... With YOUR HEADING
  Replace
   YOUR HEADING
START AT PAGE: 1//
DEVICE: 0;80;9999 UCX/TELNET
YOUR HEADING
                                              MAY 22,2012 11:53 PAGE 1
NAME
                          TAG
DVBA 2507 REQUEST
                          CNP
DVBA CHECK PATCH
                          CHECK
```

13. Fileman

13.1 Installation Procedures and Usage

All VA FileMan documentation is available on the VDL, accessible at the following URL: http://www.va.gov/vdl/application.asp?appid=5

There is also additional documentation regarding other FileMan information i.e. FileMan Tips, etc... is accessible at: http://www.hardhats.org/index.html

Note: Using the Freedom of Information Act this website obtained documentation from the VA for VISTA. In general this site gathers information from multiple sources including the VA website.

13.1.1. Environmental Setup

The <u>VA FileMan V.22 Key and Index Tutorial</u> document contains the environmental setup information at the following URL: http://www.va.gov/vdl/documents/Infrastructure/Fileman/fm22 tutorial.pdf

13.1.2. Installation Guide

Access the <u>VA FileMan Installation Guide</u> at: http://www.va.gov/vdl/documents/Infrastructure/Fileman/fm22_0ig.pdf

13.1.3. **Getting Started**

Access the VA FileMan Getting Started User Manual at: http://www.va.gov/vdl/documents/Infrastructure/Fileman/fm22_0gs.pdf

13.1.4. FileMan Access Codes

The following table is a list of recommended VA FileMan access codes associated with each file contained in the AMIE software.

FILE NUMBER	FILE NAME	DD ACCESS	RD ACCESS	WR ACCESS	DEL ACCESS	LAYGO ACCESS
31	Disability Condition	@	D	@	@	@
396	Form 7131	@	#	#	#	#
396.1	AMIE Site Parameter	@	#	#	@	@
396.2	AMIE Report	@	#	#	#	#
396.3	2507 Request	@	#	#	#	#
396.4	2507 Exam	@	#	#	#	#
396.5	2507 Cancellation Reason	@	#	@	@	@
396.6	AMIE Exam	@	#	@	@	@
396.7	2507 Body System	@	#	@	@	@
396.94	2507 Insufficient Reasons	@	#	@	@	@
396.95	AMIE C&P Exam Tracking	@	#	#	#	#

Note: The code (symbol) "@" in this table is the programmer's access. The other codes are arbitrary, and are determined by the developers during the design phase and assigned as needed to users by the Information Systems (IS) staff in the File Manager Access Code field of the New Person (#200) file.

13.1.5. Advanced User

Access the <u>VA FileMan Advanced User Manual</u> at: http://www.va.gov/vdl/documents/Infrastructure/Fileman/fm22_0um.pdf

13.1.6. Programmer Manual

Access the <u>VA FileMan Programmer Manual</u> at: http://www.va.gov/vdl/documents/Infrastructure/Fileman/fm22_0pm.pdf

13.1.7. **Technical Manual**

Access the VA FileMan Technical Manual at:

http://www.va.gov/vdl/documents/Infrastructure/Fileman/fm22_0tm.pdf

13.1.8. Package-wide Variables

There are no package-wide or special variables in the AMIE software.

13.1.8.1. Key Variables

• PNAM = Patient name

• DFN = Internal ^DPT number

• SSN = Social security number

• CFLOC = Claim folder location

• DCHGDT = Discharge date

ADMDT = Admission date

13.1.8.2. How to Generate Online Documentation

This section describes some of the various methods by which users may secure AMIE technical documentation. Online technical documentation pertaining to the AMIE software, in addition to that which is located in the help prompts may be generated through utilization of several Kernel options. These include XINDEX and VA FileMan List File Attributes. Further information about other utilities which supply online technical documentation may be found in the Kernel Reference Manual.

13.1.8.3. XIndex

This option analyzes the structure of a routine(s) to determine in part if the routine(s) adheres to VistA Programming Standards. The XINDEX output may include the following components: compiles list of errors and warnings, routine listing, local variables, global variables, naked globals, label references, and external references. By running XINDEX for a specified set of routines, the user is afforded the opportunity to discover any deviations from VistA Programming Standards which exist in the selected routine(s) and to see how routines interact with one another, that is, which routines call or are called by other routines.

To run XINDEX for the AMIE software, specify the following namespace at the "routine(s)?>" prompt: DVBA* and DVBC*. AMIE initialization routines which reside in the UCI in which XINDEX is being run, as well as compiled template routines found within the AMIE namespace, should be omitted at the "routine(s)?>" prompt. To omit routines from selection, preface the namespace with a minus sign (-).

13.1.8.3.1. Data Dictionary List File Attributes

This VA FileMan option allows the user to generate documentation pertaining to files and file structure. Utilization of this option via the "Standard" format will yield the following data dictionary information for a specified file(s): file name and description, identifiers, cross-references, files pointed to by the file specified, files which point to the file specified, input templates, print templates, and sort templates. In addition, the following applicable data is supplied for each field in the file: field name, number, title, global location, description, help prompt, cross-reference(s), input transform, date last edited, and notes.

Using the "Global Map" format of this option generates an output which lists all cross-references for the file selected, global location of each field in the file, input templates, print templates, and sort templates.

For a comprehensive listing of AMIE files used by CAPRI, please use the following link (URL) to locate the "Files" section of the AMIE Technical Manual: http://www.va.gov/vdl/application.asp?appid=31

14. Archiving, Purging, and Frequency

CAPRI relies on the AMIE application for any archiving and purging functionality.

Although the AMIE software has no archiving capabilities AMIE's purging capabilities are handled by the DVBA REGIONAL PURGING PROGRAM option deletes all FINALIZED requests which are older than the date set in the AMIE SITE PARAMETER file (#396.1). It should normally be set to run daily on TaskMan, as it takes several minutes to run in programmer mode. In addition to purging the FORM 7131 file (#396), it also purges the AMIE REPORT file (#396.2).

The frequency is based on the amount of 7131 information purged by this program. It is determined by the NUMBER OF DAYS TO KEEP HISTORY parameter set through the Regional File Site Parameter Setup option. It is suggested to keep at least 30 days on file at all times, but no more than 120 days. The NUMBER OF DAYS TO KEEP HISTORY field (#9) of the AMIE SITE PARAMETER file (#396.1) will automatically keep 30 days of report data if no value is in that field.

While the AMIE software uses a very small amount of disk space, it is wise not to let the data accumulate if it is not needed by the hospital.

The DVBA C Purge 2507 option deletes all 2507 requests with the following statuses and that are older than the number of days in the DAYS TO KEEP 2507 HISTORY parameter: Completed, Printed by RO; Completed, Transferred Out; Cancelled by Medical MAS; Cancelled by RO. This option should be scheduled through TaskMan to run nightly. It may be run in programmer mode but will take several minutes. The 2507 EXAM (#396.4) file will be purged in conjunction with the 2507 REQUEST file (#396.3).

15. **Security**

15.1 **Security Management**

VA Directive 10-93-142 prohibits local modifications to VistA software.

15.2 **General Security**

For CAPRI GUI security refer to the following document:

http://www.va.gov/vdl/documents/Financial Admin/CAPRI/dvba 27 p000 um.pdf

This manual includes instructions for setting up CAPRI users, as well as descriptions of all Security Keys used by the CAPRI GUI application.

For AMIE file and VistA-specific security see the CAPRI GUI User Manual at: http://www.va.gov/vdl/application.asp?appid=133

15.2.1. Remote Systems

The AMIE software does not transmit data to any remote systems. For CAPRI interactions with remote systems, refer to the Systems Architecture diagram in Section 3.1.1.

15.2.2. Contingency Planning

Your facility should have a local contingency plan in the event of application problems in a live environment. It should identify the procedure for maintaining functionality provided by the AMIE software as well as the CAPRI GUI application, in the event of system outage.

15.2.3. Interfacing

There are no special interfacing requirements for the AMIE or the CAPRI software.

15.2.4. **Electronic Signatures**

The CAPRI GUI application uses electronic signatures. Use the following link to locate the CAPRI GUI User Manual: http://www.va.gov/vdl/application.asp?appid=133

15.2.5. Security Keys

Take the following steps to get information about the security keys used with the AMIE software.

- 1. VA FileMan Menu
- 2. Print File Entries Option
- 3. Output from what File: SECURITY KEY
- 4. Sort by: Name
- 5. Start with name: DVBA to DVBC
- 6. Within name, sort by: <RET>

7. First print field: Name

8. Then print field: Description

Note: Some keys do not affect the menu operation. This is due to some options having several different functions which are limited in scope by the key. This limitation is done internally by the program being used.

16. CAPRI Troubleshooting and Error Information

Note: In all cases, please print the error message for your local IRM staff.

A majority of CAPRI issues that are initially called into the Service Desk or are created into Remedy tickets are not often CAPRI related issues, but are due to other issues regarding networks and users accesses/permissions, etc... Those few CAPRI issues that are identified as a CAPRI issue are forwarded onto the CAPRI Team. The team works to replicate and identify the issue, then to develop solutions or workarounds to correct or eliminate the issue. Some of these issues result in identification of a CAPRI defect or an issue that may become a future CAPRI enhancement. These issues are often unique and not reported in any significant numbers. The CAPRI Team forwards these specific issues onto the VA who will determine if the issue(s) is something that should be recognized as a defect or a possible CAPRI enhancement scheduled for one of the next CAPRI patch installation deployment.

The remainder of this section includes general CAPRI troubleshooting and error information that is located in the <u>CAPRI GUI User Manual</u> at the following URL: http://www.va.gov/vdl/application.asp?appid=133

Select the latest version of the document; refer to the section "Troubleshooting and Error Messages".

16.1 CAPRI Not Installed in VistA

The user receives the message in the following screenshot if the VHA Medical Center has not loaded the VHA half of the CAPRI software. The user should contact local IRM staff after receiving this message.



16.2 CAPRI GUI Option Not Assigned to User in VistA

The user receives the message in the following screenshot if the VHA medical center has not assigned the CAPRI option to RO users. The user must contact local IRM staff upon receiving this message.




16.3 VistA Server Down

The user receives the message in the following screenshot, or a similar one such as WSAETIMEDOUT, when there are performance issues in the VA Wide Area Network (WAN), if a server is down, or if a server was not restarted after being down. When this happens, AMIE II may or may not connect, depending on the exact problem. The user should test the AMIE II connection.



16.4 VistA Limits Ability to See Patient Records

The user receives the message in the following screenshot if the medical facility made local permission modifications in VistA that prohibit users from seeing the contents of patient records.




16.5 Network Problems

The user receives the message in the following screenshot if the connection to the medical facility is lost unexpectedly. The user should try to connect to the medical facility again.



16.6 Institution File in VistA has Been Locally Modified

The user may receive the message in the following screenshot when requesting exams, requesting 7131s, or entering new patients if the VHA medical facility has an incomplete or incorrect Regional Office list in their system.



16.7 Too Many Invalid Attempts at Access Code / Verify Code

The user receives the message in the following screenshot if the user attempted to log on and entered the wrong Access Code / Verify Code combination three or more times.



16.8 Multiple Sign-Ons

The user may receive the message in the following screenshot if the user did not log out of CAPRI correctly or if the session was unexpectedly disconnected.



16.9 **General Error Message**

The user may receive the message in the following screenshot for a number of reasons. Upon receiving this message, the user should cancel the current task, close CAPRI, and sign on again. If the user receives this error message again, local IRM staff should be contacted for assistance.



Appendix A - CAPRI Remote Procedure Calls for MUMPS

The DVBA CAPRI GUI menu option contains all the CAPRI RPCs.

Name: DVBA CAPRI GUI Menu Text: Capri GUI (Broker) Type: Broker (Client/Server)

Package: AUTOMATED MED INFO EXCHANGE

Description: This is the "B" type option used by CAPRI GUI client application. It contains all the RPCs used by the CAPRI GUI

application.

The table that starts on the next page shows a correlation between the CAPRI's MUMPS RPCs and DELPI's RPCs associated within supporting the CAPRI application.

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DG SENSITI VE RECORD ACCESS	PTSEC	DGSEC4	ARRAY	This Remote Procedure Call (RPC) will: - Verify user is not accessing his/her own Patient file record if the Restrict Patient Record Access (#1201) field in the MAS parameters (#43) file is set to yes and the user does not hold the DG RECORD ACCESS security key. If parameter set to yes and user is not a key holder, a social security number must be defined in the New Person file for the user to access any Patient file		RESULT(1) = -1-RPC/API failed Required variable not defined 0-No display/action required Not an employee, not sensitive or not accessing own Patient record 1-Display warning message Sensitive - inpatient or a DG SENSITIVITY key holder or Employee and DG SECURITY OFFICER key holder 2-Display warning message, require OK to continue and call DG SENSITIVE RECORD BULLETIN RPC to update DG Security Log file and generate Sensitive Record Access mail message. Sensitive - not an inpatient and not a key holder or Employee/not a DG SECURITY OFFICER key holder 3-Access to record denied Accessing own Patient file record 4-Access to Patient file (#2) records denied SSN not definedRESULT(2-n) = error message or warning/Privacy	DG SENSITI VE RECORD ACCESS'	patientlistr estricted	RPCBroker1	FMCvrListBox1 Pt.GetselectedR ecord.IEN or FMCvrListBox2 Pt.GetselectedR ecord.IEN or FMCvrListBox3 Pt.GetselectedR ecord.IEN PType := literal; for all params FMListBox1.Ge tSelectedRecord .IEN; PType := literal;

MUMPS						DELPHI			
TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
NOTICE	DGSEC4	SINGLE VALUE	record. - Determine if user accessing a sensitive record or an employee's record This Remote Procedure Call (RPC) will add an entry to the DG SECURITY LOG (#38.1) file and/or generate the sensitive record access bulletin depending on the value in ACTION input parameter. If ACTION parameter not defined, defaults	(Multiple)	Act message. Error and warning messages will begin in RESULT(2) array. The Privacy Act message is the longest message and will utilize RESULT(2)- RESULT(8). If RESULT(1)=1, the DG Security Log file is updated. If RESULT(1)=2, the user must acknowledge they want to access the restricted record and the application must call the DG SENSITIVE RECORD BULLETIN RPC to update the DG Security Log file and generate the Sensitive Record Access mail message. RESULT= 1 - successfully added entry and/or generated sensitive record access bulletin 0 - unsuccessful	DG SENSITIV E RECORD BULLETI N'	patientlistre stricted	RPCBroker1	PatientIEN PType := literal; 'DVBA CAPRI GUI^Capri GUI (Broker)' PType := literal; ' ' PType := literal;
			Security Log file and generate Sensitive Record Access mail						
			TAG ROUTINE TYPE NOTICE DGSEC4 SINGLE	TAG ROUTINE VALUE TYPE record Determine if user accessing a sensitive record or an employee's record NOTICE DGSEC4 SINGLE VALUE This Remote Procedure Call (RPC) will add an entry to the DG SECURITY LOG (#38.1) file and/or generate the sensitive record access bulletin depending on the value in ACTION input parameter. If ACTION parameter not defined, defaults to update DG Security Log file and generate Sensitive Record	NOTICE DGSEC4 SINGLE VALUE NOTICE DGSEC4 SINGLE VALUE Trecord. - Determine if user accessing a sensitive record or an employee's record RPC) will add an entry to the DG SECURITY LOG (#38.1) file and/or generate the sensitive record access bulletin depending on the value in ACTION input parameter. If ACTION parameter not defined, defaults to update DG Security Log file and generate Sensitive Record	TAG ROUTINE VALUE TYPE Paccord	TAG ROUTINE VALUE TYPE Tecord Determine if user accessing a sensitive record or an employee's record - This Remote VALUE VALUE NOTICE DGSEC4 SINGLE VALUE This Remote Procedure Call (RPC) will add an entry to the DG SECURITY LOG (#38.1) file and/or generate the sensitive record access bulletin depending on the value in ACTION input parameter. If ACTION parameter not defined, defaults to update DG Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file and generate Sensitive Record Security Log file Sensitive Record Security Log file Sensitive Record Security Log file Sensitive Record Sensitive Record Security Log file Sensitive Record Sensitive Record Security Log file Sensitive Record Sensitive	TAG ROUTINE RETURN VALUE TYPE DESCRIPTION DESCRIPTION PARAMETER (Multiple) record Determine if user accessing a sensitive record or an employee's record an employee's record NOTICE DGSEC4 NOTICE DGSEC4 SINGLE VALUE NOTICE DGSEC4 SINGLE VALUE NOTICE DGSEC4 SINGLE VALUE NOTICE DGSEC4 SINGLE VALUE NOTICE VALUE NOTICE DGSEC4 SINGLE VALUE NOTICE DGSEC4 SINGLE VALUE NOTICE VALUE NOTICE DGSEC4 SINGLE VALUE NOTICE DGSEC4 SINGLE VALUE NOTICE VALUE NOTICE VALUE NOTICE VALUE NOTICE DGSEC4 SINGLE VALUE This Remote VALUE Procedure Call (RPC) will add an entry to the DG SECURITY LOG (#38.1) file and/or generate dessnitive record access bulletin depending on the value in ACTION input parameter. If ACTION parameter not defined, defaults to update DG Security Log file and generate Sensitive Record Security Log file and generate was patientlistre stricted explain and generate the sensitive record access bulletin depending on the value in ACTION parameter not defined, defaults to update DG Security Log file and generate Sensitive Record Security Log file and generate the Sensitive Record Access mail message. RESULT— 1 - successfully added entry and/or generated sensitive record access bulletin depending on the value in ACTION parameter not defined, defaults to update DG Security Log file and generate Sensitive Record Security Log file and generate the Sensitive Record Access mail message is the longest message and will utilize RESULT(1)=1, the DG Security Log file and generate the Sensitive Record Access mail message is the longest message and will utilize RESULT(2) array. The Privacy Act message is the longest message and will utilize RESULT(2) array. The Privacy Act message is the longest message is the longest message and will utilize RESULT(2) array. The Privacy Act message is the longest message and will utilize RESULT(2) array. The Privacy Act message and will utilize the long	ROUTINE Continue Continue

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DVBA CHECK PATCH	CHEC	DVBAB1 B	SINGLE VALUE	This RPC is a wrapper for the supported \$\$PATCH^XPDU TL API to determine whether a given patch is installed or not "1^Patch Is Installed" is returned on success; otherwise "0^Patch Is Not Installed" is returned.	DVBPAT CH	Returns "1^Patch Is Installed" on success; otherwise returns "0^Patch Is Not Installed".	DVBA CHECK PATCH'	CAPRISup port	RPCBroker1	No Params
DVBA FIX MOVED MESSAGE	SETML MS	DVBAB1	SINGLE VALUE	Using Delphi Fileman controls to manage mail messages does not provide adequate control over new global nodes. This routine allows a newly created message to be assigned to a specific mailbox and IEN within the mailbox instead of sequentially, which is the default behavior. Used during message termination, deletion, or moving a message to a new box.	param1 param2		DVBA FIX MOVED MESSAGE	MailMessa ge	RPCBroker1	tempIEN PType:= literal; '.5'; // .5= Wastebasket PType := literal

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DVBAB ATE LIST	LST	DVBABA T	GLOBAL ARRAY	Return list of Audit Trail Entries in 395.98	ZIEN ZCNT	Y(0) is NXT^CNT; CNT=count fetched, NXT=IEN to begin NEXT fetch (0 if No More) Y(1) thru Y(CNT) are "^" piece separated as follows: Piece - Description 1 - USER NAME 2 - PATIENT NAME 3 - PATIENT ICN 4 - PATIENT SSN 5 - REMOTE SITE NAME 6 - DATE/TIME ACCESSED 7 - SENSITIVE RECORD? 8 - CLAIM NUMBER 9 - DIVISION TEXT	DVBAB ATE LIST'	Audit	RPCBroker1	No Params
DVBAB ATE QUANTIT Y	NUM	DVBABA T	SINGLE VALUE	Get number of entries in Audit Trail.			DVBAB ATE QUANTIT Y'	Audit	RPCBroker1	No Params
DVBAB CHECK CREDENT IALS	CHKCR ED	DVBAB1	SINGLE VALUE	Verifies the user has been granted access to AMIE II/CAPRI			DVBAB CHECK CREDENT IALS' 'DVBAB CHECK CREDENT IALS'	viewaddres s viewexam	RPCBroker1 RPCBroker1	No Params No Params
DVBAB DATETIM E	DTTM	DVBAB1	SINGLE VALUE	Returns the current date/time from VistA			DVBAB DATETIM E' 'DVBAB DATETIM E'	REPORTS telnet	RPCBroker1	No Parms No Params

				MUMPS		DELPHI				
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DVBAB DOD INFO	INFOM SG	DVBABD OD	SINGLE VALUE	This remote procedure call returns a message to be displayed in CAPRI. The RPC is designed specifically for the FHIE VistA server not the local VAMC facilities. It is distributed nationally with the CAPRI application to keep the remote procedures and the DVBA CAPRI GUI option consistent on all systems using CAPRI. Please do not use.			DVBAB DOD INFO	Main	RPCBrokerD OD	No Params

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DVBAB DOD REPORT	SENDR PT	DVBABD OD	GLOBAL ARRAY	This remote procedure call returns a DOD report from the FHIE framework. The RPC is designed specifically for the FHIE VistA server not the local VAMC facilities. It is distributed nationally with the CAPRI application to keep the remote procedures and the DVBA CAPRI GUI option consistent on all systems using CAPRI. Please do not use. Input: IEN = Patient's DFN DATATYPE = Type of data being requested BEGDATE = Beginning search date ENDDATE = Ending search date ORMAX = Max number of entries for report	IEN DATATY PE BEGDAT E ENDDAT E ORMAX		DVBAB DOD REPORT'	Main	RPCBrokerD OD	No Params

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DVBAB DOD REPORT TYPES	RPTTY PS	DVBABD OD	ARRAY	This remote procedure call returns a list of available report types. The RPC is designed specifically for the FHIE VistA server not the local VAMC facilities. It is distributed nationally with the CAPRI application to keep the remote procedures and the DVBA CAPRI GUI option consistent on all systems using CAPRI. Please do not use.			DVBAB DOD REPORT TYPES'	Main	RPCBrokerD OD	No Params
DVBAB EXAMS BY DATE	EXAMB YDT	DVBABE BD	GLOBAL ARRAY	Provides a report by date range of all AMIE/CAPRI exam requests.	BEGDT ENDT		DVBAB EXAMS BY DATE'	REPORTS	RPCBroker1	Value := FMToDateConver t(FormatDateTime ('mm/dd/yyyy', DateTimePicker1. DateTime)); PType := literal Value := FMToDateConver t(FormatDateTime ('mm/dd/yyyy', DateTimePicker2. DateTime)) PType := literal

				MUMPS			DELPHI				
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter	
DVBAB FETCH 1U4N	U1N4	DVBABF RM	GLOBAL ARRAY	Retrieve the 1u4n field for the list of patient IENS provided as the only argument. Each IEN will be sent back with field .0905 appended after a caret.	ARR	List of Patient IENs in piece 1,followed by 1U4N in piece 2	DVBAB FETCH 1U4N'	unsigned	RPCBroker1	Mult[IntToStr(i + 1)] := FMListBoxIPR1. GetSelectedRecor d.IEN; PType := list;	
DVBAB FIND DFN BY ICN	ICN	DVBABD OD	GLOBAL ARRAY	This remote procedure call returns the patient's DFN associated with the ICN passed to the RPC. The DFN is the internal entry number in the Patient (#2) file. The RPC is designed specifically for the FHIE VistA server not the local VAMC facilities. It is distributed nationally with the CAPRI application to keep the remote procedures and the DVBA CAPRI GUI option consistent on all systems using CAPRI. Please do not use.	ICN		DVBAB FIND DFN BY ICN'	Main	RPCBrokerD OD	No Params	

				MUMPS			DELPHI				
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter	
DVBAB FIND DUPS	DUP	DVBAB8 4	GLOBAL ARRAY	Find potential duplicates within the PATIENT File (#2) At least one of NAM, DOB, or SSN must be passed Possible matches are "better" when more than one of these is passed	NAM DOB SSN	BYREF - Passed by reference, will contain name of a TMP Global housing the results Subscript 0: - 1^ERROR_MESSAGE (in the event of an error) OR Subscript 0: Number of potential matches found (if no errors) Subscript 1-K: Patient's matching ALL 3 of NAM, DOB, SSN have a weighting of 3 (see Note) Subscript K+1-L: Patient's matching ANY 2 of NAM, DOB, SSN have a weighting of 2 (see Note) Subscript L+1-M: Patient's matching ONLY 1 of NAM, DOB, SSN have a weighting of 1 (see Note) Note) ^TMP(1-M) = DFN^ZERO_NODE where DFN is the Patient IEN ZERO_NODE is the data from ^ DPT(DFN,0) NOTE: Potential matches within a weighting (if any) will be sorted by Patient Name	DVBAB FIND DUPS' 'DVBAB FIND DUPS'	EnterPt	RPCBroker1	nam := LastName.text + ',' + FirstName.text; nam := LastName.text + ',' + FirstName.text;	

				MUMPS			DELPHI				
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter	
DVBAB FIND EXAMS	FINDEX AM	DVBAB1	ARRAY	Lists all of the patient's AMIE II C&P exam requests whether complete, new or	INPUT1		DVBAB FIND EXAMS'	ManageRep orts	RPCBroker1	FMExamRequestL istbox.GetSelected Record.IEN PType := literal;	
				pending.			'DVBAB FIND EXAMS'	loadexamco mments	RPCBroker1	FMExamRequestL istbox.GetSelected Record.IEN PType := literal;	
							'DVBAB FIND EXAMS'	newexam	RPCBroker1	FMExamRequestL istbox.GetSelected Record.IEN PType := literal;	
							'DVBAB FIND EXAMS'	tiusign	RPCBroker1	Value := FMExamRequestL istbox.GetSelected Record.IEN; PType := literal;	
							'DVBAB FIND EXAMS'	uncosigned utility	RPCBroker1	Value := FMExamRequestL istbox.GetSelected Record.IEN; PType := literal;	
							'DVBAB FIND EXAMS'	viewexam	RPCBroker1	frmMain.FMExam RequestListbox.G etSelectedRecord.I EN; PType := literal; PType := literal;	

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DVBAB FORM DATA BACKUP	BACKU P	DVBABF RM	SINGLE VALUE	Makes a backup copy of a CAPRI template in case of data loss. The backup is restored through the CAPRI GUI.	DVBIEN LISTBOX TEXT		DVBAB FORM DATA BACKUP'	PNCSMain	RPCBroker1	Piece(xFMEdit2.I ENS, ',', 1); PType := literal; or 'MANAGE TEMPLATES restore-point' PType := literal; or 'Template CLOSED / ' + VersionUser; PType := literal; or 'TEMPLATE RESTORE restore-point'; PType := literal; or SaveName + ' / ' + VersionUser; PType := literal; or frmMain.RPCBro ker1.Param[2].Val ue + ' / ' + AuthorName;
DVBAB FORM DATA BACKUP DELETE	DELET E	DVBABF RM	SINGLE VALUE	String returned is "^" piece separated, as follows: Piece Item 1	IEN		DVBAB FORM DATA BACKUP DELETE';	tiusign	RPCBroker1	Value := Piece(PNCSForm. xFMEdit2.IENS, ',', 1); PType := literal;
DVBAB FORM DATA BACKUP RESTORE	RESTO RE	DVBABF RM	SINGLE VALUE		IEN SIEN		DVBAB FORM DATA BACKUP RESTORE'	PNCSMain	RPCBroker1	Piece(xFMEdit2.I ENS, ',', 1); PType := literal; IntToStr(WhichVe rsionToLoad); PType := literal;

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DVBAB INCREASE EXAM COUNT	INCEXA M	DVBAB 1	SINGLE VALUE	Used to record the number of exams pending for a specified patient.			DVBAB INCREAS E EXAM COUNT'	viewexam	RPCBroker1	No Params
							'DVBAB INCREAS E EXAM COUNT'	newexam	RPCBroker1	No Params
DVBAB LOAD FORM	LOAD	DVBAB FRM	GLOBAL ARRAY	Set DVBTPSV to 3 for a regular load, 9 for a load from the redundant save field and 10 for the cancellation field. If no value is set, the routine assumes a value of 3.	DVBIEN DVBTPS V		DVBAB LOAD FORM'	penShow	RPCBroker1	Value := frmMain.Piece(F MGetsIPRFile.IE NS, ',', 1); PType := literal;
DVBAB MAIL FIX MOVED MESSAGE	SETMLM SG	DVBAB XMB	SINGLE VALUE	Fixes global due to Delphi functionality issues.	PARAM1 PARAM2		DVBAB MAIL FIX MOVED MESSAGE	MailMan	RPCBroker1	tempIEN PType := literal; '.5' PType := literal;
							'DVBAB MAIL FIX MOVED MESSAGE	MailMessa ge	RPCBroker1	tempIEN PType := literal; '.5'; // .5= Wastebasket PType := literal;

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DVBAB MPI ASSIGN ICN	MPI	DVBCPA TA	SINGLE VALUE	This call should be made after a new patient is added into the patient file. It will call	DFN		DVBAB MPI ASSIGN ICN'	EnterPt	RPCBroker1	PatientIEN, ',', 1
				the MPI to assign an ICN. If no ICN can be obtained after 30 seconds, a local ICN will be			'DVBAB MPI ASSIGN ICN'	entersimple	RPCBroker1	PatientIEN, ',', 1
				assigned and the local ICN flag set.			'DVBAB MPI ASSIGN ICN'	enterptsimp le140	RPCBroker1	Value := Piece(PatientIEN, ',', 1); PType := literal;
							'DVBAB MPI ASSIGN ICN'	enterpt140	RPCBroker1	Value := Piece(PatientIEN, ',', 1); PType := literal;
DVBAB NOTE TITLES	NOTET L	DVBABT IU	ARRAY	Returns list of note titles from TIU in format name+" "+type+" "+status			'DVBAB NOTE TITLES'	PNCSMain	RPCBroker1	No Params
DVBAB ORIGINAL PROCESSI NG DATE	XDA	DVBAB8 9	GLOBAL ARRAY		DFN		'DVBAB ORIGINAL PROCESSI NG DATE'	REPORTS	RPCBroker1	Value := PatientIEN; PType := literal
DVBAB PENDING C&P REPORT	STRT	DVBAB6	GLOBAL ARRAY	Generates a report containing the pending C&P exam requests.	DVBCSO RT RSTAT ERDAYS OLDAYS ADIVNU M ELTYP		'DVBAB PENDING C&P REPORT'	REPORTS	RPCBroker1	Mulitpule parms are set depending on evaluation conditions, however all Values are of type Literal.

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DVBAB REPORT ADMISSIO N INQUIRY	ENBRO KER	DVBAA DRP	ARRAY	Returns display text indicating when the report was last run			DVBAB REPORT ADMISSIO N INQUIRY'	REPORTS	RPCBroker1	No Params
DVBAB REPORT EXAM CHKLIST	STRT	DVBAB4	ARRAY	Generates an exam worksheet.			'DVBAB REPORT EXAM CHKLIST'	REPORTS	RPCBroker1	No Params
DVBAB REPORT NEW NOTICES DC	ENBRO KER	DVBADS NT	GLOBAL ARRAY	Broker-enabled version of option DVBA NOTICE/DISCH ARGE PRINT, Print New Notices of Discharge.			'DVBAB REPORT NEW NOTICES DC'	REPORTS	RPCBroker1	No Params
DVBAB REPORT PENDING7 131	STRT	DVBAB5 7	GLOBAL ARRAY	Generates a list of pending 7131 requests.	SELDIV DIV		'DVBAB REPORT PENDING 7131'	REPORTS	RPCBroker1	Value := " PType := literal; Note: the Value param is set base on multipule conditions. See code for conditions.
DVBAB REPORT SPECIAL	SPECRP T	DVBASP D2	GLOBAL ARRAY	Generates a Special Report for Pension and Advisory & Assistance (A&A), in either standard or delimited format, for the specified parameters.	DCTYPE S BDATE EDATE RONUM REP DVBADL MTR		'DVBAB REPORT SPECIAL'	specialrepo rt;	RPCBroker1	This RPC has 6 possible parms that can be set base on evaluation conditions. All of the Parms have a Type set to Literal.

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DVBAB REPORTS	START	DVBAB8 2	GLOBAL ARRAY	CAPRI REGIONAL OFFICE 21 DAY CERTIFICATE PRINTING	REPORT TYPE REPORT STRING		'DVBAB REPORTS'	REPORTS	RPCBroker1	Value := '1'; // 21 Day Cert Print PType := literal; Value := " PType := literal;
							'DVBAB REPORTS'	REPORTS	RPCBroker1	Has two Parms with the type equal to literal. This RPC is called 4 times depending on which report is to be executed.
							'DVBAB REPORTS'	REPORTS	RPCBroker1	Value := '3'; // C&P FINAL (MANUAL) PType := literal; Value := "; // PType := literal;

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DVBAB SEND MSG	MSG	DVBAB1	SINGLE VALUE	Used to generate e-mail messages for specific CAPRI actions, such as changing a C&P exam request.	VAL1 VAL2 VAL3 VAL4 VAL5		DVBAB SEND MSG'	EnterPt	RPCBroker1	AuthorIEN 'CAPRI: New C&P Veteran Added to Patient File' MailManBuffer.Li nes 'DVBA C NEW C&P VETERAN
							'DVBAB SEND MSG'	entersimple	RPCBroker1	AuthorIEN 'CAPRI: New C&P Veteran Added to Patient File' MailManBuffer.Li nes[i] 'DVBA C NEW C&P VETERAN'
							'DVBAB SEND MSG'	viewexam	RPCBroker1	Value := AuthorIEN; //DUZ Of Author of Note PType := literal; Value := 'CAPRI: Cancellation of 2507 Exams'; //Max 45 Chars PType := literal; PType := list; Mult[IntToStr(i + 1)] := frmMain.MailMan Buffer.Lines[i]; Value := 'DVBA C 2507 CANCELLATIO N'; //Mail Group Name PType := literal;

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DVBAB SET DIVISION	DUZ2	DVBAB8 4	SINGLE VALUE	Set the Division	NUM	Return O^ERR_MESSAGE (upon failure) IEN^INSTITUTION_NAME (upon success)	DVBAB SET DIVISION'	REPORTS	RPCBroker1	Value := RemoteUserDivisi onNumber; PType := literal;
DVBAB TEMPLAT E DEFINITI ON	DEFINE	DVBABF RM	GLOBAL ARRAY	C&P Worksheet Templates are made of 3 files: a form definition, a code definition, and a script definition. Set DVBIEN to the internal entry number of the form Set DVBTYPE to the definition you want: 1= Form, 2=Script, 3=Report	DVBIEN DVBTYP E		DVBAB TEMPLAT E DEFINITI ON' 'DVBAB TEMPLAT E DEFINITI ON' 'DVBAB TEMPLAT E DEFINITI E DEFINITI ON'	pcnShow printtempla te	RPCBroker1 RPCBroker1	Value := formToMergeIEN; PType := literal; Value := '1'; PType := literal; Value := formToMergeIEN; PType := literal; Value := '1'; PType := literal;

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
DVBAB TEMPLAT E DEFINITI ON UPDT	UPDAT E	DVBABF RM	SINGLE VALUE	C&P Worksheet Templates are made of 3 files: a form definition, a code definition, and a script definition. Set DVBIEN to the internal entry number of the form Set DVBTYPE to the definition you want: 1= Form, 2=Script, 3=Report Set DVBLINES to the lines to be saved Set DVBLINEN to the starting line # in the global. This allows for forms to be sent in chunks.	DVBIEN DVBTYP E DVBLIN ES DVLINE COUNT DVBLIN EN		DVBAB TEMPLAT E DEFINITI ON UPDT'	managetem platedefs	RPCBroker1	tempIEN PType := literal; '1' PType := literal;
DVBAB TEMPLAT E REPORT FULL	RPTST AT	DVBAB8 5	GLOBAL ARRAY	Returns report of exam templates, including current status	STRTDT ENDDT		DVBAB TEMPLAT E REPORT FULL';	REPORTS	RPCBroker1	Value := FMToDateConver t(FormatDateTime ('mm/dd/yyyy', DateTimePicker3. DateTime)); PType := literal; Value := FMToDateConver t(FormatDateTime ('mm/dd/yyyy', DateTimePicker4. DateTime)); PType := literal;

				MUMPS					DELPHI	
1	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
ZIII	P2CIT Y	DVBABA DR	ARRAY	The remote procedure returns a list containing city, county, and state for a given ZIP code. Results format: Result(0)=ResultC ount_"^"_ErrorMs g Result(1n)=City"^"_County"^"_S tate The remote procedure returns a list containing city, county, and state for a given ZIP code. Results format: Result(0)=ResultC ount"^"_ErrorMs g Result(1n)=City"^"_County_"^"_S tate The remote procedure returns a list containing city, county, and state for a given ZIP code. ResultC ount"^"_ErrorMs g Result(1n)=City"^"_County_"^"_S tate The remote procedure returns a list containing city, county, and state for a given ZIP code. Results format: Result(0)=ResultC ount"^"_ErrorMs g	DVBZIP	ZIP code value in ZIP+4 format. RETURN PARAMETER DESCRIPTION: RESULT(0)=ResultCount_"^"_Err orMsg RESULT(1)=City_"^"_County_"^" _State RESULT(n)=City_"^"_County_"^" _State	DVBAB ZIP2CITY 'DVBAB ZIP2CITY'	EnterPt entersimple	RPCBroker1 RPCBroker1	Zipcode as text aZipCode
				"^"_County_"^"_S tate The remote procedure returns a list containing city, county, and state for a given ZIP code. Results format: Result(0)=ResultC ount_"^"_ErrorMs g Result(1n)=City_ "^"_County_"^"_S tate The remote procedure returns a list containing city, county, and state for a given ZIP code. Results format: Result(0)=ResultC ount_"^"_ErrorMs g						

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
ORPRF GETFLG	GETFL G	ORPRF	ARRAY				ORPRF GETFLG'	FormPtRec ordFlags	RPCBroker1	labelPatientDFN.C aption PType := literal; Piece(ORListBox Flags.Items[ORListBoxFlags.ItemInd ex], '^', 1); PType := literal;
ORPRF HASFLG	HASFL G	ORPRF	ARRAY				'ORPRF HASFLG'	patientlist	RPCBroker1	PatientDFN PType := literal;
ORPRF TRIGGER POPUP	TRIGRP OP	ORPRF	SINGLE VALUE	Returns 1 if popup flag display should be triggered for given patient upon patient selection. If not, returns 0. Does not require clean-up after calling it since it does not set arrays or globals.		Returns 1 if popup flag display should be triggered for given patient upon patient selection. If not, returns 0.	'ORPRF TRIGGER POPUP'	patientlist	RPCBroker1	frmMain.Piece(F MCvrGets1Pt.IEN S, ',', 1); PType := literal;
ORWCIRN FACLIST	FACLIS T	ORWCIR N	ARRAY	Returns a list of the remote VA facilities at which the selected patient has been seen.			ORWCIRN FACLIST' 'ORWCIR N FACLIST'	patientlist patientlistre stricted	RPCBroker1	frmMain.Piece(F MCvrGets1Pt.IEN S, ',', 1); PType := literal; FMListBox1.GetS electedRecord.IEN ; PType := literal;

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
ORWLRR CHART	CHART	ORWLR R	GLOBAL ARRAY				'ORWLRR CHART'	frmLabGra ph	RPCBroker1	PatientIEN; // Patient IEN PType := literal; FMToDateConver t(FormatDateTime ('mm/dd/yyyy', DateTimePicker2. Date)) + '.2359'; //Stop Date PType := literal; FMToDateConver t(FormatDateTime ('mm/dd/yyyy', DateTimePicker1. Date)); //Start Date PType := literal; '0'; // 0 for "All Specimens" PType := literal; ''
ORWORB FASTUSE R	FASTU SER	ORWOR B	GLOBAL ARRAY	Function returns notifications for current user.			'ORWORB FASTUSE R'	tiucosignat ure	RPCBroker1	No Params
ORWPT ADMITLS T	ADMIT LST	ORWPT	ARRAY	Returns a list of admissions for a patient (for visit selection).			'ORWPT ADMITLS T'	PNCSMain	RPCBroker1	xPatientIENS.Capt ion PType := literal;

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
ORWU DT	DT	ORWU	SINGLE VALUE	Returns date in internal VA FileMan format.			ORWU DT'	MailMan	RPCBroker1	NOW' PType := literal;
				rnewan format.			'ORWU DT'	tiusign	RPCBroker1	Value := 'NOW' PType := literal;
							'ORWU DT'	EditPatient Lists	RPCBroker1	'NOW'
							'ORWU DT'	EnterPt	RPCBroker1	'NOW'
							'ORWU DT'	entersimple	RPCBroker1	'NOW'
							'ORWU DT'	ManageRep orts	RPCBroker1	'NOW' PType := literal;
							'ORWU DT'	managetem platedefs	RPCBroker1	'NOW' PType := literal;
							'ORWU DT'	PNCSMain	RPCBroker1	'NOW' PType := literal;
							'ORWU DT'	remoteusers iteseditor	RPCBroker1	Value := 'NOW'; PType := literal;
							'ORWU DT'	tiucosignat ure	RPCBroker1	Value := 'NOW'; PType := literal;
							'ORWU DT'	uncosigned utility	RPCBroker1	Value := 'NOW'; PType := literal;
							'ORWU DT'	viewexam	RPCBroker1	Value := 'NOW'; PType := literal;
ORWU VALIDSIG	VALIDS IG	ORWU	SINGLE VALUE	Validates a broker encrypted electronic			'ORWU VALIDSIG	tiusign	RPCBroker1	Value := encrypt(Edit3.Text);
				signature.						PType := literal;

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
TIU CREATE ADDEND UM RECORD	MAKEA DD	TIUSRVP	SINGLE VALUE	This Remote Procedure allows the creation of addenda to TIU Documents.		This is the record number of the resulting addendum. NOTE: If no addendum record may be created, then the return variable will look as follows: "-1^Could not create addendum."	'TIU CREATE ADDEND UM RECORD'	tiucosignat ure	RPCBroker1	Value := CoSigTIUNoteIE N; PType := literal; Mult['1202'] := authorIEN; Mult['1301'] := dttm PType := list; Value := '1'; PType := literal;

				MUMPS					DELPHI	
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter
TIU CREATE RECORD	MAKE	TIUSRVP	SINGLE VALUE	This remote procedure allows the creation of TIU DOCUMENT records.		If the call is successful, this will be the record number (IEN) of the resulting entry in the TIU DOCUMENT FILE (#8925). In the event of a filing error, the first "^"-piece will be zero, and the second "^"-piece of this scalar return variable will be a textual message describing the nature of the error (e.g., 0^Invalid TITLE Selected.").	'TIU CREATE RECORD'	tiusign	RPCBroker1	Value := PNCSform.xPatie ntIENS.Caption; // Patient PType := literal; Value := aTitleIEN; // Title PType := literal; Value := "; // VDT PType := literal; Value := "; // VDT PType := literal; Value := "; // VLOC PType := literal; Value := "; // VisitIDIEN; //VSIT PType := literal; Mult['1202'] := AuthorIEN; Mult['1301'] := Piece(aVisitIDIEN , ';', 2); // Reference Date Mult['1205'] := Piece(aVisitIDIEN , ';', 1); // Location Mult['1208'] := FMEdit16.Text; // Cosigner Mult['1701'] := "; //Subject PType := list; Value := aVisitIDIEN; // Visit Location; Date/Time; Service category (Optional) PType := literal; .Value := '1'; //Suppress? PType := literal;

	MUMPS							DELPHI				
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter		
TIU DELETE RECORD	DELET E	TIUSRVP	SINGLE VALUE	Deletes TIU Document recordsEvaluates authorization.		Returns error message with ERR=1^Explanation text if the user is NOT authorized to delete the named record (e.g., it's his, but signed; or it's not his, and he better keep his paws off it).	'TIU DELETE RECORD'	tiusign	RPCBroker1	Value := aTIUNoteIEN; PType := literal; Value := Encrypt(aSignatur e); PType := literal;		
TIU GET ALERT INFO	GETAL RT	TIUSRVP	SINGLE VALUE	Given a TIU XQAID, return the patient anddocument type for the item being alerted.		TIUDA^DFN^gui tab indicator where TIUDA is the document IEN in ^TIU(8925 DFN is the patient IEN gui tab indicator is an arbitrarily set constant based on the document type.	'TIU GET ALERT INFO'	tiucosignat ure	RPCBroker1	Value := frmMain.Piece(O RListBox1.Items[ORListBox1.ItemI ndex], '^, 8); PType := literal;		
TIU GET RECORD TEXT	TGET	TIUSRV R1	GLOBAL ARRAY	This RPC will get the textual portion of a TIU Document Record.			TIU GET RECORD TEXT'	tiusign	RPCBroker1	Value := aTIUNoteIEN; PType := literal;		
				Document Record.			'TIU GET RECORD TEXT'	uncosigned utility	RPCBroker1	Value := TIUNoteIEN; //TIU Document number PType := literal;		
							'TIU GET RECORD TEXT'	tiucosignat ure	RPCBroker1	Value := frmMain.Piece(fr mMain.Piece(frm Main.Piece(ORLis tBox1.Items[ORLi stBox1.ItemIndex], '\', 8), ';', 1), 'U', 2); PType := literal;		
					***************************************		'TIU GET RECORD TEXT'	tiudisplayu nit	RPCBroker1	Value := editTIUDocument Number.text; PType := literal; No Params		

	MUMPS								DELPHI				
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter			
TIU LOAD BOILERPL ATE TEXT	BLRSHELL	TIUSRVD	GLOBAL ARRAY	This RPC will load the boilerplate text associated with the selected title, and execute the methods for any objects embedded in the boilerplate text.			'TIU LOAD BOILERPL ATE TEXT'	PNCSMain	RPCBroker1	Copy(PNCSForm. xFMPNTitles.Item s[xFMPNTitles.Ite mIndex], Pos(' IEN#', PNCSForm.xFMP NTitles.ItemIn dex]) + 6, 99); PType := literal; xPatientIENS.Capt ion; {Patient IEN} PType := literal;			
TIU REQUIRES COSIGNA TURE	REQCOS	TIUSRVA	SINGLE VALUE	This Boolean RPC simply evaluates whether the current user requires cosignature for TIU DOCUMENTS, and returns a 1 if true, or a 0 if false.		Boolean result: 0 if FALSE, OR 1 if TRUE.	'TIU REQUIRE S COSIGNA TURE'	tiusign	RPCBroker1	Value := Copy(pncsForm.x FMPNTitles.Items [x], Pos(' IEN#', pncsForm.xFMPN Titles.Items[x]) + 6, 99); PType := literal; Value := '0'; PType := literal; Value := AuthorIEN; PType := literal;			
TIU SET DOCUME NT TEXT	SETTEXT	TIUSRVPT	SINGLE VALUE	This RPC buffers the transmittal of text (i.e., the body of TIU Documents) from the Client to the Server. It allows documents of indefinite size to be filed, without risk of an allocate error on the M Server.		Four 'N'-piece scalar result formatted as follows: If successful: <ien document="" file="" in="" tiu="">^<last_page_recei ved="">^<total_pages_exp ected=""> If unsuccessful: 0^0^0^Explanatory text</total_pages_exp></last_page_recei></ien>	TIU SET DOCUME NT TEXT';	tiucosignat ure	RPCBroker1	Value := addendIEN; PType := literal; Mult["TEXT",' + inttostr(x + 1) + ',0'] := addendumtext.line s[x]; or Mult["HDR"] := '1^1'; PType := list; Value := '0'; PType := literal;			

				MUMPS				DELPHI				
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter		
TIU SIGN RECORD	SIGN	TIUSRVP	SINGLE VALUE	This API Supports the application of the user's electronic signature to a TIU document while evaluating authorization, and validating the user's electronic signature.		This is the error code which may result if the user enters an invalid code, or if the Authorization/Subscription Utility determines that the user is NOT authorized to sign (or cosign) the document, as specified by the site's business rules.	TIU SIGN RECORD' 'TIU SIGN RECORD'	tiusign tiucosignat ure	RPCBroker1 RPCBroker1	Value := aTIUNoteIEN; PType := literal; Value := Encrypt(aSignatur e); PType := literal; Value := addendIEN; PType := literal; Value := Encrypt(TIUSignF orm.Edit3.Text); PType := literal;		
TIU UPDATE RECORD	UPDAT E	TIUSRVP	SINGLE VALUE	This API updates the record named in the TIUDA parameter, with the information contained in the TIUX(Field #) array. The body of the modified TIU document should be passed in the TIUX("TEXT",i,0) subscript, where i is the line number (i.e., the "TEXT" node should be ready to MERGE with a word processing field). Any filing errors which may occur will be returned in the single valued ERR parameter (which is passed by reference).			'TIU UPDATE RECORD'	tiucosignat ure	RPCBroker1	Value := addendIEN; PType := literal; Mult['1202'] := authorIEN; Mult['1301'] := dtm Mult['1701'] := "; PType := list; Value := '1'; PType := literal;		

	MUMPS							DELPHI				
NAME	TAG	ROUTINE	RETURN VALUE TYPE	DESCRIPTION	INPUT PARAMETER (Multiple)	RETURN PARAMETER DESCRIPTION	Procedure Name	Locations	Broker Name	Parameter		
XUS SET VISITOR	SETVIS IT	XUSBSE 1	SINGLE VALUE				XUS SET VISITOR'	CheckRem oteConnecti ons	RPCBroker1	No Params		
							'XUS SET VISITOR'	FindPatient Anywhere	RPCBroker1	No Params		
XWB GET VARIABL E VALUE	VARVA L	XWBLIB	SINGLE VALUE	This RPC accepts the name of a variable which will be evaluated and its value			XWB GET VARIABL E VALUE' 'XWB GET	essoselect PNCSMain	RPCBroker1 RPCBroker1	DUZ'		
				returned to the server. For example, this RPC			VARIABL E VALUE'			PType := reference;		
				may be called with a parameter like DUZ which will be returned as 123456.			'XWB GET VARIABL E VALUE'	REPORTS	RPCBroker1	Value := 'DUZ("2")' PType := reference		
							'XWB GET VARIABL E VALUE'	telnet	RPCBroker1	Value := 'DUZ("2")'; PType := reference;		
							'XWB GET VARIABL E VALUE'	tiudisplayu nit	RPCBroker1	Value := 'DUZ("2")'; PType := reference;		