

Jar包运行文档

Jar包位于 `html-editor` 项目文件夹根目录下，在 `html-editor` 文件夹下执行 `java -jar html-editor.jar` 即可启动运行编辑器，需要执行 `init/read` 初始化命令方可执行其他命令

命令格式与lab1说明文档一致，如下

```
Edit Commands:
  insert <tagName> <idValue> <insertLocation> [textContent]
  append <tagName> <idValue> <parentElement> [textContent]
  edit-id <oldId> <newId>
  edit-text <element> [newTextContent]
  delete <element>

Display Commands:
  print-indent [indent] - Print HTML with indentation
  print-tree           - Print HTML as tree structure
  spell-check          - Check spelling in text content

File Commands:
  init                 - Initialize empty HTML template
  read <filepath>      - Read HTML from file
  save <filepath>      - Save HTML to file

History Commands:
  undo                 - Undo last edit operation
  redo                 - Redo last undone operation

Other Commands:
  status               - Show editor status
  help                 - Show this help message
  exit                 - Exit the editor
```

其中 `read filepath` 的路径根目录即 `html-editor` 的根目录，`testcases` 文件夹中包含 `test-read.html` 文件可供运行，执行 `read testcases/test-read.html` 即可读取 `test-read.html` 文件