Raffle

Public Functions:

receive()
initialize(IRaffle.RaffleInitParams)
buyEntries(address,uint128)
requestDraw()
enableRefunds()
settleWinningTicket(uint256)
redeemWinningTicket(uint256)
refundTickets(uint256[])
releaseSponsorProceeds()
releaseProtocolFees()
releaseSponsorPrize()
onERC721Received(address,address,uint256,bytes)
getVrfRequestPrice()
estimateVrfRequestPrice(uint256)
vrfWrapper()
ticketRange(uint256)
drawRequestDeadline()
callbackDeadline()
accountedQuoteBalance()
grossSales()
name()
symbol()

Private Functions:

_update(address,uint256,address)
fulfillRandomWords(uint256,uint256[])
_settleWinningTicket(uint256)
_transferQuote(address,uint256)
_requireStatus(IRaffle.Status)
_requireWinningTicket(uint256)
_isProtocolDestination(address,address)
_validatedVrfWrapper(address)

Public Variables:

ENTRY_PRICE
callbackGasLimit
requestConfirmations
factory
quoteToken (IERC20)
sponsor
sponsorRecipient
protocolTreasury
prizeToken (IERC721)
prizeTokenId
raffleId
reserveEntries
endTime
totalEntries
ticketCount
unsettledPot
remainingRefundLiability
winnerRecipient
winnerProceeds
sponsorProceeds
protocolFees
vrfRequestId
drawRequestedAt
resolvedAt
winningEntry
winningTicketId
status
settlementComplete
winnerRedeemed
prizeClaimed
initialized

Private Variables:

_ticketRanges
_requestInFlight

RaffleFactory

Public Functions:

createRaffle(IRaffleFactory.CreateRaffleParams)

Private Functions:

_validateCreateParams(IRaffleFactory.CreateRaffleParams)
_requireContract(address)

Public Variables:

callbackGasLimit
requestConfirmations
quoteToken
vrfWrapper
protocolTreasury
raffleImplementation
raffleCount
raffleById
idByRaffle
isRaffle

3

1

2

VRFV2PlusWrapperConsumerBase

Public Functions:

rawFulfillRandomWords(uint256,uint256[])
getBalance()
getLinkToken()

Private Functions:

requestRandomness(uint32,uint16,uint32,bytes)
requestRandomnessPayInNative(uint32,uint16,uint32,bytes)
fulfillRandomWords(uint256,uint256[])

Public Variables:

i_vrfV2PlusWrapper (IVRFV2PlusWrapper)

Private Variables:

i_linkToken (LinkTokenInterface)

ERC721

Public Functions:

name()
symbol()
safeTransferFrom(address,address,uint256)

Private Functions:

_baseURI()
_ownerOf(uint256)
_getApproved(uint256)
_isAuthorized(address,address,uint256)
_checkAuthorized(address,address,uint256)
_increaseBalance(address,uint128)
_update(address,uint256,address)
_mint(address,uint256)
_safeMint(address,uint256)
_safeMint(address,uint256,bytes)
_burn(uint256)
_transfer(address,address,uint256)
_safeTransfer(address,address,uint256)
_safeTransfer(address,address,uint256,bytes)
_approve(address,uint256,address)
_approve(address,uint256,address,bool)
_setApprovalForAll(address,address,bool)
_requireOwned(uint256)

Private Variables:

_name
_symbol
_owners
_balances
_tokenApprovals
_operatorApprovals

ReentrancyGuard

Private Functions:

_nonReentrantBeforeView()
_nonReentrantBefore()
_nonReentrantAfter()
_reentrancyGuardEntered()
_reentrancyGuardStorageSlot()

Modifiers:

nonReentrant()
nonReentrantView()

Private Variables:

REENTRANCY_GUARD_STORAGE
NOT_ENTERED
ENTERED

c12663_IRaffleFactory

1

2

Context

Private Functions:

_msgSender()
_msgData()
_contextSuffixLength()

ERC165

Public Functions:

supportsInterface(bytes4)