


Question:

Q1. [4x5=20]



Consider the network shown above. Using the OSPF algorithm, calculate the shortest paths from B to all the other routers. (That is, show the status of the R, T, and current node in every iteration of the algorithm.)

Ans:

- Initially:**

Node: B

Set (R): {B}

R = {B, B, 0}

T = {<A, A, 3>, <D, D, 5>, <C, C, 8>}

Here, Shortest is $\langle A, A, 3 \rangle$

- **Iteration 1:**

Node: A

Set (R): $\{B, A\}$

$R = \{\langle B, B, 0 \rangle, \langle A, A, 3 \rangle\}$

$T = \{\langle C, C, 6 \rangle, \langle D, D, 5 \rangle\}$

C: $3+3$, D: 5 (Lesser than 13)

Now as D here has the smallest value;

- **Iteration 2:**

Node: D

Set (R): $\{B, A, D\}$

$R = \{\langle B, B, 0 \rangle, \langle A, A, 3 \rangle, \langle D, D, 5 \rangle\}$

$T = \{C, C, 6\}$

C: 6 (Less than 13) – No change among.

- **Iteration 3:**

Node: C

Set (R): $\{B, A, D, C\}$

$T = \{\}$

Hence, the shortest paths from B to all the other routers.

$B \rightarrow A$: 3 (B to A)

$B \rightarrow B$: 0

$B \rightarrow C$: 6 (B to C via A)

$B \rightarrow D$: 5 (B to D)