8/21/24, 12:31 PM Advanced Selectors in CSS

Advanced Selectors in CSS

There are various types of advanced selectors in CSS viz:

- 1. Tag Selector: If we want to select any element of any tag, we can use tag selector. For example: A, B, C, etc.
- 2. Descendant Selector: If we want to select any element inside the DOM subtree of other element, we can use descendant selector. For example: A B refers that any B that is present inside the subtree of A. A and B can be id selectors or tag selectors.
- 3. Class Selector: If we want to select any element with a particular class, we can use class selector. The class selector is denoted with a dot. For example: .classname
- 4. Combination Selector: If we want to select any element with a particular class or tag, we can use combination selector. For example: A .classname
- 5. Comma Combination Selector: If we want to select multiple elements together, we can use comma combination selector. For example: A, B
- 6. Adjacent Sibling Selector: If we want to select any element that is adjacent to another element, we can use adjacent sibling selector. For example: A + B
- 7. General Sibling Selector: It selects an element that follows another element. For example: $A \sim B$
- 8. Child Selector: It directly selects an element that is a child of another element. For example: A > B
- 9. First Child Pseudo Selector: It selects an element that is the first child of another element. For example: A:first-child
- 10. Only Child Pseudo Selector: It selects an element that is the only child of another element. For example: A:only-child

- 11. Nth Child Pseudo Selector: It selects an element that is the nth child of another element. For example: A:nth-child(3)
- 12. Last Child Pseudo Selector: It selects an element that is the last child of another element. For example: A:last-child
- 13. ID Selector: If we want to select any element with a particular id, we can use id selector. The id selector is denoted with a hash. For example: #id
- 14. First of Type Selector: It selects the first element of the specific type. For example: A:first-of-type
- 15. Nth of Type Selector: It selects the nth element of the specific type. For example: A:nth-of-type(3)
- 16. Attribute Selector: It selects an element with a particular attribute. For example: A[attribute]