

Backend API

This page gathers all the API calls that can be used by the front end.

Front end -> Backend

Global configuration

Collection of all functions/API calls available to the front end that handles the global variables.

saveConfigParams(configParams)

saveConfigParams(configParams)

Saves the config parameters to the persistent file

React usage example

```
import { saveConfigParams } from './api/backend-api';  
  
saveConfigParams(globalConfig);
```

loadConfigParams()

loadConfigParams()

Loads the config parameters from the persistent file

React usage example

```
import { loadConfigParams } from './api/backend-api';  
  
globalConfig = loadConfigParams();
```

Data base

Collection of all functions/API calls available to the front end that handles the communication with the data base, such as fetching and storing data.

getMaterialList()

getMaterialList()

TODO

React usage example

```
import { getMaterialList } from "../api/backend-api";

globalConfig = getMaterialList();
```

getMaterialAt(index)

getMaterialAt(index)

Returns the material at an `index` from the database.

React usage example

```
import { getMaterialAt } from "../api/backend-api";

const elem21 = getMaterialAt(21);
```

getExperimentAt(index)

getExperimentAt(index)

Returns the experiment at an `index` from the database.

React usage example

```
import { getExperimentAt } from "../api/backend-api";

const elem21 = getExperimentAt(21);
```

getDataPointArrayAt(index)

getDataPointArrayAt(index)

Returns an array of `DataPoint` at an `index` from the database.

React usage example

```
import { getDataPointArrayAt } from "../api/backend-api";
import { DataPointType } from "types/DataPointTypes";

const dataPointArrya: DataPointType[] = getDataPointArrayAt(21);
```

Core

startExperimentRoutineJS()

startExperimentRoutineJS()

This function calls the `start_experiment_routine()` on the backend.

Usually it should be used to handle when the user press a "start experiment" button or something similar.

React usage example

```
import { getMaterialList } from "../api/backend-api";

onClick(()=>{
  startExperimentRoutineJS();
});
```

endExperimentRoutineJS()

endExperimentRoutineJS()

This function calls the `end_experiment_routine()` on the backend.

Usually it should be used to handle when the user press a "end experiment" button or something similar.

React usage example

```
import { getMaterialList } from "/api/backend-api";

onClick(()=>{
  endExperimentRoutineJS();
};)
```