CS601: Software Development for Scientific Computing


Autumn 2024

Week12: Structured Grids

Recap

Application: Heat Equation


Example: heat conduction through a rod



- u = u(x, t) is the temperature of the metal bar at distance x from one end and at time t
- Goal: find u


Initial and Boundary Conditions

Example: heat conduction through a rod



- Metal bar has length l and the ends are held at constant temperatures u_L at the left and u_R at the right
- Temperature distribution at the initial time is known f(x), with $f(0) = u_L$ and $f(l) = u_R$

Example: heat conduction through a rod




$$\frac{\partial u}{\partial t} = \alpha \frac{\partial^2 u}{\partial x^2}$$

 α is thermal diffusivity

(a constant if the material is homogeneous and isotropic. copper = 1.14 cm² s⁻¹, aluminium = 0.86 cm² s⁻¹)


Example: heat conduction through a rod



$$\frac{\partial u}{\partial t} = \alpha \frac{\partial^2 u}{\partial x^2}$$
 (0 < x < l, t > 0)
 \alpha is thermal diffusivity
 (a constant if the material is homogeneous and isotropic.
 copper = 1.14 cm² s⁻¹, aluminium = 0.86 cm² s⁻¹)

Exercise: what kind of a PDE is this? (Poisson/Heat/Wave?)


Example: heat conduction through a rod



$$\partial_t u = \alpha \Delta u$$

as per the notation mentioned earlier

Example: heat conduction through a rod




$$\partial_t u = \alpha \Delta u$$

Can also be written as:

$$\partial_t u - \alpha \Delta u = 0$$

Example: heat conduction through a rod



$$\partial_t u - \alpha \Delta u = 0 ,$$

Based on initial and boundary conditions:

$$u(0,t) = u_L,$$

$$u(l,t) = u_R,$$

$$u(x,0) = f(x)$$

Summarizing:

1.
$$\partial_t u - \alpha \Delta u = 0$$
, $0 < x < l$, $t > 0$

2.
$$u(0,t) = u_L, t > 0$$

3.
$$u(l,t) = u_R, t > 0$$

4.
$$u(x,0) = f(x), 0 < x < l$$

Solution:

$$u(x,t) = \sum_{m=1}^{\infty} B_m e^{-m^2 \alpha \pi^2 t/l^2} \sin(\frac{m\pi x}{l}) ,$$
where, $B_m = 2/l \int_0^l f(s) \sin(\frac{m\pi s}{l}) ds$

Summarizing:

1.
$$\partial_t u - \alpha \Delta u = 0$$
, $0 < x < l$, $t > 0$

2.
$$u(0,t) = u_L, t > 0$$

3.
$$u(l,t) = u_R, t > 0$$

4. But we are interested in a numerical solution

Solution:

$$u(x,t) = \sum_{m=1}^{\infty} B_m e^{-m^2 \alpha \pi^2 t/l^2} \sin(\frac{m\pi x}{l}) ,$$
 where, $B_m = 2/l \int_0^l f(s) \sin(\frac{m\pi s}{l}) ds$

- Suppose y = f(x)
 - Forward difference approximation to the first-order derivative of f w.r.t. x is:

$$\frac{df}{dx} \approx \frac{\left(f(x+\delta x) - f(x)\right)}{\delta x}$$

 Central difference approximation to the first-order derivative of f w.r.t. x is:

$$\frac{df}{dx} \approx \frac{\left(f(x+\delta x)-f(x-\delta x)\right)}{2\delta x}$$

 Central difference approximation to the second-order derivative of f w.r.t. x is:

$$\frac{d^2f}{dx^2} \approx \frac{\left(f(x+\delta x)-2f(x)+f(x-\delta x)\right)}{(\delta x)^2}$$

• In example heat application f = u = u(x, t) and $\frac{\partial u}{\partial t} = \alpha \frac{\partial^2 u}{\partial x^2}$

– First, approximating
$$\frac{\partial u}{\partial t}$$
:


$$\frac{\partial u}{\partial t} \approx \frac{\left(u(x,t+\delta t)-u(x,t)\right)}{\delta t}$$
, where δt is a small increment in time

– Next, approximating $\frac{\partial^2 u}{\partial x^2}$:


$$\frac{\partial^2 u}{\partial x^2} \approx \frac{\left(u(x+\delta x,t)-2u(x,t)+u(x-\delta x,t)\right)}{(\delta x)^2}$$
, where δx is a small

increment in space (along the length of the rod)

- Divide length l into J equal divisions: $\delta x = l/J$ (space step)
- Choose an appropriate δt (time step)



• Find sequence of numbers which approximate u at a sequence of (x,t) points (i.e. at the intersection of horizontal and vertical lines below)



• Approximate the exact solution $u(j \times \delta x, n \times \delta t)$ using the approximation for partial derivatives mentioned earlier

$$\frac{\partial u}{\partial t} \approx \frac{\left(u(x, t + \delta t) - u(x, t)\right)}{\delta t}$$
$$= \frac{\left(u_j^{n+1} - u_j^n\right)}{\delta t}$$

where u_j^{n+1} denotes taking j steps along x direction and n+1 steps along t direction

Similarly,
$$\frac{\partial^2 u}{\partial x^2} \approx \frac{\left(u(x+\delta x,t)-2u(x,t)+u(x-\delta x,t)\right)}{(\delta x)^2}$$

$$= \frac{\left(u_{j+1}^n-2u_j^n+u_{j-1}^n\right)}{(\delta x)^2}$$

Plugging into
$$\frac{\partial u}{\partial t} = \alpha \frac{\partial^2 u}{\partial x^2}$$
:

$$\frac{(u_j^{n+1} - u_j^n)}{\delta t} = \alpha \frac{(u_{j+1}^n - 2 u_j^n + u_{j-1}^n)}{(\delta x)^2}$$

This is also called as difference equation because you are computing difference between successive values of a function involving discrete variables.

Simplifying:


$$u_{j}^{n+1} = u_{j}^{n} + r(u_{j+1}^{n} - 2u_{j}^{n} + u_{j-1}^{n})$$

$$= ru_{j-1}^{n} + (1 - 2r)u_{j}^{n} + ru_{j+1}^{n},$$

$$where r = \alpha \frac{\delta t}{(\delta x)^{2}}$$

visualizing,

$$u_j^{n+1} = ru_{j-1}^n + (1 - 2r)u_j^n + ru_{j+1}^n$$



To compute the value of function at blue dot, you need 3 values indicated by the red dots – 3-point stencil

Initial and boundary conditions tell us that:

$$u(0,t) = u_L,$$

$$u(l,t) = u_R,$$

$$u(x,0) = f(x)$$

- $u_0^0, u_1^0 u_2^0, \dots u_J^0$ are known (at time t=0, the temperature at all points along the distance is known as indicated by $f(x) = f_j$).
- u_0^1 is $u_{L_i}u_J^1$ is u_R
- Now compute points on the grid from left-to-right:

Now compute points on the grid from left-to-right:

$$u_1^1 = u_1^0 + r(u_0^0 - 2u_1^0 + u_2^0)$$

$$u_2^1 = u_2^0 + r(u_1^0 - 2u_2^0 + u_3^0)$$
.

 $u_{J-1}^1 = u_{J-1}^0 + r(u_{J-2}^0 - 2u_{J-1}^0 + u_J^0)$

- This constitutes the computation done in the first time step.
- Now do the second time step computation...and so on..


```
• Given: l = 1, u(0,t) = u_L = 0, u(l,t) = u_R = 0, u(x,0) = f(x) = x(l-x) \alpha = 1,
```

- Choose: $\delta x = 0.25, \delta t = 0.075$
- Solve.

• Initialize u_j^0 values from initial and boundary conditions i.e. get time-step 0 values


$$u_0^0 = 0$$

 $u_1^0 = f(\delta x) = \delta x(l - \delta x) = .1875$
 $u_2^0 = f(2\delta x) = 2\delta x(l - 2\delta x) = .25$
 $u_3^0 = f(3\delta x) = 3\delta x(l - 3\delta x) = .1875$
 $u_4^0 = 0$



Compute time-step 1 values

$$u_j^{n+1} = ru_{j-1}^n + (1 - 2r)u_j^n + ru_{j+1}^n$$




Nikhil Hegde

Compute time-step 1 values

$$u_j^{n+1} = ru_{j-1}^n + (1 - 2r)u_j^n + ru_{j+1}^n$$

What about values of u(x,t) at \circ ?




Nikhil Hegde

Compute time-step 1 values

$$u_j^{n+1} = ru_{j-1}^n + (1 - 2r)u_j^n + ru_{j+1}^n$$

What about values of u(x, t) at \circ ?

Get it from boundary conditions




Compute time-step 1 values

$$u_j^{n+1} = ru_{j-1}^n + (1 - 2r)u_j^n + ru_{j+1}^n$$

$$r = \alpha \delta t / (\delta x)^2 = 1.2$$

$$u_1^1 = u_1^0 + r(u_0^0 - 2u_1^0 + u_2^0) = 0.03678$$




Nikhil Hegde

Compute time-step 1 values

$$u_j^{n+1} = ru_{j-1}^n + (1 - 2r)u_j^n + ru_{j+1}^n$$

$$r = \alpha \delta t / (\delta x)^2 = 1.2$$

$$\begin{aligned} & u_1^1 = u_1^0 + r(u_0^0 - 2u_1^0 + u_2^0) = 0.03678 \\ & u_2^1 = u_2^0 + r(u_1^0 - 2u_2^0 + u_3^0) = 0.1 \\ & u_3^1 = u_3^0 + r(u_2^0 - 2u_3^0 + u_4^0) = 0.03678 \end{aligned}$$




Compute time-step 2 values

$$u_j^{n+1} = ru_{j-1}^n + (1 - 2r)u_j^n + ru_{j+1}^n$$

$$u_1^2 = u_1^1 + r(u_0^1 - 2u_1^1 + u_2^1) = 0.06851$$

$$u_2^2 = u_2^1 + r(u_1^1 - 2u_2^1 + u_3^1) = -0.05173$$


$$u_3^2 = u_3^1 + r(u_2^1 - 2u_3^1 + u_4^1) = 0.06851$$



Nikhil Hegde

- Temperature at $2\delta x$ after $2\delta t$ time units went into negative! (when the boundaries were held constant at 0)
 - Example of instability

$$u_2^2 = u_2^1 + r(u_1^1 - 2u_2^1 + u_3^1) = -0.05173$$



The solution is stable (for heat diffusion problem) only if the approximations for u(x,t) do not get bigger in magnitude with time

Nikhil Hegde

 The solution for heat diffusion problem is stable only if:

$$r \leq \frac{1}{2}$$

Therefore, choose your time step in such a way that:


$$\delta t \le \frac{\delta x^2}{2\alpha}$$

But this is a severe limitation!

Implicit Method: Stability

Overcoming instability:

$$u_j^{n+1} = u_j^n + 1/2 \text{ r}(u_{j-1}^n - 2u_j^n + u_{j+1}^n + u_{j-1}^{n+1} - 2u_j^{n+1} + u_{j+1}^{n+1})$$



To compute the value of function at blue dot, you need 6 values indicated by the red dots (known) and 3 additional ones (unknown) above

Implicit Method: Stability

Overcoming instability:

$$u_j^{n+1} = u_j^n + 1/2 \text{ r}(u_{j-1}^n - 2u_j^n + u_{j+1}^n + u_{j-1}^{n+1} - 2u_j^{n+1} + u_{j+1}^{n+1})$$

- Extra work involved to determine the values of unknowns in a time step
 - Solve a system of simultaneous equations. Is it worth it?

Suggested Reading

 J.W. Thomas. Numerical Partial Differential Equations: Finite Difference Methods

Parabolic PDEs:

https://learn.lboro.ac.uk/archive/olmp/olmp_reso urces/pages/workbooks_1_50_jan2008/Workbo ok32/32_4_prblc_pde.pdf

Nikhil Hegde 34

Exercise

Consider the boundary-value problem:

$$u_{xx} + u_{yy} = 0$$
 in the square $0 < x < 1, 0 < y < 1$
 $u = x^2y$ on the boundary.

Is this Laplace equation or Poisson equation?

Elliptic Equation – Numerical Solution

- 1. Approximate the derivatives of $\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} = f(x, y)$ using central differences
- 2. Choose step sizes δx and δy for x and y axis resp.
 - 1. Both and x and y are independent variables here.
 - 2. Choose $\delta x = \delta y = h$
- 3. Write difference equation for approximating the PDE above

1. Approximate the derivatives of $\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} = f(x, y)$ using central differences

$$\frac{\partial^2 u}{\partial x^2} \approx \frac{\left(u(x+\delta x,y) - 2u(x,y) + u(x-\delta x,y)\right)}{(\delta x)^2}$$

$$\frac{\partial^2 u}{\partial y^2} \approx \frac{\left(u(x, y + \delta y) - 2u(x, y) + u(x, y - \delta y)\right)}{(\delta y)^2}$$

Where, δx and δy are step sizes along x and y direction resp.

• Substituting in
$$\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} = f(x, y)$$
:

$$\frac{\left(u(x+\delta x,y)-2u(x,y)+u(x-\delta x,y)\right)}{(\delta x)^2}$$


+

$$\frac{\left(u(x,y+\delta y)-2u(x,y)+u(x,y-\delta y)\right)}{(\delta y)^2}$$

$$\frac{(u(x + \delta x, y) + u(x, y + \delta y) - 4u(x, y) + u(x - \delta x, y) + u(x, y - \delta y))}{(h)^2}$$


$$= f(x, y)$$

• Representing u(x, y)




Notation: **u**_{i,i}

• Representing $u(x - \delta x, y)$




Notation: $u_{i-1,j}$

• Representing $u(x + \delta x, y)$




Notation: $u_{i+1,i}$

• Representing $u(x, y - \delta y)$



Notation: $u_{i,j-1}$

• Representing $u(x, y + \delta y)$



Notation: $u_{i,j+1}$

Rewriting:

$$\frac{\left(u(x + \delta x, y) + u(x, y + \delta y) - 4u(x, y) + u(x - \delta x, y) + u(x, y - \delta y)\right)}{(h)^{2}}$$

$$= f(x, y)$$

$$u_{i+1,j} + u_{i,j+1} - 4u_{i,j} + u_{i-1,j} + u_{i,j-1}$$


$$h^{2}$$


$$j$$
5-point stencil

Consider the boundary-value problem:

$$u_{xx} + u_{yy} = 0$$
 in the square $0 < x < 1, 0 < y < 1$
 $u = x^2y$ on the boundary, $h = 1/3$

$$\frac{u_{i+1,j} + u_{i,j+1} - 4u_{i,j} + u_{i-1,j} + u_{i,j-1}}{h^2} = 0$$






Computing u₁₁

$$(u_{i+1,j} + u_{i,j+1} - 4u_{i,j} + u_{i-1,j} + u_{i,j-1} = 0)$$

 $u_{21} + u_{12} - 4u_{11} + u_{01} + u_{10} = 0$

 $u_{21} + u_{12} - 4u_{11} + 0 + 0 = 0$




Computing u₂₁

$$(u_{i+1,j} + u_{i,j+1} - 4u_{i,j} + u_{i-1,j} + u_{i,j-1} = 0)$$

 $u_{31} + u_{22} - 4u_{21} + u_{11} + u_{20} = 0$

$$1/3 + u_{22} - 4u_{21} + U_{11} + 0 = 0$$




Computing u₁₂

$$(u_{i+1,j} + u_{i,j+1} - 4u_{i,j} + u_{i-1,j} + u_{i,j-1} = 0)$$

 $u_{22} + u_{13} - 4u_{12} + u_{02} + u_{11} = 0$

$$u_{22} + 1/9 - 4u_{12} + 0 + u_{11} = 0$$




Computing u₂₂


$$(u_{i+1,j} + u_{i,j+1} - 4u_{i,j} + u_{i-1,j} + u_{i,j-1} = 0)$$


 $u_{32} + u_{23} - 4u_{22} + u_{12} + u_{21} = 0$

$$2/3 + 4/9 - 4u_{22} + u_{12} + u_{21} = 0$$



System of Equations





Computing System of Equations:

$$u_{21} + u_{12} - 4u_{11} + 0 + 0 = 0$$
 $1/3 + u_{22} - 4u_{21} + u_{11} + 0 = 0$
 $u_{22} + 1/9 - 4u_{12} + 0 + u_{11} = 0$
 $2/3 + 4/9 - 4u_{22} + u_{12} + u_{21} = 0$

$$\begin{pmatrix} -4 & 1 & 1 & 0 \\ 1 & -4 & 0 & 1 \\ 1 & 0 & -4 & 1 \\ 0 & 1 & 1 & -4 \end{pmatrix} \begin{pmatrix} u_{11} \\ u_{21} \\ u_{12} \\ u_{22} \end{pmatrix} = \begin{pmatrix} 0 \\ -1/3 \\ -1/9 \\ -10/9 \end{pmatrix} \quad \text{Ax=B}$$

$$\begin{pmatrix} 0 \\ -1/3 \\ -1/9 \\ -10/9 \end{pmatrix} \quad \text{Ax=B}$$

$$X = B \quad 1$$


$$X = B \quad 1$$

$$A \quad X = B \quad 1$$


• Consider the boundary-value problem (here u_{xx} denotes $\partial^2 u/\partial x^2$)

$$u_{xx} + u_{yy} = 0$$
 in the square $0 < x < 1, 0 < y < 1$

 $u = x^2y$ on the boundary, h = 1/5



 Computing stencil (boundary values are all given): 16 unknowns (u₁₁ to u₄₄), So, 16 equations.



				_						_		_
-4	1	0	0	1								
1	-4	1	0	0	1							
0	1	-4	1	0	0	1						
0	0	1	-4	1	0	0	1					
1	0	0	1	-4	1	0	0	1				
	1	0	0	1	-4	1	0	0	1			
		1	0	0	1	-4	1	0	0	1		
			1	0	0	1	-4	1	0	0	1	
				1	0	0	1	-4	1	0	0	1
												\Box

- Lot of Zeros!
- Five non-zero bands
 - Top-left to bottom-right diagonals
- Main diagonal is all -4 (from center of the stencil)
- What about others?

Nikhil Hegde

54

												\sim
-4	1	0	0	1								
1	-4	1	0	0	1							
0	1	-4	1	0	0	1						
0	0	1	-4	1	0	0	1					
1	0	0	1	-4	1	0	0	1				
	1	0	0	1	-4	1	0	0	1			
		1	0	0	1	-4	1	0	0	1		
			1	0	0	1	4	1	0	0	1	
				1	0	0	1	-4	1	0	0	1
		ĺ										\Box

Lot of Zeros!

Five non-zero bands

Left

- Top-left to bottom-right diagonals
- Main diagonal is all -4 (from center of the stencil)
- What about others?

Nikhil Hegde

55

Right

										_		_
-4	1	0	0	1								
1	-4	1	0	0	1							
0	1	-4	1	0	0	1						
0	0	1	-4	1	0	0	1					
1	0	0	1	-4	1	0	0	1				
	1	0	0	1	-4	1	Q	0	1			
		1	0	0	1	-4	1	Q	0	1		
			1	0	0	1	-4	1	9	0	1	
				1	0	0	1	-4	1	0	0	1
									X			

Lot of Zeros!

Five non-zero bands

Top-left to bottom-right diagonals

- Main diagonal is all -4 (from center of the stencil)
- What about others?

_													_
_	4	1	0	0	1								
1		-4	1	0	0	1							
C)	1	-4	1	0	0	1						
)	0	1	-4	1	0	0	1					
<u>[</u> 1		9	0	1	-4	1	0	0	1				
		1	Q	0	1	-4	1	0	0	1			
			1	Q	0	1	-4	1	0	0	1		
				1	Q	0	1	-4	1	0	0	1	
					1	0	0	1	-4	1	0	0	1

Lot of Zeros!

Bottom

- Five non-zero bands
 - Top-left to bottom-right diagonals
- Main diagonal is all -4 (from center of the stencil)
- What about others?

												_
-4	1	0	0 (1								
1	-4	1	0	0	1							
0	1	-4	1	0	0	1						
0	0	1	-4	1	0	0	1					
1	0	0	1	-4	1	0	0	1				
	1	0	0	1	-4	1	0	0	1			
		1	0	0	1	-4	1	0	0	1		
			1	0	0	1	-4	1	0	0	1	
				1	0	0	1	-4	1	0	0	1

Lot of Zeros!

Five non-zero bands

- Top-left to bottom-right diagonals
- Main diagonal is all -4 (from center of the stencil)
- What about others?

Computing Stencil – Iterative Methods

- Jacobi and Gauss-Seidel
 - Start with an initial guess for the unknowns u⁰;
 - Improve the guess u¹;
 - Iterate: derive the new guess, uⁿ⁺¹_{ij}, from old guess
 uⁿ_{ij}
- Solution (Jacobi):
 - Approximate the value of the center with old values of (left, right, top, bottom)

Background – Jacobi Iteration

- Goal: find solution to system of equations represented by AX=B
- Approach: find sequence of approximations X⁰
 X¹ X² . . . Xⁿ which gradually approach X .
 X⁰ is called initial guess, X¹ s called *iterates*

Method:

Split A into A=L+D+U e.g.

$$\begin{pmatrix} -4 & 1 & 1 & 0 \\ 1 & -4 & 0 & 1 \\ 1 & 0 & -4 & 1 \\ 0 & 1 & 1 & -4 \end{pmatrix} = \begin{pmatrix} 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 1 & 1 & 0 \end{pmatrix} + \begin{pmatrix} -4 & 0 & 0 & 0 \\ 0 & -4 & 0 & 0 \\ 0 & 0 & -4 & 0 \\ 0 & 0 & 0 & -4 \end{pmatrix} + \begin{pmatrix} 0 & 1 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 \end{pmatrix}$$
Nikhil Hegde

Background – Jacobi Iteration

• Compute: AX=B is (L+D+U)X=B

$$\Rightarrow$$
 DX = -(L+U)X+B

$$\Rightarrow$$
 DX^(k+1)= -(L+U)X^k+B (iterate step)

$$\Rightarrow X^{(k+1)} = D^{-1} (-(L+U)X^k) + D^{-1}B$$

(As long as D has no zeros in the diagonal $X^{(k+1)}$ is obtained)

• E.g.
$$\begin{pmatrix} -4 & 0 & 0 & 0 \\ 0 & -4 & 0 & 0 \\ 0 & 0 & -4 & 0 \\ 0 & 0 & 0 & -4 \end{pmatrix} \begin{pmatrix} u_{11} \\ u_{21} \\ u_{12} \\ u_{22} \end{pmatrix} = -\begin{pmatrix} 0 & 1 & 1 & 0 \\ 1 & 0 & 0 & 1 \\ 1 & 0 & 0 & 1 \\ 0 & 1 & 1 & 0 \end{pmatrix} \begin{pmatrix} u_{11} \\ u_{21} \\ u_{12} \\ u_{22} \end{pmatrix} + \begin{pmatrix} 0 \\ -1/3 \\ -1/9 \\ -10/9 \end{pmatrix},$$


u_{ij} 's value in (1)st iteration is computed based on u_{ij} values computed in (0)th iteration

Background – Jacobi Iteration

• E.g.
$$\begin{pmatrix} -4 & 0 & 0 & 0 \\ 0 & -4 & 0 & 0 \\ 0 & 0 & -4 & 0 \\ 0 & 0 & 0 & -4 \end{pmatrix} \begin{pmatrix} u_{11} \\ u_{21} \\ u_{12} \\ u_{22} \end{pmatrix} = -\begin{pmatrix} 0 & 1 & 1 & 0 \\ 1 & 0 & 0 & 1 \\ 1 & 0 & 0 & 1 \\ 0 & 1 & 1 & 0 \end{pmatrix} \begin{pmatrix} u_{11} \\ u_{21} \\ u_{12} \\ u_{22} \end{pmatrix} + \begin{pmatrix} 0 \\ -1/3 \\ -1/9 \\ -10/9 \end{pmatrix},$$

 u_{ij} 's value in $(k+1)^{st}$ iteration is computed based on u_{ij} values computed in $(k)^{th}$ iteration

Center's value is updated. Why?



5-point stencil

- Jacobi and Gauss-Seidel (Solution approach)
 - Start with an initial guess for the unknowns u⁰;
 - Improve the guess u¹_{ij}
 - Iterate: derive the new guess, u^{n+1}_{ij} , from old guess u^{n}_{ij}
- Solution (Jacobi):
 - Approximate the value of the center with old values of (left, right, top, bottom)

•
$$u_{right} + u_{top} - 4u_{center} + u_{left} + u_{bottom} = 0$$


=> $u_{center} = 1/4(u_{right} + u_{top} + u_{left} + u_{bottom})$

Applying Jacobi Iteration:

$$u_{center}^{(k+1)} = 1/4(u_{right}^{(k)} + u_{top}^{(k)} + u_{left}^{(k)} + u_{bottom}^{(k)})$$

Example: applying Jacobi Iteration:

$$u_{center}^{(k+1)} = 1/4(u_{right}^{(k)} + u_{top}^{(k)} + u_{left}^{(k)} + u_{bottom}^{(k)})$$




Iteration 1

1) Compute u_{11} using initial guess for u_{12} and u_{21} . u_{01} and u_{10} are known from boundary conditions

Example: applying Jacobi Iteration:

$$u_{center}^{(k+1)} = 1/4(u_{right}^{(k)} + u_{top}^{(k)} + u_{left}^{(k)} + u_{bottom}^{(k)})$$




Nikhil Hegde

Iteration 1


- 1) Compute u_{11} using initial guess for u_{12} and u_{21} . u_{01} and u_{10} are known from boundary conditions
- 2) Compute u_{21} using initial guess for u_{11} , u_{31} , and u_{22} . u_{20} are known from boundary conditions

In 2), note that the initial guess for u_{11} is used even though u_{11} was updated just before in 1)

 In every iteration, suppose we follow the computing order as shown (dashed):




In any iteration, what are all the points of a 5-point stencil already updated while computing u_{ij} ?




Nikhil Hegde

67



What are the points that are already computed at u_{i,i}?



Background – Gauss-Seidel Iteration

• Compute: AX=B is (L+D+U)X=B

$$\Rightarrow$$
 (L+D)X = -UX+B

$$\Rightarrow$$
 (L+D)X^(k+1)= -UX^k+B (iterate step)

$$\Rightarrow X^{(k+1)} = (L+D)^{-1} (-UX^k) + (L+D)^{-1}B$$

(As long as L+D has no zeros in the diagonal $X^{(k+1)}$ is obtained)

• E.g.
$$\begin{pmatrix} -4 & 0 & 0 & 0 \\ 1 & -4 & 0 & 0 \\ 1 & 0 & -4 & 0 \\ 0 & 1 & 1 & -4 \end{pmatrix} \begin{pmatrix} u_{11} \\ u_{21} \\ u_{12} \\ u_{22} \end{pmatrix} = - \begin{pmatrix} 0 & 1 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 \end{pmatrix} \begin{pmatrix} u_{11} \\ u_{21} \\ u_{12} \\ u_{22} \end{pmatrix} + \begin{pmatrix} 0 \\ -1/3 \\ -1/9 \\ -10/9 \end{pmatrix}$$

Computing Stencil – Gauss-Seidel

Gauss-Seidel: Applying for 2D Laplace Equation

$$u_{center}^{(k+1)} = 1/4(u_{right}^{(k)} + u_{top}^{(k)} + u_{left}^{(k+1)} + u_{bottom}^{(k+1)})$$


- Gauss-Seidel: Observations
 - For a given problem and initial guess, Gauss-seidel converges faster than Jacobi
 - An iteration in Jacobi can be parallelized

Finite Element Method

- Agenda
 - Motivation
 - Handling irregular geometries
 - Avoiding truncation errors
 - Ease of capturing difficult boundary conditions
 - Method of weighted residuals
 - "Element"

(in the backdrop of 1D problem)

Source of Unstructured Finite Element Mesh: Vertebra




Source: M. Adams, H. Bayraktar, T. Keaveny, P. Papadopoulos, A. Gupta

03/09/06 Credits: CS267 USBerkeley

Multigrid for nonlinear elastic analysis of bone


Mechanical testing for material properties






Micro Computed Tomography @ 22 μm resolution

3D image



Source: M. Adams et al.

μFE mesh 2.5 mm³ 44 µm elements



Up to 537M unknowns **4088 Processors (ASCI White)** Credits: CS267 UC Berkeley 70% parallel efficiency

• Taylor series - if a function f(x) is infinitely differentiable at x = a (i.e. the derivatives exist at x = a) then it can be written as:

$$f(x) = f(a) + f'(a)(x - a) + \frac{f''(a)(x - a)^2}{2!} + \frac{f'''(a)(x - a)^3}{3!} + \dots + \infty$$

• In 1D rod problem, suppose we know the temperature, u_i , at grid point i. Can we compute u_{i+1} ?

$$u_{i+1} = u_i + u'(i) (\Delta x) + \frac{u''(i)(\Delta x)^2}{2!} + \frac{u'''(i)(\Delta x)^3}{3!} + \cdots$$

$$u'(i) = (u_{i+1} - u_i)/\Delta x - 1/\Delta x (\frac{u''(i)(\Delta x)^2}{2!} + \frac{u'''(i)(\Delta x)^3}{3!} + \cdots)$$

• In 1D rod problem, suppose we know the temperature, u_i , at grid point i. Can we compute u_{i-1} ?

$$u_{i-1} = u_i - u'(i) (\Delta x) + \frac{u''(i)(\Delta x)^2}{2!} - \frac{u'''(i)(\Delta x)^3}{3!} + \dots$$

$$u'(i) = (u_i - u_{i-1})/\Delta x + 1/\Delta x (\frac{u''(i)(\Delta x)^2}{2!} - \frac{u'''(i)(\Delta x)^3}{3!} + \cdots)$$

 Central difference approximation to second order derivative – add equations

$$u_{i-1} = u_i - u'(i) (\Delta x) + \frac{u''(i)(\Delta x)^2}{2!} - \frac{u'''(i)(\Delta x)^3}{3!} + \dots$$

$$u_{i+1} = u_i + u'(i) (\Delta x) + \frac{u''(i)(\Delta x)^2}{2!} + \frac{u'''(i)(\Delta x)^3}{3!} + \cdots$$

$$u''(i) = (u_{i+1} - 2u_i + u_{i-1})/(\Delta x)^2$$

Truncation error is $O(\Delta x^2)$

 Refer to class notes for discussion on weighted residual method and FEM.