

Python第5次(第5周)作业 (参考答案)

考试形式：开卷

考试时间：2024-3-25

院系：东吴学院 年级：2024 专业：非计算机专业

学号： 姓名： 分数：

一、选择题（每小题1.0分，共20.0分）

- | | | | | |
|-------|-------|-------|-------|-------|
| 01. A | 02. B | 03. A | 04. C | 05. C |
| 06. C | 07. D | 08. A | 09. D | 10. B |
| 11. C | 12. C | 13. B | 14. C | 15. D |
| 16. D | 17. A | 18. C | 19. D | 20. D |

二、填空题（每空2.0分，共20.0分）

01. False
02. True
03. [3]
04. [2, 4]
05. [7, 5, 3]
06. [1, 2, 3]
07. 7
08. [0, 2, 4]
09. 1
10. [4, 6, 8, 9]

三、编程题（每小题6.0分，共60.0分）

01. (6.0分) 答：

```
x=[11, 22, 33, 44, 55, 66, 77, 88, 11, 22, 33, 44, 11, 22, 33, 11, 22, 11]
```

```
n,w=eval(input())
```

```
if n in x:
```

```
    if w<len(x) and x[w]==n:
```

```
        print('Right')
```

```
    else:
```

```
        print('ErrorIndex')
```

```
else:
```

```
    print('Notfound')
```

02. (6.0分) 答：

```
ls=eval(input())
```

```
max_=max(ls)
```

```
maxn=[]
```

```
for i in range(len(ls)):
```

```
    if ls[i]==max_:
```

```
        maxn+=[i+1]
print(maxn)
```

03. (6.0分) 答:

```
a = eval(input())
s=[]
for i in a:
    if i not in s:
        s.append(i)
print(s)
```

04. (6.0分) 答:

```
ls= eval(input())
a=[]
b=[]
for i in ls:
    if i%2==0:
        a.append(i)
    else:
        b.append(i)
a.sort()
b.sort(reverse=True)
```

```
ls=a+b
```

```
print(ls)
```

05. (6.0分) 答:

```
ls= eval(input())
a=max(ls)
b=min(ls)
ave=(sum(ls)-a-b)/(len(ls)-2)
print("%.2f"%ave)
```

06. (6.0分) 答:

```
ls= eval(input())
b=[ls[0]]
for i in range(1,len(ls)):
    s=0
    for j in range(i+1):
        s+=ls[j]
    b.append(s)
print(b)
```

07. (6.0分) 答:

```
ls= eval(input())
key=eval(input())
if key in ls:
    ls.remove(key)
else:
```

```

    ls.insert(0, key)
print(ls)
08. (6.0分) 答:
ls= eval(input())
prime=[]
for num in ls:
    k=0
    for i in range(1, num+1):
        if num%i==0:
            k+=1
    if k==2:
        if num not in prime:
            prime.append(num)
if not prime:
    print("Error")
else:
    max_prime=max(prime)
    print(ls.index(max_prime))

```

09. (6.0分) 答:

```

ls= eval(input())
num=eval(input())
m=[]
for i in ls:
    if i>num:
        m.append(i)
if not m:
    print(None)
else:
    print(m)

```

10. (6.0分) 答:

```

ls= eval(input())
max_three=ls[0:3]
sum_three=sum(ls[0:3])
for i in range(1, len(ls)-2):
    s=ls[i:i+3]
    m=sum(s)
    if m>sum_three:
        sum_three=m
        max_three=s
print(max_three)

```