

# Preface

## Scope

This document describes what to download the required software and example files from github. You do not need Android Studio nor build any apk file. It further explains how to install everything up to the point of starting the emulator. Once that works you do not need this document any longer. For help on actually using the emulator see the other documents as listed in the Readme on Github. For beginners the next document is the “Introduction to the emulator”.

## ***Tested system settings***

- Windows10, 64 bit
- python 3.7, 3.8, 3.10
- AAPS versions for logfile: orefl & SMB for 2.3 – 3.1.0.3
- AAPS versions for determine\_basal: orefl & SMB for 2.5 – 3.1.0.3

I know other users installed it successfully on MAC or Linux.

## ***Prepare Installation***

Download the Github repo (<https://github.com/ga-zelle/AAPS-Emulator>) as a zip archive. The next steps depend on where you want the emulator to run.

# Installation On Windows<sup>10</sup>

Before you start is a good idea to now think about how you organise your input and output data on your PC. You may want to create virtual drives<sup>1</sup> to avoid very long filepath names whenever you need to provide those filenames. There are 3 groups of files involved, each with their own drive:

- S: Holds the software for the emulator itself
- L: holds your study topics with subfolders per project like "L:\tutorials\"
- Z: holds your zipped logfiles; may be grouped in subfolders by month like "Z:\2023-01\"

Extract the zip-archive downloaded from Github to a folder containing

- "determine\_basal.py" into "S:" as the emulation of the original java version
- "emulator\_GUI.py" into "S:" which manages the user input in an interactive window
- create a shortcut on your desktop to point to this GUI file.
- "emulator\_batch.py" into "S:" which alternatively manages the user input in a DOS window
- "emulator\_core.py" into "S:" the main programme which manages the whole process
- "<variant\_label>.vdf" into "L:" which contains the definition of the settings you want to change

To get python if you do not have it yet on your PC the best option is to download its installer from <https://realpython.com/installing-python/#how-to-install-python-on-windows>. When the installer starts select user specific options rather than standard configuration. In the dialogue that follows select

- add python to the system variable for PATH
- select to also download and install "pip"

After the python installation is completed you need to download the matplotlib library. This is done in a DOS window by entering "pip install matplotlib" on the command line.

The last action to make python fit for this project is to define a system variable<sup>2</sup> PYTHONUTF8=1 to allow use of special characters from the UTF-8 character set like the Greek Δ for labelling next-Δ.

## **Verify the emulator starts**

Start by clicking on the shortcut created on the desktop during the installation process. This opens a DOS window. The DOS window should remain empty but may be error messages will show up and I recommend to check for those before quitting the GUI. I tried to catch such messages in the code for display in the form itself but you never know.

After opening that DOS window another window opens which contains a form itself to manage the whole process. The size of the window may be adjusted so longer filenames are displayed without scrolling. In general, boxes with white background are used to enter text, mostly filenames. Boxes with rounded corners and grey background are command buttons to start certain actions:

- Browse - will start the standard file selection dialogue to find the respective file
- Edit - loads that file into your standard Editor (as long as your system has assigned a standard app for that file type)
- Show - similar to „Edit“ apart from the result PDF where it uses your standard PDF viewer

The process goes from top to bottom and from left to right but of course you can jump to wherever. First, you select the working folder, i.e. the one containing your variant definition file and later the result files.

---

<sup>1</sup> See appendix V how to create a virtual drive

<sup>2</sup> See appendix S how to define a system variable

# Installation on the AAPS phone

- From the play store download and install qpython3 („QPython 3L – Python for Android“ by QpythonLab).
- This should create a folder „qpython“ at the top level
- Go to its subfolder „scripts3“
- From the Github archive downloaded above extract the following 3 script files (i.e. the python programmes) to this subfolder
  - „determine\_basal.py“
  - „emulator\_batch.py“
  - „emulator\_core.py“
- "<variant\_label>.vdf", the vdf-file is the same as on Windows and is copied to the folder containing the AAPS logfiles.

## Verify the emulator starts on the AAPS phone


On the phone press the „QPython3L“ button created during installation. There, press Programs, select „emulator\_batch.py“ and finally select „Run“.

After some Android12 update the previously used GUI dialogues no longer worked and I had to create a keyboard based version similar to the typical telephone dialogues “for option X dial 2”. The top part of those screens lists the available options to select from where one of them has a label “ (default)” appended, meaning it is the current selection. The bottom part lists the steps to take once your intended option is selected and labelled as default. Those steps typically are Next, Test and Exit.


The first dialogue is used to select the language for the speech synthesis.

Select „Test“ to listen to a sample speech synthesis.


Select „Next“ to proceed.



The next dialogue is for selecting your variant definition file. Use a “noChange” version or the one that comes with the examples. All vdf-files found in the logfile folder will be listed.




The next dialogue is used to select your favourite configuration file.



After you activate the selection you get a message of how many columns the selected tabular output will occupy. This is a convenient time to rotate the phone to landscape to see longer filenames nicely displayed and to prepare for the result table display.

Press ENTER-key to proceed.



Now you should see a screen like this:

UTC		-----ISF factors-----						-----ISFs-----			insulin Req		---SMB---	
time	bg	auto	acce	bg	pp	delta	dura	orig	prof	emul	orig	emul	orig	emul
10:29Z	125	1.0	0.84	1.15	1	1	1.11	97.3	95	98.1	0	0	0	0
10:34Z	127	1.0	0.88	1.16	1.02	1	1.16	88.9	95	92.9	0	0	0	0
10:39Z	128	1.0	0.91	1.16	1.02	1	1.22	81.8	95	85.4	0.02	0.0	0	0
10:41Z	128	1.0	0.91	1.16	1.02	1	1.22	81.8	95	85.2	0.05	0.02	0	0
10:44Z	129	1.0	0.94	1.17	1.02	1	1.28	75.7	95	78.6	0.12	0.1	0.1	0
10:49Z	129	1.0	0.94	1.17	1.01	1	1.34	73.1	95	75.9	0.04	0.01	0	0
10:54Z	128	1.0	0.88	1.17	1	1	1.4	77.3	95	77.3	0	0	0	0
10:59Z	126	1.0	0.88	1.17	1	1	1.45	74.4	95	74.3	0	0	0	0
11:04Z	121	1.0	0.77	1.17	1	1	1.5	82	95	81.9	0	0	0	0
11:09Z	121	1.0	1.03	1.16	1	1	1.55	61.4	95	61.3	0	0.0	0	0
11:14Z	121	1.0	1.17	1.16	1	1	1.6	59.6	95	59.4	0.17	0.17	0.1	0.1
11:18Z	123	1.0	1.07	1.15	1.02	1	1.65	57.7	95	57.6	0.28	0.28	0.2	0.2
11:24Z	123	1.0	1	1.15	1.01	1	1.7	56	95	55.8	0.07	0.07	0	0
11:29Z	120	1.0	0.72	1.15	1	1	1.75	75.5	95	75.3	0	0	0	0

Variant "TT\_boost\_50pct"  
waiting 300 sec for next loop at 13:34

If so, congratulations! You are done with setting up your phone for the emulator. Next you can read the “Introduction to the AAPS emulator” for first steps on how to use it.

Status: 09-Jan-2023 @ 00:46

## Appendix S      How to define a new system variable


You can search the web for tips. Here is an example instruction set taken from <https://geekflare.com/system-environment-variables-in-windows/>

### Steps for Windows 10


Go to settings and enter the “About” menu.

Now go to “Advanced system settings.” The System Properties dialogue box should appear on your screen.


Click on the “Advanced” tab and select “Environment Variables.” Windows 10 will now display the entire list of user and system variables stored on your computer.



Click on “Environment Variables” to get:



Click “New...” underneath the System variables. A form opens where you enter PYTHONUTF8 as name and 1 as value.



The image shows a Windows dialog box titled "New User Variable". It has a close button (X) in the top right corner. Inside the dialog, there are two text input fields. The first is labeled "Variable name:" and contains the text "JAVA\_HOME". The second is labeled "Variable value:" and contains the text "C:\Program Files\Java\jdk-17.0.1\bin". Below these fields, there are four buttons: "Browse Directory...", "Browse File...", "OK", and "Cancel". The "OK" button is highlighted with a blue border.

Click “OK” a few times to finish the assignment and close the forms.

## Appendix V: How to create a virtual drive

virtual drive windows 10 - Sucher x

https://www.bing.com/search?q=virtual+drive+windows+10&form=WNS...

**To Create Virtual Drive From A Folder in Windows 10,**

1. Open a new command prompt instance.
2. Type the following command: `subst <drive:> path\to\folder`.
3. Replace the <drive:> portion with the actual drive letter you want to assign to the virtual drive. ...
4. Substitute the path\to\folder portion with the full path to the source folder you want to mount as a drive.
5. Hit the Enter key. ...

