

METHOD OF PROCEDURE (MOP)

MOP ID: MOP-2024-001

Title: Enable OSPF Dynamic Routing Between Two Routers

Date: July 4, 2026

Change Owner: Heli Makwana

Risk Level: Low

1. Objective

Configure OSPF on Router0 and Router1 to enable dynamic route advertisement between two LAN networks (192.168.1.0/24 and 192.168.2.0/24), replacing existing static routes.

2. Current State

- **Router0:** Connected to Switch0 (LAN A: 192.168.1.0/24)
- **Router1:** Connected to Switch1 (LAN B: 192.168.2.0/24)
- **Interconnect:** Serial link (10.0.0.0/30)
- **Status:** Static routes currently configured

3. Implementation Steps

Step 1: Pre-Checks

1. Verify connectivity: Ping 192.168.2.2 from the LAN A PC.
2. Document current routing: Run *show ip route* on both routers.
3. Verify interface status: Run *show ip interface brief*.

Step 2: Configure OSPF on Router0

None

```
Router0(config)# router ospf 1
Router0(config-router)# network 192.168.1.0 0.0.0.255 area 0
Router0(config-router)# network 10.0.0.0 0.0.0.3 area 0
Router0(config-router)# end
Router0# write memory
```

Step 3: Configure OSPF on Router1

None

```
Router1(config)# router ospf 1
```

```
Router1(config-router)# network 192.168.2.0 0.0.0.255 area 0
Router1(config-router)# network 10.0.0.0 0.0.0.3 area 0
Router1(config-router)# end
Router1# write memory
```

Step 4: Remove Static Routes

None

```
Router0(config)# no ip route 192.168.2.0 255.255.255.0 10.0.0.2
Router1(config)# no ip route 192.168.1.0 255.255.255.0 10.0.0.1
```

4. Post-Validation

Test	Expected Result
<i>show ip ospf neighbor</i>	Full adjacency (State: FULL)
<i>show ip route</i>	OSPF routes (marked "O") visible
Ping 192.168.2.2 from LAN A	Successful
Ping 192.168.1.2 from LAN B	Successful

5. Rollback Plan

If validation fails within 15 minutes:

1. Re-apply static routes removed in Step 4.
2. Remove OSPF configuration: *no router ospf 1* on both routers.
3. Re-verify connectivity using ping tests.
4. Escalate if the issue persists.

Approved By: _____ Date: 4th July 2026