CS 251 - Lecture 2

Graham Cooper

May 4th, 2015

Binary Refresh:

$$101 = 1 \times 2^2 + 0 \times 2^1 + 1 \times 2^0$$

Jump:
$28 \times 4 = 112$
PC $\leftarrow$ offset $\times$ 4
Overwrite PC. Example: j 28 sets the PC to 28×4

jump and branch are I-format

beq \$1 , \$2 , 100

branch if equal
if \$1 == \$2 go to offset relative to PC, else continue to next instruction

We don't multiple by 4 so that we can get more space for the 16 bits we have for the value 100, ie going from 400, if we multiply by 4, it goes to 1600

PC $\leftarrow 100 \times 4 + (PC + 4)$

Slide 26:

$$\begin{aligned} PC &\Leftarrow (-3) \times 4 + (PC + 4) \\ &= -12 + 120 \\ &= 108 \end{aligned}$$

Memory Access - I-Format
jump and branch are I-format

lw \$s1 , 100(\$s2)

100(\$s2) is computing an address
\$s1 $\Leftarrow$ M[address]

sw \$1 , 100(\$2)

M[100 + \$s2] $\Leftarrow$ \$s1 Memory is written to!!

lw/sw Eample:

```
0  add  $4, $7, $0
4  addi $1, $0, 20
8  lw   $3 0($4)
12 addi $1, $1, -1
16 sw   $3, O($5)
20 addi $4, $4, 4
24 addi $5, $5, 4
28 bne  $1, $0, -6
32 add  $8, $3, 0
```

0:4 - Setting $4 to beginning of an array
8:28 - Loop (goes 20 times)
8 - Load from memory into $3
16 - Store into Data memory, contents of $3
20:24 - Adding from one array to another array in memory

ARM vs MIPS
add command has to add when using the $0 register, while ARM has a move commmand which bypasses the add.