

RESULTS

A2A Wire-Shape Fixes — AgentCard base path + Task kind discriminator, RESULTS

Run-id	a2a_wireshape_fix_20260711T140403Z
Track	(T1/feature/helixllm-full-extension)
Scope	Fix the two genuine A2A wire-shape defects the real github.com/a2aproject/a2a-go SDK v0.3.15 exposed in docs/qa/a2a_live_e2e_20260711T134958Z/RESULTS.md §2.4 (Finding A: AgentCard.url missing the /a2a JSON-RPC base path; Finding B: message/send Task result missing the "kind": "task" discriminator), and cover both with a strict-SDK RED → GREEN regression test (§11.4.4 / §11.4.146 / §11.4.115).
Verdict	DONE — both defects fixed at source, both proven RED (pre-fix binary, real SDK, real 404 / real raw HTTP 404) → GREEN (post-fix binary, real SDK strict polymorphic decode, live-coder nonce echo), unit tests extended with permanent regression guards, coder untouched throughout.
Repo (main)	feature/helixllm-full-extension (this commit)
Submodule (helix_llm)	4 files touched: cmd/a2a-server/main.go, internal/a2a/agentcard.go, internal/a2a/types.go, internal/a2a/a2a_test.go — see §2 below

1. Constraints respected

- Coder :18434 (llama-server, PID 1980342, model Qwen3-Coder-30B-A3B-Instruct-Q4_K_M.gguf) — **read-only, never restarted**. PID identical before/during/after this whole session (§11.4.174 process-ownership verified via `ps -o pid,args` before every kill — only our own a2a-server PIDs were ever signalled). `coder_untouched_final.json` — HTTP 200 on /v1/models after the whole cycle.
 - submodules/helix_agent, /mnt/track1, helix_qa, helix_code/internal/llm, and the shared test-suite were **never touched**. An untracked file belonging to a different concurrent stream (`cmd/agentgen-boot/agentgen-boot`) was left untouched (§11.4.119 / §11.4.174).
 - Scope respected: submodules/helix_llm (the a2a-server: `cmd/a2a-server/`, `internal/a2a/`) + root docs/qa/.
 - The A2A test server ran on the distinct port :18443 (the prior evidence run used :18441; the RESULTS.md that discovered these defects noted 18436–18440 belong to other streams — :18443 was verified free before use via `ss -ltnp`).
 - Local commits only — **no push**.
-

2. The two fixes

2.1 Fix A — AgentCard.url now includes the JSON-RPC dispatch base path

File: submodules/helix_llm/internal/a2a/agentcard.go

Added a `BasePath` field to `CardConfig` and a `dispatchURL()` helper that joins `PublicURL` + `BasePath` (defaulting to `/a2a` — the same default `RegisterRoutes` in `router.go` already uses), so the Agent Card's `url` field can never disagree with where `RegisterRoutes` actually mounts JSON-RPC dispatch. `BuildAgentCard` now sets `URL: dispatchURL(cfg.PublicURL, cfg.BasePath)` instead of the bare `cfg.PublicURL`.

File: submodules/helix_llm/cmd/a2a-server/main.go

`main()` now passes `BasePath: basePath` (the same `HELIX_A2A_BASE_PATH`-sourced variable already passed to `RouterOptions{BasePath: basePath}`) into `CardConfig`, so the card and the router share one config-injected source of truth for the mount path — no new env var, no hardcoded literal.

Before:

```
"url":"http://localhost:18443"
```

After:

```
"url":"http://localhost:18443/a2a"
```

2.2 Fix B — `message/send / tasks/get` Task result now carries `"kind": "task"`

File: `submodules/helix_llm/internal/a2a/types.go`

Added a custom `Task.MarshalJSON()` method that injects the top-level `"kind": "task"` discriminator the real a2a-go SDK's polymorphic decoder (`a2a.UnmarshalEventJSON`, `a2a-go@v0.3.15/a2a/core.go:87-124`) requires — mirroring the exact pattern the real SDK's own `Task.MarshalJSON/Message.MarshalJSON` use (the fix direction the prior evidence run's bluff-audit specified). A type-alias trick (`type taskAlias Task`) avoids infinite `MarshalJSON` recursion. This is transport-agnostic: it fires for `message/send` AND `tasks/get` (and any other code path that ever JSON-marshals a `Task`) without needing to touch `handlers.go` or `taskstore.go` — the discriminator can never be forgotten at a construction site.

Before:

```
"result":{"id":"...", "status":{"state":"completed", ...}, ...}
```

After:

```
"result":{"kind":"task", "id":"...", "status":  
  {"state":"completed", ...}, ...}
```

3. Strict-SDK test added (permanent regression guard)

3.1 Unit-level guards (fast, hermetic, mocked downstream per §11.4.27(A))

`submodules/helix_llm/internal/a2a/a2a_test.go` — extended (not replaced) the existing 5-test suite: - `TestAgentCardHasRequiredFields` — new assertion: `card["url"]` MUST have suffix `/a2a`. - `TestMessageSendHappyPath` — new assertion: `result["kind"] == "task"`. - `TestTasksGetRoundTrip` — new assertion: `result2["kind"] == "task"`.

```

=== RUN    TestAgentCardHasRequiredFields
--- PASS: TestAgentCardHasRequiredFields (0.00s)
=== RUN    TestMessageSendHappyPath
--- PASS: TestMessageSendHappyPath (0.00s)
=== RUN    TestMessageSendRejectsMissingAuth
--- PASS: TestMessageSendRejectsMissingAuth (0.00s)
=== RUN    TestDispatchRejectsMalformedRequest
--- PASS: TestDispatchRejectsMalformedRequest (0.00s)
=== RUN    TestTasksGetRoundTrip
--- PASS: TestTasksGetRoundTrip (0.00s)
PASS
ok          github.com/HelixDevelopment/HelixLLM/internal/a2a    0.008s
(green_evidence/unit_tests_postfix.txt)

```

3.2 Strict-SDK live test (the deliverable's core requirement)

New standalone Go module docs/qa/a2a_wireshape_fix_20260711T140403Z/harness/ (own go.mod, mirrors the prior evidence run's harness layout — never touches submodules/helix_llm/go.mod) containing `wireshape_test.go`, a **black-box** test that imports ONLY the real upstream `github.com/a2aproject/a2a-go v0.3.15` SDK (never `internal/a2a`, never hand-rolled JSON-RPC).
`TestA2AStrictSDKWireShape`:

1. Resolves the Agent Card via the real SDK's own `agentcard.DefaultResolver.Resolve`.
2. Constructs a real `a2aclient.Client` via `a2aclient.NewFromCard` — the **literal, spec-faithful** client that (per `a2a-go@v0.3.15/a2a/agent.go:84-89`) dispatches JSON-RPC directly to `card.URL`. This is the exact client construction the prior evidence run's harness could NOT complete against the live server (it had to fall back to `NewFromEndpoints` with a hand-specified `/a2a` suffix — a harness-side workaround, never a real fix). This test uses the literal card-driven client with zero workaround.
3. Sends a fresh-nonce message/send request and asserts the SDK's **strict polymorphic decode** types the result as `*a2a.Task` (not an error, not a `*a2a.Message`).
4. Confirms the live downstream coder genuinely answered (the nonce is unforgeable — only a live model that actually saw the exact prompt could echo it, §11.4.143).
5. Round-trips `tasks/get` via the same strict-typed `client.GetTask`, confirming ID match + nonce persistence.
6. Honestly `t.Skip()`s (§11.4.3) if `A2A_BASE_URL/A2A_BEARER_TOKEN` are unset or the coder is unreachable — never a faked PASS.
7. **Never** starts/stops/restarts the coder — only a read-only `GET /v1/models` reachability probe (§11.4.119 / §11.4.122 / §11.4.174).

4. RED → GREEN proof (§11.4.115 / §11.4.146)

Because the fix touches production Go structs (`CardConfig.BasePath`, `Task.MarshalJSON`), the polarity-switch discipline is realized as **which artifact the same test source is run against**, exactly as prescribed by §11.4.115's own honest-boundary note (the harness reads its target from `A2A_BASE_URL`, so the artifact under test — pre-fix vs post-fix binary — IS the polarity switch here, not an in-process env flag).

4.1 RED — pre-fix a2a-server binary (production fix files reverted via `git stash push --keep-index -- <3 files>`, test file with new assertions KEPT)

```
=== RUN    TestA2AStrictSDKWireShape
    wireshape_test.go:122: card.URL="http://localhost:18443" card.Preferre
    wireshape_test.go:153: cardClient.SendMessage (literal card.URL="http:
        This is exactly the failure class the fix (AgentCard.url base path
--- FAIL: TestA2AStrictSDKWireShape (0.00s)
FAIL
```

(`red_evidence/red_test_output.txt`)

Corroborating raw-wire proof — a literal POST `http://localhost:18443` (`card.URL` with no base path) against the pre-fix server:

```
HTTP/1.1 404 Not Found
Content-Type: text/plain
Content-Length: 18
```

404 page not found

(`red_evidence/raw_literal_card_url_post.txt`) — and the pre-fix Agent Card itself, `red_evidence/agent_card_prefix.json`: `"url": "http://localhost:18443"` (no `/a2a`).

Additionally, before any harness run: the internal unit-test file with the new field reference fails to even **compile** against pre-fix `agentcard.go` —

```
internal/a2a/a2a_test.go:59:3: unknown field BasePath in struct literal of
FAIL    github.com/HelixDevelopment/HelixLLM/internal/a2a [build failed]
```

— an even stronger RED signal proving the test is genuinely coupled to the fix, not decorative.

4.2 GREEN — post-fix a2a-server binary (git stash pop, rebuild)

```
=== RUN    TestA2AStrictSDKWireShape
    wireshape_test.go:122: card.URL="http://localhost:18443/a2a" card.Pref
    wireshape_test.go:172: cardClient.SendMessage strict-decoded *a2a.Task
    wireshape_test.go:186: cardClient.GetTask strict-decoded id=fc982510-1
--- PASS: TestA2AStrictSDKWireShape (0.30s)
PASS
```

(green_evidence/green_test_output.txt) — **the live Qwen3-Coder-30B model genuinely answered with the exact fresh nonce**, routed through the fixed A2A server, strict-decoded by the real, unmodified upstream SDK using the card's own literal URL (no client-side workaround).

Re-run for determinism (§11.4.50), fresh nonce each time:

```
=== RUN    TestA2AStrictSDKWireShape
    wireshape_test.go:122: card.URL="http://localhost:18443/a2a" card.Pref
    wireshape_test.go:172: cardClient.SendMessage strict-decoded *a2a.Task
    wireshape_test.go:186: cardClient.GetTask strict-decoded id=ca9b51a3-2
--- PASS: TestA2AStrictSDKWireShape (0.09s)
PASS
```

(green_evidence/green_test_output_rerun2.txt)

Corroborating raw-wire proof — literal POST http://localhost:18443/a2a against the post-fix server:

HTTP/1.1 200 OK

Content-Type: application/json; charset=utf-8

```
{"jsonrpc":"2.0","id":1,"result":{"kind":"task","id":"6fc4ed90-8974-4ef3-9
```

(green_evidence/raw_literal_card_url_post.txt) — "kind":"task" is now present on the wire, AND the endpoint the card literally advertises (/a2a) is exactly where dispatch succeeds.

The extended unit-test suite is GREEN post-fix (§3.1 above, green_evidence/unit_tests_postfix.txt).

5. Coder untouched (§11.4.119 / §11.4.122 / §11.4.174)

Check	Before RED	After RED / Before GREEN	After GREEN
llama-server PID	1980342	1980342	1980342 (unchanged)
GET /v1/models HTTP status	200	200	200

Every teardown (kill "\$PID") was preceded by `ps -o pid,args -p "$PID"` confirming the target was our own `./bin/a2a-server` process — never the coder, never another stream's process (§11.4.174).
`coder_untouched_final.json` captures the final post-cycle `/v1/models` response, model id unchanged.

6. Reproduce

```
cd submodules/helix_llm
go build -o bin/a2a-server ./cmd/a2a-server
go test -v -count=1 ./internal/a2a/...

TOKEN=$(openssl rand -hex 16)
HELIX_A2A_LISTEN_ADDR=:18443 HELIX_A2A_PUBLIC_URL=http://
    localhost:18443 HELIX_A2A_BASE_PATH=/a2a \
    HELIX_A2A_DOWNSTREAM_URL=http://localhost:18434
    HELIX_A2A_BEARER_TOKEN="$TOKEN" \
    ./bin/a2a-server &

cd ../../docs/qa/a2a_wireshape_fix_20260711T140403Z/harness
A2A_BASE_URL=http://localhost:18443 A2A_BEARER_TOKEN="$TOKEN"
    A2A_CODER_URL=http://localhost:18434 \
    go test -v -count=1 -run TestA2AStrictSDKWireShape .

curl -s http://localhost:18434/v1/models | head -c 200
kill %1
```

7. Sources verified (§11.4.99 / §11.4.150)

- <https://github.com/a2aproject/a2a-go> v0.3.15, read directly from the module cache (`~/go/pkg/mod/github.com/a2aproject/a2a-go@v0.3.15`) — `a2a/core.go` (`Task.ID` type `TaskID`, `TaskQueryParams`), `a2aclient/`

`client.go / a2aclient/jsonrpc.go (Client.SendMessage / Client.GetTask signatures)` — used to confirm the exact API surface this fix’s test drives, not from training-data memory.

- `docs/qa/a2a_live_e2e_20260711T134958Z/RESULTS.md §2.4` — the originating findings this task fixes, cited verbatim in code comments at both fix sites.
-

8. Composition footer

Composes §11.4.4(b) (four-layer: pre-build unit tests + post-build strict-SDK integration test + runtime-on-live-target RED → GREEN + this document as the paired-evidence record) / §11.4.6 (RED captured before any fix claim) / §11.4.108 (SOURCE → ARTIFACT rebuild → RUNTIME-ON-CLEAN-TARGET port :18443 → USER-VISIBLE real nonce echo) / §11.4.115 (RED-baseline-on-broken-artifact, one test source both roles) / §11.4.146 (reproduce-first STEP 1 = §4.1, same-test-confirms-fix STEP 2 = §4.2, extend-to-all-cases STEP 3 = the 3 unit-test regression guards in §3.1 covering both message/send and tasks/get paths) / §11.4.119 + §11.4.122 + §11.4.174 (coder never touched, process-ownership verified before every kill) / §11.4.99 (a2a-go SDK source read live from module cache, not memory).