

CLAUDE_INDEX

CLAUDE_INDEX.md — Thin Always-Loaded Index (§11.4.141)

Purpose: ~5-8K token entry point for fresh sessions. Full rules in constitution/Constitution.md. **Session state:** .remember/remember.md (§11.4.131)

Essential Rules (one line each, literal anchors for propagation gates)

- **No CI/CD pipelines** — no .github/workflows/, .gitlab-ci.yml, Jenkinsfile (§11.4.156)
- **No mocks in production** — mocks/stubs only in unit tests (§11.4.27/CONST-050)
- **SSH-only Git** — git@github.com:... URLs, never HTTPS (CONST-043)
- **Real data for non-unit tests** — real DB, real HTTP, real containers (§11.4.27)
- **100% challenge coverage** — every component needs Challenge scripts (CONST-048)
- **Reproduction-before-fix** — reproduce bug BEFORE fixing (§11.4.43)
- **Definition of done** — pasted terminal output from real run required (§11.4.5)
- **No self-certification** — “verified/tested/working” forbidden without evidence (§11.4.6)
- **Zero-bluff mandate** — tests must guarantee Quality+Completion+Usability (CONST-035/§11.4)
- **No force-push** — merge-onto-latest-main, never force (§11.4.113)
- **No hardcoded content** — all user-facing text from LLM/i18n/metadata (CONST-046)
- **Submodule-dependency manifest** — every submodule ships helix-deps.yaml (CONST-054)
- **Fetch-before-edit** — git fetch -all FIRST in every session (CONST-060)
- **Subagent-driven default** — fresh implementer per task (§11.4.70)
- **Zero-idle** — never sit idle if work is progressable (§11.4.94)
- **CodeGraph mandatory** — codegraph init + index for all AI-agent projects (§11.4.78)

Build & Test Commands

```
# Root governance gates (from repo root)
make no-silent-skips      # fail on bare t.Skip()
make demo-all             # run every submodule's demo
./setup.sh               # first-time: submodules + deps + build

# Inner application (from helix_code/)
make build                # → bin/helixcode
make verify-compile       # quick compile sanity
make test                 # all unit tests
make test-coverage        # coverage with -race
make dev                  # build + run with dev config

# Full integration (real PG + Redis + Ollama)
make test-infra-up        # start docker-compose stack
make test-full            # ALL tests, ZERO skips
make test-infra-down      # tear down

# Anti-bluff smoke
grep -rniE "\bsimulated\b|\bfor now\b|TODO implement" helix_code/
    internal helix_code/cmd | grep -v _test.go | grep -q .
    && echo "BLUFF" || echo "clean"
```

Anti-Bluff Checklist (§5)

- ☐ No simulation/placeholder in production code
- ☐ Real HTTP calls (not mocked)
- ☐ Real database operations
- ☐ Real process execution (os/exec)
- ☐ Tests validate reality, not function call counts
- ☐ Challenge validates end-to-end
- ☐ No bare t.Skip() without SKIP-OK marker
- ☐ Evidence pasted in commit/PR

Technology Stack (§3.1)

Go 1.26 (inner app), Gin v1.11.0, PostgreSQL 15+, Redis 7+, golang-jwt/v4, Viper v1.21.0, Cobra v1.8.0, AWS Bedrock, Azure azcore, Fyne v2.7.0 (desktop), tview (TUI), stretchr/testify.

Repo Layout (§3.2)

```
helix_code/          # meta-repo root (governance + submodules)
├─ helix_code/       # inner Go application (dev.helix.code)
├─ submodules/       # owned submodules (per .gitmodules)
├─ constitution/     # constitution submodule (source of truth)
├─ dependencies/     # third-party submodules
├─ docs/             # architecture, QA evidence, research
├─ scripts/          # init, governance, gates
└─ .remember/        # session resumption (§11.4.131)
```

Current State

See `.remember/remember.md` for live HEAD, branch, queue, and execution plan.