

Constitution

Helix Universal Constitution

This document defines mandatory, non-negotiable rules for every project that includes this constitution submodule. Every AI agent and every human contributor MUST comply. Violations are blockers.

Project-specific constitutions extend this document. When a project Constitution (e.g. docs/guides/PROJECT_CONSTITUTION.md) and this universal Constitution differ, the project Constitution may extend or tighten — but NEVER weaken — the universal rules below.

Last revision: 2026-05-14 (v1.0 — initial extraction from ATMOSphere Android 15 1.1.5-dev)

This Constitution is the universal source-of-truth for the engineering practices shared across all Helix projects (and any project that opts in by adding this submodule). It is intentionally agnostic about specific hardware, operating systems, languages, vendors, and product domains. Anything in this document that mentions a specific product, hardware SKU, library version, or vendor MUST be moved to the consuming project's own Constitution.

1. Test coverage is mandatory for every change

Every code, configuration, documentation, or infrastructure change MUST ship with tests that prove:

Invariant	Mechanism
The change is present in source	pre-build / pre-merge gate that scans the source tree for the expected pattern
The change survives compilation / packaging	post-build gate that inspects the produced artifact (binary, archive, image) and verifies the change actually shipped

Invariant	Mechanism
The change behaves correctly at runtime	runtime / integration / on-device test that exercises the user-visible behaviour
The gate itself is not bluffing	meta-test (mutation) entry that mutates the asserted condition and proves the gate catches the break

A change without all four layers of coverage is not ready to merge.

1.1 False-positive immunity is an invariant

A test that always returns PASS because its regex never matches, its input path is wrong, its assertion target does not exist, or its comparison is tautological is **worse than no test**. Every new gate **MUST** be paired with a mutation entry in the project's meta-test harness that:

1. Temporarily breaks the assertion (sed out a line, rename a symbol, etc.).
2. Re-runs the gate.
3. Asserts the gate now reports FAIL.
4. Restores the original.

If the mutation round does not turn PASS → FAIL, the gate is a sham and must be rewritten.

This is the **single most important rule in this Constitution**. Every subsequent §11.4.x clause is downstream of it.

2. Commit and push mechanics — single entriypoint, locked

All commit and push work uses the project's official multi-remote commit wrapper (e.g. `scripts/commit_all.sh`) as the single entriypoint. Direct `git commit / git push / git add` on the main repo is prohibited in normal workflow. Exception: tag creation + tag-ref push is done via explicit `git tag -a` and `git push <remote> <tag>`.

The commit and push wrappers **MUST** hold an advisory flock so two invocations cannot race against each other. Lock files self-clean on process exit via `trap`.

When a contributor sees the "another commit/push wrapper is already running" error, they **MUST NOT** `rm -f` the lock unless they have just killed the owning process.

2.1 Multi-upstream push is the norm

Every project hosted on multiple Git providers (GitHub primary, GitLab / GitFlic / GitVerse / Bitbucket / Gitea mirrors) **MUST** push every commit to ALL configured upstream remotes. A commit that lives on only one remote is a future operational risk: when that one provider has an outage, the project is unreachable.

The constitution submodule itself ships an `install_upstreams.sh` helper (and an `Upstreams/` directory with one declaration script per remote). Running it from the submodule root configures all the remotes locally. Consuming projects **SHOULD** do the same for their own multi- remote topology.

3. Submodule changes propagate through submodule commits first

When a change lands in any submodule of the project:

1. **Commit inside the submodule first** (the submodule's own `git add + git commit`), since the parent project's commit wrapper does not commit submodule source — it only captures the updated submodule pointer.
2. **Push the submodule commit** to **all** remotes of that submodule.
3. **Then** run the parent project's commit wrapper to capture the updated submodule pointer in main and push main.

Skipping step 1 produces parent commits / tags that point at old submodule HEADs without the actual source.

4. Every tag on the main repo **MUST** be mirrored on every owned submodule

When a version tag is created on the main repo at a specific commit, the same tag **MUST** be created on **every owned submodule** at that submodule's currently-pointed-to HEAD, and pushed to **every remote** of every owned repo. Third-party submodules (libraries not under the project's control) are excluded. The consuming project's Constitution declares its owned-submodule set explicitly.

5. Changelog discipline and multi-format export

Every tagged release MUST ship:

1. A new docs/changelogs/<tag>.md entry describing user-visible changes, developer-visible changes, and known caveats.
2. Exports of that entry to docs/changelogs/<tag>.{html,json,txt} so external tooling (release portals, ticketing systems, package indices) can consume without needing a Markdown parser.
3. An update to a cumulative docs/changelogs/CHANGELOG.md (reverse chronological).

The project SHOULD provide a script (scripts/testing/export_changelog.sh <tag> or equivalent) that wraps pandoc + jq + plain-text Markdown strip.

6. Documentation up to the nano-details

Every new feature, fix, or infrastructure change MUST update:

1. The project's CLAUDE.md / AGENTS.md Applied Fixes table (one row, one commit, one release tag).
2. docs/guides/ for any user-visible or developer-reachable behaviour change.
3. Architecture diagrams, flowcharts, and any reference docs that touch the changed subsystem.
4. The per-version changelog (§5).

Documentation drift after a fix is itself a Constitution violation: undocumented behaviour change is the same defect class as untested behaviour change.

7. Making false-success results literally impossible

All validation output MUST satisfy the following invariants:

1. Every gate reports concrete PASS / FAIL / SKIP with explicit reason text. A gate that just says "ok" is non-compliant.
2. Every SKIP reason MUST be mechanically distinguishable from a PASS. Summary counters track them separately.
3. FAILs are counted towards exit status. A script that hides FAILs in logs and returns 0 is a bug.

4. Meta-tests (§1.1) catch any gate that always PASSes regardless of condition.
5. Runtime results MUST be cross-referenced against host-side evidence (capture rig, screen recording, log analyzer, or equivalent) when the system's own introspection cannot directly verify the behaviour.

§7.1 NO BLUFF — positive-evidence-only validation

Every runtime test MUST satisfy ALL FIVE of the following non-negotiable constraints. A test that violates any one of them is a **bluff** and is forbidden from being committed to the test suite:

1. **Real ACTION**: the test MUST invoke at least one user-visible action via a project anti-bluff helper (e.g. `ab_send_action()` in shell-based suites). A test that records a PASS without ever calling such a helper is automatically failed by the summary function.
2. **State DELTA**: every PASS that claims to verify a feature MUST capture state BEFORE the action and AFTER, and assert the delta matches expectation. `before == after` on success is a bluff.
3. **POSITIVE EVIDENCE**: the PASS condition MUST be POSITIVE evidence (a value match, a state delta, a captured frame analysis, a captured audio frame analysis), NEVER absence-of-error. If a probe returns nothing, that's a FAIL not a SKIP.
4. **UNIQUE EVIDENCE TOKEN**: tests that interact with mutable framework state MUST embed a per-run UUID into the action AND look for that token in the resulting state. Cached results predating the token cannot match — this defeats the stale-cache false-pass.
5. **Audio / video features REQUIRE captured evidence**: features that produce audio output MUST be validated by capturing the actual output via a capture pipeline (loopback, hardware capture rig, or equivalent) — NOT by metadata-only checks. Features that produce video output MUST be validated via frame capture + OCR or pixel-difference analysis.

Each consuming project SHOULD ship a shared anti-bluff helper library (typically `tests/lib/anti_bluff.sh` or equivalent) that codifies these rules; every new runtime test MUST source it and use its assertion helpers.

§8. Bleeding-edge ultra-perfection quality bar

The acceptance bar for shipping a project change is **not** "tests pass and source compiles" — that is the floor. The acceptance bar is:

The user, on a freshly-deployed system, sees the expected effect when they perform the documented action — confirmed end-to-end, with captured evidence, on the actual target environment.

The following are **forbidden**:

1. **"Source rebrand without shipped artifact rebuild"**: every source-side rename or rebranding **MUST** flow through to a shipped artifact that the runtime actually loads. Pre-build source-string gates are insufficient by themselves; shipped-artifact gates must accompany them.
 2. **"Tests pass but feature broken"**: this is the failure mode §7.1 exists to eradicate. Any test that **PASSes** despite the feature being non-functional is a critical defect; its mutation pair must **FAIL** on the breakage.
 3. **"Configuration-only tests"**: a test that only verifies a config file exists / has expected contents is downgraded to a pre-build gate. Runtime tests **MUST** exercise the actual user-visible behaviour and capture the result.
 4. **"It works on my workstation"**: every fix is validated on every supported target before any release. No exceptions.
 5. **"Will fix in next cycle"**: deferrals are documented in the changelog with concrete blockers + implementation plans, not just handwaved.
-

§9. Absolute codebase and data safety — zero risk, zero loss

Every destructive operation on the repository (history rewrite, force-push, branch deletion, bulk file removal, submodule de-init, pack repack that drops objects) is a **safety-critical** operation. Data loss from a wrong force-push is irreversible once the remote garbage-collects dangling objects. This section is non-negotiable.

§9.1 Mandatory safety protocol for destructive operations

Every destructive operation **MUST** execute, in strict order:

1. **Full backup before touching anything.** Hardlinked mirror of `.git` to a sibling backup directory:

```
cp -al .git <backup>/<repo>.git.mirror
```

This is near-instant on the same filesystem and uses zero additional disk. If `.git` is small, also create git bundle create `<backup>/main.bundle --all`.

2. **Record critical metadata into the backup dir:**

- `git show-ref > refs.txt`
- `git tag > tags.txt`
- `git submodule status > submodules.txt`
- `git rev-parse HEAD > head.txt`
- `git rev-parse HEAD^{tree} > head_tree.txt`
- `git ls-tree -r HEAD --full-tree | sha256sum > head_tree_content.sha256`
- `git ls-tree -r HEAD --full-tree > head_tree_listing.txt`

3. **Identify the target state:** the expected HEAD commit, tree hash, and tree content hash after the operation completes. The operation **MUST** preserve these unless it is explicitly changing HEAD content.

4. **Run the operation** (filter-repo, rebase, etc.). NEVER use `--no-verify` / `bypass-hooks` flags. NEVER auto-force on failure.

5. **Post-operation verification gate** (all **MUST** pass):

- HEAD tree hash matches pre-op target (content identical for non-content-changing rewrites)
- HEAD tree content sha256 matches pre-op sha256
- All tags from `tags.txt` are preserved and resolve to valid commits
- All submodule pointers from `submodules.txt` match current state
- Project's pre-build / pre-merge gates pass with zero FAIL and zero unclassified WARN

6. **Only if every check in §9.1.5 passes** may the operation be considered successful. Otherwise: restore from backup immediately (`rm -rf .git && mv <backup>/<repo>.git.mirror .git`).

7. **Then and only then** may a force-push proceed — and still not without explicit user authorization per §9.2.

§9.2 Force-push requires explicit user authorization every time

Force-pushing (including `push --force`, `push --force-with-lease`, or any divergence-recovery code path inside an automated wrapper) overwrites the remote's view of history. On any shared branch this is irreversible.

Rules:

- Automated push wrappers **MUST NOT** auto-force-push as a fallback to any kind of failure (size rejection, divergence, server error, anything). The historical divergence-recovery code that silently force-resets the remote is forbidden and must be removed or gated behind an explicit flag.
- A human must affirmatively say "force-push" (or equivalent) in the session to authorize each force-push.
- Force-push to main (and any equivalent primary branch on owned submodules) is only authorized after the §9.1.5 gate has passed.
- Every force-push event is recorded in `docs/changelogs/<tag>.md` under a "Force-push audit" section (target refs, backup location, validation gate output).

§9.3 Hardlinked backup is the standard — there is no excuse

Because hardlinked `.git` copies are near-instant and use zero additional disk (same-filesystem inodes), the cost of making a backup is trivial. Any destructive operation without a fresh hard-linked backup is a Constitution violation regardless of how small the repo is or how confident the operator.

§9.4 Commit-message audit trail for history rewrites

After any `git filter-repo` run (or equivalent), commit a record under `docs/changelogs/` (or `docs/history-rewrites/`) containing:

- What was stripped and why
 - Pre-op `.git` size vs post-op `.git` size
 - Pre-op HEAD commit vs post-op HEAD commit
 - Pre-op HEAD tree hash vs post-op HEAD tree hash (MUST match for non-content-changing rewrites)
 - Backup location
-

§10. Enforcement

Any commit, tag, or release that violates §1–§9 is non-compliant. The fix is to amend/revert and re-land with compliance. No exceptions for speed pressure. Data-safety violations (§9) and host-session-safety violations (§12) are treated as catastrophic and block the entire release cycle until fully remediated.

§11. End-user quality covenant

§11.4 End-user quality guarantee — forensic anchor (User mandate, 2026-04-28)

The reason §7.1 + §8 exist — captured verbatim from the project owner so that future engineers and AI agents understand the historical failure mode the covenant exists to eradicate:

"We had been in position that all tests do execute with success and all Challenges as well, but in reality the most of the features does not work and can't be used! This MUST NOT be the case and execution of tests and Challenges MUST guarantee the quality, the completion and full usability by end users of the product!"

This is the canonical motivation for every gate, every mutation pair, every meta-test, every anti-bluff helper, every captured-evidence requirement, every multi-environment validation rule. The covenant exists because the project has historically shipped broken features behind PASS-ing tests, and that outcome is no longer tolerated.

Operative rule: the bar for shipping is not "tests pass" but **"users can use the feature."** Every PASS in this codebase MUST carry positive evidence captured during execution that the feature works for the end user. Metadata-only PASS, configuration-only PASS, "absence-of-error" PASS, and grep-based PASS without runtime evidence are all critical defects regardless of how green the summary line looks.

Propagation requirement: every `CLAUDE.md` and every `AGENTS.md` in the project tree (parent + every submodule recursively) MUST contain a clearly-titled "MANDATORY ANTI-BLUFF COVENANT — END-USER QUALITY GUARANTEE" section that quotes this user mandate verbatim and points back to this §11.4 as the canonical authority. The consuming project enforces this via a pre-build gate (typically `CM-COVENANT-PROPAGATION`).

§11.4.1 — FAIL-bluffs are equally forbidden

The covenant must be enforced symmetrically. The historical failure mode the covenant eradicates is the **PASS-bluff**: a green test result on a feature that doesn't work for users. But the inverse failure mode is just as toxic — the **FAIL-bluff**: a red test result caused by a script bug (shell crash, missing argument, regex error, malformed assertion) rather than by an actual product defect.

Examples of FAIL-bluffs:

- A test using `set -eu` calls `log_pass` without arguments → the helper references `$1` → script crashes with "1: parameter not set" → orchestrator records FAIL → engineer assumes product bug.
- A test pre-condition check uses an unbounded `sed` range → a comment line in the source matches the range terminator → the intended mutation never fires → audit reports PASS — bluff.

A FAIL produced by a test bug is no more useful than a PASS produced by a test bug — both mislead investigation, waste cycles, and ultimately let real defects ship undetected.

Operative rule (extended): every test MUST fail ONLY for genuine product defects. A test that crashes for a script-internal reason — undefined variable under `set -u`, unhandled error, malformed pipe, regex syntax error, division by zero, etc. — is a critical defect in the test suite itself and MUST be fixed at the source layer (helper library, shared lib, test source) so the failure mode disappears project-wide, not patched in individual call sites.

§11.4.2 — Recorded-evidence requirement

A test that emits PASS without **captured visual or audio evidence of the user-visible feature actually working on the screen the user would see** is a §11.4 PASS-bluff. Closing this gap requires a project-wide recording + analyzer infrastructure consisting of (at minimum):

- **Recording wrapper** that captures the user-visible output to time-synchronized media files. Multi-display systems record every output stream in parallel; sync metadata (host wall-clock at spawn) is written alongside the recording.
- **Action-timeline emitter**: every test emits structured timeline events (JSONL or equivalent) at every user-visible transition.
- **Frame / audio analyzer**: scans the recordings, extracts samples at a configurable interval, feeds them to recognizers (OCR for text overlays, speech-to-text for audio, pixel-diff for

frame health), correlates against the timeline, and emits findings.

Closure criterion: every PASS for a user-visible feature MUST be cross-checked by the analyzer against the recording + action timeline. A PASS that lacks at least one matched timeline event in the analyzer findings is treated as a §11.4 PASS-bluff.

§11.4.3 — Per-environment-topology test dispatch

Tests that depend on environment topology (presence/absence of secondary displays, microphones, network interfaces, peripheral devices, cloud services, etc.) MUST detect topology at test entry and dispatch the topology-appropriate variant. A test that runs the WRONG variant for the actual topology and PASSes is a §11.4 PASS-bluff: it claims a feature works while never having exercised it on the configuration the user actually has.

A topology-touching test that does NOT have a dispatcher AND a per-topology variant is a §11.4 violation regardless of how it "passes" on any specific configuration. Single-test-multi-topology scripts MUST gate every topology-dependent assertion behind an explicit topology check that emits SKIP-with-reason if the required topology is absent — never PASS-by-default.

§11.4.4 — Test-interrupt-on-discovery + retest-from-clean-baseline

A test cycle that *continues running past a freshly discovered defect* is itself a §11.4 PASS-bluff: it produces "all green" summaries that the operator might tag as a release while the codebase under test is known-broken at the moment those greens were recorded.

The mandatory protocol — non-negotiable:

1. **Interrupt immediately.** The moment a defect is re-discovered, re-produced, or newly identified during a test cycle, the cycle MUST stop. No "let it finish for the data" — the data is contaminated.
2. **Systematic debugging before any fix.** Identify root cause at source layer (not symptom), blast radius across related tests/features/subsystems, and regression-protection seam. Symptom patching is forbidden.
3. **Fix at root cause** per §11.4.1: source-layer fix, not symptom patch in the calling site. The fix MUST be safe (no new failure modes), minimal (no surrounding cleanup smuggled in), and non-regressive.
4. **Four-layer test coverage per fix.** Every fix lands with positive-evidence coverage in every applicable layer:
 - **Pre-build / pre-merge gate** (source-level catch)
 - **Post-build / packaging gate** (artifact-level catch)

- **Runtime / on-device test** (end-user-behaviour catch)
 - **Meta-test paired mutation** (proves the gate is not itself a bluff)
5. **Documentation MUST be updated for every fix** — Issues → Fixed migration on closure, Applied Fixes table row, user-facing guides, architecture diagrams, per-version changelog.
 6. **Rebuild the system.** Full build via the canonical build script. Skipping rebuild — even when the fix is host-only — invites stale-artifact contamination of the retest baseline.
 7. **Re-deploy on every supported target.** A target left on the pre-fix build is a confounder.
 8. **Repeat the full test suite** from the beginning on every target, sequentially per host memory cap. Partial reruns are a §11.4 violation.
 9. **No-bluff certification per cycle.** Before tagging: meta-test harness returns all gates green AND every gate's paired mutation FAILs.

§11.4.5 — Captured-evidence quality analysis

§11.4.2 mandates *captured* evidence; §11.4.5 mandates the **content** of that evidence be analyzed for quality, not merely for presence.

Audio quality analysis — every audio test that PASSes MUST verify:

1. **Presence** — non-trivial RMS amplitude in captured output.
2. **Channel count** — analyzer reports the exact channel count the test claims (2.0 stereo, 5.1 surround, etc.). Stereo downmix in a "5.1 PASS" claim is a PASS-bluff.
3. **Sample rate + bit depth** — match the codec / pipeline under test.
4. **Glitch census** — underruns, XRUNs, dropouts above tolerance MUST be explicitly classified (PASS within budget, WARN above, FAIL on hard limits). Silently ignoring counts is a PASS-bluff.
5. **Coexistence-artifact census** — radio / IPC / shared-resource contention above tolerance.

Video quality analysis — every video test that PASSes MUST verify:

1. **Presence** — captured recording has non-zero size AND decoded-frame total > 0. A 0-byte file is the canonical PASS-bluff.
2. **Routing target** — analyzer confirms video appeared on the intended display / surface.
3. **Frame health** — drop count, jitter, freeze detection, tearing.
4. **Obstruction census** — OCR scan for hostile overlays (error dialogs, sign-in dialogs, geo-restriction overlays, paywall, etc).

5. **Resolution + codec** — captured dimensions match what the test claims.

§11.4.6 — No-guessing mandate

Tests, gates, status reports, closure narratives, commit messages, and any operator-facing text **MUST NOT** use words like likely, probably, maybe, might, possibly, presumably, seems, appears to, guess, seemingly, apparently, perhaps, supposedly, conjectured, or their synonyms when describing CAUSES of test failures, system behaviour, or fix effectiveness.

Either:

1. **Prove the cause** with captured forensic evidence (logs, kernel ring buffer, kernel ramoops, structured snapshots, OS journals, strace, etc.) and state it as fact, OR
2. **Explicitly mark UNCONFIRMED + PENDING_FORENSICS** with a tracked-task ID for follow-up.

Every "X likely caused Y" sentence in the codebase or documentation is a §11.4.6 violation. Every "appears to be benign" without a concrete forensic trace is a §11.4.6 violation.

§11.4.7 — Demotion-evidence rule

A demotion from any FAIL classification (OPEN, POSSIBLE PRODUCT DEFECT, FAIL) to a lower-severity classification (INVESTIGATED, MITIGATED, RESOLVED, WORKING-AS-INTENDED) requires positive evidence captured under the SAME CONDITIONS that originally exposed the defect:

1. **Same target** — defect on Target-A needs Target-A evidence; cross-target claims need every target.
2. **Same build** — evidence captured BEFORE a relevant fix landed does not validate post-fix behaviour.
3. **Same cycle position** — a stress-soak FAIL is not refuted by an isolated-test PASS.
4. **Same load profile** — a contention-mode FAIL is not refuted by a quiescent-mode PASS.

"I cannot reproduce in isolation" is a HYPOTHESIS, not a finding. Per §11.4.6 it **MUST** be tagged UNCONFIRMED: until same-conditions retest produces positive evidence.

§11.4.8 — Deep-web-research-before-implementation

Before designing a non-trivial fix, before implementing a new feature, before declaring an architectural choice — perform deep web research to verify the chosen approach is informed by current state-of-the-art. The research surface includes:

1. **Official documentation** of the platform, framework, language, or service.
2. **Vendor technical guides** for the hardware / cloud / library.
3. **Open-source codebases** that already solved analogous problems.
4. **Coding tutorials + technical articles.**
5. **Issue trackers** for the relevant projects.

Operative rule. A fix that re-invents a wheel (or reproduces a known-broken pattern) when the open-source community has already solved the problem is a §11.4 violation by omission.

Documentation requirement. Every non-trivial fix's commit message (or accompanying entry in the project's Issues / Fixed file) **MUST** cite the research sources that informed it: at least one external link OR the literal "NO external solution found — original work".

§11.4.9 — Batch-source-fixes-before-rebuild

When working through a multi-defect closure cycle, all source-side fixes that DO NOT require runtime validation to design **MUST** be landed **BEFORE** the next artifact rebuild. The anti-pattern this mandate eliminates is Fix A → rebuild → flash → cycle → fix B → rebuild → ... which serializes operator time onto rebuild latency.

Exceptions where a fix **DOES** require interim rebuild **MUST** be documented in the fix's commit message as `REQUIRES_REBUILD:` <reason>. The default is the batch path; rebuild-now is the operator-authorized exception.

§11.4.10 — Credentials-handling mandate

Forensic anchor — direct user mandate:

"Credentials or any secret and sensitive data **MUST NOT** leak! This **MUST BE** added as the mandatory constraint into all Submodules and main project's Constitution, CLAUDE.MD and AGENTS.MD."

All credentials, secrets, API tokens, passwords, phone numbers, OAuth refresh tokens, signing keys, encryption keys, and any other authentication-or-authorization-bearing data used by test scripts, build automation, or any project tooling **MUST** be handled per the following rules without exception:

1. **No tracked-file storage.** Credentials **NEVER** live in any file that git tracks. Placeholder templates with `<replace ...>` or `EXAMPLE_VALUE_DO_NOT_USE` placeholders **ARE** allowed in `.example` files committed to show operators what keys to populate.
2. **Repository-wide ignore.** `.gitignore` **MUST** exclude all credential-bearing paths:
 - `.env`, `.env.*`, `*.env`, `.<service>.env`, `*.<service>.env`
 - `scripts/testing/secrets/*` with `.example` + `README.md` exception
3. **Runtime-load-only.** Tests load credentials **AT EXECUTION TIME** from operator-populated files under `scripts/testing/secrets/` (or per-project equivalent). If the file is missing, the test **SKIPS** with "credentials not configured for " — it does **NOT** proceed without credentials and does **NOT** use defaults.
4. **No echo / no log.** Test scripts **MUST NEVER** print, log, or include credentials in error paths, stack traces, screen recordings, or output artifacts.
5. **Per-service file separation.** One file per service keeps blast radius small.
6. **Filesystem permissions.** `.env` files are `chmod 600`, parent directory is `chmod 700`.
7. **Rotation on suspected leak.** Rotate at provider, update local files, audit captured artifacts.

The consuming project's `.gitignore` **MUST** be verified before every commit: `git ls-files --cached | grep -E "\\..env$" MUST show no real .env files (only .env.example).`

§11.4.10.A — Pre-store credential leak audit (User mandate, 2026-05-17)

Forensic anchor — verbatim user mandate (2026-05-17):

"Us these for all future testing (full automation testing) and make sure they are not leaking anywhere or get git versioned!"

[Discovered during execution: the operator-provided test credentials **ALREADY** existed in 5 tracked files dating to prior project cycles. §11.4.10 + §11.4.30 catch new commits but did not detect the pre-existing leak when the operator re-provided the same values for a new use.]

When an operator provides credentials, API tokens, signing keys, or any other secret material to be stored in the project's git-ignored configuration (`.env`, `scripts/testing/secrets/`, `secrets/`, etc.),

the agent or human storing them **MUST FIRST** execute a repo-wide audit for prior leaks of **THOSE** specific values **BEFORE** storing.

The audit **MUST**:

1. **Grep every tracked file** for the literal credential value(s). `git ls-files | xargs grep -l <value>` is the canonical form. Search **MUST** cover all file types — `.md`, `.json`, `.yaml`, `.kt`, `.go`, `.py`, `.sh`, `.sql`, build configs, docs.
2. **Grep the entire git history** for the literal credential value(s). `git log -S<value> --all --source --remotes` reveals historical commits even if the current tree is clean. A history-only leak is a §11.4.10 violation of equal severity to a tree-leak — anyone who pulled an older commit still has the value in their working copy of any branch they cloned.
3. **Report findings to the operator BEFORE storing the new value in any operator-controlled location.** The operator may then decide whether to (a) rotate the credential at the upstream provider before reusing, (b) accept the historical leak as a known-compromise and proceed, or (c) abort the storage. Storing the value without surfacing the audit is itself a §11.4 PASS- bluff at the security layer.
4. **If a leak is found:** open a forensic incident record per the project's §6/§7 sixth-law-incidents discipline (or equivalent), redact the literal values from all tracked files in-place (replace with `<redacted-per-§11.4.10>` placeholders), and record an **OPERATOR ACTION REQUIRED** for rotation per §11.4.10 sub-clause 7. The redaction commit lives on master **IMMEDIATELY**; the history- purge follow-up (`git-filter-repo` / `BFG` / equivalent + `force-push` to every upstream) requires explicit per-operation operator authorization per §9.2.
5. **Strengthen pre-push hook detection** when a previously-undetected class of literal credential is discovered. The pre-push hook's credential-pattern `grep` **MUST** be extended to catch the specific pattern class that escaped (literal usernames matched with literal passwords in the same file, well-known credential SHA-256 hashes, org-specific naming conventions for service accounts, etc.). The extension **MUST** land in the same commit as the redaction.

Pre-build gate (recommended) `CM-PRE-STORE-CREDENTIAL-AUDIT` (when implemented in consuming project) checks the commit message body of any commit that touches `.env`, `.env.example`, `scripts/testing/` `secrets/`, or equivalent for an `Audit-Pre-Stored:` stamp citing the audit's outcome. Paired mutation (§1.1) strips the stamp and asserts gate FAILs.

Composes with §11.4.10 (the core credentials mandate this extends), §11.4.30 (`.gitignore` + `no-versioned-artifacts` — overlapping enforce- ment surface), §11.4.6 (no-guessing — audit findings

stated as fact or as PENDING_FORENSICS), §11.4.7 (demotion-evidence — "I think it's not leaked" without grep evidence is a guess). Classification: universal (per §11.4.17). No escape hatch.

§11.4.11 — File-layout discipline

Project files **MUST** be organised by purpose, not by historical accident. Source code goes under canonical project roots. Tests go under canonical test directories. Logs and forensic artifacts go under operator-controlled directories (~/Documents/, qa-results/, /tmp/, OS-equivalent) — **NEVER** scattered at the repo root, **NEVER** inside working source trees, **NEVER** tracked unless they are reference assets explicitly required for evidence-replay.

Discovered drift is fixed by **moving** files to their canonical location and updating every caller — never by adding redirect shims or by leaving the misplaced copy "for backwards compatibility".

§11.4.12 — Auto-generated docs sync mandate

Every auto-generated document (Issues_Summary, API reference, build manifest, etc.) **MUST** be regenerated in the **same commit** as any edit to its source. Stale auto-generated docs are §11.4 PASS-bluffs in document form: an operator reading them gets a divergent view of project state.

All three file types **MUST** stay in sync at all times — Markdown source + HTML export + PDF export (or equivalent multi-format output the project ships). Enforced by a pre-build gate that checks mtime ordering and content hash agreement.

§11.4.13 — Out-of-band sink-side captured-evidence

Whenever a downstream consumer (HDMI sink, cloud service, monitoring target, downstream system) provides a network-accessible introspection API that reports what was actually received, the test suite **MUST** consume that report as captured-evidence for every test asserting end-to-end delivery.

The on-source-side view **ALONE** is insufficient — that is the exact "tests pass but the feature doesn't work" pattern §11.4 forbids. Sink-side reports **MUST** be:

- Identity-verified (MAC, serial, UUID match) before consumed as evidence.
- Topology-dispatched (§11.4.3) — sink-probe-unreachable → SKIP, never FAIL.

- Cross-referenced with the on-source state at a matching wall-clock instant.

§11.4.14 — Test playback cleanup mandate

A test that completes (PASS, FAIL, or SKIP) MUST leave the target in a quiescent state — no orphan playback, no orphan recording, no orphan capture, no orphan background process continuing after the test's last assertion. Tests are transient probes; their side-effects on shared target state MUST NOT outlive the test.

Mandatory protections:

1. Every test that issues a playback or capture command MUST issue the matching cleanup at test end (force-stop the app, stop the recorder, close the file descriptor, terminate the helper).
2. Cleanup is mandatory on EVERY exit path — PASS, FAIL, SKIP, error, trap, signal, parent-killed. Use shell trap '<cleanup>' EXIT or try/finally.
3. Tests MUST verify the cleanup succeeded via positive evidence (§11.4.5).
4. The orchestrator MUST run a post-test sanity check between tests and FAIL the just-completed test if it left orphan state. This blames the leaker, not the next-test victim.
5. No grace period for "the next test will clean it up" — that is precisely the §11.4 PASS-bluff pattern. Cleanup is the test's responsibility, not the next test's, not the orchestrator's.

§11.4.15 — Item-status tracking mandate

Every active item tracked in the project's Issues file MUST carry a ****Status:**** line within five lines of its heading. The status value is drawn from a closed set:

State	Meaning
Queued	In backlog, no work has started. Sub-state qualifier Queued – BLOCKED on <reason> permitted.
In progress	Active investigation or coding underway.
Ready for testing	Source-side fix landed (pre-build / meta-test gates green), waiting for the next deploy cycle.
In testing	A deploy + cycle is in flight that exercises the fix; live captured-evidence is being collected per §11.4.2 + §11.4.5.
Reopened	Item failed its runtime test cycle and is back to active work. Carries a reference to the failure-cycle artefact.

State	Meaning
Fixed (→ Fixed file)	Item closed: captured-evidence per §11.4.5 collected, runtime test PASSes, paired meta-test mutation FAILs, item migrated to the Fixed file.

Status MUST be updated as the item progresses. Every commit that changes an item's lifecycle state MUST update its Status line in the same commit.

All three Issues / Issues_Summary / Fixed file types MUST be in sync at all times (Markdown + HTML + PDF).

§11.4.16 — Item-type tracking mandate

Every active item tracked in the project's Issues file MUST carry a **Type:** line within eight non-blank lines of its heading (the same window the §11.4.15 Status audit uses). The type value is drawn from a CLOSED set of three values:

Type	Meaning
Bug	Product defect / regression / user-visible broken behaviour. The product worked before (or was expected to) and now does NOT for the end user.
Feature	New capability not previously offered to end users — a new integration, new output, new probe, new bank, new architectural surface.
Task	Internal workstream — not user-visible. Refactor, infrastructure, documentation, audit, covenant clause, gate, mutation, propagation enforcement, host-session-safety hardening. The largest class by count; the lowest-stakes default when the classification is ambiguous.

The vocabulary is CLOSED — only Bug, Feature, Task. Any other value is a violation. When ambiguous, fall back to Task.

Type tells the operator WHAT KIND of work an item is — distinct from severity (HOW URGENT) and status (WHERE IN LIFE-CYCLE). The three axes together drive ownership routing, testing strategy, release-note framing, and changelog classification.

The Issues_Summary file MUST carry the Type column for every active item. All three file types (Markdown + HTML + PDF) MUST stay in sync under the same CM-DOCS-EXPORT-SYNC discipline as §11.4.12 + §11.4.15.

Pre-build gates CM-ITEM-TYPE-TRACKING (scans Issues file for `**Type:**` presence within the audit window) and CM-COVENANT-114-16-PROPAGATION (anchor presence in every project CLAUDE.md / AGENTS.md) enforce the mandate. Paired mutations in the project's meta-test prove neither gate is a bluff gate.

No escape hatch — items that genuinely don't fit **MUST** be re-classified as `INFORMATIONAL` and excluded from the active-item set rather than carry a fabricated Type.

§11.4.17 — Universal-vs-project classification of new rules (User mandate, 2026-05-14)

Forensic anchor — direct user mandate (verbatim, 2026-05-14):

"Adding any new rules or mandatory constraints or anything relevant which should be added into Constitution, CLAUDE.MD, AGENTS.MD and relevant files **MUST BE** determined as reusable / universal VS project specific. If it is universal and reusable it **MUST BE** added into our root / main constitution Submodule, otherwise into our project level Constitution, AGENTS.MD and CLAUDE.MD (or Submodule if it is Submodule related)."

Before any new rule, mandatory constraint, covenant clause, gate declaration, or "MUST"-bearing statement is added to a project's Constitution / CLAUDE.md / AGENTS.md or to a child submodule's equivalents, the author **MUST** first classify it along this axis:

Classi- fica- tion	Definition	Destination
Uni- versal (re-usable)	The rule applies to ANY project — independent of language, framework, target platform, or domain. Examples: anti-bluff covenant, no-guessing mandate, credentials-handling, host-session safety, item-status tracking, multi-upstream push, file-layout discipline, deep-web-research-before-implementation.	This constitution submodule's Constitution.md + CLAUDE.md + AGENTS.md. Propagates to every consuming project via inheritance.
Pro- ject- specif- ic	The rule references a specific hardware target, vendor, model, SoC, vendor-fork, project-internal package name, deployment topology,	The project's own Constitution.md / CLAUDE.md / AGENTS.md (top-level), OR the affected submodule's

Classi- fica- tion	Definition	Destination
	or company-internal asset. Examples (illustrative — these are intentionally NOT in this universal file): the SoC's specific power-management quirks; a particular Android/iOS/Linux SDK behaviour; a specific app or service bundled with the project.	equivalents (when the rule scopes to that sub-module).

A rule that mentions hardware part numbers, vendor names, specific package identifiers, geographic regions, or company-internal asset names is **project-specific by definition** — it cannot be lifted into the universal layer without genericising those references first. A universal rule MAY reference patterns (e.g., "USB-HID multitouch panels") but MUST NOT name specific vendors.

Anti-bluff: the universal-vs-project classification is itself an auditable artefact. Every new rule's commit message MUST include a one-line classification statement (e.g., `Classification: universal — applies to any project tracking items through an Issues/Fixed lifecycle`). A commit that adds a rule without classification justification is a §11.4.17 violation.

Authors who are uncertain SHOULD default to project-specific (narrower scope). Lifting a project-specific rule to universal later is cheap (one merge); generalising a universal rule that turned out to leak project-specific assumptions is expensive (every consumer must update).

Pre-build gate CM-UNIVERSAL-VS-PROJECT-CLASSIFICATION audits the last N commits for rule additions and asserts each one carries a classification statement. Paired mutation strips the classification literal and asserts the gate FAILs.

§11.4.20 — Subagent-driven-by-default mandate (User mandate, 2026-05-14)

Forensic anchor — direct user mandate (verbatim, 2026-05-14):

"Make sure we ALWAYS WORK EVERYTHING subagents-driven if it is possible or applicable!"

When operating in a multi-agent runtime (Claude Code with sub-agents, Cursor with task-runners, Aider with sub-sessions, or any CLI tool that supports delegated execution), the primary agent **MUST** default to subagent delegation for any task that satisfies **AT LEAST ONE** of:

1. **Multi-step scope** — three or more discrete editing / file-creation / verification phases. Hand-off boundaries are where stalls happen; pre-planned subagent decomposition avoids them.
2. **Parallelisable work** — two or more independent tasks with no shared mutable state. Parallel subagents finish wall-clock-faster than sequential foreground work **AND** insulate the primary agent's context window from the volume of file reads.
3. **Long-running diagnostic loops** — repeated probe / re-test cycles, build-flash-cycle loops, soak tests. Subagents survive context compression boundaries that would otherwise truncate progress.
4. **Domain-specific or specialised workflows** — code review, security audit, infrastructure change review, performance triage, documentation propagation across N files. Specialised subagents (code-reviewer, iac-reviewer, general-purpose) bring pre-curated tool sets and disciplines the primary agent would re-derive from scratch.

The primary agent **SHOULD** only do foreground work when **AT LEAST ONE** of:

- The task is a single edit or single file read with no follow-up.
- The task requires conversational clarification with the operator mid-execution (subagents cannot ask the operator questions).
- The task is gating critical state (a commit, a push, a tag cascade) that must be sequenced before the next operator action.
- The task is so quick (under ~30 seconds of execution) that subagent spin-up overhead exceeds the work itself.

Anti-stall discipline. Subagents have watchdog timeouts in most runtimes (Claude Code: ~600 s of no-progress). When delegating, the parent agent **MUST**: (a) scope tightly (no "complete everything" prompts — break into 4-6 tightly-scoped tasks); (b) require **checkpoint commits** after each major task so partial progress is preserved even on stall; (c) explicitly prohibit destructive operations the subagent might attempt to "be helpful" (`git reset --hard`, `git push --force`, `--no-verify`); (d) provide explicit discipline pointers (§11.4.6 no-guessing, §11.4.10 credentials, §11.4.17 classification).

Anti-bluff applied. A subagent that returns "completed" without captured evidence in commits / outputs / artifacts is a §11.4 PASS-bluff at the multi-agent layer. The parent agent **MUST** verify subagent claims against repo state (git log, git status, post-completion gate runs) before treating the work as landed.

Coordination. When parallel subagents touch overlapping files, the parent agent **MUST** partition the work so subagents work on **non-overlapping files**. The parent's `commit_all.sh --auto-cascade` naturally bundles both subagents' dirty files into atomic commits via `git add -A` — exploit this for "forward-reference + provider" patterns where one subagent creates files another subagent references.

No escape hatch. Operating exclusively in the foreground when subagent delegation is feasible burns operator wall-clock time, risks context-window overflow on large tasks, and forfeits the parallelism that multi-agent runtimes were designed to provide. Pre-build gate CM-SUBAGENT-DELEGATION-AUDIT (when implemented per consuming project) scans recent session transcripts for multi-step foreground work that should have been delegated; paired mutation enforces the gate is not a bluff.

§11.4.18 — Script documentation mandate (User mandate, 2026-05-14)

Forensic anchor — direct user mandate (verbatim, 2026-05-14):

"Make sure that every single script inside the scripts dir (in all subdirs in depth) is fully documented and covered with full user manuals and user guides! ... Whenever is some bash script modified we **MUST** document it fully and create for it complete user guide(s) and manual(s) - if already exists make sure all of it is in sync and fully updated! No documentation ever can be out of sync with its codebase!"

Every Bash / shell / POSIX-sh script ANYWHERE in a project (anywhere under scripts/, bin/, tests/, library directories, Upstreams/, deployment hooks, CI helpers, etc. — depth-N recursive) **MUST** carry:

1. **In-source documentation block** at the top of the file:

- Purpose: one-sentence description of what the script does.
- Usage: complete invocation syntax with all flags, env vars, positional arguments, examples.
- Inputs: env vars, files read, command-line args, stdin.
- Outputs: files written, stdout/stderr behaviour, exit codes.
- Side-effects: anything that changes system state outside the script's own scratch directory.

- Dependencies: required commands (and how to install them) + required system state (e.g., "must be run as root", "must run from project root").
- Cross-references: companion guides under docs/.

2. **External user guide** under docs/scripts/<script-name>.md (Markdown). Required sections:

- **Overview** — what the script does in plain English.
- **Prerequisites** — environment + dependencies.
- **Usage examples** — copy-paste recipes for the common cases.
- **Edge cases** — unusual invocations, error conditions, how to diagnose them.
- **Internal behaviour** — for advanced users / future maintainers: what the script does step-by-step.
- **Related scripts** — companion scripts and how they compose.
- **Last verified version / date** — when the doc was last reconciled against the script source.

Whenever the script source is modified, the in-source documentation block AND the external user guide MUST be updated in the SAME commit. A commit that touches a script but leaves its documentation unchanged (or worse, lets it drift) is a §11.4.18 violation.

Pre-build gate CM-SCRIPT-DOCS-SYNC walks every *.sh and *.bash under scripts/ (or equivalent script directories), verifies a companion docs/scripts/<name>.md exists, AND verifies the doc was modified in the same commit as the script (by SHA cross-reference, or by mtime ≥ script mtime as a softer floor). Paired mutation strips the doc-sync invariant and asserts the gate FAILs.

No documentation ever can be out of sync with its code-base.

This mandate composes with §11.4.11 (file-layout discipline — docs live under docs/, scripts live under scripts/) and §11.4.12 (auto-generated docs sync — the on-disk Markdown + its rendered HTML/PDF must all stay synchronised).

§11.4.19 — Fixed-document column-alignment mandate (User mandate, 2026-05-14)

Forensic anchor — direct user mandate (verbatim, 2026-05-14):

"Make sure that Fixed document (all 3 file formats) is consistent and has the same structure and columns as Issues and Issues_Summary documents! This has to be added as detail to Constitution, CLAUDE.MD and AGENTS.MD (constitution Submodule where these information shall exist)."

Every project that maintains an Issues / open-work tracker AND a Fixed / closed-archive tracker MUST keep the two structurally aligned along the same lifecycle axes — at minimum **Status** and **Type** — so an operator reading either gets a consistent view across the entire lifecycle (open → in progress → ready for testing → in testing → reopened → fixed).

Specifically:

1. **Per-entry annotation.** Every heading in the Fixed archive document MUST carry, within 8 non-blank lines of the heading, a ****Status:**** line and a ****Type:**** line — exactly as §11.4.15 + §11.4.16 require for the Issues tracker. For Fixed entries the Status value is drawn from the **closure-set**:

- Fixed (→ Fixed.md) — fully verified on device with captured evidence per §11.4.5.
- Fixed — pending device verification — source-side fix landed, regression-protection gate wired, awaiting the next firmware build + flash + cycle for captured evidence.
- Fixed — RECLASSIFIED — item was reclassified during investigation (test-side defect, environment-only, etc.).

Type values follow §11.4.16: Bug | Feature | Task. Default on missing-annotation: Task.

2. **Auto-generated companion summary.** A Fixed_Summary.md MUST exist alongside Fixed.md, regenerated by an automation script (e.g. generate_fixed_summary.sh), and MUST mirror the column structure of Issues_Summary.md exactly:

```
| # | Level | Status | Type | One-line description |
```

The Level (severity) column uses the **original severity** the item had when it was open — so an operator can correlate a closed item with its original priority bucket. The same deterministic classification rules apply (REAL PRODUCT DEFECT / PARTIAL-or-WORKSTREAM-or-DEEP-DIVE / everything-else mapping to C / M / L).

3. **Three-format sync.** All three file types (.md, .html, .pdf) for BOTH the Fixed archive AND the Fixed_Summary MUST stay in sync at all times — same .html + .pdf export pipeline that §11.4.12 requires for Issues + Issues_Summary. The single-shot sync wrapper (e.g. sync_issues_docs.sh) MUST invoke the

Fixed_Summary generator AND export all five doc variants (Issues, Issues_Summary, Fixed, Fixed_Summary, CONTINUATION) in one operation so they all carry the same mtime.

4. **Cross-lifecycle consistency.** A status line in Issues.md that reads Fixed (→ Fixed.md) is a **migration marker**, not a self-describing closure: when an Issues.md entry resolves, it **MUST** be moved to Fixed.md in the same commit, then disappear from Issues_Summary (because Issues_Summary only enumerates OPEN items) and appear in Fixed_Summary (because Fixed_Summary enumerates CLOSED items). Per §11.4.4 fix-closure protocol + §11.4.5 captured-evidence requirement, the migrated entry in Fixed.md **MUST** carry: closure cycle, closure commit SHA, captured evidence pointer, regression-protection gate name + paired mutation reference.

Pre-build gate CM-FIXED-COLUMN-ALIGNMENT (5+ invariants):

- docs/Fixed_Summary.md exists.
- docs/Fixed_Summary.md table header line contains both Status and Type columns (column-alignment with Issues_Summary).
- mtime(Fixed_Summary.md) >= mtime(Fixed.md) (regenerated after Fixed.md edits).
- Generator script exists (generate_fixed_summary.sh or equivalent integrated branch in generate_issues_summary.sh).
- Sync wrapper invokes the Fixed_Summary generator (grep for the script name in sync_issues_docs.sh or equivalent).
- HTML + PDF exports for both Fixed and Fixed_Summary exist (docs/Fixed.html, docs/Fixed.pdf, docs/Fixed_Summary.html, docs/Fixed_Summary.pdf).

Paired mutation: strip the Status column from Fixed_Summary.md table header (or rename the generator) → gate FAILs. Enforced by meta_test_false_positive_proof.sh.

Propagation. This anchor is a §11.4.17-classified **universal** rule — it composes naturally with §11.4.12 (auto-generated docs sync), §11.4.15 (Status tracking), §11.4.16 (Type tracking) and is mandatory across every consuming project's CLAUDE.md / AGENTS.md. The propagation gate CM-COVENANT-114-19-PROPAGATION (when implemented per consuming project) enforces the anchor's presence in every covenant file.

No escape hatch. A Fixed archive that lacks Status/Type columns or whose Summary companion drifts out of sync is the exact "different lifecycles report different facts" hazard §11.4 forbids — an operator reading Issues_Summary can no longer answer "where is item X now?" by cross-referencing Fixed_Summary because the schemas diverge. Non-compliance is a release blocker regardless of context.

§11.4.21 — Operator-blocked status + self-resolution exhaustion mandate (User mandate, 2026-05-14)

Forensic anchor — direct user mandate (verbatim, 2026-05-14):

"Add into Issues and Issues_Summary new status: Operator blocked! We need another column with details in Issues document with exact details on how exactly is operator blocked issue! Before issue becomes operator blocked we MUST investigate in-depth all ways on how it can be resolved without operator's involvement - by you, or by activating any relevant mechanism for the resolution!"

Every project that maintains an Issues / open-work tracker MUST treat operator dependency as a **last-resort classification**, earned only after documented exhaustion of self-resolution paths. Routing an item to the operator without proving the agent + tooling cannot unblock it themselves is the §11.4 PASS-bluff pattern transplanted into the planning layer — the work stalls indefinitely while the agent claims "nothing more I can do."

1. Status vocabulary extension. §11.4.15's closed-set of Status values is extended with a seventh value, Operator-blocked. The full closed-set becomes:

#	Status value	Meaning
1	Queued	Awaiting work to start.
2	In progress	Active agent / developer work.
3	Ready for testing	Source-side fix landed, awaiting verification.
4	In testing	Captured-evidence cycle running.
5	Reopened	Previously closed item resurfaced (regression).
6	Operator-blocked	NEW. Cannot proceed without an operator action that the agent + available tooling cannot perform.
7	Fixed (→ Fixed.md)	Closure migration marker per §11.4.15 + §11.4.19.

2. Self-resolution exhaustion mandate. BEFORE classifying any item as Operator-blocked, the agent MUST verifiably exhaust every self-resolution path applicable to the project:

- **(a) CLI / ADB / SSH / API access** — can the work be done via any access the agent already has? (e.g. adb shell pm clear, gh api, aws ssm, kubectl exec, psql).

- **(b) Subagent delegation** — can a specialised subagent (per §11.4.20) reach further than the primary agent? (e.g. general-purpose for multi-step probing, code-reviewer for architectural blockers, iac-reviewer for infra access).
- **(c) Existing tooling** — is there a script / helper / library already in the repo that handles this case? (e.g. scripts/testing/<helper>.sh, project-specific automation).
- **(d) Captured fallback** — can the blocker be sidestepped with a synthetic event, test asset substitution, mock, or topology-aware SKIP per §11.4.3? (e.g. simulate the input, substitute a stand-in fixture, downgrade to a pre-build gate).
- **(e) Documentation + research** — per §11.4.8, has the agent consulted external sources (official docs, vendor guides, open-source codebases, issue trackers) for a self-resolution pattern the community has already solved?

Only AFTER each applicable path is **verifiably attempted and documented as exhausted** is Operator-blocked the correct classification. "I didn't try X because I assumed it wouldn't work" is a §11.4.6 no-guessing violation AND a §11.4.21 self-resolution violation.

3. Operator-Block-Details mandate. Every Status: Operator-blocked item MUST carry an ****Operator-Block-Details:**** line within 8 non-blank lines of its heading (mirroring the §11.4.15 Status placement pattern). The content MUST state ALL of:

- **WHAT** — the specific concrete action the operator must perform (verb + object + target system). Generic "the operator must investigate" is forbidden — name the action.
- **WHY** — the alternatives that were exhausted, enumerated. Each exhausted path from §11.4.21.2 above gets a one-line statement of what was attempted and why it could not unblock the item. "Subagent delegation: tried general-purpose with X scope — blocked because Y" is the bar.
- **UNBLOCK CONDITION** — the observable signal that the operator has completed the action (e.g. "operator confirms hardware rev-B installed", "operator pastes new API key into scripts/testing/secrets/.foo.env", "operator force-pushes PR #123 merge to upstream"). Without this, the agent cannot automatically detect when to re-evaluate.
- **WHO** — the handle / contact / pointer to the document where operator-side details live if questions arise (e.g. "operator: @username", "see docs/operator/<topic>.md", "vendor: support-id 12345"). Operator-blocked without WHO is operationally untrackable.

4. Issues_Summary inclusion as sortable axis. The auto-generated Issues_Summary.md (per §11.4.12 + §11.4.15) MUST include Operator-blocked as a first-class Status value in the table — the

column header is unchanged but operators can sort / filter on it deterministically. The summary generator MUST also emit a count of Operator-blocked items in any rollup line / header.

5. Periodic re-evaluation requirement. Items in Operator-blocked status MUST be re-evaluated every Nth tag-cycle (project-defined, recommended every 3rd tag cycle). Operator dependencies change over time: CI may have been added, hardware may have been swapped, automation may have matured, vendor APIs may have unlocked. An item that was correctly Operator-blocked at tag T may be self-resolvable at tag T+3. Re-evaluation MUST follow the same §11.4.21.2 exhaustion checklist and document each re-attempt.

6. Anti-bluff layer. A fake Operator-blocked (classification applied without exhausting §11.4.21.2 alternatives) is a §11.4 covenant violation at the planning layer — equivalent severity to a PASS-bluff at the testing layer. The agent's commit message introducing or maintaining an Operator-blocked classification MUST contain evidence of self-resolution attempts (the explicit "Attempted: a — exhausted because X; b — exhausted because Y; c — exhausted because Z" form).

7. Pre-build gates (recommended, per consuming project):

- **CM-ITEM-OPERATOR-BLOCKED-DETAILS** — every heading whose Status line equals Operator-blocked has an `**Operator-Block-Details:**` line within 8 non-blank lines. Paired mutation strips the details line → gate FAILs.
- **CM-OPERATOR-BLOCKED-SELF-RESOLUTION-AUDIT** — every NEW Operator-blocked item introduced in a commit carries an "Attempted: ..." audit trail (either in the Issues.md entry body OR in the commit message). Paired mutation introduces an Operator-blocked item without the audit trail → gate FAILs.

Propagation. This anchor is a §11.4.17-classified **universal** rule — it composes with §11.4.15 (Status tracking), §11.4.16 (Type tracking), §11.4.19 (Fixed-document column alignment), §11.4.12 (auto-generated docs sync), §11.4.20 (subagent delegation as a self-resolution path), §11.4.8 (research-before-implementation as a self-resolution path), §11.4.6 (no guessing about what the operator "would have to do"). Propagation gate CM-COVENANT-114-21-PROPAGATION (when implemented per consuming project) enforces the anchor's presence in every CLAUDE.md / AGENTS.md across the parent + every owned submodule + every dependency.

No escape hatch. Items that legitimately need operator intervention are real and unavoidable — hardware swaps, vendor contracts, physical-world inputs, account credentials, irreversible business decisions. But the classification must be **earned** via doc-

umented exhaustion. An Operator-blocked heading without an audit trail of self-resolution attempts is a §11.4 release blocker regardless of context.

§11.4.22 — Document-sync commit discipline (User mandate, 2026-05-14)

Forensic anchor — direct user mandate (verbatim, 2026-05-14):

"For Issues, Issues_Summary and Fixed docs (and all its exports) we **MUST** commit and push (only them) as soon as they are updated (synced). Continuation doc and other similar / relevant documentation **MUST** be committed and pushed too! Like this we will always have up to date status of working items without need to do full commit and push of everything if that is not possible to do!"

Classification: §11.4.17-classified **universal** — every project that tracks work items through an Issues / Fixed lifecycle has the same problem, so the discipline lives in the Constitution and every consuming project implements its own wrapper.

The defect this anchor closes. Until this anchor existed, the only way to push a status update was the full-tree commit wrapper. When the working tree had unrelated heavy churn (large submodule diffs, in-flight rebase, partial-network conditions, ongoing build), operators had two bad options: (a) wait until the heavy work finishes — which can be hours — leaving the doc-status stale to every other agent; (b) skip the doc-status update entirely — which is a §11.4.4 documentation-drift violation. Neither option is acceptable.

The mandate. Every project under this Constitution that ships a status-tracking doc set **MUST** provide a **lightweight commit path** distinct from the full-repo commit wrapper. The lightweight path stages, commits, and pushes **only** the status-tracking doc set:

1. The active issue tracker (docs/Issues.md in ATMOSphere's layout; the project's equivalent file elsewhere) and its HTML + PDF exports.
2. The auto-generated issues summary (docs/Issues_Summary.md) and its HTML + PDF exports.
3. The fixed-bug archive (docs/Fixed.md) and its HTML + PDF exports.
4. The auto-generated fixed summary (docs/Fixed_Summary.md) and its HTML + PDF exports.
5. The cross-session continuation document (docs/CONTINUATION.md, per §12.10) and its HTML + PDF exports.

6. Any auto-generated audit artifact (docs/anti_bluff_audit.md or equivalent) that pairs with the above.

The lightweight wrapper **MUST**:

1. **Auto-invoke the project's export-regeneration pipeline first** — so Markdown + HTML + PDF are all synchronised before push. (Skipped only when an explicit `--no-sync` flag is passed AND the operator just ran the pipeline manually.)
2. **Stage ONLY the doc-set files** — `git add` of an explicit file list, NEVER `git add -A` (which would catch unrelated WIP churn).
3. **Use a separate flock** disjoint from the full-tree commit wrapper's lock — so the two can run in parallel without contention on disjoint file sets.
4. **Push to every parent-repo remote** (reusing the project's push-all driver where available).
5. **Exit code semantics** — 0 success, 1 validation failure, 2 lock contention, 3 nothing-to-commit (informational, not an error — so the wrapper can be wired into automation that tolerates no-op outcomes).

The lightweight wrapper **MUST** be invocable either standalone OR via a flag on the full-tree wrapper (e.g. `commit_all.sh --docs-only`) so operators have a single mental model.

§9 preflight inheritance. The lightweight wrapper inherits the parent project's §9 preflight discipline — if `meta_test_*` is mid-mutation or `*.mut.bak` files exist, the wrapper refuses to run, same as the full-tree wrapper.

Pre-build gates (recommended, per consuming project):

- **CM-COMMIT-DOCS-EXISTS** — verifies the lightweight wrapper exists + is executable, its external user guide (per §11.4.18) exists, the full-tree wrapper advertises the delegation flag, and the wrapper's doc-set enumeration lists $\geq N$ entries (N depends on project — ATMOSphere's set is 15). Paired mutation strips the doc-set array → gate FAILs.

Propagation. Composes with §11.4.12 (export-sync invariant — HTML + PDF in sync with Markdown after every edit), §11.4.15 (item status tracking — Status lines must be visible quickly), §11.4.18 (every script ships with an in-source doc block + an external user guide), §12.10 (CONTINUATION document maintenance — the lightweight wrapper is one of the mechanisms that keeps CONTINUATION current).

No escape hatch. The discipline exists because doc-status drift is itself a §11.4 PASS-bluff pattern at the documentation layer: a green-looking `Issues_Summary.html` that doesn't reflect Markdown reality is the same class of defect as a passing test that doesn't re-

flect runtime reality. Operators who can't run the lightweight wrapper for some reason **MUST** run the full-tree wrapper and accept the heavier cost — the doc-status drift is non-negotiable.

§11.4.23 — Visual-cue & grouping mandate for Issues docs (User mandate, 2026-05-14)

Forensic anchor — direct user mandate (verbatim, 2026-05-14):

"We **MUST** make sure that Issues, Issues_Summary and Fixed docs and its exported files (PDFs and HTMLs) have one small improvement: we **MUST** introduce some background coloring for cells of item type and status! Also, we **MUST** group items by the status! ... Base colors for types would be: bug - background pale red, task - background pale blue, feature - background pale yellow. However, changing the status affects the color of the cell of the type and the status cell background color: queued - no color, no effect, fixed - both cells pale green, in progress - only status cell is pale green, reopened - status cell is pale red, blocker - status cell is red (not pale, however **MUST BE** still readable), anything else please follow the same logic!"

Classification: §11.4.17-classified **mixed** — the discipline (visual cues + status grouping for tracked-item docs) is universal across every project that maintains an Issues / Fixed lifecycle. The implementation (CSS classes, HTML post-processor, weasyprint integration) is project-specific because each project's export toolchain differs (pandoc, asciidoctor, sphinx, etc.).

The defect this anchor closes. A long, multi-column tracked-item table where every row looks identical at first glance is a §11.4 operational-readability defect — operators have to *read* every Status column to identify what is queued vs in-progress vs fixed. With dozens to hundreds of items, this is slow enough that operators inevitably skim, and the doc effectively becomes write-only. Color cues + status grouping make at-a-glance triage possible.

The mandate. Every project under this Constitution that ships tracked-item docs (per §11.4.15) **MUST** apply visual-cue coloring **AND** status grouping to those docs' HTML + PDF exports. The Markdown source stays free of color noise (Markdown is the canonical text), but the HTML + PDF exports **MUST** be enriched in a post-processing stage:

Type cell base colors:

Type	Background
Bug	pale red (#FFE5E5 or equivalent — ~5% red saturation)
Task	pale blue (#E5F0FF)
Feature	pale yellow (#FFF8DC)

Status cell colors (override the Status column; Fixed also overrides Type cell):

Status	Status cell	Effect on Type cell
Queued	no color (transparent)	keeps base type color
In progress	pale green (#D4F1D4)	keeps base type color
Ready for testing	pale green-blue (#C6EAEF)	keeps base type color
In testing	pale green-yellow (#E7F4D6)	keeps base type color
Reopened	pale red (#FFCCCC)	keeps base type color
Fixed	pale green (#A8E6A8)	also pale green
Operator-blocked / Blocker	vibrant red (#FF4444) with white text for readability	keeps base type color

Status grouping: items in the rendered table MUST be grouped by Status, emitting an H3-class heading for each Status group with the item count. Group order (most-actionable first; closed last):

1. Operator-blocked / Blocker
2. In testing
3. Ready for testing
4. In progress
5. Reopened
6. Queued
7. Fixed

This ordering surfaces the items requiring operator attention at the top of the doc; closed/archived items sink to the bottom.

Print-fidelity requirement. The CSS MUST declare print-color-adjust: exact (or the project's renderer's equivalent) so PDF exports preserve the cell backgrounds. A weasyprint default-rendered PDF that strips colors is a §11.4 export-drift defect — HTML and PDF MUST be visually equivalent.

Pre-build gates (recommended, per consuming project):

- **CM-DOC-COLOR-GROUPING-DISCIPLINE** — verifies the project's CSS carries the type+status class set, the post-processor exists and is executable, the sync wrapper invokes it, AND after sync the rendered HTML carries the grouping-heading + per-cell color classes (the captured-evidence proof — without this last invariant a stub post-processor could silently pass the static gate). Paired mutation strips a Status class literal from CSS → gate FAILs.

Propagation. Composes with §11.4.12 (export-sync invariant — HTML + PDF in sync with Markdown after every edit), §11.4.15 (item status tracking — every active item carries a Status line from the closed-set vocabulary), §11.4.19 (Fixed_Summary column-aligned companion), §11.4.22 (lightweight commit path for doc-set updates).

No escape hatch. Color cues are not optional polish — they are the operational-readability seam that converts a long tracked-item table from a write-only Markdown blob into a self-triaging document.

§11.4.24 — Build-resource stats tracking mandate (User mandate, 2026-05-14)

Forensic anchor — direct user mandate (verbatim, 2026-05-14):

"We need to incorporate through the Containers Submodule we use to run our System build Container the following mechanism safely: during its working lifetime we **MUST** track in proper Markdown document exported into PDF and HTML stats on System resources use! What was the peak and the minimum **EVER** the Container / System building process used! ... In top of the document we **MUST** have this ever values. ... After this we **MUST** present properly sorted divided by version tags names all build processes we were running with notes if the process completed with success or not, and resources usage during the process! Besides min and max values ever and per build iteration we **MUST** have for each resource we have average values — average memory usage, average CPU usage, and all other parameters IO and other resources!"

Classification: §11.4.17-classified **mixed** — the discipline of tracking host-side build-resource usage with min / max / mean / p95 per-build PLUS ever-values across all builds in a versioned Markdown + HTML + PDF triple is universal across every long-

build project (AOSP, kernel, large monorepo, ML model training, multi-hour data pipelines). The implementation (registry path, monitor script name, exporter wiring) is project-specific.

The defect this anchor closes. Long builds (multi-hour AOSP builds, ML training runs, large monorepo CI) consume highly variable resource profiles over their lifetime — soong_build's 33 GB peak coexists with quiescent linker-only stretches at <2 GB. Without per-build sampling + ever-values, operators have NO empirical basis to (a) size containers correctly, (b) detect resource regressions across versions, (c) prove which build iteration was the OOM-killer's trigger, (d) reason about parallelism caps (cf. §12.7-j2 hard cap whose forensic basis would have been one full Stats.md generation earlier had this discipline been in place). Memory pressure debugging without time-series data is the bluff this anchor forbids.

The mandate. Every project under this Constitution with a build exceeding **1 minute wall-clock** MUST:

1. Run a host-side resource sampler for every build. The sampler runs as a sibling background process (not inside the build's own process tree), reads /proc/meminfo + /proc/loadavg + /proc/stat

- /proc/diskstats (or platform equivalents on non-Linux) at a fixed interval (recommended 5 s default — fine-grained enough to catch seconds-long peaks; coarse enough to keep itself <5% CPU and <50 MB RSS). Samples written as TSV.

2. Compute per-build summaries on stop. Per metric (memory used, CPU%, load average, disk read/write): **min, max, mean, p95**. p95 is the 95th-percentile sample value — required because mean alone hides extended-peak behaviour (a 2 h build with one 33 GB soong_build peak has mean $\approx$ 18 GB but p95 $\approx$ 32 GB; the latter is what operators must size for).

3. Append per-build summaries to a registry. One TSV row per build (build_id, status SUCCESS/FAIL/UNKNOWN, start/end timestamps, per-metric min/max/mean/p95, total disk read/write). The registry is the single source of truth — the Markdown report is derived.

4. Maintain ever-values across ALL builds. Min / max / mean across every tracked build, computed on every Markdown regeneration from the registry. Surface at the **top** of the report per User mandate verbatim.

5. Markdown + HTML + PDF triple. Stats.md (auto-generated), exported to Stats.html + Stats.pdf through the project's normal export pipeline. Triple stays in sync per §11.4.12. Committed via the project's lightweight doc-sync wrapper per §11.4.22.

6. Sort per-build entries by recency (most recent first) AND, where applicable, **group by version tag.** Operators reading the report want the latest build's profile at the top and the historical sweep underneath.

7. Track status per build. SUCCESS / FAIL / UNKNOWN — and if FAIL, capture the reason (exit code, OOM, ANR, etc.). A FAIL build's resource profile is the most operationally interesting one in the report — never silently drop FAIL entries.

8. Performance budget for the sampler itself. <50 MB RSS, <5% CPU. The monitor MUST NOT itself contribute to the resource pressure it is measuring (Heisenberg-class observer effect at scale). Pure /proc reads + awk arithmetic is the reference implementation; vmstat / pidstat acceptable; psrecord / heavy-Python-import samplers are forbidden.

9. Survive build failures. The stop hook MUST be called from both the success AND failure paths of the build wrapper so FAIL builds still produce a row. Hooking only the success path is a PASS-bluff at the telemetry layer.

Pre-build gate (recommended, per consuming project):

- **CM-BUILD-RESOURCE-STATS-TRACKER** — verifies (a) the monitor script exists + executable, (b) the Stats.md target file exists, (c) the build wrapper invokes start AND stop, (d) the doc-sync wrapper enumerates the Stats.{md,html,pdf} triple, (e) the exporter advertises the build-stats slug. Paired mutation hides the monitor script aside → gate FAILs.

Propagation. Composes with §11.4.12 (export-sync invariant — HTML + PDF in sync with Markdown), §11.4.18 (script-documentation discipline — the monitor ships with an external user guide), §11.4.22 (lightweight doc-sync commit wrapper enumerates the Stats.{md,html,pdf} triple), §12.6 / §12.7 / §12.9 (host-safety + containerized-build envelope whose forensic anchors are the empirical motivation for this telemetry).

No escape hatch. Build-resource tracking is not optional polish — it is the operational-evidence seam that converts post-mortem "the build OOM'd, no idea why" into "build X at git-SHA Y peaked at Z GB at minute N, which is W% above the rolling p95". The discipline pays for itself the first time it diagnoses a build-resource regression.

§11.4.25 — Full-Automation-Coverage Mandate (User mandate, 2026-05-15)

Forensic anchor — verbatim user mandate (2026-05-15):

"Make sure that every feature, every functionality, every flow, every use case, every edge case, every service or application, on every platform we support is covered with full automation tests which will confirm anti-bluff policy and provide the proof of fully working capabilities, working implementation as expected, no issues, no bugs, fully documented, tests covered! Nothing less than this does not give us a chance to deliver stable product! This is mandatory constraint which **MUST BE** respected without ignoring, skipping, slacking or forgetting it!"

Operative rule. For every consuming project under this Constitution, no feature, functionality, flow, use case, edge case, service, or application on any supported platform may be considered **deliverable** until it is covered by automation tests that collectively prove six invariants:

1. **Anti-bluff posture (per §7.1 + §11.4):** every assertion carries captured runtime evidence; metadata-only / configuration-only / grep-based / absence-of-error PASSes are forbidden.
2. **Proof of working capability:** the user-visible behaviour is exercised end-to-end on the target platform topology (per §11.4.3), not in a mock or in-memory facsimile.
3. **Working implementation as expected:** assertions match the product's documented promise (in user manual, README, specs), not an implementation-detail back-door.
4. **No issues, no bugs:** the test suite is the canonical seam for surfacing defects — passing without producing defect signals means defects do not exist or have been previously surfaced, tracked (per §11.4.15 / §11.4.16), and closed.
5. **Fully documented:** the feature has a user-facing doc entry (per §11.4.18 for scripts, and project-level user-manual coverage for everything else); the doc is kept in sync with the tests (per §11.4.12).
6. **Tests-covered (the four-layer floor per §1):** pre-build presence-of-change gate, post-build artifact-shipped gate, runtime / integration / on-device gate, AND meta-test paired mutation that proves the runtime gate catches the break.

Cross-cutting reach. This mandate is **universal** — it applies to every project consuming this Constitution, every feature surface they expose (HTTP endpoints, CLI commands, slash commands, IPC channels, plugins, hooks, MCP servers, agents, providers, integrations, GUI flows, mobile flows, scheduled jobs), and every supported platform (Linux, macOS, Windows, iOS, Android, AuroraOS, HarmonyOS, embedded, containers, headless servers, kiosk, etc.). A project that ships a feature without satisfying all six invariants is **not delivering a stable product**, irrespective of how green its summary line looks.

Coverage audit. Consuming projects MUST publish a coverage ledger (matrix of: feature × platform × invariant-1..6 × status) that is regenerated as part of the release-gate sweep. The ledger itself is documented (per §11.4.18 / §11.4.12) and committed via the §11.4.22 lightweight doc-sync wrapper. Gaps in the ledger (UNCONFIRMED: / PENDING: / BLOCKED: cells) MUST cite a tracked work item per §11.4.15 + §11.4.16; rows that quietly omit a platform are §11.4.25 violations.

Composition. §11.4.25 explicitly stacks on top of §1 (four-layer test-coverage floor), §1.1 (false-positive immunity), §7.1 (positive-evidence-only validation), §11.4.1 (FAIL-bluffs forbidden), §11.4.2 (recorded-evidence requirement), §11.4.3 (per-environment-topology dispatch), §11.4.6 (no-guessing), §11.4.15 / §11.4.16 (status + type tracking), §11.4.17 (universal-vs-project classification — this rule is universal), §11.4.18 (script documentation), §11.4.20 (sub-agent delegation when the work is multi-step), §11.4.22 (lightweight doc-sync). It does NOT supersede them; it forecloses the loophole "the feature works locally for me, ship it".

Classification: universal (per §11.4.17). No escape hatch. Severity-equivalent to a §11.4 PASS-bluff at the release-gate layer — a project claiming "Done" without honoring §11.4.25 is making a false claim regardless of how the work-item tracker labels the row.

§11.4.26 — Constitution-Submodule Update Workflow Mandate (User mandate, 2026-05-15)

Forensic anchor — verbatim user mandate (2026-05-15):

"Every time we add something into our root (constitution Submodule) Constitution, CLAUDE.MD and AGENTS.MD we MUST FIRST fetch and pull all new changes / work from constitution Submodule first! All changes we apply MUST BE committed and pushed to all constitution Submodule upstreams! In case of conflict, IT MUST BE carefully resolved! Nothing can be broken, made faulty, corrupted or unusable! After merging full validation and verification MUST BE done!"

Operative rule. Before ANY agent or operator modifies the constitution/Constitution.md, constitution/CLAUDE.md, or constitution/AGENTS.md files of a project that consumes this Constitution as a submodule, the agent or operator MUST execute the following pipeline in order, with NO step skipped:

1. **Fetch + pull first.** From inside the constitution/ submodule worktree, run `git fetch <every-configured-remote>` followed by `git pull --ff-only origin <branch>` (or `--rebase` if non-FF-mergeable; **never** `--strategy=ours` / `--allow-unrelated-histories` without explicit operator authorization). The submodule MUST be at upstream tip BEFORE any local edit is applied.

2. **Apply the change.** Edit the relevant file(s). The edit **MUST** classify itself per §11.4.17 (universal vs project-specific) — only universal additions belong in the constitution submodule; project-specific clauses belong in the consuming project's own governance files. The edit **MUST** include the verbatim user mandate (if it originated from one) as a forensic anchor.
3. **Validate before commit.** Run the constitution submodule's `meta_test_inheritance.sh` (or equivalent) to confirm the inheritance chain still resolves. Verify no governance file was left with merge-conflict markers (`<<<<<<<, =====, >>>>>>>`). Verify all three governance files (Constitution + CLAUDE + AGENTS) cross-reference the new clause consistently.
4. **Commit + push to ALL upstreams.** Stage only the governance files (NEVER `git add -A` inside the constitution submodule — stray local artefacts **MUST NOT** enter governance). Commit with a message that cites the user mandate (verbatim quote) + the classification line per §11.4.17. Push to **every** configured remote of the constitution submodule. A commit that lives on one upstream but not others is a §11.4.26 violation equivalent to a §2.1 multi-upstream-push violation.
5. **Conflict resolution.** If `pull --ff-only` reports non-fast-forward, the merge **MUST** be performed carefully: inspect both sides, preserve the union of governance content (no clause silently dropped), re-classify per §11.4.17, validate per step 3. Force-push to "make conflicts go away" is **FORBIDDEN** (§9.2). Nothing about the constitution may be broken, made faulty, corrupted, or rendered unusable by the merge.
6. **Post-merge validation + verification.** After the push lands, re-clone (or `git submodule update --remote --init`) in a throwaway worktree and re-run the consumer project's inheritance-cascade verifier (e.g. `scripts/verify-governance-cascade.sh`) to confirm the new clause reaches every owned submodule per CONST-047. Any cascade gap **MUST** be closed in the same change-window.
7. **Update the consuming project's pointer.** The consuming project's `.gitmodules`-tracked submodule pointer **MUST** be bumped to the new constitution HEAD in the **SAME** commit as any downstream cascade work; out-of-sync submodule pointers are a §11.4.26 violation.

Operational scope. This workflow applies regardless of who initiates the change (operator, primary agent, subagent per §11.4.20, automated lint suggestion). The workflow **CANNOT** be shortcut by "I'll fetch later" or "I'll push to the other upstreams in the next commit". The constitution is the **single source of truth** for every project that imports it; allowing it to fragment across upstreams is the structural equivalent of a §11.4 PASS-bluff at the governance layer.

Cross-cutting reach. §11.4.26 composes with: §2 (single-entry-point commit wrapper), §2.1 (multi-upstream push), §3 (submodule changes propagate through submodule commits first), §9.1 /

§9.2 (data-safety + force-push authorization), §11.4.17 (universal-vs-project classification), §11.4.22 (lightweight doc-sync), §11.4.25 (full-automation coverage — the post-merge validation step is itself a form of automation coverage). It does NOT supersede them.

Classification: universal (per §11.4.17). No escape hatch. A constitution-submodule change that violates §11.4.26 is a release blocker for every consuming project, equivalent in severity to a force-push without §9.2 authorization.

§11.4.31 — Submodule-Dependency-Manifest Mandate (User mandate, 2026-05-15)

Forensic anchor — verbatim user mandate (2026-05-15):

"We MUST HAVE mechanism for each Submodule to determine / know what are its Submodule dependencies so new projects or palces we are incorporate them can add these Submodules to the project root and make them available! Suggested idea is configuration file with expected Submodules Git ssh urls perhaps? New project can read it, and recursively add each Submodule to the root of the project and install / expose it to everyone. This MUST be analyzed and applied. We MUST apply the best strategy for this which can be easily executed just by following our root Constitution, AGENTS.MD and CLAUDE.MD! Process this, extend out Constitution, AGENTS.MD and CLAUDE.MD with mandatory instructions and then process project root and all Submodules deep recursively so proper configuration Submodules dependency files are created! Document EVERYTHING and cover with all supported test types! Any kind of bluff is strictly forbidden! All wotk MUST come with mechanism for validation and verification by creating proper proofs for all critical points!"

Operative rule. Every owned-by-us submodule MUST ship a machine-readable, version-controlled **dependency manifest** at the canonical path `helix-deps.yaml` (or `helix-deps.json` / `helix-deps.toml` if the submodule's ecosystem strongly prefers a different serialisation — but only one canonical file per submodule, and its name MUST appear in the submodule's `README.md` + governance trio).

Manifest schema (CONST-051(C)-aligned):

```
# helix-deps.yaml
# Declares this submodule's own-org dependencies. Consuming
# projects
# read this manifest recursively and add each declared dependency
# to
# their root at <root>/<name>/ or <root>/submodules/<name>/ per
```



```

# CONST-051(C). Nested own-org submodule chains are FORBIDDEN –
  this
# manifest is the bridge.

schema_version: 1
deps:
  - name: Challenges                                # canonical
    name (will become snake_case per §11.4.29)
    ssh_url: git@github.com:vasic-digital/Challenges.git
    ref: main                                       # branch or
    pinned tag
    why: "Cross-cutting Challenges + Panoptic browser harness"
    layout: flat                                  # 'flat' =
    <root>/<name>/; 'grouped' = <root>/submodules/<name>/
  - name: HelixQA
    ssh_url: git@github.com:HelixDevelopment/HelixQA.git
    ref: main
    why: "Anti-bluff QA orchestration + autonomous-session driver"
    layout: flat

transitive_handling:
  # Each declared dep itself ships a helix-deps.yaml. The
    incorporator
  # tooling MUST recurse – top-level project gets the union of all
  # transitively-declared deps, flattened to root.
  recursive: true

  # When two submodules declare the same dependency at different
  # refs, CONFLICT – operator MUST resolve before incorporation
  # proceeds. The incorporator aborts on conflict (never silently
  # picks one).
  conflict_resolution: operator-required

language_specific_subtree: false                # set true for Android/
  Kotlin/Apple
  # roots (per §11.4.29
  exception);
  # excludes inner subtree
  from
  # snake_case enforcement.

```

Tooling contract. A consuming project MUST be able to bootstrap its entire own-org dependency graph by:

1. Running `incorporate-submodule <ssh-url>` (canonical name; lives in the constitution submodule's scripts/ or in a parent project's bin path).
2. The script:
 - Adds the supplied submodule at its declared canonical path (per CONST-051(C) flat vs grouped layout).
 - Reads the newly-added submodule's `helix-deps.yaml`.

- For each declared dep, checks if it already exists at the consuming project's root; if missing, recurses (incorporate-submodule on the dep's `ssh_url`).
- On conflict (same name declared at different ref by two submodules), aborts with a directed error pointing the operator at the conflicting declarations.
- Emits a final manifest-of-manifests file at `<root>/helix-manifest.yaml` listing every submodule + its declared deps, for audit + reproducibility.

Anti-bluff guarantee. Every manifest **MUST** be paired with a **verification proof**: a Challenge script (per §11.4.27 + CONST-050(B)) that:

- Bootstraps a throwaway consuming project from scratch in a temp directory.
- Runs `incorporate-submodule` against the manifest under test.
- Verifies the produced submodule layout matches the manifest's declarations (every dep present at its declared layout path; no extras; no missing).
- Runs the submodule's own test suite against the bootstrapped layout; asserts pass.
- Captures wire evidence (per §11.4.2) of every step.

A manifest without this verification proof is a §11.4.31 violation of equal severity to a §11.4 PASS-bluff at the dependency-graph layer.

Cascade requirement. Every owned-by-us submodule **MUST** ship `helix-deps.yaml` at its root, recursively (sub-submodules of submodules ship their own). The constitution submodule itself ships a manifest declaring its own deps (currently empty for the universal Constitution; project consumers may have project-specific extensions). The verifier (`scripts/verify-governance-cascade.sh` or its successor) **MUST** check every owned submodule for manifest presence.

Composition. §11.4.31 directly enables §11.4.28 / CONST-051(C) flat-layout enforcement: nested own-org submodule chains can be mechanically flattened because each submodule declares what it needs, and the incorporator places those deps at the root. Composes with §1 (manifest schema is itself tested for parse + validation), §3 (submodule-first commit discipline applies to manifest changes too), §11.4.12 (manifest changes regenerate any derived docs/diagrams), §11.4.17 (universal — no project-specific assumptions in the manifest format), §11.4.18 (manifest documented in script-doc + external user guide), §11.4.20 (subagent delegation for cross-submodule manifest authoring), §11.4.25 (manifest presence in coverage ledger), §11.4.26 (constitution-update workflow when extending manifest schema), §11.4.27 (manifest test matrix), §11.4.28 (this rule is its operational complement), §11.4.29 (mani-

fest use snake_case names + canonical paths), §11.4.30 (manifest is tracked source — not a build artefact), CONST-047 (manifests cascade recursively).

Classification: universal (per §11.4.17). No escape hatch. Severity-equivalent to a §11.4 PASS-bluff at the dependency-graph layer.

§11.4.32 — Post-Constitution-Pull Validation Mandate (User mandate, 2026-05-15)

Forensic anchor — verbatim user mandate (2026-05-15):

"Every time we fetch and pull new changes on constitution Submodule we MUST process the whole project and all Submodule (deep recursively) for validation and verification taht every single rule or mandatory constraint is followed and respected! If it is not, IT MUST BE!"

Operative rule. Whenever a consuming project's constitution submodule is fetched + pulled with **any** content change (rule addition, rule revision, gate addition, anchor reference, version bump), the consuming project MUST execute a full-project + recursive-submodule validation sweep BEFORE the new constitution HEAD is treated as canonical for any other work.

Validation sweep contract. The sweep is implemented as scripts/verify-all-constitution-rules.sh (canonical name) which:

1. Re-runs the existing governance-cascade verifier (scripts/verify-governance-cascade.sh) covering every §11.9 + CONST-* anchor across every owned submodule (recursive per CONST-047).
2. For each rule whose enforcement gate is implementable programmatically (e.g., CONST-053 .gitignore-pattern audit; CONST-051(C) nested-own-org-chain audit; CONST-052 case-conformance audit; CONST-050(A) mock-path-from-production-code audit; CONST-035 anti-bluff smoke-scan), the sweep runs the corresponding gate against the post-pull tree.
3. Any failure produces a directed FAIL entry naming the rule (e.g., FAIL: CONST-053 – *.log tracked at HelixCode/foo.log)
 - the canonical fix.
4. Failures populate the project's Issues tracker per §11.4.15 with Status: Reopened (since a previously-passing audit now fails) and Type: Bug (since real codebase state violates the constitution).
5. The agent or operator MUST resolve every FAIL before treating the new constitution HEAD as canonical — closure of each reopened item per the existing §11.4 anti-bluff covenant (positive-evidence-only, captured wire evidence).

Pull-time invocation. `git submodule update --remote constitution` MUST trigger the sweep automatically (post-update hook OR the operator's commit wrapper invokes it as part of any commit that advances the constitution submodule pointer). Operator-explicit manual invocation MUST also be available (`./scripts/verify-all-constitution-rules.sh`).

Anti-bluff guarantee. A sweep that exits PASS without actually running every implementable gate is a §11.4.32 violation. The sweep's own meta-test (paired mutation, §1.1) MUST plant a known violation of each enforced gate and assert the sweep reports FAIL for the planted gate.

Composition. §11.4.32 is the **enforcement engine** for every other §11.4.x and CONST-NNN rule. Without it, new rules cascade as anchors but never get enforced in the codebase. Composes with every rule that has a programmatic gate: §1, §1.1, §11.4.10, §11.4.12, §11.4.15, §11.4.16, §11.4.18, §11.4.20, §11.4.22, §11.4.24, §11.4.25, §11.4.26, §11.4.27, §11.4.28, §11.4.29, §11.4.30, §11.4.31, CONST-035, CONST-038, CONST-042, CONST-043, CONST-044, CONST-045, CONST-046, CONST-047, CONST-048, CONST-049, CONST-050, CONST-051, CONST-052, CONST-053, CONST-054.

Classification: universal (per §11.4.17). No escape hatch. Severity-equivalent to a §11.4 PASS-bluff at the constitutional- enforcement layer — without §11.4.32, every other rule is a decorative anchor rather than an enforced gate.

§11.4.30 — .gitignore + No-Versioned-Build-Artifacts Mandate (User mandate, 2026-05-15)

Forensic anchor — verbatim user mandate (2026-05-15):

"every project module, every Submodule, every service and application MUST HAVE proper .gitignore file! We MUST NOT git version build artifacts, cache files, tmp files, main .env file(s) or any files containing sensitive data, API keys or token! Any build derivative which we can recreate by executing proper mechanism for generating MUST NOT be versioned! We MUST pay attention what is going to be committed every time we are preparing to execute commit! If any violation is detected it MUST be fixed before commit is executed!"

Operative rule. Every project module, owned-by-us submodule, service, and application under this Constitution **MUST** ship a proper `.gitignore` covering its full set of forbidden-from-version-control patterns. The following file/directory classes **MUST** NEVER appear in version control:

1. **Build artefacts** — anything produced by a build / compile / package step that can be regenerated from sources:
 - Binaries (`/bin/`, `/build/`, `/dist/`, `/out/`, `target/`, `*.exe`, `*.dll`, `*.so`, `*.dylib`, `*.a`, `*.o`, `*.class`, `*.pyc`).
 - Generated source files where the generator is committed (e.g. `protobuf.pb.go` may be checked in OR ignored — project decides — but never both).
 - Bundled assets where the bundler is committed.
2. **Cache files** — anything a tool regenerates on demand:
 - `__pycache__/`, `.pytest_cache/`, `.mypy_cache/`, `.ruff_cache/`, `node_modules/`, `.next/`, `.nuxt/`, `.cache/`, `.gradle/`, `.idea/cache/`, `.vscode-test/`, `target/`, `.terraform/`, `language-server` caches.
3. **Temp files** — `*.tmp`, `*.swp`, `*.swo`, `*~`, `.DS_Store`, `Thumbs.db`, IDE backup files, `*.orig`, `*.rej`.
4. **Sensitive-data files** — anything containing credentials, tokens, keys, or personal data:
 - `.env`, `.env.*` (allow `.env.example` / `.env.sample` / `.env.template` with placeholder values only — never real secrets even as examples).
 - `*.pem`, `*.key`, `*.crt`, `*.p12`, `*.pfx`, `id_rsa*`, `id_ed25519*`, `*.kdbx`, `.netrc`, `secrets/` directory trees.
 - `api_keys.sh`, any file containing `BEGIN PRIVATE KEY`, credential tokens, or session cookies.
5. **Generated reports / logs** — `*.log`, `coverage.out`, `*.coverage`, `htmlcov/`, `*.gcda`, `*.gcno`, screenshots/ recordings that aren't reference assets.
6. **OS / IDE / personal-state files** — `.idea/`, `.vscode/` (except shareable `.vscode/settings.json` etc. if explicitly project-shared), `.history/`, `.svn/`, editor-state files.
7. **Test playback artefacts** (§11.4.14) — every test's runtime capture goes under an ignored evidence directory unless the capture IS the reference asset.

Anti-bluff invariant. Per CONST-035 / §11.4 the presence of a `.gitignore` line alone is not sufficient — the project **MUST** also verify that no file matching the forbidden patterns is currently

tracked. A .gitignore that lists *.log while app.log sits tracked in the repo is a §11.4.30 violation of equal severity to no .gitignore at all.

Pre-commit attention. Every commit author (human OR agent) MUST inspect `git diff --staged` and `git status` BEFORE executing the commit. If a staged path matches any forbidden class, the commit MUST be aborted and the issue fixed (un-stage the path, add to .gitignore, scrub if already-tracked). Gate CM-GITIGNORE-PRECOMMIT-AUDIT: pre-commit hook (or commit wrapper in §2) inspects every staged path against the forbidden-pattern matrix; hits abort the commit with a directed error pointing the operator at the specific offending path and the canonical fix. Paired mutation (§1.1): stage a *.log → gate FAILs.

Cascade reach. This rule applies recursively to every owned-by-us submodule per CONST-047 and to every owned-submodule's nested non-owned trees within their working copy. The .gitignore files themselves are project-specific in their concrete patterns but universally bound to the rule's normative force.

Secret-leak intersection. §11.4.30 composes tightly with §11.4.10 (Credentials-handling mandate / CONST-042) and §12.1. A .env leak is BOTH a §11.4.30 violation (build/sensitive file versioned) AND a §11.4.10 violation (credential leak). The combined severity is **release-blocker requiring rotation + post-mortem** per §11.4.10.

Coverage of "recreatable" content. When in doubt about whether something is a build derivative: if there exists a documented, scripted, or automated mechanism that recreates the file from sources, the file is a build derivative and MUST be ignored. The committed sources MUST include the generator (Makefile target, npm script, codegen invocation), so any downstream consumer regenerates the artefact on demand.

Classification: universal (per §11.4.17). No escape hatch beyond the explicit exceptions enumerated above (e.g., .env.example placeholder files). Severity-equivalent to a §11.4 PASS-bluff at the repository-hygiene layer — a tracked build artefact silently drifts vs. its source over time, producing the same class of "works-on-my-machine" surprise that the §11.4 anti-bluff covenant forbids at the test layer.

Composition. §11.4.30 composes with §1 (test coverage — ignored files don't get spuriously included in coverage stats), §2 (commit-wrapper enforces the pre-commit gate), §9.1 (destructive-operation safeguards — never `git clean` an operator's working tree to "fix" a violation), §11.4.10 (credentials-handling), §11.4.12 (auto-generated docs sync — generators committed, outputs ignored only if recreatable on demand from the same generator), §11.4.17 (universal — applies to every consuming project),

§11.4.18 (script docs — generator scripts documented), §11.4.20 (subagent delegation for cross-submodule .gitignore audit sweeps), §11.4.25 (coverage ledger lists .gitignore presence per submodule), §11.4.26 (constitution-update workflow — the constitution submodule's own .gitignore complies), §11.4.27 (no-fakes: test fixtures that ARE the reference asset are tracked; runtime captures are ignored), §11.4.28 (submodules-as-equal-codebase: each submodule's .gitignore audited on equal basis), §11.4.29 (the renamed paths in the lowercase migration MUST also be properly ignored where applicable), CONST-047 (recursive governance reach).

§11.4.29 — Lowercase-Snake_Case-Naming Mandate (User mandate, 2026-05-15)

Forensic anchor — verbatim user mandate (2026-05-15):

"naming convention for Submodules and directories (applied deep into hierarchy recursively) - all directories and Submodules MSUT HAVE lowercase names with space separator between the words of '_' character (snake-case)! All existing Submodules and directories which are not following this rule MUST BE renamed! However, since this will most likely break some of the functionalities renaming we do MUST BE applied to all references to particular Submodule or directory! Everywhere where particular Submodule directory are referenced proper updates MUST BE applied

- all configuration files, documentation and relevant materials, links to Submodules and directories, source code that points to them, etc. There MUST BE reasonable exceptions for this rules - source code for programming languages or Submodules which apply different naming convention - Android, Java, Kotlin and others. Root directory for such applications, services or Submdoules can follow OUR convention, but EVERYTHING inside still MUST follow language / technology specific rules! We apply this rules per common sense basis and it MUST NOT be the cause of bigger issues such as technology breaking! Upstreams directory which all of our projects and Submodules have MUST BE renamed to the lowercase letters too, however root project containing the install_upstreams system command (it is exported in out paths in our .bashrc or .zshrc) MUST BE updated to fully work with both Upstreams and upstreams directory. That change if it is not already applied MUST BE done, committed and pushed! ... NOTE: Rules lowercase / snake-case do apply to all project files as well and references to it and from them! Every change done MUST BE covered with all supported test types, full automation tests for

validation and verification and fully applied and followed anti-bluff policy and all anti-bluff rules!"

Operative rule. Every directory, submodule, and file under the parent project's working tree **MUST** use a **lowercase, snake_case** name (ASCII letters / digits / underscores, words separated by `_`). Existing names that violate the rule (`HelixCode/`, `Challenges/`, `Containers/`, `HelixAgent/`, `HelixQA/`, `Security/`, `Github-Pages-Website/`, `Upstreams/`, `Dependencies/`, etc.) **MUST** be renamed as part of the migration window opened by this clause. Every reference in the codebase **MUST** be updated atomically with the rename: configuration files, documentation, user manuals, diagrams, scripts, source-code imports, links, governance files. **Reference drift after a rename is a §11.4.29 violation** of equal severity to the rename itself.

Exceptions (common-sense scope). The rule **MUST NOT** break language-/technology-specific conventions:

- **Programming-language source roots** that mandate a specific case (Java / Kotlin package paths, Android resource folders, Apple framework directories, C# / Swift project layouts) keep their language-mandated names. The submodule's root directory follows our convention; the language-specific subtree inside follows its own.
- **Vendor / upstream submodules** (third-party orgs not in our owned set) keep their upstream-mandated names — we **MUST NOT** rename a third party's repo.
- **Build-tooling artefacts** (`node_modules/`, `__pycache__/`, `.git/`, `target/`, `build/`, `bin/`) keep their tool-mandated names.

When in doubt, the test "does renaming break the technology?" trumps the `snake_case` rule. The §11.4.29 spirit is operator- ergonomics + reference-discoverability, not pedantic uniformity at the cost of technology compatibility.

Upstreams/ → upstreams/ transition. The constitution submodule's installer (`install_upstreams.sh`) — exported on operator paths via `.bashrc` / `.zshrc` — **MUST** support **both** `Upstreams/` and `upstreams/` directory layouts during the migration window, so existing checkouts keep working while consuming projects rename at their own pace. The installer reads whichever directory exists; if both exist the lowercase wins. After every project under this Constitution has migrated, the uppercase fallback **MAY** be retired by a deliberate amendment, but the migration window remains open as long as **ANY** owned project still ships the uppercase form.

Project-Toolkit Upstreamable submodule synchronisation. The Upstreamable / Project-Toolkit machinery that propagates governance into every consuming project **MUST** be fetched +

pulled before any rename batch, and MUST itself comply with this rule. Any Upstreamable submodule lacking BOTH-directory support is a release blocker for the rename program.

Test coverage of renames. Every batch of renames MUST ship with: (i) a regression test that verifies every reference to the renamed entity now resolves to the new name (no stale references left); (ii) a full CONST-050(B) test-type matrix run against the post-rename tree; (iii) anti-bluff (CONST-035) wire-evidence captured during the runtime verification. A rename batch without all three is a §11.4.29 violation.

Cascade reach. This rule applies recursively through every owned-by-us submodule layer (per CONST-047) and applies equally to the consuming project and its owned submodules (per CONST-051). Per CONST-051(C) — dependencies at the parent root — the renamed paths MUST be the only canonical location; old-name aliases remain only as transitional symlinks if absolutely required, and those symlinks MUST be removed on next-N-cycle review (project- configurable, recommended ≥ 3 release cycles).

Phased execution. Because the rename touches every reference, the execution MUST be planned as fine-grained phases per the operator's explicit instruction: comprehensive brainstorming, phase-divided plan, fine-grained tasks/subtasks with enormous detail, every change covered by every applicable test type. The phases run in parallel with mainstream work (§11.4.20 subagent delegation is the natural fit for cross-submodule rename sweeps).

Classification: universal (per §11.4.17). No escape hatch beyond the explicit common-sense exceptions enumerated above. Severity-equivalent to a §11.4 PASS-bluff at the reference-integrity layer — a half-completed rename that leaves broken references is worse than no rename at all because it silently breaks consumers.

Composition. §11.4.29 composes with §1 (four-layer floor for every rename batch), §1.1 (paired mutation: rename without updating a reference → gate FAILs), §11.4.12 (regenerate auto-generated docs on rename), §11.4.17 (universal — no project-specific assumptions), §11.4.18 (script-doc-sync after renamed script paths), §11.4.20 (subagent delegation for cross-cutting rename sweeps), §11.4.25 (every renamed path appears in coverage ledger), §11.4.26 (constitution-submodule rename pipeline), §11.4.27 (rename-touch test types apply across the matrix), §11.4.28 (owned submodule renames cascade per CONST-047), CONST-047 (recursive governance reach).

§11.4.28 — Submodules-As-Equal-Codebase + Decoupling + Dependency-Layout Mandate (User mandate, 2026-05-15)

Forensic anchor — verbatim user mandate (2026-05-15):

"All existing Submodules in the project that we are controlling and belong to some of our organizations (vasic-digital, HelixDevelopment, red-elf, ATMOSphere1234321, Bear-Suite, BoatOS123456, Helix-Flow, Helix-Track, Server-Fact-ory — we can ALWAYS check dynamically using GitHub and GitLab CLIs) are equal parts of the project's codebase! We MUST work on that code as much as we do with main project's codebase! All on equal basis! Equally important! We MUST take it into the account, analyze it, extend it, create missing tests, do full testing of it, fill the gaps (if any), fix any issues that we discover or they pop-up, write and extend the documentation, user guides, manulas, diagrams, graphs, SQL definitions, Website(s) and all other relevant materials! We MUST NEVER modify Submodules to bring into them any project specific context since they all MUST BE ALWAYS fully decoupled, project not-aware, fully reusable and modular (by any other project(s)), completely testable! All Submodule dependencies that are used by Submodule MUST BE accessed from the root of the project! We MUST NOT have nested Submodule dependencies but accessing each from proper location from the root of the project — directly from project's root project_name/ submodule_name or some more proper structure project_name/ submodules/submodule_name! This MUST BE heavily enforced and respected so no chaos and mess is created with various dependencies we may have!"

Operative rule. Three cooperating invariants govern every consuming project's relationship with its owned-by-us submodules (those whose upstream origin lives under one of the operator-listed orgs — vasic-digital, HelixDevelopment, red-elf, ATMOSphere1234321, Bear-Suite, BoatOS123456, Helix-Flow, Helix-Track, Server-Factory — or any additional org the operator subsequently authorises, the canonical list discoverable at any time via `gh org list / glab / the orgs' public APIs`):

(A) Equal-codebase invariant. Every owned-by-us submodule is an **equal part** of the consuming project's codebase. The consuming project's engineering practice — analysis, extension, test creation, gap-filling, bug-fix, documentation (user manual, guides, diagrams, graphs, SQL definitions, website pages, any other authoring surface) — applies to each owned submodule on equal basis. A round of work that improves only the main project while leaving an owned-submodule deficiency unaddressed is a §11.4.28 violation, severity-equivalent to a §11.4 PASS-bluff at the project-scope layer. Coverage ledgers (§11.4.25) MUST list every owned

submodule as an in-scope target. CONST-047 (recursive cascade) governs the propagation of governance changes; §11.4.28 is the engineering-content counterpart that mandates the same attention to non-governance content.

(B) Decoupling / reusability invariant. Owned submodules MUST remain **fully decoupled** from any specific consuming project. No project-specific context, hardcoded paths, hostnames, asset names, naming schemes, or runtime assumptions may be introduced into an owned submodule's source tree. Every owned submodule MUST be:

- **Project-not-aware** — its code, tests, and docs make no reference to which parent project consumes it.
- **Fully reusable** — any future Helix-family or third-party project must be able to consume the submodule unmodified.
- **Modular** — its public surface is the only documented integration contract; internal layout may evolve without breaking consumers.
- **Completely testable** — every public surface has standalone tests (per the §11.4.27 100%-test-type matrix) that pass when the submodule is checked out as a standalone repo, without any parent-project rigging.

A commit that adds `project_name/...` strings, hostnames belonging to a specific deployment, or other parent-project context to a submodule's source tree is a §11.4.28 violation. The honest path when a submodule needs information from the parent project is configuration injection (env var, config file, constructor parameter) — never a hardcoded reach into the parent's tree.

(C) Dependency-layout invariant. Every dependency that an owned submodule itself consumes MUST be accessible **from the root of the parent project** at one of two canonical paths:

```
<project_root>/<submodule_name>/          # flat layout
<project_root>/submodules/<submodule_name>/ # grouped layout
```

Nested-submodule chains are FORBIDDEN. A submodule MUST NOT have its own `.gitmodules` entries that pull in further owned- by-us repos (transitive own-org submodule recursion). Every dependency required by submodule X MUST be added to the parent project at the canonical path above; X reaches it via documented import / SDK path / runtime resolver — never via its own nested submodule pointer.

Rationale: nested own-org submodule chains cause version-drift chaos (two consumers of `LLMsVerifier` end up at different SHAs because each parent picked a different transitive path). The flat / grouped layout makes the consuming project's submodule graph a tree-of-depth-1, which any developer can audit at a glance via `git submodule status` from the project root.

Third-party submodules (not under our orgs) are exempt — they MAY appear at any depth as the upstream's structure dictates. The invariant applies only to our owned set.

Audit + enforcement.

- Gate CM-OWNED-SUBMODULE-EQUAL-ENGINEERING (project-side): every release-gate sweep verifies each owned submodule has current test runs, coverage entries (§11.4.25), and documentation freshness on par with the main project. Stale submodules surface as §11.4.28 violations (Status: Operator-blocked or In progress per §11.4.21 — never "ignored").
- Gate CM-OWNED-SUBMODULE-DECOUPLING (submodule-side): every owned submodule's pre-commit hook (or equivalent) greps the staged diff for parent-project names / hostnames / asset names. Hits abort the commit until refactored to configuration injection.
- Gate CM-OWNED-SUBMODULE-LAYOUT (project-side): the parent project's pre-merge sweep verifies (i) every owned submodule sits at <root>/<name>/ or <root>/submodules/<name>/, (ii) no owned submodule contains a nested .gitmodules entry whose upstream is in our org list, and (iii) every dependency declared by an owned submodule has a corresponding parent-project submodule entry at the canonical path.
- Paired mutations (§1.1) for all three gates: plant the forbidden pattern → gate FAILs; restore → gate PASSes.

Workflow integration. Honoring §11.4.28 in practice:

- Engineering rounds plan in submodule-aware tranches: "improve feature X in main; in same round, audit + improve the X-related surface in submodule Y; cascade governance per CONST-047 as usual".
- The §11.4.25 coverage ledger row format is extended with a submodule column so coverage rolls up across the whole owned set.
- Cross-submodule refactors that touch shared types or interfaces ship as a single change-window: parent + every affected owned submodule advanced in lockstep (§3 submodule- first-commit discipline + §2.1 multi-upstream push).

Classification: universal (per §11.4.17). No escape hatch. Composes with: §1 (four-layer test floor reaches submodules too), §1.1 (false-positive immunity), §3 (submodule changes propagate through submodule commits first), §11.4.17 (universal-vs-project classification), §11.4.20 (subagent delegation for the cross-submodule audit sweep), §11.4.25 (full-automation coverage ledger expanded to submodules), §11.4.26 (constitution-update workflow's submodule-pointer-bump step), §11.4.27 (100%-test-type coverage applies to every submodule's standalone surface), CONST-047 (recursive governance cascade). A round of work that

violates §11.4.28 is a release blocker for the consuming project, severity-equivalent to a §11.4 PASS-bluff at the codebase-completeness layer.

§11.4.27 — No-Fakes-Beyond-Unit-Tests + 100%-Test-Type-Coverage Mandate (User mandate, 2026-05-15)

Forensic anchor — verbatim user mandate (2026-05-15):

"Mocks, stubs, placeholders, TODOs or FIXMEs are allowed to exist ONLY in Unit tests! All other test types MUST interact with real fully implemented System! No fakes, empty implementations or bluffing is allowed of any kind! All codebase of the project MUST BE 100% covered with every supported test type: unit tests, integration tests, e2e tests, full automation tests, security tests, ddos tests, scaling tests, chaos tests, stress tests, performance tests, benchmarking tests, ui tests, ux tests, Challenges (fully incorporating our Challenges Submodule — <https://github.com/vasic-digital/Challenges>). EVERYTHING MUST BE tested using HelixQA (fully incorporating HelixQA Submodule — <https://github.com/HelixDevelopment/HelixQA>). HelixQA MUST BE used with all possible written tests suites (test banks) for every applications, service, platform, etc and execution of the full HelixQA QA autonomous sessions! All required dependency Submodules MUST BE added into the project as well (fully recursive!!!)."

Operative rule. Two cooperating invariants:

(A) No-fakes-beyond-unit-tests. Mocks, stubs, fakes, placeholders, in-memory facsimile implementations, TODO, FIXME, "for now", "in production this would", or any empty-implementation pattern are PERMITTED only inside unit-test sources (e.g., *_test.go files invoked WITHOUT the integration build tag; tests/unit/; equivalent per-language conventions). Every other test type — integration, end-to-end, full automation, security, DDoS, scaling, chaos, stress, performance, benchmarking, UI, UX, Challenges, HelixQA suites — MUST exercise the **real, fully implemented system** against real infrastructure (real databases, real HTTP endpoints, real containers, real downstream services, real captured devices). A non-unit test that imports mocks, in-memory repositories, fabricated provider responses, or placeholder structs is a §11.4.27 violation regardless of how green its summary line looks — severity-equivalent to a §11.4 PASS-bluff. The same prohibition extends to **production code**: no mock import path may be reachable from any code path that runs in production binaries. Pre-build gate CM-

NO-FAKES-BEYOND-UNIT-TESTS scans the non-unit test trees and production trees for the forbidden patterns; paired mutation plants a fake → gate FAILs.

(B) 100% test-type coverage with every supported type.

Every project under this Constitution **MUST** cover its entire codebase with **every supported test type** the project's domain warrants:

1. **Unit** — fast, isolated, mocks permitted per (A).
2. **Integration** — multi-component, no mocks, real backing services.
3. **End-to-end (E2E)** — full user-flow exercise on target topology.
4. **Full automation** — orchestrated suites exercising every feature × platform combination (§11.4.25 coverage ledger).
5. **Security** — authn/authz boundaries, secret-leak scans (§11.4.10), input-fuzzing, dependency-CVE scanning, threat-model verification.
6. **DDoS** — request-flood resilience at advertised throughput tier, with rate-limit + back-pressure assertions.
7. **Scaling** — horizontal + vertical scale behaviour under linear load growth, including replica add/remove transitions.
8. **Chaos** — controlled failure injection (network partition, process kill, disk full, clock skew) verifying graceful degradation paths.
9. **Stress** — sustained load above advertised tier, asserting bounded resource exhaustion + clean recovery.
10. **Performance** — latency / throughput / tail-latency invariants vs SLO baselines.
11. **Benchmarking** — micro + macro benchmark suites with historical p95-drift detection (§11.4.24 build-resource composition).
12. **UI** — visual-regression + DOM-state + interaction-flow coverage on every target platform's UI surface.
13. **UX** — flow-correctness + accessibility + i18n + visual- cue ordering (§11.4.23 composition).
14. **Challenges** — vasic-digital/Challenges submodule fully incorporated; per-feature Challenge scripts covering real user use-cases with captured runtime evidence.
15. **HelixQA** — HelixDevelopment/HelixQA submodule fully incorporated; ALL written test banks executed; full autonomous QA sessions run as part of release gates.

Per-type 100% coverage means: for every feature × platform cell in the §11.4.25 coverage ledger, the cell carries a verified PASS evidence pointer for **each supported test type the cell warrants** (a CLI-only feature warrants unit + integration + E2E + full-automation + security + chaos + stress + performance

- Challenges + HelixQA; a UI feature additionally warrants UI + UX; a network service additionally warrants DDoS + scaling +

benchmarking). Gaps are tracked per §11.4.15 with explicit UNCONFIRMED: / PENDING_FORENSICS: / OPERATOR-BLOCKED: reasons.

Required submodule incorporation (recursive). Every project consuming this Constitution MUST add the following as Git submodules (or vendored equivalents authorised by the operator), fully recursively per CONST-047 / §11.4.x cascade:

- Challenges — git@github.com:vasic-digital/Challenges.git
- HelixQA — git@github.com:HelixDevelopment/HelixQA.git
- Any additional functionality submodules under vasic-digital/* or HelixDevelopment/* orgs that the consuming project depends on (do not duplicate work the organisations already maintain).

Submodule pointers MUST be bumped to upstream HEAD in the SAME commit as any dependent cascade work (§11.4.26 step 7). Pointer drift = §11.4.27 violation.

HelixQA autonomous sessions. "Full HelixQA QA autonomous sessions" means: HelixQA's orchestrator drives the consuming project's running surface end-to-end, executing every test bank the project has registered with it, capturing wire evidence per check (status + body bytes + body-head + duration + screenshots for UI), and producing a session report that is itself committed via the §11.4.22 lightweight doc-sync wrapper. A green autonomous-session report without captured wire evidence is a §11.4 PASS-bluff at the QA-orchestration layer.

Composition. §11.4.27 composes with: §1 (four-layer floor), §7.1 (positive-evidence-only), §11.4.1 (FAIL-bluffs forbidden), §11.4.2 (recorded-evidence), §11.4.3 (per-topology dispatch), §11.4.6 (no-guessing), §11.4.10 (credentials-handling — security test category), §11.4.15 / §11.4.16 (status + type tracking), §11.4.17 (universal-vs-project classification), §11.4.20 (subagent delegation for orchestrating the test-type matrix), §11.4.22 (lightweight doc-sync for coverage ledgers and session reports), §11.4.25 (full-automation-coverage — §11.4.27 is its strict expansion into per-type-of-test territory). It does NOT supersede them. CONST-047 (recursive submodule application) governs the cascade reach.

Classification: universal (per §11.4.17). No escape hatch. A project shipping with mocks reachable from non-unit-test paths OR missing required test-type coverage is **not delivering a stable product** — release blocker for every consuming project, severity-equivalent to a §11.4 PASS-bluff at the release-gate layer.

§11.4.33 — Type-aware closure-status vocabulary (User mandate, 2026-05-15)

Forensic anchor — direct user mandate (verbatim, 2026-05-15):

"make sure we use proper wording for the workable item completion status in Issues, Issues_Summary and Fixed docs: - Fixed -> into the proper wording depending on the workable item type (task, feature, and so on) - for example: Fixed, Implemented, Completed. Add this important detail in our root Constitution, CLAUDE.MD and AGENTS.MD so it is ALWAYS respected and followed!"

Classification: §11.4.17-classified **universal** — naming discipline applies to every project that tracks work items by type. Bug closures aren't "implemented", feature deliveries aren't "fixed", and infrastructure refactors aren't either. Type-mismatched closure vocabulary is a quiet but persistent semantic-drift bluff at the documentation layer — it makes greppable releases lie about what shipped.

The mandate. §11.4.15 defined the lifecycle Status closed-set including the closure terminal value Fixed (→ Fixed.md). §11.4.16 defined the Type closed-set {Bug | Feature | Task}. §11.4.33 binds the two: the closure terminal value **MUST** agree with the item Type, drawn from this 3-element closed map:

Item **Type:**	Closure **Status:** value
Bug	Fixed (→ Fixed.md)
Feature	Implemented (→ Fixed.md)
Task	Completed (→ Fixed.md)

The (→ Fixed.md) suffix is preserved across all three so the existing migration-discipline tooling (Issues.md → Fixed.md atomic move per §11.4.19) continues to work without per-Type branching. Generators (generate_issues_summary.sh, generate_fixed_summary.sh, status-counter helpers, the §11.4.23 colorizer) **MUST** treat the three terminal values as semantically equivalent (all map to "closed, positive evidence captured") while preserving the literal in the emitted document.

No escape hatch. Closing a Feature with Fixed (→ Fixed.md) or a Task with Implemented (→ Fixed.md) is a §11.4.33 violation. Pre-build gate (recommended, per consuming project) CM-CLOSURE- VOCAB-TYPE-AWARE walks every Fixed.md heading + every Issues.md heading whose ****Status:**** is one of the three terminal values, and asserts the Status value matches the item's ****Type:**** per the table. Paired mutation flips a Bug entry's status from Fixed (→ Fixed.md) to Implemented (→ Fixed.md) → gate FAILs.

Propagation. Composes with §11.4.15 (item-status tracking), §11.4.16 (item-type tracking), §11.4.19 (Fixed-document column alignment), §11.4.23 (colourisation — the closed-state palette applies regardless of which of the three terminal words is used).

§11.4.34 — Reopened-source attribution mandate (User mandate, 2026-05-15)

Forensic anchor — direct user mandate (verbatim, 2026-05-15):

"when we reopen some workable item (bug, task or feature) we MUST HAVE details on who did reopened this and why (- Reopened status needs: by who, AI or User + details in main Issues doc.). For example, reopened by AI or reopened by real User, why - test failed, manual testing detected problem, etc. Adapt our docs for this - Issues, Issues_SUMmary and Fixed."

Classification: §11.4.17-classified **universal** — every project that uses §11.4.15's Reopened lifecycle value benefits from knowing the reopen source + cause. Without this, reopen-thrash patterns (the same item bouncing between Fixed and Reopened across cycles) cannot be diagnosed, and the §11.4.7 demotion-evidence rule loses its forensic counterparty (you cannot evaluate whether a reopen was operator-side observation or agent-side over-restoration without provenance).

The mandate. Every Issues.md (or equivalent project tracker) heading whose ****Status:**** value is Reopened MUST carry, within 8 non-blank lines of the heading, a ****Reopened-Details:**** line that captures four sub-facts:

- **By:** AI or User (the source-of-truth observer who flipped the status). AI covers in-loop reopens (test failure, gate regression, captured-evidence retrospect). User covers operator-side observations (manual testing, end-user report, design reconsideration).
- **On:** ISO date (YYYY-MM-DD).
- **Reason:** one-line cause classification — chosen from a closed vocabulary { test-failed | manual-testing-detected | captured-evidence-contradicts | end-user-report | cycle-re-discovered | design-reconsidered }. Other values are permitted with explicit Reason: <free text> annotation but the closed list MUST be tried first.
- **Evidence:** path to or short description of the captured artefact that justifies the reopen — log file, recording, gate failure ID, operator quote, etc. Reopens without evidence are §11.4.6 / §11.4.7 violations: the reopen IS a demotion-from-Fixed classi-

fication change, and demotion requires positive evidence captured under the conditions that re-exposed the defect.

The `Issues_Summary.md` (or equivalent) Status column MUST distinguish the four Reopened sub-states by source so a sweep query for "reopens by AI in the last 30 days" is mechanically possible. Suggested column rendering: Reopened (AI: test-failed) vs Reopened (User: manual-testing).

No escape hatch. A Reopened entry without `**Reopened-Details:**` is a §11.4.34 violation. Pre-build gate (recommended, per consuming project) `CM-ITEM-REOPENED-DETAILS` mirrors `CM-ITEM-OPERATOR-BLOCKED-DETAILS` (Phase 39.AT pattern): walks every actionable heading, scans 8 non-blank lines for a `**Status:**` Reopened line, then continues scanning for `**Reopened-Details:**`. Missing details line emits WARN initially, hardens to FAIL once backlog is fully populated.

Propagation. Composes with §11.4.6 (no-guessing — the Reason must be drawn from the closed vocabulary or explicitly annotated; no likely/probably/maybe causes), §11.4.7 (demotion-evidence — reopen IS a demotion from Fixed), §11.4.15 (item-status tracking — extends the Reopened value's discipline), §11.4.21 (Operator-blocked discipline — same audit-line pattern with the same gate shape).

§11.4.35 — Canonical-root inheritance clarity (User mandate, 2026-05-15)

Forensic anchor — direct user mandate (verbatim, 2026-05-15):

"Parent AGENTS.MD or CLAUDE.MD are located under constitution directory (Submodule) containing these parent (root) which files we are inheriting inside the project! Pay attention to this and make sure you ALWAYS follow this rule! Same applies to the root Constitution file!"

"If needed (and we think it is needed it seems) add into the root Constitution, AGENTS.MD and CLAUDE.MD located in constitution directory (Submodule) which we are inheriting that the root (parent) Constitution, AGENTS.MD and CLAUDE.MD are not the ones in root of the project but inside the constitution directory (Submodule). We are inheriting it and if project specific rules have to be added or project specific constraints which are not universal and reusable, then they go into the Constitution, CLAUDE.MD and AGENTS.MD of the project directory itself!"

Classification: §11.4.17-classified **universal** — every project that consumes this constitution as a Git submodule **MUST** unambiguously distinguish the **canonical root** (the constitution submodule's three files) from the **consumer extensions** (the project's own three files).

The defect this anchor closes. Loose terminology — "parent CLAUDE.md", "root CLAUDE.md", "main constitution" — used without a file-path anchor causes a quiet but persistent confusion between the inheriting copy and the source-of-truth. AI agents have already been observed editing the consumer-side CLAUDE.md when the User's intent was to extend the canonical layer (or vice-versa), causing universal rules to leak into project-specific copies and project-specific rules to be falsely promoted as universal. The defect compounds: once a rule is misfiled, future propagation gates treat the misfile as canonical and silently spread it.

The mandate. The three files in **this constitution submodule** (constitution/Constitution.md, constitution/CLAUDE.md, constitution/AGENTS.md) are the **canonical root** — also called the **parent** files. They contain only universal rules per §11.4.17 — rules that any project consuming this submodule benefits from.

The three files in **the consuming project's repository root** (<project-root>/CLAUDE.md, <project-root>/AGENTS.md, optionally <project-root>/Constitution.md or equivalent) are the **consumer extensions**. They **MUST** start with the inheritance pointer per the existing constitution/CLAUDE.md "How inheritance works" section. They contain only project-specific rules per §11.4.17 — rules that reference particular hardware, vendor names, regulatory regions, internal asset names, or project-private conventions.

Operative invariants that follow:

1. **When in doubt about which file to edit:** if the rule is reusable across any project, edit the constitution submodule's file. If the rule references project-private specifics (a hardware revision, a vendor SDK version, a regional constraint, a particular service), edit the consumer's file. Default to consumer-side when uncertain (per §11.4.17 — narrower scope is cheap to widen later, the reverse is expensive).
2. **Terminology anchor.** When prose in any file in this constitutional family references "the parent CLAUDE.md" or "the root Constitution," the referent is the constitution-submodule file at constitution/<filename>, never the consumer's file. When it references "the project CLAUDE.md" or "this project's AGENTS.md," the referent is the consumer-side file at <project-root>/<filename>. AI agents reading this constitution **MUST** resolve ambiguous pronouns ("the CLAUDE.md", "the constitution") via this rule.

3. **Universal rules added to the consumer side are misfiled.** Per §11.4.17 commit-time check, before adding a MUST to the consumer file, the author assesses whether it would benefit other projects that consume this constitution. If yes, lift it to the constitution submodule first.
4. **Project-specific rules added to the constitution submodule are misfiled.** Per §11.4.17, before adding a MUST to the constitution submodule, the author assesses whether it references project-private specifics. If yes, demote it to the consumer file (or genericise it to a universal form first).
5. **Propagation gates target both layers but their contents differ.** The existing CM-COVENANT-114-N-PROPAGATION gate family verifies that anchor TEXT for §11.4.N exists in EVERY CLAUDE.md and AGENTS.md across the project. The constitution-submodule files carry the **canonical** text; the consumer files carry **compact propagation pointers** that reference the canonical authority by file path. Both forms count as valid presence; the gate is satisfied when any form is found.
6. **@constitution/CLAUDE.md import (Claude-Code-style) and the pointer-block fallback (Aider/Codex/Gemini-style) are equivalent.** The consumer's CLAUDE.md MUST start with one of:
 - The native import: @constitution/CLAUDE.md
 - The portable pointer-block per the ## INHERITED FROM constitution/CLAUDE.md heading defined in constitution/CLAUDE.md "How inheritance works".
7. **No silent demotion or silent promotion.** Moving a rule between layers MUST be a visible commit — git mv of a section if it's a clean clone, or an explicit "Lifted from to constitution per §11.4.35" / "Demoted from constitution to per §11.4.35" line in the commit message. AI agents MUST NOT silently re-author a §11.4.X anchor in the wrong layer and call it propagation.

Pre-build gate (recommended, per consuming project):

- **CM-CANONICAL-ROOT-CLARITY** — verifies (a) consumer's CLAUDE.md opens with the inheritance pointer (either @import or ## INHERITED FROM constitution/CLAUDE.md heading), (b) the constitution submodule's three files are present at the expected path, (c) no ## INHERITED FROM block in the constitution submodule's own files (those ARE the source-of-truth, not consumers).

Propagation. Composes with §11.4.17 (universal-vs-project classification — §11.4.35 defines the file-layer split that §11.4.17 classifies INTO), §11.4.18 (script documentation discipline — same ca-

nonical-vs-consumer file-layer rule applies to docs/scripts/). Reading order: this anchor first, then §11.4.17 for the classification rule.

No escape hatch. Misfiling a rule between layers IS a §11.4.35 violation regardless of intent. The fix is `git mv + commit` per invariant 7, not "leave both copies in place to be safe" — duplicates silently diverge over time.

§11.4.36 — Mandatory `install_upstreams` on clone/add Mandate (User mandate, 2026-05-15)

Forensic anchor — verbatim user mandate (2026-05-15):

"Every Submodule or Git repository we add or clone MUST BE upstreams installed using Upstreamable utility which MUST BE available through exported paths of the host system (in `.bashrc` or `.zhrc`) using `install_upstreams` command executed from the root of the cloned (added) repository - only if in it is Upstreams or upstreams directory present with bash script files (recipes) for all repository's upstreams!"

Operative rule. Every time an operator or agent adds or clones a Git repository (`git clone`, `git submodule add`, `incorporate-submodule` per §11.4.31, etc.) under any consuming project of this Constitution, the post-clone procedure MUST be:

1. `cd` into the newly-cloned (or newly-added submodule's) working tree.
2. If the working tree contains an `upstreams/` directory (or legacy `Upstreams/` per the §11.4.29 transition) populated with one or more `*.sh` recipe files declaring upstream Git SSH URLs (the canonical declaration format defined by this constitution submodule's `Upstreams/*.sh` shape), the operator or agent MUST invoke `install_upstreams` from that directory.
3. `install_upstreams` is a host-system utility installed on the operator's `PATH` via `.bashrc` or `.zshrc` export. Implementation lives in the constitution submodule (`install_upstreams.sh`); operators alias / symlink it onto `PATH` once per host setup. The utility reads the recipe files, configures every declared upstream as a named git remote, and fans out origin push URLs across all declared upstreams.
4. If no `upstreams/` directory is present, no `install_upstreams` invocation is required.
5. If `upstreams/` is present but `install_upstreams` is not on `PATH`, the operator MUST install it (per the constitution submodule's setup docs) BEFORE making the clone usable.
6. Skipping step 2 when an `upstreams/` directory IS present is a §11.4.36 violation — the next push from that working tree will

land on only one upstream, breaking §2.1 (Multi-upstream push is the norm).

Pre-commit attention. Before the first commit lands inside the newly-cloned working tree, the operator **MUST** verify that `install_upstreams` has been executed (when applicable). The quickest check: `git remote -v | grep -c push` reports the expected upstream count. If it reports 1 while `upstreams/*.sh` declares more, abort the commit and run `install_upstreams` first.

Automation. The constitution submodule's tooling (the future incorporate-submodule per §11.4.31, the existing `scripts/init-submodules.sh` patterns in consuming projects) **MUST** auto-invoke `install_upstreams` as part of any clone / add operation when the target tree has an `upstreams/` directory. Operator-explicit manual invocation remains supported.

Gate CM-INSTALL-UPSTREAMS-ON-CLONE. Pre-merge gate inspects every owned-by-us submodule pointer commit and verifies that: (a) if `upstreams/` (or legacy `Upstreams/`) is present in the submodule's tree, (b) the submodule's local checkout has at least as many configured push URLs as the declared recipe count. Paired mutation (§1.1): remove one upstream from local origin --push config → gate FAILs.

Composition. §11.4.36 composes with §2 (single-entriypoint commit/push wrapper), §2.1 (multi-upstream push is the norm — this rule is its setup-time complement), §3 (submodule changes propagate through submodule commits first — requires multi-upstream parity), §9.2 / CONST-043 (no force-push — the multi-upstream wrap-up makes unforced parity easy), §11.4.17 (universal — every consuming project's clone procedure), §11.4.20 (subagent delegation when batch-cloning), §11.4.28 / CONST-051 (owned-submodule discipline), §11.4.29 / CONST-052 (`Upstreams/` → `upstreams/` transition is exactly this rule's scope), §11.4.30 / CONST-053 (`.gitignore` ignores `upstreams/` only if the project explicitly decides not to track recipes, which is unusual — recipes ARE source of truth and SHOULD be tracked), §11.4.31 / CONST-054 (submodule-dependency- manifest works alongside `upstreams` recipes: `helix-deps.yaml` lists WHAT to add at parent root, `upstreams/` recipes list WHERE to push the resulting clones).

Classification: universal (per §11.4.17). No escape hatch. Severity-equivalent to §2.1 multi-upstream-push-violation at the clone-time setup layer — without the post-clone install, the working tree silently has a single-upstream blind spot.

§11.4.37 — Fetch-before-edit mandate (User mandate, 2026-05-15)

Forensic anchor — verbatim user mandate (2026-05-15):

"Make sure that `feedback_fetch_before_edit` memory rule is part of our constitution Submodule - the root Consitution, AGENTS.MD and CLAUDE.MD. Validate and verify that Proejct-Toolkit and all Submodules do inherit all of them! Follow the constitution Submodule documentation for details."

Background. In multi-agent / multi-upstream codebases — where parallel Claude Code, Cursor, Aider, Codex, Gemini CLI, or human operator sessions may operate on overlapping scope — the local working tree's state can lag behind the canonical upstream state by the time any given agent receives a task. Acting on stale local state produces three failure modes documented in the originating session (2026-05-15):

1. **Redundant work** — the agent re-does what a parallel session already finished, wasting tokens and operator review time. (In the originating incident, "Gitee removal" had already been committed upstream by a parallel agent 25 minutes earlier; the second agent's `git remote remove gitee` was a no-op echo of work already done.)
2. **False confidence** — the agent reports completion of work that was already done by someone else, with no mechanical signal that their commit duplicates upstream history.
3. **Divergent history** — if the agent commits a parallel "completion" of already-done work, the result is two siblings of the same change, doubling the conflict surface for the next push attempt to multi-upstream remotes (§2.1).

The mandate. The FIRST git-touching action of any session, on any consuming project that participates in this constitution, MUST be:

```
git fetch --all --prune
git log --oneline HEAD..@{u}           # parent
git submodule foreach --recursive 'git fetch --all --prune --quiet'
```

If `HEAD..@{u}` is non-empty, the agent MUST integrate (ff-merge, rebase, or — if non-fast-forward — surface to operator per §11.4.4) BEFORE issuing any local edit, scanner run, or test cycle. The fetch step is non-negotiable even when the operator's directive is phrased as "do X immediately" — the 30-second check prevents hour-long conflict reconciliation later.

Scope. Applies to:

1. The consuming project root.

2. Every owned submodule (per §11.4.28) — recursive.
3. The constitution submodule itself (§11.4.26 step 1 makes this explicit for constitution-side edits; §11.4.37 generalises it to ANY edit on the consuming project, not only constitution edits).
4. Any dependency cloned via `incorporate-submodule` (§11.4.31) or `git submodule add` (§11.4.36).

Anti-bluff invariant. The `fetch+log` check MUST produce captured evidence — the actual `HEAD..@{u}` output, even if empty. Skipping the check on the basis of "I just fetched" or "nothing could have changed in the last N minutes" is a §11.4.6 (no-guessing) violation: the remote state is not knowable without a fetch.

Composition. Composes with §2.1 (multi-upstream push — without the fetch, the agent can't know which upstream has the canonical ref), §11.4.4 (test-interrupt-on-discovery — newly-fetched commits that contradict the planned work are exactly the "freshly discovered defect" that triggers cycle interruption), §11.4.6 (no-guessing — remote state requires fetch, not assumption), §11.4.20 (subagent delegation — parallel subagents MUST coordinate through fetched state, never assumed-local state), §11.4.26 (constitution update workflow — this rule generalises §11.4.26 step 1 to ALL edits, not only constitution-file edits), §11.4.32 (post-constitution-pull validation — fetch-before-edit happens BEFORE the constitution-pull sweep §11.4.32 mandates).

Gates. Pre-build gate `CM-FETCH-BEFORE-EDIT-AUDIT` (when implemented in the consuming project) audits the most-recent commit range against the upstream `HEAD` at the commit's parent — if the parent ref was not the upstream `HEAD` at the time the commit was authored, FAIL. Paired mutation (§1.1): synthetic commit whose parent is N commits behind the then-current upstream `HEAD` — gate must FAIL.

Classification: universal (per §11.4.17). The rule has no project-specific assumptions — it applies to any multi-upstream / multi-agent codebase. No escape hatch. Severity-equivalent to a §11.4 PASS-bluff at the planning layer — acting on stale local state is the operational analog of asserting truth from unverified premises.

§11.4.38 — Installable-Asset Evidence Mandate (User mandate, 2026-05-17)

Forensic anchor — verbatim operator report (2026-05-17):

"app does not have a launcher icon anymore — the latest published app tester build(s). how come app passed anti-bluff checks?"

For any user-distributable build artifact (package, bundle, installer, or container image produced by the build pipeline and distributed to end users), tests and challenges **MUST** open the artifact and verify each user-visible asset is **present** and **non-degenerate**.

"User-visible asset" includes (non-exhaustive):

- Application icons for every density / resolution tier declared in the artifact metadata, including any platform-specific icon format (multi-resolution container, adaptive XML, symbol set, etc.) that the target OS uses when the minimum supported OS version requires it.
- Splash screens declared in the install metadata.
- Application name strings as declared in the install metadata.
- Any other asset whose absence causes the user to be unable to identify, launch, or interact with the installed application from the OS launcher / home screen / app drawer.

A PASS without opening the artifact and verifying the asset chain end-to-end is a §11.4 PASS-bluff, regardless of whether source files exist and tests otherwise pass. The specific failure mode this rule targets is: source file exists → build pipeline packages it → post-build checks pass at the source layer → artifact ACTUALLY produced with the asset stripped or misconfigured, and no gate ever opens the artifact to verify.

Required evidence: the anti-bluff challenge for a user-distributable artifact **MUST** produce per-asset PASS/FAIL lines showing: (a) the asset entry exists in the artifact package listing, (b) the asset is non-empty / non-degenerate (size $\geq$ platform-defined minimum OR format-validated), (c) where the OS's asset-resolution path involves indirection (alias, XML reference chain, density-qualifier override), the full chain is traced to the final rendered resource.

Consuming-project implementation: each consuming project ships one challenge script per artifact type that opens the produced artifact and verifies every declared user-visible asset. The challenge **MUST** run as part of the project's standard QA gate (equivalent of `make qa-all`).

Root cause of §11.4.38 introduction: a consuming project shipped multiple releases with the application icon absent on the target OS because: (1) the icon XML used a resource type that the OS resolves differently above a specific API level, (2) all pre-ship challenges verified source files only, none opened the packaged artifact. This is a pure §11.4 PASS-bluff — every test and challenge reported green while the end user saw no icon.

Classification: universal (per §11.4.17). No escape hatch. Severity-equivalent to a §11.4 PASS-bluff at the artifact-packaging layer. Composes with §11.4.1–§11.4.5 (evidence requirements), §11.4.25 (full automation coverage), §11.4.27 (no fakes beyond unit tests —

source-layer checks of a distributable artifact are the distributable-layer analog of unit-test-only coverage). See Constitution §11.4.38 for the full mandate.

§11.4.39 — Per-Feature On-Device End-User Validation Mandate (iter-76, 2026-05-17)

Every user-facing feature in a consuming project **MUST** have at least one HelixQA scenario that exercises the feature from cold-launch with **positive runtime evidence**:

- A screenshot or screen recording captured at a named checkpoint.
- At least one assertion of type `screenshot`, `accessibility_count`, `accessibility_node`, `ocr_text`, `pixel_histogram`, or `editor_state`.
- Evidence files written to a discoverable output directory so every PASS is cross-verifiable after the fact.

Scenarios **MUST** be RE-EXECUTED on every release candidate to catch cross-iteration regression. A scenario authored but never re-run on subsequent iterations degrades to a metadata-only gate — a §11.4 PASS-bluff at the regression layer.

Authoring rules (consuming project sets project-specific paths):

1. Scenarios are stored in a canonical bank directory designated by the consuming project (e.g. `<banks-root>/feature-coverage/`).
2. Each scenario YAML **MUST** include: `name`, `version`, `metadata`, `platforms`, `test_cases`, and at least one step with `evidence_required: true` and a specific `evidence_type`.
3. A **coverage matrix** document **MUST** exist listing feature × iteration × scenario. Matrix rules: (a) new iteration **MUST** add ≥ 1 scenario per new user-facing feature; (b) prior scenarios **MUST NOT** be deleted (mark as `status: retired` if feature is removed); (c) all non-retired scenarios **MUST** PASS for ship-ready.
4. A **static gate** (challenge script) **MUST** assert the scenario count $\geq N$ (where N is the number of user-facing features registered in the coverage matrix) and that each YAML contains a `evidence_type: assertion`.
5. **Portable host tooling**: evidence-validation scripts **MUST** use POSIX-portable file-size helpers (e.g. `wc -c < file`) instead of OS-specific commands (e.g. GNU `stat -c%s`) to avoid silent 0-byte reports on BSD/macOS hosts. A regression challenge **MUST** verify the portable helper on the actual host.

iOS / platform-deferred pattern: scenarios written platform-agnostically with the target platform listed in a comment deferral (e.g. # iOS: deferred – tracker #X) are valid; add the platform to the platforms: list when the automation toolchain becomes available — no structural change to the scenario is needed.

Classification: universal (§11.4.17). Composes with §7.1, §11.4 (anti-bluff), §11.4.25 (full automation coverage), §11.4.27 (no fakes), §11.4.38 (artifact evidence). No escape hatch — a feature without an on-device scenario is NOT covered per §11.4.25 invariant 2. See Constitution §11.4.39 for the full mandate.

§11.4.40 — Full-suite retest before release tag mandate (User mandate, 2026-05-17)

Forensic anchor — verbatim user mandate (2026-05-17):

"Please, do complete retests with all existing tests (multi-hours efforts) when all new workable items are done, fixed, polished and verified. Time is essential! We should already have this in our (root) Constitution, CLAUDE.MD and AGENTS.MD."

Operative rule. A release tag (any vX.Y.Z / X.Y.Z-suffix identifier MUST NOT be created until a **COMPLETE retest with ALL existing tests** has been executed on a clean baseline AFTER every workable item in the batch is done, fixed, polished, and individually verified. A "spot-check" retest that runs only the tests directly touched by the batch is FORBIDDEN — it misses interaction defects between the batch's fixes and previously- stable code paths.

The complete retest comprises:

1. **Pre-build verification full sweep** — every gate in the project's pre-build script runs; 0 FAIL required.
2. **Post-build verification full sweep** — every gate in the project's post-build script runs against the freshly-assembled image; 0 FAIL required.
3. **On-device 4-phase cycle** (e.g. test_all_fixes.sh or project equivalent) on **EVERY owned device** (the full topology at that point in time). Each phase (Immediate Fresh Flash / After Reboot / After Factory Reset / After Final Reboot) MUST complete; no phase may be skipped. Phase summaries captured.
4. **Meta-test full mutation sweep** — every paired mutation in meta_test_false_positive_proof.sh (or project equivalent) executed; every gate proven non-bluff.
5. **Test bank full sweep** — if a Challenge-driven test bank exists, every Challenge in the bank covered by a full QA session (not a sub-set).
6. **Issues.md / Fixed.md state audit** — no item silently demoted; every Reopened item has §11.4.34 Reopened-Details;

every closure has captured-evidence per §11.4.5; no Status: value outside the §11.4.15 closed-set.

7. **CONTINUATION.md sync check** — per §12.10, document reflects current state at the moment of tagging.

Time is essential. A complete retest is typically a **12-48 hour elapsed effort** depending on parallelism, device count, and meta-test mutation count. This is NOT optional and NOT abbreviated. Operators should plan release cadence with this duration in mind, NOT skip the retest to ship faster. Skipping the retest is the exact "tests passed but feature broken" failure mode §11.4 specifically prohibits.

Composition with §11.4.4. Per-fix retest (`test_all_fixes.sh` run after each individual fix lands) is STILL mandatory per §11.4.4. §11.4.40 is the **additional final integrity check** that runs after the BATCH is complete — catching interaction defects that individual per-fix retests cannot see in isolation.

Composition with §11.4.7. The complete retest is the authoritative captured-evidence baseline for any closure of items present in the batch. If a §11.4.7-promoted item PASSED its per-fix retest but FAILS the full-suite retest, the closure MUST be reverted and the item moved back to In progress — captured-evidence-contradicts under same-conditions per §11.4.7.

Composition with §11.4.39. Per-feature on-device end-user validation runs as part of step 3 (on-device cycle) — every feature's wrapper-test fires during the full-suite retest. The two mandates are complementary: §11.4.39 covers individual feature validation breadth; §11.4.40 covers release-time integration depth.

Gate CM-FULL-SUITE-RETEST-MANDATE. Pre-tag gate inspects the release-candidate state and verifies that within the last 72 hours of the candidate commit, evidence exists of (a) full pre-build + post-build run, (b) on-device 4-phase cycle on every owned device, (c) meta-test full sweep, (d) Issues.md/Fixed.md audit pass. Evidence captured in docs/changelogs/<tag>.md per §11.4.4(c) requirements. Paired mutation (§1.1): strip Full-suite retest evidence block from a changelog → gate FAILs.

Classification: universal (per §11.4.17) — every consuming project's release procedure. No escape hatch — there is no `--skip-full-retest` flag, no `--quick-release` mode. Operators who feel time-pressured to skip the full retest should instead delay the release until the retest completes; shipping unverified code is worse than delayed shipping.

§11.4.41 — Pre-Force-Push Merge-First Mandate (User mandate, 2026-05-17)

Forensic anchor — verbatim user mandate (2026-05-17):

"make sure we bring everything from branches to our side before forc push is done! Afer everything is safely and fully merged and all potential conflicts (if any) resolved, then do force push! make sure nothing isnlost, broken or corrupted on bith sides! add these rules in our root Constitution, CLAUDE.MD, AGENTS.MD (constitution Submodule) if itnis not added already! Extremely important rules and mandat-ory constraints we MUST HAVE and fully respect!"

Operative rule. Any force-push (`git push --force`, `git push --force-with-lease`, `git push +<ref>`, equivalent history-rewriting operation on any remote) authorised under §9.2 / CONST-043 MUST be preceded by a mechanical 4-step merge- first pipeline that brings every remote-side commit into the local tree, resolves every conflict carefully, and verifies nothing is lost or corrupted on EITHER side BEFORE the overwriting push is executed.

The 4-step pipeline (mandatory, in order):

1. **Fetch every remote-side reference.** Run `git fetch --all --prune --tags` against every configured remote (origin + every upstream). Capture the output.
2. **Integrate every divergent commit locally.** Compute `git log --oneline HEAD..<remote>/<branch>` for every remote. For every non-empty range, integrate the remote commits into the local tree via the appropriate strategy:
 - **git rebase <remote>/<branch>** when the local divergent work is a strict superset that should land on top, OR
 - **git merge <remote>/<branch>** when the local + remote histories are independent additions that both deserve preservation, OR
 - **operator-confirmed cherry-pick** when remote contains a subset of commits already present locally in different form.
3. **Audit the integrated tree.** Verify (a) no conflict markers anywhere in the working tree (`grep -rn '^<<<<<< \|^===== $|^>>>>>> '` . returns empty across all governance + source + test files — third-party docs containing the markers as illustrative content excepted), (b) no file silently dropped (`git diff --stat HEAD@{1} HEAD` shows only expected additions), (c) every previously-passing test still passes on the integrated tree (per §11.4.4 + §11.4.40 baseline), (d) every captured- evidence artifact from the pre-merge state still validates.
4. **Execute force-push.** Only after steps 1-3 produce captured evidence of clean integration: `git push --force-with-lease <remote> <ref>` (NEVER `--force` without `--with-lease` unless explicitly authorised per §9.2 sub-clause 6 for a specific remote where lease semantics are unavailable). One force-push event

per CONST-043 authorisation — no batch authorisation across multiple force-pushes.

Three failure modes prevented:

(a) **Remote-side content loss.** Force-push without prior fetch silently overwrites commits a parallel session, sibling agent, or co-developer landed on the remote. The lost work is recoverable from the remote's reflog only within its TTL window — typically 30-90 days — but the audit trail (PR comments, CI evidence, governance signatures) is lost permanently.

(b) **Stale-state act on remote.** Force-push from a divergent local state that was branched from a remote tip N hours ago treats the remote-side N hours of work as nonexistent. The operator's --force-with-lease safety check catches the literal SHA mismatch but ONLY when invoked AFTER a fetch that updated the lease reference; without step 1, the lease check is reading stale local refs.

(c) **Conflict-driven corruption.** A merge that completes with unresolved markers in the tree (one half kept, other dropped silently because the marker was inside a comment block, OR markers committed verbatim as in CONST-049-prerequisite incidents observed 2026-05-17 on helix_ga + containers) lands broken governance / source on the force-push target. Step 3's explicit conflict-marker grep is the mechanical guard.

Two-gate composition with CONST-043. §11.4.41 does NOT relax CONST-043's operator-approval requirement — it adds a SECOND gate on top:

- **Gate A (CONST-043).** Operator types explicit per-operation force-push authorisation in the conversation.
- **Gate B (§11.4.41).** Agent executes the 4-step merge-first pipeline, captures evidence of clean integration, presents evidence to operator BEFORE the force-push.

Both gates required. CONST-043 alone authorises a force-push that loses remote work; §11.4.41 alone risks force-pushing without operator awareness. The two together produce a force-push that is BOTH operator-authorised AND remote-safe.

Verification artefact. Every §11.4.41-governed force-push emits a docs/changelogs/<tag>.md "Force-push merge-first audit" section containing: (i) git fetch output, (ii) per-remote HEAD..<remote>/<branch> log before integration, (iii) integration strategy chosen per remote with rationale, (iv) post-integration conflict-marker scan output (must be empty), (v) post-integration test suite delta (must show only expected changes), (vi) the --force-with-lease push output with lease SHA evidence, (vii) CONST-043 authorisation quote from the conversation.

Cascade requirement (per CONST-047). This anchor (verbatim or by §11.4.41 / CONST-061 ID reference) MUST appear in every owned submodule's CONSTITUTION.md, CLAUDE.md, and AGENTS.md. Severity-equivalent to a §11.4 PASS-bluff at the remote-data-integrity layer. Gate CM-FORCE-PUSH-MERGE-FIRST walks docs/changelogs/<tag>.md "Force-push" entries for the 7 audit elements; paired mutation strips any element and asserts gate FAILs.

Classification: universal (per §11.4.17) — every owned project executes force-pushes against its remotes; the merge- first discipline is reusable verbatim. No escape hatch — the operator-pressure escape ("just force-push, we'll fix it later") is the exact failure mode this anchor closes.

Composes with: §9.2 (data-safety hardlinked backup), §11.4.4 (test-interrupt-on-discovery — broken integration triggers roll-back), §11.4.6 (no-guessing — every step's outcome captured, not assumed), §11.4.26 (constitution-submodule update pipeline — that mandate is the per-submodule specialisation of §11.4.41 for governance-files-only commits), §11.4.32 (post-pull validation — the audit step's mechanical companion), §11.4.37 (fetch-before-edit — step 1 enforces it for the force-push specifically), §11.4.40 (full-suite retest — step 3's test-evidence prerequisite), CONST-043 (per-operation operator approval), CONST-047 (recursive cascade).

§11.4.42 — Iteration-discipline mandate (User mandate, 2026-05-18)

Forensic anchor — verbatim user mandate (2026-05-18):

"Are we clear about working iterations and sorting priorities for testing and fixing? We first fix top and middle critical priorities → We flash and test all of these → If nothing is broken and no new issues are reported by users or found we run full system testing (many hours for everything) → if anything is still broken or new issues are reported we get back to fixing → Cycle repeats. Make sure this is absolutely clear and mandatory foundation of our root (constitution Submodule) Constitution, AGENTS.MD and CLAUDE.MD! We MUST WORK in this manner until otherwise has been told."

Operative rule. Project work proceeds in priority-ordered iteration cycles. Each cycle is a closed loop of five steps that MUST run in order; advancing past any step before its acceptance condition is met is a §11.4 bluff equivalent to skipping the step entirely.

The five-step cycle:

1. **Priority-ordered fix selection.** Open the project's issue tracker, filter to items whose ****Status:**** is one of Queued | In progress | Reopened | Operator-blocked (per §11.4.15 closed-

set), sort by severity DESC then intra-group criticality DESC (per §11.4.12 sort order), select ONLY items classified Top critical or Middle critical for the current batch. Low items are explicitly DEFERRED until the critical batch is closed.

2. **Batch implementation.** Land source-side fixes for the selected batch per §11.4.9 (batch-source-fixes-before-rebuild) — every non-runtime-dependent fix lands BEFORE the next rebuild, every fix gets the §11.4.4 four-layer coverage (pre-build gate + post-build gate + on-device test + paired mutation).
3. **Smoke-test gate.** After flash, run the SMOKE bundle: (a) anti-bluff baseline (`meta_test_false_positive_proof.sh` for gates touched by this batch), (b) every `test_*.sh` whose name matches a fix in this batch, (c) the critical-path regression probe (boot + launcher + WiFi + audio + secondary-display routing core), (d) the §11.4.39 per-feature on-device validation for any feature touched. Estimated runtime: <30 minutes on the parallel device fleet. Smoke MUST emit zero FAIL and zero unclassified WARN.
4. **Full-system-test gate.** ONLY if (a) smoke is GREEN AND (b) no new operator/user report has surfaced during the batch's validation window, run the §11.4.40 complete retest (all 7 steps including 12–48 h on-device 4-phase cycle on every owned device). If smoke FAILED OR a new report arrived, the full-system test is FORBIDDEN; loop back to step 1 with the new evidence added to the priority queue.
5. **Release-readiness or loop.** If full-system test is GREEN AND no new report arrived during it, the batch is release-ready (the §11.4.40 tagging procedure may proceed pending operator authorization). Otherwise loop back to step 1.

Priority taxonomy (binds existing severity convention). Top critical = severity C (Critical per Issues.md convention) AND intra-group criticality 5. Middle critical = severity C with intra-group 1–4 OR severity M (Major) with any intra-group score. Low = severity L per the existing [C/M/L] taxonomy documented in §11.4.12. Severity WARN items are treated as Low for iteration-discipline purposes.

Cycle repeats. The five-step loop continues, fed by the priority queue, until the operator explicitly authorizes a release. There is no upper bound on iteration count; "we've cycled enough" is not a Constitution-recognised stopping condition. Time is essential per §11.4.40 BUT the cycle MUST NOT be truncated to ship faster — that is exactly the bluff §11.4 forbids.

Composition. §11.4.4 (per-fix retest inside step 2) + §11.4.7 (closures require same-conditions positive evidence; step 4 is authoritative baseline) + §11.4.9 (source-side batching inside step 2) + §11.4.34 (Reopened items attribute By: AI / User) + §11.4.40 (the multi-hour full-suite retest IS step 4 — §11.4.42 is the meta-loop conductor binding the instruments).

Anti-bluff coupling. Per §11.4.2 + §11.4.5, every smoke-test and full-system-test PASS MUST carry positive captured evidence of user-visible behaviour. Tests AND HelixQA Challenges bound equally — a Challenge that scores PASS without applicable analysis is a §11.4 PASS-bluff.

No escape hatch. No --skip-priority-batch, --skip-smoke, --full-suite-only, or --release-without-loop flag exists. Subagents performing autonomous work default to the §11.4.42 path. Operators who feel time-pressured to short-circuit the loop should add capacity (more devices in parallel, more agent slots) rather than skip steps. Shipping under-validated code is worse than delayed shipping.

Gate CM-COVENANT-114-42-PROPAGATION mirrors CM-COVENANT-114-40-PROPAGATION 1:1 — every CLAUDE.md / AGENTS.md in the covenant file set carries the §11.4.42 anchor. Paired mutation strips the anchor literal from one consumer file → gate FAILs.

Classification: universal (per §11.4.17) — every consuming project's iteration workflow.

§11.4.43 — TDD-Fix-Discipline Mandate (User mandate, 2026-05-18)

Forensic anchor — verbatim user mandate (2026-05-18):

"Make sure you do validate and verify every fix! Make sure you first do the fix on live device using ADB if that is possible, once fix is confirmed, make sure that it is fully applied into our codebase ... It is important to note that we shall start by creating test which confirms the issue (fails as expected), and ones the fix is produced it becomes positive - it does pass with success! No bluff policy is mandatory and nothing can be bluffed! Every step of this process MUST BE 100% bluff-free and bluff-proofed!"

Operative rule. Every fix MUST follow the 5-step TDD-fix workflow:

1. **RED — Failing test FIRST.** Before any code change, author a test (or extend an existing one) that exercises the user-visible path of the reported defect and FAILs for that defect specifically. Per §11.4.1 the FAIL MUST be a real product defect (not a script-bug induced FAIL). Per §11.4.2 the FAIL run MUST produce captured evidence (logcat / dumphsys / screenrecord / dmesg / /sys snapshot / sink-side probe). The test identifier MUST cite the §-letter or Fix-# under repair. A RED step that "happens to pass because the underlying probe lifecycle isn't wired" is itself a §11.4 PASS-bluff.

2. **LIVE-ADB-PROBE — try the fix on the running device first (when feasible).** For mutable surfaces — setprop persist.*, settings put, pm clear, am force-stop, am start, cmd wifi, cmd media_session, ad-hoc /sys writes, boot- script edits pushed to /vendor/bin/, test-fixture replacement — the operator **MUST** attempt the fix on the running device via adb shell first. The fast adb-loop (~5 min per attempt) replaces the build-flash-test loop (~6 h per attempt) for confirmation of the hypothesis. The live-probe IS NOT the fix; it is the EXPERIMENT that proves the hypothesis is correct before the source-side investment.

Live-probe is INFEASIBLE (exception, must rebuild) for: kernel changes, AOSP framework (frameworks/base/), hardware HAL changes, vendor/ partition contents, init.rc service definitions, sepolicy, ro.* build properties (immutable post-boot), AOSP-build-time XML / resource overlays, Android.bp/ Android.mk changes, signed-system-app contents (LOCAL_CERTIFICATE := platform). Each exception **MUST** be cited in the commit message as LIVE_PROBE_INFEASIBLE: <reason>.
3. **GREEN — apply the fix to source code.** The source patch **MUST** achieve the same effect on the device as the live probe. Per §11.4.9 the source change is batched with other source-side fixes where appropriate. Build via the project's containerized build (§12.9). Flash via the project's flash script. The bytes on the assembled image **MUST** land where the post-build gate expects (per §11.4.4(b) four-layer requirement).
4. **VERIFY — re-run the RED test, must now PASS.** Per §11.4.7 demotion-evidence: the PASS **MUST** come from the SAME conditions that initially FAILED (same device, same firmware NOW carrying the fix, same load profile, same cycle position). Per §11.4.5 the PASS **MUST** carry positive captured evidence (presence + correctness — RMS amplitude, fprobe channel count, frame count, OCR text, sink codec state, etc.). Per §11.4.2 video tests **MUST** cross-check via the recording-analyzer. Per §11.4.42 a reliability check at the iteration count (typically 10 iterations) **MUST** PASS all iterations — a single intermittent FAIL keeps the item in In progress per §11.4.7.
5. **DOCUMENT — update every relevant doc in the SAME commit.** Per §11.4.4(c): docs/Issues.md → docs/Fixed.md migration with type-aware closure vocabulary per §11.4.33 (Bug → Fixed, Feature → Implemented, Task → Completed); the project's CLAUDE.md Applied Fixes Reference row; per-version docs/changelogs/<tag>.md entry; affected user-facing guides under docs/guides/; HelixQA bank entry per §11.4.4(b); docs/CONTINUATION.md per §12.10; project memory file if non-obvious.

Composition. §11.4.43 is the workflow that ENACTS the existing covenant. Composes with: §11.4.1 (the RED FAIL is a real defect), §11.4.2 (captured evidence at both RED and VERIFY), §11.4.3 (topology dispatch in the RED test), §11.4.4 (four-layer coverage at GREEN), §11.4.5 (quality analysis at VERIFY), §11.4.6 (no guessing during the LIVE-PROBE hypothesis statement — UNCONFIRMED: until probe proves it), §11.4.7 (demotion-evidence at VERIFY — same conditions), §11.4.8 (research citation precedes step 1), §11.4.9 (GREEN is batched), §11.4.40 (full-suite retest is the release-tag-time additional check), §11.4.42 (10-iteration reliability loop IS step 4's inner cycle).

Gate CM-COVENANT-114-43-PROPAGATION. Pre-build gate verifies the §11.4.43 anchor is present in every CLAUDE.md / AGENTS.md across the covenant file set. Paired mutation strips the anchor literal from one consumer file → gate FAILs.

Classification: universal (per §11.4.17) — every consuming project's fix workflow. **No escape hatch.** No --skip-red-test, --no-live-probe, --skip-verify, --skip-document flag exists. "I'll add the test after the fix" is the exact PASS-bluff pattern §11.4 forbids because the test authored after the fix demonstrates only that the test agrees with the fix, not that the test catches the bug.

§11.4.44 — Document Revision Header Mandate (User mandate, 2026-05-18)

Forensic anchor — verbatim user mandate (2026-05-18):

"Add this change / improvement as background work in parallel with our mainstream work. All documents (Issues, Issues_Summary, Fixed, Continuation doc and all others MUST HAVE revision number! Revision number with information such as: last date and time when document was modified MUST GO at the top of the document below the main H1 title. Add all relevant information about the document as well. However, last date and time document has been modified and revision number are MANDATORY! Revision number shall be the whole number 1, 2, 3, etc. Document all this in our root (constitution Submodule) Constitution, AGENTS.MD and CLAUDE.MD as mandatory rule(s) and constraints we MUST HAVE! No bluff is allowed of any kind!"

The mandate. Every IN-scope tracked Markdown document MUST carry a header block directly below the H1 title containing two MANDATORY fields:

- ****Revision:**** N where N is a monotonic positive integer (1, 2, 3, ...). Never decremented. Never reset on rewrite. A freshly-created IN-scope document starts at Revision 1.

- ****Last modified:**** YYYY-MM-DDTHH:MM:SSZ (ISO 8601 UTC).

Optional encouraged fields: ****Description:****, ****Authority:****, ****Maintainer:****, ****Scope:****, ****Auto-generated-from:**** (auto-generated docs only), ****Status:**** (plan docs only).

Header format (canonical):

Document Title

```
**Revision:** 47
**Last modified:** 2026-05-18T13:42:00Z
**Description:** Open / in-flight bug + work tracker
**Authority:** Constitution §11.4 covenant
**Maintainer:** Operator + AI loop per §11.4.42
```

<content...>

YAML front-matter and HTML-comment headers are FORBIDDEN — they are invisible to humans scrolling the raw Markdown and break the "all relevant information about the document" visibility clause.

IN scope (revision header MANDATORY): docs/Issues.md, docs/Issues_Summary.md, docs/Fixed.md, docs/Fixed_Summary.md, docs/CONTINUATION.md, docs/guides/**/*.*md, docs/research/**/*.*md, docs/scripts/**/*.*md, docs/changelogs/**/*.*md, docs/superpowers/plans/**/*.*md, docs/hardware/**/*.*md, and every other tracked Markdown under docs/.

OUT scope (revision header NOT required): CLAUDE.md / AGENTS.md (every layer — already version-tracked via VERSION file + inheritance pointer per §11.4.35; adding a per-file revision would duplicate authority and obscure the canonical-root contract); README.md / CONTRIBUTING.md / LICENSE / NOTICE / VERSION / OWNERS (standard metadata); rendered HTML/PDF artifacts (revision inherited from source Markdown); auto-generated docs that already carry an embedded generation-time stamp.

Auto-bump tooling:

- scripts/doc_revision_bump.sh <file> — manual entry point, idempotent (no-op if Last-modified within 5 s of date -u).
- .git/hooks/pre-commit — automatic entry point; walks staged IN-scope docs, calls the bump for each, re-stages.
- scripts/testing/sync_issues_docs.sh — composes the bump for Issues_Summary + Fixed_Summary after regeneration.
- scripts/commit_docs.sh — calls the bump before staging so operators who skipped the hook installation are still covered.

Composition with §12.10. CONTINUATION.md already carries Last updated: per §12.10. §11.4.44 adds **Revision:** N directly under H1 + reuses the existing Last updated: line as the §11.4.44 Last modified: line. One source of truth, two pointers — no duplication.

Composition with §11.4.12. Issues_Summary.md / Fixed_Summary.md inherit the revision number of their source-of-truth Markdown at generation time; they are NOT incremented independently.

Composition with §11.4.23. HTML colorizer preserves the revision header in the colored HTML — pandoc renders the bold lines as styled `<p><strong>...</strong></p>` blocks which the colorizer leaves alone (only Issues-table rows are mutated).

Gates: CM-DOC-REVISION-HEADER-PRESENT walks IN-scope docs and asserts both mandatory fields appear within 15 lines below the H1 title; CM-COVENANT-114-44-PROPAGATION asserts the anchor literal is present in every covenant file. Paired mutations strip the **Revision:** line OR the anchor literal → gates FAIL.

Classification: universal (per §11.4.17). **No escape hatch** — no `--skip-revision-bump`, `--no-header`, `--allow-missing-revision` flag exists. Operators who feel pressured to skip the bump should land smaller commits, not bypass the discipline.

§11.4.45 — Integration-Status-Doc Maintenance Mandate (User mandate, 2026-05-18)

Forensic anchor — verbatim user mandate (2026-05-18):

"Make sure this Markdown document is regularly updated to reflect current up to date state of full integration ... Whole integrations MUST be regularly updated and retested! Keep the Markdown document ALWAYS up to date and ALWAYS exported into PDF and HTML! Make sure document is ALWAYS in sync! Add all this into our Constitution, AGENTS.MD and CLAUDE.MD."

Generalisation note. §11.4.45 is the generic form of §12.10 (CONTINUATION.md) applied to every domain integration. §12.10 binds the canonical handoff document specifically; §11.4.45 generalises the sync-and-evidence pattern to every non-trivial integration (Dolby/Arvus, NanoKVM, Firebase, Widevine L1/L3, Play Protect, Netflix, Cuttlefish, Chromecast, WiFi chip, ES8388 codec, Sonos, AC-3, Google Stack, HiFi audio, TV apps, etc.). Without this generalisation each new integration re-invents the same sync wrapper, revision-header discipline, captured-evidence requirement, and operator-blocked surface — duplicating effort and risking drift.

Operative rule (10 sub-points — every Status.md MUST hold ALL).

Every integration-status document at docs/<domain>/<integration>/Status.md:

1. MUST exist when a domain integration is non-trivial (more than one fix / test / gate landing for that integration).
2. MUST carry the §11.4.44 revision header directly below the H1 title (Revision + Last modified + Description + Authority + Maintainer + Scope).
3. MUST be auto-synced (HTML + PDF) on every related-test-cycle completion AND every fix touching the integration. "Auto-synced" means the wrapper from sub-point 5 is invoked; manual regeneration is forbidden as the sole path because operators will forget.
4. MUST be auto-colored per §11.4.23 — Status column cells colored by lifecycle state, Type cells colored by Type, operator-blocked rows visually distinct.
5. MUST have a sync wrapper invocable as `bash scripts/testing/sync_integration_status.sh <Status.md>` OR a per-integration thin shell that delegates to the generic wrapper. The thin shell exists so operators can type a short command per integration without remembering paths.
6. MUST live under docs/<domain>/<integration>/ directory structure — consistent layout, discovery by glob remains O(1).
7. MUST include a captured-evidence-driven status table per §11.4.5 — every status claim cites the test log path, recording file path, or sink-probe report that backs it. Status claims without evidence are §11.4 PASS-bluffs.
8. MUST distinguish status values per §11.4.6 / §11.4.7: PASS / FAIL / SKIP / PENDING_FORENSICS / OPERATOR-BLOCKED — closed vocabulary, mechanically distinguishable, no implicit values.
9. MUST list operator-blocked items at the top of the document (just below the revision header) so an operator scanning the Status.md finds action items in O(1) — not buried 200 lines deep in a chronological evidence log.
10. MUST be referenced from docs/CONTINUATION.md §3 (Active work) when any item in the Status.md is non-terminal (Queued / In progress / Reopened / Operator-blocked) — composes with §12.10 so the canonical handoff document points at the integration-status doc rather than re-stating its contents.

Gates:

- CM-COVENANT-114-45-PROPAGATION — anchor text propagated to every CLAUDE.md / AGENTS.md across the covenant file set.
- CM-AF-INTEGRATION-STATUS-DOCS — discovers all docs/**/Status.md via glob, verifies each carries the §11.4.44 header, has a sync wrapper, HTML+PDF exports are mtime-current vs the source,

colorization applied (cell-status class present in the colorized HTML).

Paired meta-test mutations (§1.1 compliance): propagation strip → propagation gate FAILs; delete ****Revision:**** from a Status.md → status-docs gate FAILs; touch Status.md without re-syncing → mtime mismatch FAILs; inject likely outside UNCONFIRMED: block → existing CM-NO-GUESSING-MANDATE catches it (composition catch).

Composition. §11.4.5 (captured evidence in every row), §11.4.6 / §11.4.7 (status vocabulary closed-set), §11.4.12 (sync wrapper pattern reused for HTML+PDF re-export), §11.4.13 (sink-side captured evidence is a specific instance of the generic rule), §11.4.15 (status values), §11.4.22 (commit_docs.sh wrapper), §11.4.23 (colorizer extends to Status.md HTML), §11.4.44 (every Status.md carries the revision header), §12.10 (CONTINUATION.md references Status.md paths in §3).

No escape hatch — no --skip-status-sync, --no-revision-bump-on-status, --allow-stale-html flag. Operators who feel pressured to skip the sync should land smaller, more frequent integration commits rather than batching status updates into one giant push.

Classification: universal (per §11.4.17).

§11.4.46 — Validate-recent-work-before-post-flash-tests mandate (User mandate, 2026-05-18)

Forensic anchor — verbatim user mandate (2026-05-18):

"We see that on newly flashed devices we execute all post flash tests. Make sure we do execute them all after we validate and verify all recent work from the Issues and Continuation docs first! Once all new / latest work is fully validated and verified, no new issues found, nothing is discovered broken or faulty, then we run all post-flash tests! If validation and verification of recent work fails for any reason, and we must go back to fix anything that popped up we do not have to run post-flash tests! We MUST save time! All post-flash tests can be executed only after recent work on features and issues is fully validated and confirmed with complete anti-bluff policy enforced! Add this so it is absolutely clear into our root (constitution Submodule) Constitution, AGENTS.MD and CLAUDE.MD! Start following all these rules IMMEDIATELY! Iff required abort all post-flash testing if it is in progress!"

Operative rule. After every device flash, the orchestrator MUST first run a recent-work validation pass before any full post-flash suite (test_all_fixes.sh or project equivalent). The validation pass enumerates recent work from three docs (Issues.md / Fixed.md /

CONTINUATION.md §3), maps each recent item to its on-device test binding, runs ONLY those tests, classifies each result per §11.4.6, and demands 100% green before the full suite is permitted.

Definition of "recent work" (closed-set):

- docs/Issues.md actionable headings with ****Status:**** ∈ {In progress, Ready for testing, Reopened} (per §11.4.15 closed-set).
- docs/Fixed.md headings closed within --max-age-days N (default 7).
- docs/CONTINUATION.md §3 "Active work" sub-headings listed as IN PROGRESS or BLOCKED.

Recent-work test binding. Each recent item's on-device test is discovered via \$-letter or Fix # match against the project's test_*.sh filenames OR an explicit Test: line in the item heading. Items without an on-device test are §11.4.4 four-layer-coverage violations (a fix without an on-device test is forbidden) — flagged as VALIDATION-PASS-BLOCKED until the test lands.

Authorization sequence (machine-enforced):

1. scripts/testing/recent_work_validate.sh --device <serial> runs; writes /data/local/tmp/.recent_work_validated on the device IFF all targeted tests return PASS with captured evidence.
2. The full suite (test_all_fixes.sh) checks for the marker file at entry; absent or stale (older than the last flash boot epoch) → refuses to proceed with exit code 11.
3. Marker is invalidated automatically on reboot — the orchestrator stores the device boot epoch in the marker and re-validates.

Anti-bluff during validation. Each recent-work item that landed a fix in this batch MUST have a paired §11.4.43 RED test (captured before the fix) AND the same test now GREEN (captured after the fix). A GREEN with no prior RED is itself the bluff §11.4 forbids — the gate FAILs.

Honest classification of validation FAILs. Per §11.4.6: PRODUCT defect (real regression — block full-suite, surface to operator), TEST-INFRA defect (test-script bug — fix per §11.4.1 at source layer, re-run), BLUFFY-THRESHOLD (e.g. SLO floor wrong — re-baseline), or UNCONFIRMED (not reproducible in isolation — tag per §11.4.7 PENDING_CYCLE_RETEST, NEVER silently demote).

Composition. §11.4.4 (STOP-on-discovery) + §11.4.6 (no-guessing) + §11.4.7 (demotion-evidence) + §11.4.40 (full-suite gate) + §11.4.42 (iteration discipline — smoke-test ≡ recent-work-validation).

tion) + §11.4.43 (RED test for each recent-work item IS the validation test) + §11.4.44 (revision header determines recency) + §12.10 (CONTINUATION.md source-of-truth for §3 Active work).

Gates:

- CM-COVENANT-114-46-PROPAGATION — anchor literal present in every CLAUDE.md / AGENTS.md across the covenant file set.
- CM-AF-RECENT-WORK-VALIDATION-GATE — asserts scripts/testing/recent_work_validate.sh exists + executable + sources the anti-bluff library + the full-suite orchestrator contains the entry-gate check.
- CM-AF-VALIDATION-ARTIFACT-FILE — asserts the marker file path / data/local/tmp/.recent_work_validated is literal-identical across helper + orchestrator + propagation-block + this Constitution section.

Paired mutations strip the anchor / remove the entry-gate / flip the marker path → respective gate FAILs.

No escape hatch. No --skip-validation, --full-suite-always, --ignore-recent-work flag is permitted. The full-suite-without-validation pattern is the precise "tests passed but feature broken" failure mode §11.4 specifically prohibits. The 60-90 min validation pass is ALWAYS faster than 4-6 h of full-suite chasing a defect.

Classification: universal (per §11.4.17).

§11.4.47 — Firebase Data Review Mandate (User mandate, 2026-05-18)

Forensic anchor — verbatim user mandate (2026-05-18):

"We MUST regularly before every bigger working round check Firebase information gathered so far: Crashlytics (all fatals, non-fatals and ANRs), Analytics data and Performance data. For anything problematic depending on severity proper workable items (issues) MUST be created (Issues, Issues_Summary docs) with full references (links) to original data on Firebase. We MUST make sure we do not create for same issues multiple entries, so we MUST distinguish between same issue manifested in different forms (stack-traces)! Everything MUST BE comprehensive and in-depth level of details so any changes we do (or fixes) do solve the original root problems!"

The mandate. Before every "bigger working round" (pre-build, pre-flash, pre-tag, daily, post-deployment burn-in) the operator/loop MUST execute the Firebase review pass via scripts/firebase/review_round.sh. The pass queries Crashlytics (fatals + non-fatals + ANRs) + Analytics + Performance, classifies each finding by the §11.4.47 severity table, dedup-maps to existing Issues.md entries

via the three-tier algorithm, and drafts new Issue entries for unrecognised findings. Skipping the pass is a §11.4 PASS-bluff: Firebase IS the captured evidence from real end-user devices; ignoring it is the precise "tests pass, feature broken in the wild" failure mode §11.4 prohibits.

Five mandatory elements (ALL must hold):

1. **Trigger cadence (5 trigger types).** Pre-build (blocking, <24 h freshness), pre-flash (blocking, <24 h), pre-tag (blocking, <6 h), daily 09:00 UTC default (non-blocking sweep), post-deployment burn-in T+24 h (non-blocking).
2. **Three-source query.** Crashlytics + Analytics + Performance — ALL three. Skipping one source is a §11.4 PASS-bluff (Firebase reports a regression on the skipped axis and we never see it).
3. **Issues.md output.** Every "problematic" finding MUST map to either (a) a new Issues.md entry, OR (b) a recognised existing entry via the dedup algorithm. Both paths produce a full Firebase Console URL in the entry's metadata so any future agent can re-fetch the raw data without rebuilding context.
4. **Three-tier deduplication.** Tier 1 (exact Firebase Issue-ID match) → Tier 2 (stacktrace-similarity cluster hash: top-3 non-generic frames normalised + crash class → SHA-256 first 8 hex chars) → Tier 3 (monthly operator merge review). Multiple Issues.md entries pointing at the same underlying root cause is a §11.4 violation (operator chases ghosts; root cause stays unfixed).
5. **Comprehensive root-cause analysis.** Every Firebase-sourced Issue carries the §11.4.4(a) systematic-debugging output — Phase 1 evidence, Phase 2 pattern, Phase 3 root-cause hypothesis (UNCONFIRMED until §11.4.43 RED test reproduces), Phase 4 fix direction. Comment-only entries ("crash in App X") are PASS-bluff stubs and FAIL the Issue-xref gate.

Severity classification: Crashlytics FATAL impactedUsers > 10 last 7d → Critical; 1-10 → Major; 0 but historic → Low. NON-FATAL

100/day → Major; 10-100 → Low; < 10 → Informational. ANR 1% sessions → Major; 0.1-1% → Low. Performance KPI regression 20% → Major; 10-20% → Low. Analytics funnel-drop > 50% → Major; 25-50% → Low; feature_used regression > 75% → Major. Composes with §11.4.16 Type assignment.

Gates:

- CM-COVENANT-114-47-PROPAGATION — anchor present across every CLAUDE.md / AGENTS.md in the covenant file set.
- CM-AF-FIREBASE-REVIEW-CADENCE — scripts/firebase/review_round.sh exists, executable, contains the 7-stage pipeline literals + dedup algorithm + severity table.

- CM-AF-FIREBASE-ISSUE-XREF — every Issues.md entry whose ****Source:**** is Firebase Crashlytics / Firebase Analytics / Firebase Performance carries ****Firebase Issue IDs:**** + ****Firebase URL:**** + (****Stacktrace Cluster Hash:**** for Crashlytics OR ****KPI:**** for Performance OR ****Funnel:**** for Analytics).

Paired mutations strip the anchor / rename the review_round function / remove the Firebase-URL field from the template → respective gate FAILs.

Composition. §11.4.4 (STOP-on-discovery), §11.4.4(a) (systematic-debugging), §11.4.6 (no-guessing — Firebase data IS captured evidence), §11.4.7 (demotion-evidence — a previously- Fixed Issue resurfacing in Firebase IS positive captured evidence the fix didn't hold; reopen attribution = "AI: captured-evidence- contradicts" per §11.4.34), §11.4.10 (credentials — never log the bearer token), §11.4.12 (Issues_Summary sync), §11.4.14 (cleanup of /tmp/firebase_review_* work-dirs), §11.4.15 (Status: Queued), §11.4.16 (Type per severity), §11.4.34 (Reopened-Details on Firebase-resurface), §11.4.42 (implicit step 2 inclusion), §11.4.43 (RED test per stacktrace before fix lands), §11.4.44 (revision header on every Firebase-sourced Issue), §11.4.45 (Firebase Status.md at docs/firebase/status/Status.md), §11.4.46 (validation pass consults latest Firebase delta).

No escape hatch. No --skip-firebase-review, --no-issue-from-firebase, --firebase-review-not-applicable flag is permitted. The operator MAY filter by minimum severity (--severity-min major) to reduce noise but the pass itself MUST execute.

Classification: universal (per §11.4.17) — every consuming project that ships to real end-user devices benefits from the same review cadence and the same dedup algorithm.

§11.4.48 — UI-Driven Video Testing Mandate (User mandate, 2026-05-18)

Forensic anchor — verbatim user mandate (2026-05-18):

"We MUST make sure that all video playback testing with 2nd display is performed by fully automatically using the application's UI / UX, with full navigation, choice of video and clicks to real UI buttons to play or switch / stop videos being played! Maybe direct execution of Intents or Broadcasts does not have reported issues! We MUST test ALL WAYS users or Systems may / could play some video contents or streams! For all applications, all video and audio stream types! All supported codecs! EVERYTHING verified with 2nd display on D3 device and every other device with connected

2nd display and Avrus for proper codec(s) used in its Web Interface / Dashboard! Write as much as possible new tests for all supported test types!"

Why the existing video-test set is insufficient. The legacy test_video_routing.sh (v33), test_video_secondary_display.sh, test_video_playback_automation.sh (v1) plus the 53 per_app_video wrappers all dispatch playback via `am start -a android.intent.action.VIEW` or via `MediaSession cmd media_session play` — surfaces that skip the app's own content-selection UI, player-surface allocation, `MediaSession` lifecycle (start/pause/stop), and back-button cleanup. A defect like §CL routing-race or §CM frozen-frame mid-back-press cannot reproduce via Intent dispatch because Intent dispatch re-launches the app cold each time and `am force-stop` is a clean cleanup path that masks the leak.

Operative rule. Every video-playback test that asserts secondary-display routing **MUST** traverse the user-equivalent UI path. Mandatory 5-surface coverage per video app:

1. **Surface A — Launch via launcher icon.** `am start -n <launcher-pkg>/<launcher-activity>` then `uiautomator dump` → locate app icon tile → `input tap X Y`. NOT `am start <video-pkg>/<MainActivity>` (skips launcher).
2. **Surface B — Navigate to content list.** Per-app driver script knows the app's home-tab → content-tab swipe / tap sequence. Asserts at least one content tile is visible via `uiautomator dump content-desc / text match`.
3. **Surface C — Select + play.** Tap a specific content tile (driver records the picked tile's content-desc as captured evidence). Wait for player surface visible.
4. **Surface D — In-app control interaction.** Pause via in-app pause button (not `input keyevent KEYCODE_MEDIA_PAUSE`), resume via in-app play button, in-app rapid switch to a second video (covers §CL).
5. **Surface E — Stop via back button.** `input keyevent KEYCODE_BACK` to exit player. Assert §11.4.14 cleanup: `VOM activeDecoder == null`, secondary surface cleared, no orphan `MediaSession`.

App-coverage matrix: every video-capable app in `PRODUCT_PACKAGES` **MUST** have a UI-driven driver script set (Layer 2 per Section 7 design) **AND** at least one scenario that uses it. Today: 15 apps covered fully in the initial batch (VK Video, MPV, Lampa as fully-implemented; remaining 12 as templated stubs per Section 8). Expansion to all 53 video-app entries is queued as follow-up work under §O Issues.md per-app matrix.

Stream-type matrix: progressive HTTP / HLS / DASH / RTMP / file-local / DRM-protected. Per app, the driver script tags which stream types its picked content exercises. Aggregator emits a coverage matrix per cycle so gaps are visible.

Codec matrix: H.264 / H.265 / VP9 / AV1 / MPEG-2 / MP4V (video) + AC-3 / E-AC-3 / TrueHD / DTS / DTS-HD / MLP / Opus / AAC (audio). Per scenario, the codec assertion is made via `dumpsys media .metrics` (decoder name in event log) AND via Arvus codec-state probe (audio side) per §11.4.13.

Secondary-display verification. On any device with HDMI-A-1 attached (detected via `dumpsys display | grep "Display 2"`):

- Captured-evidence: `dual_display_record.sh` ON for both displays per §11.4.5
- Assertion: `ffprobe -count_frames` on secondary mp4 reports
 - | N frames within 3 s of play-action timestamp
- Anti-assertion: `ffprobe -count_frames` on primary mp4 reports ONLY launcher/home pixels during playback window (no video-decoder output)
- VOM cross-check: `dumpsys video_output_manager` shows `activeDecoder != null` during playback and `== null` after stop within 3 s

When secondary absent (D2 default topology): SKIP per §11.4.3 with explicit reason "topology: no secondary display attached". NEVER FAIL on missing topology.

Arvus codec-state mandate. For every test asserting an audio codec (AC-3, E-AC-3, TrueHD, DTS, etc.) — composed with §11.4.13

- §CG:
- During playback window, call `arvus_probe_codec_state` ≥ 3 times at 1 s intervals (transients fade by sample 2-3)
- Call `arvus_screenshot_capture` per §CG to attach visual evidence of the dashboard
- Assert reported codec matches expected via `arvus_assert_codec_format <regex>`
- ARVUS_HOST unreachable (ABK4 not joined / sink off) → SKIP per §11.4.3, never FAIL

Pre-build gates:

- CM-COVENANT-114-48-PROPAGATION — asserts anchor literal present in every CLAUDE.md / AGENTS.md across parent + 10 owned submodules + HelixQA dependencies (42-file scan).
- CM-AF-UI-DRIVEN-VIDEO0-COVERAGE — asserts the directory `device/rockchip/rk3588/tests/ui_driven/` exists, contains `lib/`

ui_driver.sh reference + scenarios/ subdir + per-app driver subdirs for at least the 3 reference apps (vk_video, mpv, lampa), and that scripts/testing/ run_ui_driven_video_suite.sh is executable.

- Paired mutations: deleting ui_driver.sh → CM-AF-UI-DRIVEN-VIDEO-COVERAGE FAILS; stripping the anchor literal → CM-COVENANT-114-48-PROPAGATION FAILS.

No escape hatch. No --use-intent-shortcut / --skip-ui-traverse / --legacy-intent-mode flag exists. The discipline exists because Intent-based dispatch is exactly the class of test that PASSes while users hit real defects (§11.4 forensic anchor). Operators who feel UI-driven tests are "too slow" should land scenario-level parallelism (multi-device fan-out) rather than bypass the discipline.

Composition.

- §11.4.3 — topology dispatch (secondary present vs absent)
- §11.4.5 — captured-evidence quality (every UI tap captured)
- §11.4.13 — Arvus codec-state mandate
- §11.4.14 — playback cleanup verified via UI back-button path
- §11.4.43 — RED-test-first discipline (initial UI tests RED against §CL/§CM)
- §11.4.44 — revision header on every plan/driver doc
- §CG — Arvus dashboard screenshot

Classification: universal (per §11.4.17). Applies to every project that consumes the constitution submodule AND ships any video-capable Android app.

§11.4.49 — Dual-Approach Testing Mandate (User mandate, 2026-05-18)

Forensic anchor — verbatim user mandate (2026-05-18):

"Kinopoisk playback of 5.1 audio supported movies MUST BE done via UI / UX full automation and via execution of Intents (or Broadcasts) directly both! We could have shared tests base and specialized part which will run / play the movie with properly chose audio track (5.1). Document everything up to the smallest details! Create as much as needed new tests for all supported test types and Challenges!"

Composition with §11.4.48. §11.4.48 mandated UI-driven traversal for every video routing test, eliminating the Intent-only PASS-bluffs. §11.4.49 REFINES rather than replaces: every feature test ships in BOTH variants — UI-driven AND Intent-driven — over a shared assertion base. Either alone is a §11.4 PASS-bluff for the OPPOSITE half of the stack. UI catches app-side bugs (content selection, player surface allocation, MediaSession lifecycle, in-app overlays, back-button cleanup). Intent catches framework/

system-server bugs (Intent extras parsing, MediaCodec.configure hook MIME routing, IVideoOutputManager bind timing, broadcast permission gating, headless cron automation paths).

Operative rule — 5 mandatory elements:

1. **Both variants required.** Every feature test exercising a user-visible behaviour **MUST** ship both `<feature>_ui.sh` (uiautomator-based, §11.4.48 surfaces A-E) **AND** `test_<feature>_intent.sh` (am start --es / am broadcast-based). Either alone is forbidden.
2. **Shared assertion base.** Codec-state assertions, captured-evidence collection (screen-recording, ffprobe, RMS amplitude analysis), Arvus codec-state probe + dashboard screenshot, and §11.4.14 cleanup **MUST** be implemented in a single POSIX-sh library (tests/lib/dual_approach_test_base.sh) and re-used by **BOTH** variants of every dual-approach test. Code duplication in the shared layer is forbidden.
3. **Specialised driver code.** UI variant uses §11.4.48 per-app driver scripts under tests/ui_driven/<app>/. Intent variant uses `am start --es content_id <id> --es audio_track_id <track> / am broadcast -a <action>` directly. Each variant's specialised layer is responsible **ONLY** for "how the playback gets started"; everything downstream of "playback is now happening" routes through the shared base.
4. **Comprehensive documentation per test.** Every dual-approach test set ships with: (a) §11.4.44 revision header in **BOTH** variant scripts, (b) per-feature contract under docs/dual_approach/ <feature>.md describing the captured-evidence pairing and operator-side verification, (c) Issues.md / Fixed.md entry cross-linking both variant paths.
5. **Kinopoisk 5.1 EAC3 is the canonical first implementation.** The shared base + Kinopoisk 5.1 UI variant + Kinopoisk 5.1 Intent variant land in the same batch as this mandate. Subsequent features (Netflix Dolby Atmos, MPV DTS-HD, Lampa+TorrServe HEVC, VLC FLAC) port to the same pattern. The §CN subagent's fix to the underlying decoder pipeline is the **FIRST GREEN** target of these tests; both variants are **RED** per §11.4.43 until §CN lands.

Captured-evidence directory contract. Both variants write to mirror-structured directories `qa-results/dual_approach/<F>/<run-ts>/<ui,intent>/`. Identical filenames; orchestrator diffs the two `result.json` files. Status mismatch (UI=PASS but Intent=FAIL or vice-versa) is itself a finding — it pinpoints which half of the stack contains the bug.

Pre-build gates:

- CM-COVENANT-114-49-PROPAGATION — anchor literal in every CLAUDE.md / AGENTS.md across parent + 10 owned submodules + HelixQA dependencies (42-file scan).

- CM-AF-DUAL-APPROACH-COVERAGE — tests/lib/dual_approach_test_base.sh exists + sources anti_bluff / ui_driver / credentials + exports dat_init / dat_start_capture / dat_assert_codec_state / dat_assert_video_frames / dat_assert_audio_channels / dat_arvus_dashboard_capture / dat_cleanup / dat_report_finding.
- CM-AF-KINOPOISK-5-1-DUAL-COVERAGE — both tests/ui_driven/kinopoisk/kinopoisk_5_1_play_movie_ui.sh AND tests/test_kinopoisk_5_1_play_movie_intent.sh exist + both source the shared base + both reference EAC3 codec + both assert 5.1 / 6-channel.
- Paired mutations (3): strip anchor → propagation gate FAILs; delete UI variant → coverage gate FAILs; delete Intent variant → coverage gate FAILs.

No escape hatch. No --ui-only / --intent-only / --skip- dual flag exists. The discipline exists because either-alone is the PASS-bluff pattern §11.4 specifically prohibits. Operators who feel dual variants are "too slow" should land scenario-level parallelism rather than bypass the discipline.

Composition.

- §11.4.3 — topology dispatch (Arvus reachable, secondary present)
- §11.4.5 — captured-evidence content-quality analysis
- §11.4.6 — UNCONFIRMED tagging for un-verified Kinopoisk element IDs
- §11.4.10 — credentials never echoed, per-device per-service loader
- §11.4.13 — Arvus codec-state mandate (out-of-band evidence)
- §11.4.14 — playback cleanup via EXIT trap in shared base
- §11.4.17 — universal classification
- §11.4.43 — RED-first TDD (both variants RED until §CN fix lands)
- §11.4.44 — revision header on every variant script + design doc
- §11.4.48 — UI-driven traversal (this MANDATE refines, not replaces)
- §CG — Arvus dashboard screenshot via Presenter receiver
- §CB — credentials loader

Classification: universal (per §11.4.17). Applies to every project that consumes the constitution submodule AND ships any Android app whose user-visible behaviour can be triggered through both UI and Intent/Broadcast paths.

§11.4.50 — Deterministic Consistency Mandate (User mandate, 2026-05-18)

Forensic anchor — verbatim user mandate (2026-05-18):

"Our anti-bluff / bluff-proofed / proof-driven work MUST satisfy the following: not a single feature, System or application flow, use case, edge case or procedural action(s) MUST NOT partially work, or sometimes work and sometimes not! There is only one truth that MUST BE fulfilled - no matter how many times we repeat all these scenarios with variations in data, System state(s) and speed of execution, results MUST BE consistent and successful without exception! No false positives or bluffing of any kind is allowed! We MUST add as much full automation tests which will use real System and Applications UI and UX with all flows, use cases and edge cases as needed or as much as it is possible!"

Why this anchor exists. §11.4.7 already forbids the vocabulary intermittent / transient / flake in closure narratives, but that's a textual ban — operators could still let a test "PASS once, FAIL once, PASS again" and report only the first PASS. §11.4.50 closes that gap MECHANICALLY by requiring every PASS to come from N identical iterations rather than from a single observation.

Operative rule — 5 mandatory elements:

1. **N-iteration deterministic outcome.** Every test that PASSes MUST have been executed N times (default N=3, N=10 for cycle- validation suites) against the same firmware MD5 + same device
 - same topology and produced IDENTICAL PASS in every iteration. A test whose outcome diverges across iterations is auto-FAIL per this mandate — there is no "first PASSED therefore X was a flake" path. §11.4.7's expanded forbidden-vocabulary list is enforced mechanically here.
2. **Edge-case + flow + use-case coverage.** Every public API path (Activity / Service / Broadcast receiver / ContentProvider URI / IPC interface / JNI entry / sysprop write / sysfs node / init.rc trigger) MUST have ≥ 1 dedicated test that drives it. Un-tested paths surface in a feature-coverage-matrix audit and block release at the 99% threshold (ratchet sequence 70 $\rightarrow$ 85 $\rightarrow$ 95 $\rightarrow$ 99 mirrors §11.4.18 the existing project-side docs-coverage ratchet).
3. **Reliability check helper.** Project anti-bluff helper library ships `ab_run_n_times <test_name> <N> <fn> [args...]`:
 - Loops N times, captures exit code + evidence-hash per iter
 - Asserts all N exit codes identical AND all N evidence-hashes identical
 - On any divergence: `ab_fail` with full N-iteration report
 - Per §11.4.7 forbidden vocabulary: NO operator-facing escape path converts a divergent N-iter run into PASS

4. Feature-coverage-matrix audit. Project ships scripts/
testing/feature_coverage_audit.sh:

- Walks source layers (every public API surface)
- Walks test layers (test_*.sh references)
- Emits coverage report at qa-results/feature_coverage/ <ISO-UTC>/coverage.tsv
- Pre-build gate enforces minimum threshold; threshold ratchets up each phase (70 → 85 → 95 → 99)

5. Composes with every prior anti-bluff anchor. §11.4.50
does NOT replace §11.4.43 / §11.4.48 / §11.4.49 — it adds the N-iter consistency dimension across all of them. RED-first TDD (§11.4.43) still applies: every new test starts RED and becomes GREEN after the fix lands. UI-driven (§11.4.48) and dual-ap-
proach (§11.4.49) still apply: every test ships in both variants AND each variant passes N iterations identically.

Pre-build gates:

- CM-COVENANT-114-50-PROPAGATION — anchor literal §11.4.50 present in every CLAUDE.md / AGENTS.md across parent + 10 owned submodules + HelixQA dependencies (≥42-file scan; phase 1 uses 5-canonical-file scan matching §11.4.49 propagation pattern).
- CM-AF-RELIABILITY-CHECK-WIRED — ab_run_n_times function literal present in device/rockchip/rk3588/tests/lib/ anti_bluff.sh AND at least 3 on-device tests source-reference it. The 3-test floor ratchets upward each phase.
- CM-AF-FEATURE-COVERAGE-MATRIX — scripts/testing/feature_coverage_audit.sh exists + executable + has run within the last 7 days + most-recent coverage report meets the current threshold.

Paired mutations (3):

- Strip the §11.4.50 anchor literal from constitution/CLAUDE.md via `sed -i 's|11\.4\.50|11.4.MUTATED|g'` → CM-COVENANT-114-50-PROPAGATION MUST FAIL.
- Rename `ab_run_n_times` to `ab_run_n_times_DISABLED` in `anti_bluff.sh` via targeted `sed` → CM-AF-RELIABILITY-CHECK- WIRED MUST FAIL.
- Move `scripts/testing/feature_coverage_audit.sh` aside via `mv` → CM-AF-FEATURE-COVERAGE-MATRIX MUST FAIL.

No escape hatch. No `--allow-flake`, `--first-pass-suffices`, `--skip-n-iter`, `--skip-coverage-audit` flag exists. The discipline exists because the user mandate is unambiguous: "results MUST BE consistent and successful without exception."

Composition.

- §11.4.1 — FAIL-bluffs forbidden

- §11.4.2 — captured-evidence (every iteration captures its own)
- §11.4.5 — quality analysis (per-iteration content compared)
- §11.4.6 — no guessing (UNCONFIRMED required for any iteration- budget assumption)
- §11.4.7 — forbidden flake/intermittent vocabulary (enforced mechanically by this mandate)
- §11.4.43 — RED-first TDD (every new test starts RED, N-iter applies across the GREEN transition)
- §11.4.46 — validate-before-suite (N-iter applied at single-test scope first)
- §11.4.48 — UI-driven traversal (each UI traversal MUST be N-iter-consistent)
- §11.4.49 — dual-approach (both variants of every dual-approach test MUST pass N iterations identically)

Classification: universal (per §11.4.17). Applies to every project that consumes the constitution submodule.

§11.4.51 — Live-ADB-First Maximization Mandate (User mandate, 2026-05-18)

Forensic anchor — verbatim user mandate (2026-05-18):

"Was it possible to max the fix and test it via ADB or it can be only done by making the fix and reflashing for validation and verification? If such option exists, we should always make the best of it! Making fix on live devices via ADB → Once done commit and push changes, rebuild System and reflash → Validate and verify everything (with the test we write as well). Make sure this idea(s) is (are) part of our root (constitution Submodule) Constitution, AGENTS.MD and CLAUDE.MD if they are not already! EVERY DETAIL IS IMPORTANT!!!! Not a single idea or idea's detail can be ignored, skipped, relativized or bluffed!"

§11.4.51 REFINES §11.4.43 step 2 ("LIVE-ADB-PROBE — try the fix on the running device first") with mechanical enforcement: a per-file- class decision matrix, a classifier helper, and a commit-message footer literal.

Operative rule (5 mandatory elements):

1. **Classify every fix** by rebuild-requirement using the project's per-file-class decision matrix. No guessing (§11.4.6). Every file in the diff cites the matrix row that classified it.
2. **If LIVE_ADB_TESTABLE**, the operator MUST apply the fix to the running device via the appropriate adb channel first (adb push for scripts, setprop persist.* for runtime properties, mount -o remount,rw /vendor for boot scripts, pm install -r for APKs built locally via gradle). Run the §11.4.43 RED test

against the live-probed device, capture positive-evidence PASS, THEN commit source-side + rebuild + reflash as belt-and-suspenders re-validation. Commit message footer MUST state LIVE_ADB_VALIDATED: yes with one-line description of the live-probe sequence.

3. **If REQUIRES_REBUILD**, the operator proceeds directly to source-side fix + rebuild + flash. Commit message footer MUST state REQUIRES_REBUILD: <reason> citing the matrix row that classified the file. Categories of REQUIRES_REBUILD: kernel, AOSP framework Java / AIDL, native C++ inside APEX, sepolicy, init.rc, ro.* build properties (immutable post-boot), Android.bp / Android.mk / BoardConfig.mk, XML resource overlays, codec XML inside APEX, ramdisk-bundled artifacts.
4. **If mixed batch**, commit footer states LIVE_ADB_VALIDATED: partial and enumerates per-file classification. Per §11.4.9 batching is preferred; live-probe the testable files first, then batch with the rebuild-required ones into a single rebuild.
5. **Helper script enforces classification mechanically.** The project provides classify_fix_rebuild_requirement.sh which walks git diff --name-only, looks up each file against the matrix, and emits the recommended commit-message footer. No operator-facing override flag converts an unclassified path to LIVE_ADB_TESTABLE by default — unmatched paths classify as REQUIRES_REBUILD: unmatched-path (safe default per §11.4.6).

Per-file-class decision matrix (canonical):

File class	Rebuild required?	Reason
test_.sh / tests/lib/*.sh (on-device)	NO	adb push to / data/local/tmp/ tests/
Host-side test scripts	NO	host script — no device interaction
atmosphere-*.sh boot scripts	DEPENDS	adb push to / vendor/bin/ after remount
Markdown docs / Constitution / plans / Issues / Fixed / CONTINUATION	NO	host docs — no firmware impact
Forked-player Kotlin (Presenter, MPV, SmartTube, TorrServe, Lampa, VLC, etc.)	YES via gradle local build + adb install -r	APK re-link required but no full firmware rebuild
Framework Java (frameworks/base/**/*.*.java)	YES	

File class	Rebuild required?	Reason
		system_server requires reboot at minimum
AIDL (*.aidl)	YES	stub generation requires recompile
Native C++ (external/**/*.*.cpp, frameworks/native/**/*.*.cpp)	YES	builds into APEX or system library
APEX libraries (vendor/**/lib/**/*.*.so inside APEX path)	YES	squashfs read-only by Main-line integrity
Kernel sources (kernel-5.10/**)	YES	requires kernel rebuild + boot.img
sepolicy (*.te)	YES	requires policy build
init.rc	YES	parsed at boot only
ro.* build properties	YES	immutable post-boot
persist.* runtime properties	NO	setprop persist.* mutable
XML resource overlays	YES	RRO recompile
media_codecs_*.xml	YES	APEX-bundled
display_settings.xml (user-data)	DEPENDS	adb push possible if SELinux permits
Android.bp / Android.mk / device.mk / BoardConfig.mk	YES	rebuilt-into-image artifacts
Test fixture binary assets	NO	adb push to / data/local/tmp/

Pre-build gates: CM-COVENANT-114-51-PROPAGATION (anchor across canonical files) + CM-AF-CLASSIFY-FIX-HELPER-EXISTS (helper present + sentinel literals) + CM-AF-LIVE-ADB-FIRST-COMMIT-MARKER (advisory WARN that scans recent commits for the footer literal). Three paired meta-test mutations.

Composition.

- §11.4.43 — TDD-fix workflow (§11.4.51 REFINES step 2 with the mechanical classifier).

- §11.4.9 — batch-source-fixes-before-rebuild (compose: live-ADB- test individually, then batch-commit).
- §11.4.6 — no guessing (each classification justified by matrix row; unmatched paths default to rebuild-required, never silent testable).
- §11.4.46 — validate-recent-work-before-post-flash (live-probe IS implicit pre-validation).
- §11.4.48 — UI-driven tests (live-probe CAN use uiautomator over adb shell).
- §11.4.49 — dual-approach (live-probe applies to both UI and Intent variants).
- §11.4.50 — deterministic consistency (live-probe runs N iterations on the live device before commit).

No escape hatch — no --skip-classify, --assume-rebuild, --no-footer-required flag exists. The discipline exists because the user mandate is unambiguous: "EVERY DETAIL IS IMPORTANT!!!! Not a single idea or idea's detail can be ignored, skipped, relativized or bluffed!"

Classification: universal (per §11.4.17). Applies to every project that consumes the constitution submodule — the matrix itself MAY be project-specific (each consumer adapts the file-class list to its own source tree), but the mandate to classify-before-commit + the LIVE_ADB_VALIDATED / REQUIRES_REBUILD footer literals + the classify-helper-script + the three pre-build gates are universal.

§11.4.52 — Autonomous-Validation Mandate (User mandate, 2026-05-18)

Forensic anchor — verbatim user mandate (2026-05-18):

"Make sure we have full automation tests which will do all this work in full automation! IMPORTANT: Make sure that all existing tests and Challenges do work in anti-bluff manner — they MUST confirm that all tested codebase really works as expected! We had been in position that all tests do execute with success and all Challenges as well, but in reality the most of the features does not work and can't be used! This MUST NOT be the case and execution of tests and Challenges MUST guarantee the quality, the completion and full usability by end users of the product! This MUST BE part of Constitution of our project, its CLAUDE.MD and AGENTS.MD if it is not there already, and to be applied to all Submodules's Constitution, CLAUDE.MD and AGENTS.MD as well."

Why this anchor exists. §11.4.25 (full-automation coverage) and §11.4.27 (no-fakes-beyond-unit-tests + 100%-test-type-coverage) and §11.4.39 (per-feature on-device end-user validation) collect-

ively mandated that every user-facing feature has automation tests with captured runtime evidence. They did NOT explicitly forbid operator-attended-only validation paths — i.e., a feature whose ONLY proof of working state requires a human to physically present at the device, drive UI manually, and observe outcomes. Phase 39.§CN exposed the gap: §CN's Kinopoisk 5.1 EAC3 closure was structurally fixed (libavutil bundled in APEX, six decoders register) yet end-user-validation degraded to "operator drives remote control while test polls" because Kinopoisk's TV-Compose UI is not accessibility-instrumented and uiautomator returns near-empty hierarchy. That validation path is operator-attended, non-reproducible in CI, and cannot prove deterministic consistency (§11.4.50) across N iterations. The User mandate elevates "full automation" from "preferred" to "mandatory": every user-facing PASS MUST have at least one captured-evidence path that does NOT require operator presence.

Operative rule (4 mandatory elements):

1. **Every user-facing feature MUST have at least one autonomous validation path.** "Autonomous" means: the validation runs end-to-end via adb shell + scripted automation, produces captured runtime evidence per §11.4.5, and reaches a PASS / FAIL verdict WITHOUT a human present to drive UI, observe screen, or make decisions. Operator-attended tests are SUPPLEMENTARY, never PRIMARY. A feature whose ONLY validation path is operator-attended is a §11.4.52 violation regardless of how carefully the operator's captures match §11.4.5 evidence requirements — the path does not scale to CI, does not run on every commit, does not survive operator unavailability, and produces the exact "tests pass but feature doesn't work for users" failure mode §11.4 specifically forbids.
2. **Acceptable autonomous-validation paths** (any one or more — non-exhaustive):
 - **Programmatic instrumentation APK** — a small platform-signed app that exercises the under-test surface directly via SDK APIs (e.g., `MediaCodec.createDecoderByName`, `MediaCodec.configure`, `AudioTrack` writes) and writes a structured JSON result file to a discoverable path. Closes UI-instrumentation gaps where the target app is not accessibility-instrumented.
 - **Headless intent dispatch + state poll** — `am start --es / am broadcast --es` to dispatch the under-test code path, then poll `dumpsys`, `/proc/<pid>/maps`, `media.metrics`, `/sys/...`, kernel sysfs, or the integration's network probe for the expected state transition.
 - **ADB-driven uiautomator** — applicable ONLY if the target app exposes accessibility nodes the dump can resolve. MUST verify via `uiautomator dump | grep -c clickable=true ≥ 1` before claiming uiautomator coverage is real. A near-

empty hierarchy is itself the captured-evidence proving UI-driven automation is INFEASIBLE for that target and the test MUST fall back to instrumentation-APK or headless-intent paths.

- **Network-side sink probe** — for features that surface on a network-accessible peripheral (e.g., Arvus HDMI dashboard at <http://<sink>/>, Sonos REST API, AirPlay receiver), the sink's own report counts as autonomous out-of-band evidence per §11.4.13.
- **HelixQA autonomous QA session** — for projects that have HelixQA fully incorporated per §11.4.27, the orchestrator's end-to-end session output counts as autonomous evidence.

3. Per-feature classification + tracking. Every entry in the project's coverage ledger (§11.4.25) MUST classify each feature's autonomous-validation path as one of: AUTONOMOUS_VERIFIED (path exists + last-run-green per §11.4.46), AUTONOMOUS_DESIGNED (path exists but RED per §11.4.43), OPERATOR_ATTENDED_ONLY (path requires human presence — release blocker until promoted to one of the other states), or NOT_APPLICABLE (e.g., a CLI tool that has no UI surface and the unit + integration tests already constitute autonomous proof). OPERATOR_ATTENDED_ONLY rows MUST cite a tracked work item per §11.4.15 + §11.4.16 that designs the autonomous-path migration. Closing the work item requires the migration to land, not just the operator capture.

4. Anti-bluff for autonomous paths themselves. An autonomous path that returns PASS without exercising the user-visible behaviour is a §11.4.52 violation just as severe as the original §11.4 PASS-bluff pattern. The autonomous path MUST produce positive captured evidence per §11.4.5 (audio: channel count + sample rate + glitch census; video: frame count + routing target

- frame health + obstruction census). A grep on a metadata field that doesn't prove behaviour is not an autonomous validation — it is a metadata bluff dressed up as automation. Paired meta-test mutations (§1.1) MUST catch the autonomous path's degradation to metadata-only or grep-only.

Composition.

- §11.4.25 — full-automation-coverage mandate. §11.4.52 is the strict expansion of invariant 1 + 2: "anti-bluff posture" and "proof of working capability" cannot be carried by operator-attended-only evidence — they MUST be carried by at least one autonomous path.
- §11.4.27 — no-fakes-beyond-unit-tests + 100%-test-type-coverage. §11.4.52 is the operational layer that closes the gap

between "the project has full-automation tests" and "every PASS has an autonomous evidence path".

- §11.4.39 — per-feature on-device end-user validation. §11.4.52 refines: the on-device scenario MUST itself be autonomously drivable.
- §11.4.43 — TDD-fix-discipline. The autonomous path MUST exist in the RED state BEFORE the fix lands, then go GREEN after. An autonomous path authored after the fix is a §11.4 PASS-bluff.
- §11.4.48 — UI-driven video testing. §11.4.52 establishes that when uiautomator returns a near-empty hierarchy on the target app, UI-driven IS infeasible and the test MUST fall back to instrumentation-APK or headless-intent. The fallback is REQUIRED — not optional.
- §11.4.49 — dual-approach testing. The Intent variant in a dual-approach pair often IS the autonomous path when the UI variant requires operator assistance.
- §11.4.50 — deterministic consistency. Autonomous paths run N iterations naturally; operator-attended paths cannot satisfy the N-iteration discipline at scale.
- §11.4.51 — live-ADB-first maximization. The instrumentation-APK path is itself LIVE_ADB_TESTABLE (gradle build + adb install -r
 - run + read JSON result), so live-probe IS the design loop for the autonomous path.

Pre-build gates:

- CM-COVENANT-114-52-PROPAGATION — anchor literal §11.4.52 present in all 5 canonical files (constitution/Constitution.md, constitution/CLAUDE.md, constitution/AGENTS.md, plus the parent consumer's CLAUDE.md + AGENTS.md) PLUS the full per-consumer propagation (parent project + every owned submodule
 - nested submodules + HelixQA dependencies — same scan pattern as CM-COVENANT-114-51-PROPAGATION).
- CM-AF-AUTONOMOUS-PATH-PER-FEATURE — every entry in the consuming project's coverage ledger (§11.4.25) has a non-empty autonomous-classification column with value in {AUTONOMOUS_VERIFIED, AUTONOMOUS_DESIGNED, OPERATOR_ATTENDED_ONLY, NOT_APPLICABLE}. OPERATOR_ATTENDED_ONLY rows MUST cite a tracked migration work item. (Project-side gate — consuming projects implement the ledger surface in their own pre-build test suite.)

Paired mutations (per §1.1):

- Strip §11.4.52 literal from constitution/Constitution.md → CM-COVENANT-114-52-PROPAGATION FAILs.
- Inject a feature row with OPERATOR_ATTENDED_ONLY and NO tracked migration work item → CM-AF-AUTONOMOUS-PATH-PER-FEATURE FAILs.

No escape hatch. No `--allow-operator-attended-only`, `--skip-autonomous-path`, `--manual-validation-suffices` flag exists. The discipline exists because the user mandate is unambiguous: "execution of tests and Challenges MUST guarantee the quality, the completion and full usability by end users". Operator-attended-only validation cannot guarantee that property at the release-gate layer — only autonomous paths can.

Classification: universal (per §11.4.17). Applies to every project consuming the constitution submodule. Each consumer adapts the autonomous-validation path catalogue to its own technology surface (Android: instrumentation APK + `uiautomator` + headless intent; Web: Playwright headless + API probe; CLI: subprocess

- `stdout/stderr` assertion; mobile native: device farm headless runner) but the mandate to provide at least one autonomous path per user-facing feature is universal.
-

§11.4.53 — Fixed_Summary parity mandate (User mandate, 2026-05-18)

Forensic anchor — verbatim user mandate (2026-05-18T17:55Z):

"Note: Just like for Issues we have `Issues_Summary`, for Fixed we MUST HAVE `Fixed_Summary` - like all other docs: ALWAYS in sync and up to date and ALWAYS exported into the PDF and HTML! Add this mandatory rule / constraint into the root (constitution Submodule) Constitution, AGENTS.MD and CLAUDE.MD."

Why this anchor exists. §11.4.12 already established that `docs/Issues_Summary.md` is the canonical short-form summary of `docs/Issues.md` and MUST always be regenerated + re-exported (HTML

- PDF) whenever the source changes. §11.4.19 added the column- alignment requirement so `Fixed_Summary.md` mirrors `Issues_Summary.md` shape. §11.4.53 closes the propagation gap: the parity discipline that §11.4.12 imposes on Issues / `Issues_Summary` MUST apply symmetrically to Fixed / `Fixed_Summary`. The mechanical behaviour already exists in `scripts/testing/sync_issues_docs.sh` (lines 98- 105 regenerate `Fixed_Summary` in stage 1b alongside `Issues_Summary` in stage 1a), but the mandate was never explicit in the Constitution — and an unstated rule is a §11.4 PASS-bluff risk: future refactors of `sync_issues_docs.sh` could drop the `Fixed_Summary` half without violating any canonical authority. §11.4.53 makes the existing behaviour explicit canonical authority so the gate set can defend it.

Operative rule. docs/Fixed_Summary.md is the symmetric short-form summary of docs/Fixed.md. It MUST be regenerated whenever Fixed.md changes. Its HTML + PDF exports MUST travel with the markdown (identical mtimes within sync_issues_docs.sh granularity). Stale exports are §11.4.53 violations regardless of whether the underlying .md is correct — an operator (or future agent) reading the HTML or PDF gets a divergent view of which items are closed, and the §12.10 CONTINUATION resumption guarantee silently breaks. Same discipline as §11.4.12 Issues_Summary applied to Fixed.md.

Generator. scripts/testing/generate_fixed_summary.sh is the canonical generator. It MUST exist + be executable + emit a markdown table whose header columns include Status and Type (per §11.4.19 column-alignment) so the Fixed_Summary.md shape mirrors Issues_Summary.md exactly.

Auto-sync wrapper. scripts/testing/sync_issues_docs.sh is the single operator-facing entry point. It already regenerates BOTH Issues_Summary AND Fixed_Summary in one shot (stages 1a + 1b), then exports HTML + PDF (stage 2), then colorizes per §11.4.23 (stage 3), then re-renders the PDFs from the colorized HTML (stage 3b). MUST be invoked after any edit to Fixed.md (just as §11.4.12 requires after any edit to Issues.md). Manual invocation of just the Issues half (--issues-only-style flag) is FORBIDDEN — the wrapper has no such flag and §11.4.53 prohibits adding one.

Sort order. Same pattern as §11.4.12 — by closure date DESC (most-recent-Fixed first), with \$-letter / Fix-# secondary sort. Documented at the top of the generated file.

HTML + PDF travel-together. Per §11.4.12 + §11.4.44, the three file types (.md, .html, .pdf) MUST always have identical mtimes within sync_issues_docs.sh granularity. Stale exports violate §11.4.53 regardless of whether the underlying .md is correct.

Composition:

- §11.4.12 — Issues_Summary parity is the sibling rule §11.4.53 symmetrizes. §11.4.12 and §11.4.53 are the canonical pair: edits to one source-of-truth (Issues.md or Fixed.md) trigger regeneration of BOTH summaries via the same wrapper.
- §11.4.19 — atomic Issues→Fixed migration triggers Fixed_Summary regeneration. When an item closes (status Fixed (→ Fixed.md) / Implemented (→ Fixed.md) / Completed (→ Fixed.md) per §11.4.33), the operator moves the entry from Issues.md to Fixed.md atomically and runs sync_issues_docs.sh — both summaries refresh.
- §11.4.23 — visual-cue & grouping colorizer post-processes both Issues_Summary.html AND Fixed_Summary.html. Stale

Fixed_Summary.html would carry pre-§11.4.23 styling — itself a §11.4.53 violation.

- §11.4.33 — type-aware closure-status vocabulary.
Fixed_Summary MUST respect the three terminal values (Fixed (→ Fixed.md), Implemented (→ Fixed.md), Completed (→ Fixed.md)) and emit them literally in the Status column.
- §11.4.44 — revision-header mandate applies to Fixed_Summary.md exactly as it applies to every other tracked Markdown doc.
- §12.10 — CONTINUATION.md resumption guarantee depends on the divergent-summary problem NOT existing; §11.4.53 is the explicit symmetric closure of that risk for the Fixed half.

Pre-build gates:

- CM-FIXED-SUMMARY-SYNC — canonical artifact-level gate (6 invariants): (1) docs/Fixed_Summary.md exists; (2) docs/Fixed_Summary.html exists with mtime ≥ Fixed_Summary.md mtime; (3) docs/Fixed_Summary.pdf exists with mtime ≥ Fixed_Summary.md mtime; (4) Fixed_Summary.md mtime ≥ Fixed.md mtime; (5) scripts/testing/generate_fixed_summary.sh exists + executable; (6) scripts/testing/sync_issues_docs.sh invokes the generator. Pre-build FAILs if any invariant is violated. Partially overlaps with CM-FIXED-COLUMN-ALIGNMENT (§11.4.19 Phase 39.AV gate) and CM-DOCS-EXPORT-SYNC (§11.4.15 4-doc + 6-export scan), but is explicitly the Fixed_Summary derived-doc parity invariant for §11.4.53 enforcement.
- CM-COVENANT-114-53-PROPAGATION — anchor literal §11.4.53 present across all 5 canonical files (constitution/Constitution.md, constitution/CLAUDE.md, constitution/AGENTS.md, parent consumer's CLAUDE.md + AGENTS.md). Same propagation pattern as CM-COVENANT-114-51-PROPAGATION and CM-COVENANT-114-52-PROPAGATION. Consumer projects propagate further (owned submodules, nested submodules, HelixQA deps) at their own per-project gate granularity.

Paired mutations (per §1.1):

- Strip §11.4.53 literal from constitution/CLAUDE.md → CM-COVENANT-114-53-PROPAGATION FAILs.
- Move scripts/testing/generate_fixed_summary.sh aside (so the invariant-(5) executable-check fails) → CM-FIXED-SUMMARY-SYNC FAILs.
- Touch docs/Fixed_Summary.md to a date older than docs/Fixed.md → invariant-(4) violated → CM-FIXED-SUMMARY-SYNC FAILs.

No escape hatch. No --skip-fixed-summary-sync, --issues-only, --summary-not-applicable flag exists. The discipline exists because the user mandate is unambiguous: "like all other docs: ALWAYS in sync and up to date and ALWAYS exported into the PDF and HTML". A divergent Fixed_Summary breaks operator + AI-agent

ability to discover what is fixed vs what is still open — and that breakage IS the §11.4 "tests pass but reality differs" pattern at the documentation layer.

Classification: universal (per §11.4.17). Applies to every project consuming the constitution submodule that maintains an Issues.md / Fixed.md split (the Issues-tracking lifecycle is already a §11.4.15 universal mandate, so this clause inherits the same universal scope). Projects that do not maintain a Fixed.md (e.g., single-binary throwaway prototypes) are NOT APPLICABLE; all projects that DO maintain a Fixed.md MUST land both gates and mutations within one cycle of adopting this Constitution version.

§11.4.54 — ATM-NNN ticket identifier mandate (User mandate, 2026-05-19)

Forensic anchor — verbatim user mandate (2026-05-19):

"Every workable item in Issues.md / Issues_Summary.md / Fixed.md / Fixed_Summary.md MUST carry a stable, unique, auto-incremental ATM-NNN ticket identifier. ATM- prefix, monotonic, never renumbered, append-only — once assigned to an item it stays bound to that item for the lifetime of the project across every reopen, migration, or rename."

Why this anchor exists. §11.4.15 + §11.4.16 + §11.4.19 + §11.4.33 established the lifecycle vocabulary for tracked items, but the items themselves were identified only by §-letter or Fix-# — both of which are **unstable across migrations**. §-letter is heading-local; when an item moves from Issues.md to Fixed.md the §-letter may be reused for a different item. Fix-# is only assigned on closure for items that touched source code; tasks / features / pure-doc items have no stable identifier at all. Cross-references between commits, test logs, captured-evidence artifacts, Reopens.md history (§11.4.55), README.md doc-link rows (§11.4.57), and external systems (Firebase Crashlytics Issue-IDs, Atlassian-style tracker rows) all need an identifier that is **monotonic, stable, and project-wide unique**. §11.4.54 closes that gap.

Operative rule. Every workable item in docs/Issues.md AND docs/Fixed.md MUST carry a [ATM-NNN] ticket identifier in its heading, in the form ## \$X.Y. [ATM-NNN] <title> (or ### \$X.Y. for nested items). NNN is a positive integer, zero-padded to at least 3 digits (ATM-001, ATM-042, ATM-127, ...). Identifiers are allocated by a **canonical helper script** (scripts/testing/ assign_atm_ticket_ids.sh) that maintains an append-only state file (scripts/testing/.atm_ticket_state.json). Once assigned to an item, an ATM-NNN MUST NEVER be:

1. **Renumbered** — the bind is permanent.

2. **Reused** for a different item even if the original item is force-deleted (the helper's state file detects collisions).
3. **Decrement** — counter is monotonic-only.
4. **Skipped intentionally** — gaps are forbidden in the assignment sequence (gaps indicate state-file corruption and trigger gate FAIL).

State file format. scripts/testing/.atm_ticket_state.json is a JSON-lines file with one record per allocated ID:

```
{ "atm_id": "ATM-001", "heading_hash": "<sha256 of normalized
heading>",
  "type": "Bug|Feature|Task", "current_location": "Issues|Fixed",
  "current_status": "<lifecycle value>", "reopens_count": <int>,
  "created_at": "<ISO 8601 UTC>", "last_modified": "<ISO 8601
UTC>" }
```

The heading_hash is the canonical binding key — when the helper scans Issues.md / Fixed.md, it computes the normalized hash of each heading and looks up an existing ATM-NNN before allocating a new one. This protects against accidental renumbering on heading reflows / wording edits (the hash MUST stay stable; if the heading text changes substantially, the state file's heading_hash field is updated in place via an explicit migration command, NOT auto-rebound).

Summary-table column. docs/Issues_Summary.md and docs/Fixed_Summary.md MUST carry a leftmost ATM ID column showing the identifier. Generators (generate_issues_summary.sh, generate_fixed_summary.sh) MUST emit this column as the first data column so operators / agents can sort + filter on it.

Composition:

- §11.4.15 (Status), §11.4.16 (Type), §11.4.19 (column-alignment Issues↔Fixed), §11.4.33 (type-aware closure terminal values). All four pre-existing mandates compose with §11.4.54 — the ATM-NNN is the new universal join key.
- §11.4.12 + §11.4.53 (Issues_Summary + Fixed_Summary regen on source changes) — the helper MUST be invoked from sync_issues_docs.sh so newly added items receive ATM-NNN identifiers before summary regeneration.
- §11.4.55 (Reopens-history per-item docs) — the per-item Reopens.md lives at docs/issues/<ATM-NNN>/Reopens.md.
- §11.4.57 (README.md doc-link section) — every Issues / Fixed item may be linked by ATM-NNN in external references.
- §11.4.44 (revision header) — applies to the state file's audit log if one is maintained.

Pre-build gates:

- CM-ATM-TICKET-IDS-COMPLETE — every workable-item heading in Issues.md AND Fixed.md MUST carry an [ATM-NNN] token

matching `\[ATM-[0-9]{3,}\]`. Headings without one FAIL the gate.

- CM-ATM-TICKET-IDS-UNIQUE — no two items share an ATM-NNN. The state file's record count MUST equal the union of Issues.md + Fixed.md [ATM-NNN] occurrences (no orphan IDs, no duplicates).
- CM-ATM-TICKET-IDS-MONOTONIC — the maximum ATM-NNN in the state file MUST equal record_count (no gaps).
- CM-COVENANT-114-54-PROPAGATION — anchor literal §11.4.54 present across canonical files (constitution/Constitution.md, constitution/CLAUDE.md, constitution/AGENTS.md, parent consumer's CLAUDE.md + AGENTS.md).

Paired mutations (per §1.1):

- Remove [ATM-NNN] from one Issues.md heading → CM-ATM-TICKET-IDS-COMPLETE FAILs.
- Duplicate an ATM-NNN in the state file → CM-ATM-TICKET-IDS-UNIQUE FAILs.
- Delete ATM-NNN=2 from a 5-record state file → CM-ATM-TICKET-IDS-MONOTONIC FAILs (gap at 2).
- Strip §11.4.54 literal from constitution/CLAUDE.md → CM-COVENANT-114-54-PROPAGATION FAILs.

No escape hatch. No `--skip-atm-assignment`, `--renumber`, or `--no-atm-id-required` flag exists. The discipline exists because unstable item identity is the exact failure mode that produces "the test was passing last week, what changed?" sessions where the operator cannot tell whether a given item is the same one tracked before or a coincidentally similarly-named successor.

Classification: universal (per §11.4.17). Applies to every project consuming the constitution submodule that maintains an Issues / Fixed split (cf. §11.4.53 scoping). Projects that do not maintain such a split are NOT_APPLICABLE.

§11.4.55 — Reopens-history tracking + per-item Reopens.md doc (User mandate, 2026-05-19)

Forensic anchor — verbatim user mandate (2026-05-19):

"Add a Reopens-count column to Issues / Issues_Summary / Fixed / Fixed_Summary. For any item whose reopens-count > 0, create docs/issues/ATM-NNN/Reopens.md (+ HTML + PDF) with comprehensive reopen history + Fixed cycles. Each reopen MUST include By (AI / User), On (date), Reason, Evidence, and each Fixed-marking with its reasoning chain."

Why this anchor exists. §11.4.34 mandated that Reopened status carry a ****Reopened-Details:**** block — but that block lives in the **current** Issues.md heading and is overwritten on the next state change. A complete reopen / fix-cycle audit trail across the lifetime of an item was not previously canonical. §11.4.55 makes the full history first-class: every item that has been reopened at least once gets a dedicated Reopens.md companion doc capturing the entire chronological timeline — every reopen, every closure, every reasoning chain — so an operator / agent investigating "why was this reopened five times" has a single, authoritative source to read.

Operative rule. Every workable item with `reopens_count > 0` MUST have a companion document at `docs/issues/ATM-NNN/Reopens.md` (plus its HTML + PDF exports per §11.4.44 + §11.4.53 sync discipline). The document MUST contain:

1. **Revision header** per §11.4.44 (Revision integer + Last modified ISO 8601 UTC).
2. **Item identification** — ATM ID, Title, Type, Current Status, Current Location (Issues.md / Fixed.md), link back to the live heading.
3. **Cycle counters** — Total reopens, Total fixed cycles (items can reopen multiple times, each followed by a re-closure).
4. **Chronological timeline** — one entry per state-change event, each entry capturing:
 - **By:** AI or User (per §11.4.34 source attribution).
 - **On:** ISO date.
 - **Event:** Opened | Reopened | Fixed | Implemented | Completed.
 - **Reason:** the closed-vocabulary value from §11.4.34 (test-failed / manual-testing-detected / captured-evidence-contradicts / end-user-report / cycle-re-discovered / design-reconsidered) for reopens; captured-evidence summary for closures.
 - **Evidence:** path to or short description of captured artefact (test log path, recording path, sink-probe report, operator quote).
 - **Outcome:** what the next state transition was.
5. **Reasoning chain for each closure** — for every Fixed / Implemented / Completed event, the reasoning chain that justified marking it closed (root-cause analysis link, captured-evidence under same-conditions per §11.4.7, gate / mutation pair that defends against regression).
6. **Most-recent state-change pointer** — explicit cross-reference to the current Issues.md / Fixed.md heading.

Summary-table column. `Issues_Summary.md` and `Fixed_Summary.md` MUST carry a Reopens column showing the integer count. When the count > 0 the cell MUST be a hyperlink to

docs/issues/<ATM-NNN>/Reopens.md. Generators emit the column; the colorizer (§11.4.23) MAY apply a visual cue when reopens > 2 (repeated-reopen signal — investigate before closing again).

Composition:

- §11.4.34 (Reopened-Details on current heading) is the **per-event** capture; §11.4.55 is the **per-item history** aggregation. Both layers MUST be in sync — the state-machine helper updates Reopens.md on every Reopened-Details parse.
- §11.4.54 (ATM-NNN) provides the stable identifier so the per-item doc has a permanent path even after Issues→Fixed migration.
- §11.4.44 (revision header) applies to every Reopens.md.
- §11.4.45 (Status.md per-integration) — the per-item Reopens.md is the item-scoped analogue of the integration-scoped Status.md.
- §11.4.53 (Fixed_Summary parity) — Reopens column appears on BOTH summary tables symmetrically.

Pre-build gates:

- CM-REOPENS-DOC-EXISTS-WHEN-COUNT-GT-ZERO — for every state-file record with reopens_count > 0, docs/issues/<ATM-NNN>/Reopens.md MUST exist (+ HTML + PDF). Missing doc FAILs.
- CM-REOPENS-DOC-REVISION-HEADER — every Reopens.md carries the §11.4.44 revision header.
- CM-REOPENS-COL-IN-SUMMARIES — both Issues_Summary.md and Fixed_Summary.md carry a Reopens column.
- CM-COVENANT-114-55-PROPAGATION — anchor literal §11.4.55 across canonical files.

Paired mutations (per §1.1):

- Delete docs/issues/ATM-NNN/Reopens.md for an item with reopens_count=2 → CM-REOPENS-DOC-EXISTS-WHEN-COUNT-GT-ZERO FAILs.
- Strip revision header from a Reopens.md → CM-REOPENS-DOC-REVISION-HEADER FAILs.
- Remove Reopens column from Issues_Summary.md table header → CM-REOPENS-COL-IN-SUMMARIES FAILs.
- Strip §11.4.55 literal from constitution/CLAUDE.md → CM-COVENANT-114-55-PROPAGATION FAILs.

No escape hatch. No --skip-reopens-doc, --collapse-history, --reopens-not-applicable flag. The discipline exists because loss of reopen history is the exact failure mode that produces "why does this keep happening" sessions with no auditable answer.

Classification: universal (per §11.4.17). Applies wherever §11.4.34 applies (every project tracking Reopened status).

§11.4.56 — Status_Summary parity + two-audience format (User mandate, 2026-05-19)

Forensic anchor — verbatim user mandate (2026-05-19):

"Every Status.md doc gets a Status_Summary parity companion ALWAYS in sync, exported to HTML + PDF. Two-page format: page 1 = non-developer audience (team-specific: audio team for audio Status, video team for video Status, etc.), page 2 = software engineer summary. Auto-generated after every main Status update."

Why this anchor exists. §11.4.45 established Status.md per integration domain — but Status.md targets engineers (cites gate names, §-letter references, commit hashes, captured-evidence file paths). Non-developer stakeholders (audio team, video team, QA leads, product reviewers) need a plain-language version of the same content, **always derived** from the engineering Status.md so the two views can never diverge. §11.4.56 introduces the symmetric companion doc with a two-audience layout.

Operative rule. For every docs/<domain>/<integration>/ Status.md that satisfies §11.4.45, a companion docs/<domain>/<integration>/ Status_Summary.md MUST exist with:

1. **Revision header** per §11.4.44.
2. **Page 1 — For the <team>** (audience-specific heading; the team name is derived from the integration domain — audio team for docs/dolby/*, video team for docs/video/*, etc.). Page 1 contains:
 - Plain-language summary of current state (1-3 paragraphs).
 - **What works** (1-3 bullets, end-user-visible behaviour).
 - **What's broken or pending** (1-3 bullets).
 - **Operator / team actions** if any.
 - NO code references, NO §-letter jargon, NO captured-evidence file paths, NO gate / mutation names.
3. **Page 2 — For software engineers** — same content density as Status.md but condensed:
 - §-letter references, gate names, commit hashes, captured-evidence file paths.
 - Cross-references to Issues.md / Fixed.md items by ATM-NNN (§11.4.54).
4. **HTML + PDF exports** travel with the markdown (identical mtimes within sync wrapper granularity).
5. **Auto-generation** — the canonical helper scripts/testing/generate_status_summary.sh <Status.md path> produces both pages. The generator MUST be invoked from a sync wrapper (e.g. scripts/testing/sync_integration_status.sh per §11.4.45) every time the source Status.md is updated.

Page-1 audience derivation. The generator maps domain → audience name via a project-controlled mapping table (e.g. audio → Audio team, video → Video team, network → Network team, drm → DRM / streaming team). Unmapped domains default to Project team. The mapping table lives in the project's generator config, NOT in the Constitution (project-specific data per §11.4.17).

Composition:

- §11.4.45 (Status.md per integration) — Status_Summary.md COMPLEMENTS, never replaces. Both files exist together.
- §11.4.12 + §11.4.53 (parity discipline) — Status_Summary follows the same regeneration / HTML+PDF / mtime-alignment pattern.
- §11.4.44 (revision header) — applies to Status_Summary.md.
- §11.4.23 (colorizer) — Status_Summary.html receives the same type/status visual cues if it embeds tracked-item references.
- §12.10 (CONTINUATION.md) — non-developer stakeholders read Status_Summary; engineers read Status.md + CONTINUATION.md + Issues.md.

Pre-build gates:

- CM-STATUS-SUMMARY-EXISTS-FOR-EVERY-STATUS — for every docs/**/ Status.md, the sibling Status_Summary.md MUST exist (+ HTML + PDF) with mtime ≥ Status.md mtime – tolerance.
- CM-STATUS-SUMMARY-TWO-AUDIENCE — every Status_Summary.md contains BOTH the Page 1 – For the <team> heading AND the Page 2 – For software engineers heading. Missing either FAILs.
- CM-STATUS-SUMMARY-REVISION-HEADER — §11.4.44 header present.
- CM-COVENANT-114-56-PROPAGATION — anchor literal across files.

Paired mutations (per §1.1):

- Delete a Status_Summary.md → CM-STATUS-SUMMARY-EXISTS-FOR-EVERY-STATUS FAILs.
- Remove Page 1 heading from a Status_Summary.md → CM-STATUS-SUMMARY-TWO-AUDIENCE FAILs.
- Strip §11.4.56 literal from constitution/CLAUDE.md → CM-COVENANT-114-56-PROPAGATION FAILs.

No escape hatch. No --skip-status-summary, --engineer-only, --no-audience-split flag. Plain-language stakeholder access is not negotiable — the project ships to humans, not just to engineers.

Classification: universal (per §11.4.17). Applies wherever §11.4.45 applies (every project that maintains domain-scoped Status.md docs).

§11.4.57 — README.md doc-link section + revision metadata (User mandate, 2026-05-19)

Forensic anchor — verbatim user mandate (2026-05-19):

"Add a doc-link section to README.md — links to Issues + Issues_Summary + Fixed + Fixed_Summary + CONTINUATION + ALL Status docs + their exports. Each link shows revision + last-modified."

Why this anchor exists. Operators, AI agents, and external reviewers arriving at the project repo for the first time need a single discoverable entry point listing every canonical tracked- items + status document, along with each document's freshness (revision + last-modified). Without this surface, agents resort to `find docs -name '*.md'` which returns hundreds of files unranked. §11.4.57 makes the README.md the canonical index.

Operative rule. Every project's top-level README.md MUST contain a section titled Tracked-Items + Status Documents (or the project's localized equivalent — the section heading MUST contain the literal Tracked-Items for gate detection). The section MUST be a markdown table with columns: Document (human- readable name), Last modified (ISO 8601 UTC from the doc's §11.4.44 revision header), Revision (integer from same header), Markdown (relative link to .md), HTML (relative link to .html), PDF (relative link to .pdf).

The section MUST link to:

1. Issues.md, Issues_Summary.md (§11.4.12, §11.4.15, §11.4.16).
2. Fixed.md, Fixed_Summary.md (§11.4.19, §11.4.53).
3. CONTINUATION.md (§12.10).
4. **Every** docs/**/Status.md and its Status_Summary.md pair (§11.4.45, §11.4.56). Status docs are auto-discovered by the generator via `find docs -name 'Status.md'`.

Generator. `scripts/testing/update_readme_doc_links.sh` is the canonical helper. It:

1. Scans the canonical doc paths.
2. Extracts each doc's Revision + Last modified fields from its §11.4.44 header.
3. Renders the markdown table with current values.
4. Replaces the section between explicit markers (`<!-- doc-link-section:begin -->` and `<!-- doc-link-section:end -->`) in README.md.

The wrapper MUST be invoked from `sync_issues_docs.sh` (so every Issues.md / Fixed.md update refreshes the README freshness data) AND from `sync_integration_status.sh` (so every Status.md update likewise refreshes README).

Composition:

- §11.4.12 + §11.4.19 + §11.4.53 (Issues / Issues_Summary / Fixed / Fixed_Summary parity) — README links to all four.
- §11.4.44 (revision header) — README pulls Revision + Last modified from each doc's header.
- §11.4.45 (Status.md) + §11.4.56 (Status_Summary.md) — README enumerates every Status pair.
- §12.10 (CONTINUATION.md) — explicitly linked from README so operators discover it on arrival.

Pre-build gates:

- CM-README-DOC-LINK-SECTION-PRESENT — README.md contains the literal Tracked-Items heading AND both section markers (<!-- doc-link-section:begin -->, <!-- doc-link-section:end -->).
- CM-README-DOC-LINK-ROWS-COMPLETE — every canonical doc (Issues, Issues_Summary, Fixed, Fixed_Summary, CONTINUATION, every Status.md + Status_Summary.md found under docs/) appears as a row inside the section.
- CM-README-DOC-LINK-FRESHNESS — the Last modified value in each row matches the corresponding doc's §11.4.44 header within sync-wrapper granularity (no row staler than the source doc by more than the sync wrapper's tolerance).
- CM-COVENANT-114-57-PROPAGATION — anchor literal across files.

Paired mutations (per §1.1):

- Strip the section markers from README.md → CM-README-DOC-LINK-SECTION-PRESENT FAILS.
- Remove the CONTINUATION.md row from the section → CM-README-DOC-LINK-ROWS-COMPLETE FAILS.
- Backdate a Last modified value in a row → CM-README-DOC-LINK-FRESHNESS FAILS.
- Strip §11.4.57 literal from constitution/CLAUDE.md → CM-COVENANT-114-57-PROPAGATION FAILS.

No escape hatch. No --skip-readme-doc-links, --collapse-status-rows, --no-freshness-check flag. The discipline exists because invisible docs are non-existent docs from a discoverability standpoint, and the §11.4 covenant specifically prohibits surfaces where claims (here: doc freshness) can drift unnoticed.

Classification: universal (per §11.4.17). Applies to every project that maintains an Issues / Fixed split or Status.md docs (i.e., to every project consuming this Constitution that has any of §11.4.15 / §11.4.45 / §11.4.53 in scope).

§11.4.58 — Parallel-development methodology (User mandate, 2026-05-19)

Forensic anchor — verbatim user mandate (2026-05-19T~05:00Z MSK):

"We MUST DO one comprehensive research and planning in the background in parallel with current mainstream work: our current methodology of the development is very slow. It takes us days to fix a bunch of bugs, add some changes or features and all this to be tested, verified and shipped. From iteration to iteration we are slower and slower. We MUST CREATE adjusted improved version of working methodology where multiple workable items could be done in parallel, all come into the central (main) branch as they are done, then we at particular moment rebuild and reflash the System and in background full testing with validation and verification is done. Each parallel work on one workable (or more) item(s) must use parallel agents as much as possible! We MUST HAVE proper synchronization mechanism between parallel working routines so they do not cause conflicts, break features or create any other types of the problems! Document everything - the whole plan, whole methodology, working flow with in depth diagrams and graphs, all user guides and manuals and then add this all into our root (constitution Submodule) Constitution, CLAUDE.MD and AGENTS.MD! Make sure we start using this ASAP since we MUST increase efficiency and productivity a couple of times now! Writing in depth tests (all supported types of the tests) with Challenges and full HelixQA use is MANDATORY! Every test we execute besides executed with success MUST RESULT in proof that actual functionality being tested REALLY DOES WORK with NO BLUFF of any kind! Heavt enforcement of no-bluff / anti-bluff policy IS MANDATORY!"

Why this anchor exists. Sequential phase-chain working pattern (Phase 39.A → Phase 39.B → ... → Phase 39.DT, observed 2026-05-05 to 2026-05-19: 86 unique Phase 39.X sub-phases across 14 days = ~6/day sub-phase rotation, 224 commits / 14 days = ~16/day) serialises on five distinct bottlenecks: (B1) commit_all.sh flock at .git/.commit_all.lock, (B2) single-thread sub-phase chaining via docs/CONTINUATION.md hand-offs, (B3) rebuild-blocking on every REQUIRES_REBUILD fix (§12.7 -j2 cap = 4-6 h rebuild + 30 min flash

- 60 min validate per cycle), (B4) single-thread test_all_fixes.sh sweep (~30-60 min × 8 phase-device combinations), (B5) sub-agent dispatch latency (one-at-a-time spawn + wait pattern). Net effect: single-item wall-clock 1-4 days where productive work is < 4 h. The User mandate requires the methodology to multiply throughput several-x.

Operative rule. Project work proceeds through the Parallel Work Unit (PWU) pipeline rather than sequential phase-chain. Each PWU is a self-contained workable item with mandatory components (ATM-NNN identifier per §11.4.54, Issues.md entry per §11.4.15+§11.4.16, file- scope manifest, §11.4.43 RED test, source patch, pre-build gate per §11.4.4(b) layer 1, post-flash test per §11.4.4(b) layer 3, paired §1.1 meta-test mutation, §11.4.4(b) layer 4 HelixQA Challenge bank entry, captured-evidence directory per §11.4.5+§11.4.52). PWUs execute through five pipeline stages: **Stage 1 DEVELOP** (parallel, N PWU agents in isolated work-trees), **Stage 2 MERGE** (serial, conductor processes one PWU at a time via `commit_all.sh flock + §11.4.41 4- step merge-first pipeline`), **Stage 3 REBUILD+FLASH** (parallel where possible: AOSP build inside §12.7 bounded scope, D3+D4 flash serialised on USB hardware), **Stage 4 VALIDATE** (parallel on D3+D4+meta-test+ coverage-audit), **Stage 5 SWEEP** (parallel: HelixQA Challenge bank, Issues→Fixed migration, README.md doc-link refresh per §11.4.57, HTML+PDF exports). Stage 1 of round N+1 starts WHILE Stages 4+5 of round N are still running — this is the primary throughput multiplier.

Synchronization mechanism. Four-layer lock hierarchy: **L1** parent serial flock `.git/.commit_all.lock` (held only during Stage 2, released between PWUs), **L2** per-submodule git operations (implicit via cascade), **L3** contention-path advisory locks at `qa-results/pwu-locks/<sha256(path)>.lock` for the 10 forbidden cross- PWU paths (CLAUDE.md/AGENTS.md/Constitution.md/CONTINUATION.md/Issues.md/Fixed.md/pre_build_verification.sh/meta_test_false_positive_proof.sh/build.sh/commit_all.sh+push_all.sh/device.mk+BoardConfig.mk/ atmosphere.sh/init.rc), **L4** per-PWU git worktree (zero cross- PWU file conflicts during Stage 1). Disjoint-scope PWUs (different test files, different APKs, different drivers, different framework services) run fully parallel. Conflict detection at Stage 2 entry: `git fetch --all --prune --tags + git diff main...HEAD -- <scope>`

- cross-PWU scope overlap check. Overlap detected → PWU rejected to Stage 1 for rebase (per §11.4.41 step 2 integration-before-force-push).

Anti-bluff enforcement. Conductor REFUSES to merge a PWU lacking all four anti-bluff checks: **C1** §11.4.43 RED test captured-evidence (file exists + non-zero exit code in log + timestamp predates source patch — proves test catches regression), **C2** §1.1 paired meta-test mutation (applied + gate FAILs under mutation + restored + gate PASSes — proves gate is not a bluff gate), **C3** §11.4.50 deterministic- consistency (3 iterations for normal, 10 for cycle-validation, ALL identical exit codes AND identical evidence-hashes — eliminates §11.4.7 flake/transient/intermittent demotion path), **C4** §11.4.5 captured-evidence (audio: WAV with non-trivial RMS + fprobe channel count; video: screen recording with fprobe frame count > 0 + analyzer matched event; UI: uiautomator

dump with under-test element state; or HelixQA result.json PASS verdict + positive-evidence chain). HelixQA coverage is MANDATORY for every user-visible PWU per User mandate — Challenge bank entry in tools/helixqa/banks/atmosphere.yaml referencing the PWU's ATM-NNN + dispatching to the on-device test + scoring PASS only on positive captured evidence. Metadata-only PASS / configuration- only PASS / absence-of-error PASS / grep-without-runtime-evidence PASS all REJECTED at the merge gate.

Agent orchestration. Four roles: **Conductor** (1, main thread) — issues ATM-NNN, dispatches PWU agents, runs Stage 2 merge serially, runs Stages 3-5, owns all contention-path edits, maintains docs/CONTINUATION.md §3 live snapshot. **PWU agent** (4-6 background) — one PWU each, Stage 1 work in isolated worktree, signals qa-results/pwu-<atm>/READY_FOR_MERGE on completion. **Validator** (4 background) — Stage 4 work in parallel on D3+D4+meta-test+coverage- audit. **Sweeper** (2 background) — Stage 5 work in parallel with next round's Stage 1. Max concurrent agent count ~12 at peak, bounded by §12.6 60% memory budget (~6 GB total ≤ 38 GB budget). Composition with §12 host-session safety: conductor refuses dispatch if host_check_safety fails; per §12.7 AOSP build still hard-capped at -j2 inside bounded scope; per §12.8 + §12.8b + §12.8c concurrency gates still block on stray gradle/kotlin daemons.

Composition map (mandatory):

- §11.4.4 — four-layer test coverage per PWU (pre-build + post-build + on-device + HelixQA bank).
- §11.4.5 — audio/video quality analysis comprehensiveness (PWU captured-evidence directory).
- §11.4.6 — no-guessing mandate (every PWU claim backed by captured forensic evidence or explicit UNCONFIRMED: tag).
- §11.4.7 — demotion-evidence rule (3/3 deterministic-consistency closes the demotion-bluff path).
- §11.4.9 — batch-source-fixes-before-rebuild (Stage 2 → Stage 3 batch threshold).
- §11.4.15 + §11.4.16 + §11.4.33 — PWU status + type vocabulary + type-aware closure terminal value.
- §11.4.19 — atomic Issues.md → Fixed.md migration on PWU closure.
- §11.4.41 — Pre-Force-Push Merge-First 4-step pipeline at Stage 2 entry.
- §11.4.42 — Iteration-discipline (PWU pipeline IS the iteration conductor; §11.4.58 binds steps 1-5 to PWU stages 1-5).
- §11.4.43 — TDD RED-first per-PWU enforced at merge time.
- §11.4.45 — Integration-status-doc maintenance (PWU's Status.md updated at every stage transition).
- §11.4.49 — Dual-approach testing (PWU MUST ship both UI-driven AND Intent/Broadcast-driven variants when applicable).
- §11.4.50 — Deterministic-consistency (3-iter normal / 10-iter cycle-validation merge-time enforcement).

- §11.4.52 — Autonomous-validation (PWU's on-device test MUST run without operator presence per Stage 4 parallel design).
- §11.4.54 — ATM-NNN ticket identifier (PWU identifier replaces Phase 39.X letters).
- §11.4.57 — README.md doc-link refresh at Stage 5.
- §12.6 — 60% memory-budget ceiling (caps concurrent agent count).
- §12.7 — AOSP $m - j$ hard-cap at $-j2$ (Stage 3 build cap).
- §12.8 + §12.8b + §12.8c — concurrency hardening (Stage 3 preflight refuses on running gradle/kotlin/git-pack-objects/load-per-cpu spike).
- §12.10 — CONTINUATION.md maintenance (conductor owns the file by §3.4 forbidden cross-PWU rule).
- §9.2 — data safety (every history rewrite during Stage 2 merge-first step 2 backed by hardlinked .git backup).

Pre-build gates:

- CM-PWU-LOCK-HIERARCHY — verify lock hierarchy script exists at scripts/testing/pwu_acquire_path_lock.sh and scripts/testing/pwu_release_path_lock.sh, both executable, both reference the 10 forbidden cross-PWU paths from §3.4 of docs/guides/PARALLEL_DEVELOPMENT_METHODODOLOGY.md.
- CM-PWU-ANTI-BLUFF-COVERAGE — for every PWU with status "Ready for merge" or beyond, assert all four anti-bluff checks (C1-C4) have captured-evidence files under qa-results/pwu-<atm>/evidence/. PWU lacking any of red-test-output / mutation_patch / deterministic-consistency / captured-feature-proof FAILs the gate.
- CM-PWU-MERGE-QUEUE-DISCIPLINE — scan qa-results/pwu-queue/ for PWUs that bypassed the merge queue (commits on main without a corresponding qa-results/pwu-queue/merged/<atm> marker). Any bypass FAILs the gate.
- CM-PWU-PARALLEL-AGENT-LIMIT — assert no more than 6 concurrent background PWU agents (count tmux/screen sessions or worktree branches) — over-limit FAILs the gate (per §12.6 memory budget).
- CM-COVENANT-114-58-PROPAGATION — anchor literal §11.4.58 present in constitution/CLAUDE.md + constitution/AGENTS.md + parent CLAUDE.md/AGENTS.md + every owned-submodule CLAUDE.md/ AGENTS.md (42 files total in current ATMOSphere consumer family).

Paired mutations (per §1.1):

- Move scripts/testing/pwu_acquire_path_lock.sh aside → CM-PWU-LOCK-HIERARCHY FAILs.
- Touch a PWU's READY_FOR_MERGE marker without red-test-output.log → CM-PWU-ANTI-BLUFF-COVERAGE FAILs.

- Land a commit on main without a corresponding qa-results/pwu-queue/merged/<atm> marker → CM-PWU-MERGE-QUEUE-DISCIPLINE FAILS.
- Spawn a 7th concurrent PWU agent → CM-PWU-PARALLEL-AGENT-LIMIT FAILS.
- Strip §11.4.58 literal from constitution/CLAUDE.md → CM-COVENANT-114-58-PROPAGATION FAILS.

No escape hatch. No --skip-merge-queue, --allow-bypass, --no-anti-bluff-check, --unlimited-agents, --sequential-phase-chain-mode flag exists in any pipeline helper. The discipline exists because (a) the User mandate explicitly requires the multiplier ASAP and (b) the §11.4 covenant specifically prohibits PASS-bluffs (which the four anti-bluff merge-time checks mechanically prevent). Operators who feel they need to bypass the pipeline for a specific high-urgency fix should split the work into a single trivial PWU and let the pipeline run normally — Stage 1 of a trivial PWU is < 30 min, Stage 2 is < 5 min, Stage 3 is the same rebuild cost they would pay anyway.

Classification: universal (per §11.4.17). Applies to every project consuming this Constitution that has multiple owned-submodules

- a sequential commit/push tool + a captured-evidence testing discipline. Project-specific implementations (agent dispatch helpers, worktree layout, batch thresholds) live in consumer-side docs/guides/PARALLEL_DEVELOPMENT_METHODODOLOGY.md (this Constitution defines the discipline; consumers implement the tooling).

Reference: parent docs/guides/PARALLEL_DEVELOPMENT_METHODODOLOGY.md (full methodology with diagrams, templates, operator manual, and migration plan).

§11.4.59 — README always-sync mandate (User mandate, 2026-05-19)

Forensic anchor — direct user mandate (verbatim, 2026-05-19):

"fully review and update our main README document. Some points are not valid anymore, some are missing. Make sure main README is among documents we MUST ALWAYS keep updated and in Sync with the projects and other documentation! Make sure we always export it (on every update) into PDF and HTML. This mandatory rules/constraints MUST BE all added into the root (constitution Submodule) Constitution, AGENT.MD and CLAUDE.MD!"

README.md at the project root is a §11.4.12-class always-sync document. It MUST be:

1. **Reviewed and updated whenever** new docs / integrations / Status.md entries appear, new submodules land, applied-fixes count changes, or canonical paths shift.
2. **Kept in lockstep** with docs/CONTINUATION.md (§12.10) and the Issues / Issues_Summary / Fixed / Fixed_Summary doc set (§11.4.12, §11.4.53) — same always-sync discipline.
3. **Exported to .html and .pdf on every update.** New helper scripts/testing/sync_readme_export.sh performs the pandoc + weasyprint export; it is auto-invoked by scripts/testing/sync_issues_docs.sh so a single doc-sync run refreshes the entire doc surface (Issues / Issues_Summary / Fixed / Fixed_Summary / CONTINUATION / README — md + html + pdf).
4. **Carry a §11.4.44 revision header** (Revision N + Last modified ISO timestamp) at the top of the file.
5. **Contain a Documentation Map section** linking to every Status.md
 - Status_Summary.md + spec + plan + guide + script-companion doc + changelog + the constitution submodule, plus a per-audience navigation (end user / developer / QA / agent).
6. **Self-contained** — no hyperlinks to ephemeral external systems as the only source of truth.

Stale exports are §11.4.59 violations regardless of whether the underlying README.md is correct — an operator (or future agent) reading the HTML or PDF gets a divergent view, and the §12.10 CONTINUATION resumption guarantee silently breaks. Same discipline as §11.4.12 Issues_Summary and §11.4.53 Fixed_Summary applied to README.md.

Captured-evidence enforcement. Pre-build gate CM-README-EXPORT-SYNC locks four invariants: (a) README.md exists, (b) README.html exists, (c) README.html mtime $\geq$ README.md mtime, (d) README.pdf mtime $\geq$ README.md mtime (skipped gracefully if weasyprint is unavailable on the host but enforced when the PDF is present). Paired meta-test mutation backdates README.html + README.pdf so the source is newer $\rightarrow$ gate FAILs.

Composition. Composes with §11.4.12 (Issues_Summary parity), §11.4.18 (script-companion docs), §11.4.23 (visual-cue HTML colorizer not applicable to README's narrative format), §11.4.44 (revision header on every Status.md and now README.md), §11.4.45 (Status.md integration), §11.4.53 (Fixed_Summary parity — README is the canonical sibling at the project-overview layer), §11.4.56 (Status_Summary parity), §11.4.57 (README.md is the

canonical index per Phase 39.EW+1), §12.10 (CONTINUATION.md resumption guarantee depends on README's Documentation Map being current).

No escape hatch. §11.4.59 has NO operator-facing override flag. No --skip-readme-sync, --no-readme-export, --readme-stale-OK flag exists. The discipline exists because README.md is the first file any new agent / operator / contributor reads — letting it diverge from reality is the exact §11.4 PASS-bluff pattern but at the project-overview layer.

Classification: universal (per §11.4.17). Applies to every project consuming this Constitution. The doc-sync helper, pandoc + weasyprint dependencies, and gate name are universal; the specific Documentation Map contents are consumer-side per-project.

Canonical authority: constitution submodule Constitution.md §11.4.59.

Non-compliance is a release blocker regardless of context.

§11.4.60 — Documentation always-sync composite covenant (User mandate, 2026-05-19)

Forensic anchor — verbatim user mandate (2026-05-19 ~09:00Z):

"Double check if all documents are properly tied with our root Constitution, CLAUDE.MD and AGENTS.MD so they are always up to date, always in sync and exported into PDF and HTML! ... Issues, Issues_Summary, Fixed, Fixed_Summary, Continuation, Status and Status_Summary for all contexts (areas) — THEY ALL MUST BE REGULARLY UPDATED, IN SYNC AND CONSISTENT without giving at any moment false picture about the state of the project or particular area(s) of it!"

The covenant. Eight documentation classes constitute the project's living state surface. They MUST be in sync at all times across markdown + HTML + PDF artefacts. Per-class anchors §11.4.12 / §11.4.44 / §11.4.45 / §11.4.53 / §11.4.56 / §11.4.57 / §11.4.59 / §12.10 each govern one class; §11.4.60 binds them via a single mechanically-enforced composite invariant so the failure mode "one per-class gate silently disabled while operator reads a divergent HTML/PDF" is structurally impossible.

Eight bound doc classes (artefact triple — .md + .html + .pdf):

1. docs/Issues.md — open-item tracker (§11.4.12 + §11.4.15 + §11.4.16)
2. docs/Issues_Summary.md — auto-generated short form (§11.4.12)
3. docs/Fixed.md — closed-item archive (§11.4.53)

4. docs/Fixed_Summary.md — auto-generated short form (§11.4.53)
5. docs/CONTINUATION.md — resumption handoff (§12.10)
6. README.md — project overview + doc-link index (§11.4.57 + §11.4.59)
7. docs/**/Status.md (every domain-scoped instance) — per-integration status (§11.4.45)
8. docs/**/Status_Summary.md (every domain-scoped instance) — auto-generated short form (§11.4.56)

Mandatory composite gate. CM-DOCS-COMPOSITE-SYNC (pre-build, device/rockchip/rk3588/tests/pre_build_verification.sh):

- For every doc-class instance with .md present, verify .html mtime ≥ .md mtime AND .pdf mtime ≥ .md mtime.
- For every Status.md instance, also verify the sibling Status_Summary.md mtime ≥ Status.md mtime (if the summary exists).
- Walks docs/ recursively for Status.md — the Status fleet is not enumerated statically because new integrations land per phase.

Composite gate FAILs the build if ANY single instance fails. The per-class gates (CM-ISSUES-SUMMARY-SYNC, CM-DOCS-EXPORT-SYNC, CM-FIXED-SUMMARY-SYNC, CM-CONTINUATION-DOC-INSYNC, CM-README-EXPORT-SYNC) remain in place — §11.4.60 is the belt-and-suspenders layer that catches what they miss.

Paired mutation (per §1.1). meta_test_false_positive_proof.sh backdates docs/Issues.html to year 2000 (touch -t 200001010000.00) and asserts CM-DOCS-COMPOSITE-SYNC FAILs.

Revision-header coupling. Per §11.4.44 every one of the 8 doc classes carries the **Revision:** N + **Last modified:** ISO 8601 UTC header directly under the H1. CM-DOCS-COMPOSITE-SYNC does NOT re-check the revision header (already covered by CM-DOC-REVISION-HEADER-PRESENT) — composite gate is artefact-mtime only, by design narrow.

Auto-sync wrapper coupling. Per §11.4.12 every edit to an Issues/Fixed-class doc flows through sync_issues_docs.sh. Per §11.4.45 every edit to a Status.md flows through sync_integration_status.sh <Status.md>. Per §11.4.59 every edit to README.md flows through sync_readme_export.sh. §11.4.60 does NOT change the wrapper contract — it only catches the failure mode where an operator (or AI agent) bypassed the wrapper and committed markdown without regenerating exports.

No escape hatch. No --skip-composite-doc-sync, --allow-stale-html, --summary-not-applicable flag exists. The covenant exists for the operator's own protection — the moment a single per-class

gate is bypassed, divergence accumulates silently until release-time forensics finds it (the exact §11.4 PASS-bluff pattern the canonical covenant was authored to eliminate).

Composes with §11.4.12 (Issues_Summary), §11.4.15 (Status field), §11.4.16 (Type field), §11.4.19 (atomic Issues→Fixed migration), §11.4.23 (colorizer), §11.4.33 (type-aware closure vocabulary), §11.4.44 (revision header), §11.4.45 (Status.md), §11.4.53 (Fixed_Summary), §11.4.56 (Status_Summary), §11.4.57 (README doc-link), §11.4.59 (README always-sync), §12.10 (CONTINUATION maintenance).

Propagation. Pre-build gate CM-COVENANT-114-60-PROPAGATION enforces the §11.4.60 anchor literal in every CLAUDE.md / AGENTS.md across parent + 10 owned submodules + HelixQA dependencies (same shape as existing §11.4.5X propagation gates). The propagation gate is OPTIONAL for Phase 39.FC's initial landing — only the composite gate + its paired mutation are mandatory; propagation gates trail per established phase pattern.

Classification: universal (per §11.4.17). Applies to every project consuming this Constitution that maintains any of the 8 doc classes. The composite gate logic is universal; the specific doc-class instance paths are consumer-side per-project.

Canonical authority: constitution submodule Constitution.md §11.4.60.

Non-compliance is a release blocker regardless of context.

§11.4.63 — Workable-items procedure docs as single source of truth (User mandate, 2026-05-19)

Forensic anchor — verbatim user mandate (2026-05-19 ~10:30Z):

"To make workable items tracking and creation through all of the mentioned mandatory documents we MUST create proper procedure document which will be named in Constitution, AGENTS.md and CLAUDE.md as single source of truth for this procedure! Make sure it is created under: docs/procedures/issues/Creation.md which will be always exported to PDF and HTML whenever it is updated. We MUST create procedure documents for Updating.md, Resolution.md, Reopening.md and other workable items actions that we have. ... Everything done on project - new features, changes, tasks, bug fixes, investigation, ordinary tasks (writing documentation for example) MUST ALL go through the workable items flow and proper procedures!"

Every workable-item action — opening, updating, closing, reopening, migrating across Issues.md ↔ Fixed.md — MUST follow the canonical procedure document at docs/procedures/issues/<Action>.md. The five procedure docs are MANDATORY references; no agent or operator may invent ad-hoc procedures. The closed-set:

Procedure doc	Covers
Creation.md	Opening a new workable item (Bug / Feature / Task)
Updating.md	Non-closure, non-reopen edits — status transitions, evidence append, type re-classification
Resolution.md	Atomic Issues.md → Fixed.md close (Bug→Fixed, Feature→Implemented, Task→Completed per §11.4.33)
Reopening.md	Atomic Fixed.md → Issues.md reopen with §11.4.34 source attribution + §11.4.55 reopens-history
Migration.md	Bidirectional atomic-move mechanics + sync_issues_docs.sh internals (consumed by Resolution + Reopening)

Each procedure doc carries the §11.4.44 revision header + HTML + PDF exports synchronised to its .md source. New helper scripts/testing/sync_procedure_docs_export.sh walks the procedure-docs directory and emits matching .html + .pdf for each .md; invoked as the final stage of scripts/testing/sync_issues_docs.sh so a single operator invocation refreshes every doc-side artifact.

Universality of scope. All work — new features, behavioural changes, tasks (refactor / doc / infra / gate / audit / cleanup), bug fixes, investigation, documentation work — MUST flow through these procedures. The "I'll just tweak this one file" escape hatch is forbidden because it produces silent doc drift and reopens the §11.4 covenant's PASS-bluff failure mode at the process-tracking layer.

Composes with §11.4.6 (no-guessing — every procedure step is mechanical, no likely / seems), §11.4.7 (demotion-evidence — Reopening.md is the canonical implementation), §11.4.11 (file-layout — procedure docs live in docs/procedures/issues/, qa-results forensics live in qa-results/), §11.4.12 (Issues_Summary sync — all five procedures invoke sync_issues_docs.sh whose pipeline is documented in Migration.md), §11.4.15 (Status closed-set — all five procedures cite the same closed-set), §11.4.16 (Type closed-set), §11.4.19 (atomic Issues↔Fixed move — Migration.md is the implementation), §11.4.23 (visual cue + grouping colorization — invoked by sync wrapper, no procedure-side bypass), §11.4.33 (type-aware closure vocabulary — Resolution.md enforces),

§11.4.34 (Reopened-source attribution — Reopening.md enforces), §11.4.44 (revision header on every procedure doc), §11.4.53 (Fixed Summary parity — Migration.md documents the pipeline), §11.4.54 (ATM-NNN identifier — Creation.md allocates), §11.4.55 (Reopens-history per- item doc — Reopening.md authors), §11.4.60 (documentation always- sync composite — procedure docs are an additional doc class binding to the composite covenant).

Pre-build gate CM-PROCEDURES-DOCS-PRESENT checks (1) all 5 procedure docs exist at docs/procedures/issues/{Creation,Updating,Resolution,Reopening,Migration}.md, (2) each carries the §11.4.44 revision header, (3) each has matching .html + .pdf exports with mtime ≥ the .md mtime, (4) scripts/testing/sync_procedure_docs_export.sh exists + is executable, (5) scripts/testing/sync_issues_docs.sh invokes sync_procedure_docs_export.sh. Paired mutation: rename one procedure doc → gate FAILs.

Propagation gate CM-COVENANT-114-63-PROPAGATION enforces this anchor literal in every CLAUDE.md / AGENTS.md across parent + 10 owned submodules + nested submodules + HelixQA dependencies. Paired mutation strips the anchor literal → gate FAILs.

No escape hatch — no --ad-hoc-procedure, --skip-procedure-doc, --procedure-not-applicable flag exists. Inventing an alternate procedure for a "small" change is the exact failure mode this anchor closes.

Classification: universal (per §11.4.17). The closed-set of five procedure docs and the sync-wrapper composition are universal; the specific test-name / fix-name examples within each procedure doc may be consumer-side per-project.

Canonical authority: constitution submodule Constitution.md §11.4.63.

Non-compliance is a release blocker regardless of context.

§11.4.65 — Universal Markdown export mandate (User mandate, 2026-05-19)

Forensic anchor — direct user mandate (verbatim, 2026-05-19):

"Any markdown document inside the project and which is not part of the applications or services source code MUST BE exported (be available) in PDF and HTML! Any already existing Markdown document that fulfills this condition and which does not have HTML or PDF at all or it is not in sync with it MUST HAVE (re)generated PDF and HTML version! Every time when Markdown document (file) is modified, its

proper HTML and PDF versions MUST BE regenerated.
Markdown documents MUST BE at all times in sync with
PDF and HTML versions!"

The covenant generalizes the per-class always-sync discipline of §11.4.12 / §11.4.18 / §11.4.44 / §11.4.45 / §11.4.53 / §11.4.56 / §11.4.57 / §11.4.59 / §11.4.60 / §11.4.63 / §11.4.64 to **every Markdown document in the project that is not part of an application or service's source-code tree**. Per-class anchors govern specific files (Issues, Fixed, Status, README, etc.); §11.4.65 is the catch- all: any *other* .md file that documents the project — guides, research notes, plans, hardware-ID notes, script-companion docs, changelogs, procedure docs, README files inside owned submodules — MUST also have .html + .pdf siblings, all three artefacts in sync at all times. Stale exports of *any* documentation surface are the exact "operator reads divergent HTML/PDF while .md is correct" PASS-bluff §11.4 forbids — only the per-class enforcement so far prevented it for specifically-named docs; §11.4.65 closes the long tail.

Scope (closed-set):

INCLUDED:

- Project root *.md (README.md, CLAUDE.md, AGENTS.md, CONTRIBUTING.md, etc.)
- docs/**/* .md (guides, research, plans, changelogs, procedures, hardware notes)
- scripts/**/* .md (script-companion docs in documentation format, NOT shebang scripts)
- Owned-submodule trees at device/rockchip/atmosphere/<submodule>/: top-level README.md / CLAUDE.md / AGENTS.md / CHANGELOG.md and any docs/**/* .md
- constitution/**/* .md (the canonical-root submodule)
- tools/helixqa/<helixqa-submodule>/ top-level README.md / CLAUDE.md / AGENTS.md and any docs/**/* .md (owned HelixQA dependencies)

EXCLUDED (NOT subject to §11.4.65 — these are application/service source code or third-party trees we do not own):

- external/** (AOSP-mainline / upstream-mirror source trees)
- prebuilts/** (binary prebuilts + their bundled docs)
- packages/modules/** (AOSP mainline modules)
- kernel-5.10/** (kernel source tree — has its own upstream docs)
- out/** (build output)
- build/** (AOSP build system)
- Application / service source-code trees (e.g. Java/Kotlin module-internal *.md shipped with library code, README files inside source-only third-party gradle module directories)
- Any third-party submodule NOT in the owned-submodule set (presenter, vlc-player, nova-player, mpv-player, gramophone-

player, rhythm-player, strep-player, smarttube-player, torrsrve, lampa) or HelixQA-owned set (Challenges, Containers, DocProcessor, LLMOrchestrator, LLMProvider, VisionEngine)

Mandatory protections (ALL must hold):

1. **Every INCLUDED .md file has .html and .pdf siblings.** A missing export is a §11.4.65 violation regardless of when the markdown was last touched.
2. **.html and .pdf mtime ≥ .md mtime** (within the same sync-wrapper invocation granularity). Stale exports are violations even if the .md itself is correct.
3. **Every modification triggers regeneration.** Whether via direct sync-wrapper invocation (`sync_all_markdown_exports.sh`), a git pre-commit hook auto-regenerating on staged .md changes, or the existing per-class wrappers (§11.4.12 `sync_issues_docs.sh`, §11.4.18 `script-docs sync`, §11.4.59 `sync_readme_export.sh`, etc.) all of which delegate the universal export path to the same canonical helper.
4. **Pre-build gate enforces parity.**
CM-UNIVERSAL-MARKDOWN-EXPORT- SYNC walks the INCLUDED scope, verifies every .md has .html
 - .pdf siblings with `mtime ≥ .md mtime`, and FAILs the build if any are missing or stale.
5. **No escape hatch.** No `--skip-md-exports`, `--no-pdf-only`, `--md-export-not-applicable`, `--application-internal-doc` flag exists for files inside the INCLUDED scope. The EXCLUDED scope is the only legitimate path to opt out, and it is closed-set.

Canonical helper. `scripts/testing/sync_all_markdown_exports.sh` walks the INCLUDED scope, invokes `pandoc` (HTML) + `weasyprint` (PDF) with `timeout 60` each (graceful per-file degradation), uses `docs/_progress-style.css` for visual consistency, and supports `--check-only` (exit nonzero if any out-of-sync, print list) and `--regenerate-all` (force) modes. Caps at 500 candidates with explicit `abort+list` if the scope is unexpectedly large (e.g. after a new submodule lands without scope-update review). Idempotent.

Composition. Composes with §11.4.12 (Issues_Summary sync — universal helper is the back-end), §11.4.18 (`script-companion docs`), §11.4.23 (HTML colorizer continues to post-process the always-sync docs for visual cues), §11.4.44 (revision header on every .md the universal helper exports), §11.4.45 (`Status.md` auto-sync), §11.4.53 (`Fixed_Summary`), §11.4.59 (`README` always-sync — the universal helper covers the long tail of every *other* root-level .md too), §11.4.60 (composite always-sync covenant — §11.4.65 is the structural generalization), §11.4.63 (procedure docs — already always-sync; §11.4.65 adds catch-all for every doc

class not yet anchored), §11.4.64 (topic discoverability — summary docs the universal helper exports continue to be post-processed by `inject_topic_index.py`).

Pre-build gates:

- CM-UNIVERSAL-MARKDOWN-EXPORT-SYNC — invariants: (a) `scripts/testing/sync_all_markdown_exports.sh` exists + executable, (b) running it in `--check-only` mode returns 0 (no out-of-sync file in the INCLUDED scope).
- CM-COVENANT-114-65-PROPAGATION — anchor literal 11.4.65 in every CLAUDE.md / AGENTS.md across canonical-root + parent + 10 owned submodules + nested submodules + HelixQA dependencies (42-file fleet — same propagation set as §11.4.58).

Paired meta-test mutations: one strips the CM-UNIVERSAL-MARKDOWN-EXPORT-SYNC gate's enforcement literal; one strips the §11.4.65 anchor literal from a sentinel propagation file. Both mutations assert the corresponding gate FAILs when applied.

Classification: universal (per §11.4.17). The mandate to export every project-doc Markdown to HTML+PDF is universal across every project that consumes this Constitution; the specific INCLUDED / EXCLUDED scope path lists are consumer-side per-project (since each consumer has different submodule topology, build trees, and source- code roots).

Canonical authority: constitution submodule [Constitution.md](#) §11.4.65.

Non-compliance is a release blocker regardless of context.

§11.4.66 — Blocker-resolution interactive-clarification mandate (User mandate, 2026-05-19)

Forensic anchor — direct user mandate (verbatim, 2026-05-19):

"If any blockers which can be resolved with interactive response ever happen again, perform in depth research on options doable by your side and how much inputs from us you really need, then create options and present them to us. After we answer, preferrably you will be unblocked and be able to continue work on blocked items. Let us make this main approach when such situations (blockers) do happen!"

When any task is blocked (waiting on operator decision, hardware access, external-service authorization, ambiguous scope, or any input the agent cannot mechanically derive), the agent **MUST** follow this five-step discipline before idling or asking free-form questions:

1. **In-depth research on agent-side options.** Identify the maximum scope that can land unilaterally without operator input — research the codebase, upstream documentation, existing tooling, the current state, what files/components are involved, what tests/gates already exist. Surface every agent-actionable path even if it requires a small operator confirmation.
2. **Calculate minimum-viable operator input.** Reduce the question set to the smallest closed set of operator-only decisions (preference, authorization, scope-bounding, hardware availability, schedule). Anything that can be researched **MUST NOT** be asked.
3. **Construct 2-4 mutually-exclusive options.** Each option carries (a) a short label, (b) a one-line trade-off description, (c) an explicit statement of what the agent will do *after that answer*. One option marked "Recommended" with rationale. Options **MUST** genuinely differ — restating one option as three close variants is itself a §11.4.66 violation.
4. **Present via the platform's interactive question mechanism.** On Claude Code that is AskUserQuestion (max 4 questions, each with 2-4 options; supports multi-select for non-mutually-exclusive sets). Other platforms (Copilot CLI, Codex, Gemini CLI) use their equivalents. **NEVER** inline free-text "what would you like?" when interactive options would do — that wastes operator attention.
5. **After the operator answers, resume work without additional round-trips.** Every option's promised action **MUST** be sufficient to unblock — if a follow-up clarifying question is needed, the prior options were insufficiently researched and that's itself a §11.4.66 violation. The contract is: ask once, unblock, continue.

Composes with:

- §11.4.6 (no-guessing — interactive options replace agent guessing about operator preference)
- §11.4.7 (demotion-evidence — operator preference is captured-evidence for direction changes)
- §11.4.40 (full-suite retest — uninterrupted work post-answer means the test cycle resumes cleanly without context drift)
- §11.4.41 (merge-first — when operators make conflicting choices across sessions, the merge-first discipline preserves both)

- §11.4.42 (iteration-discipline — interactive-question loop is built into the per-cycle methodology)
- §11.4.52 (autonomous-validation — most blockers can be researched to autonomous-path level, leaving only true operator preference to interactive-ask)

Mandatory protections:

- **No silent waiting.** If blocked, ask. If genuinely no operator input is needed, do not ask — proceed.
- **No bulk-text questions when interactive options would do.** Free-text prompts are reserved for truly open-ended ideation, never for closed-set decisions.
- **Each interactive question minimizes operator cost** — the operator should be able to answer all questions in under 30 seconds total.
- **Recommended option is highlighted explicitly** — the operator should know what the agent would default to if no answer comes.
- **Out-of-band channels (slack, voice, email) NEVER substitute** — the interactive mechanism creates an audit trail that free-text channels do not.

Pre-build gate CM-COVENANT-114-66-PROPAGATION enforces the anchor literal is present across the 42-file consumer fleet (parent CLAUDE.md / AGENTS.md + 10 owned-submodule pairs + HelixQA-owned pairs). Paired meta-test mutation strips the literal → gate FAILs. No escape hatch — no --skip-ask, --silent-wait, --free-form-only flag is permitted.

Canonical authority: constitution submodule [Constitution.md](#) §11.4.66.

Non-compliance is a release blocker regardless of context.

§12. Host-session safety — directly OR indirectly signing the user out is FORBIDDEN

Every script, test, helper, and AI agent governed by this Constitution MUST respect host-session safety. Non-compliance is a release blocker.

§12.1 Forbidden operations — directly OR indirectly

1. **Suspending the host:** `systemctl suspend`, `pm-suspend`, `loginctl suspend`, `DBus org.freedesktop.login1.Suspend`, `GNOME idle-suspend`, `lid-close` handler.
2. **Hibernating / hybrid-sleeping:** any `Hibernate` / `HybridSleep` / `SuspendThenHibernate` method.
3. **Logging out the user:** `loginctl terminate-session`, `kill -u <user>`, `systemctl --user --kill`, anything that signals `user@<uid>.service`.
4. **Unbounded-memory operations** inside `user@<uid>.service` cgroup. Any single command expected to exceed ~4 GiB RSS MUST be wrapped in a bounded execution scope (e.g. `bounded_run` from a project helper library that wraps `systemd-run --user --scope -p MemoryMax=...`).
5. **Programmatic `rkill` toggles, lid-switch handlers, or power-button handlers** — these cascade into idle-actions.
6. **Disabling `systemd-logind`, GDM, or session managers** "to make things faster" — even temporary stops leave the system unable to recover.

§12.2 Required safeguards

Every script in this project that performs heavy work (build, transcription, model inference, large compression, multi-GB git operations) MUST:

1. Source the project's host-safety helper library at the top.
2. Call its pre-flight check and **abort if it fails**.
3. Wrap any subprocess expected to exceed ~4 GiB RSS in a bounded execution scope so the kernel OOM killer is contained to that scope and cannot escalate to `user.slice`.
4. Cap parallelism (`-j`) to fit available RAM (estimate per-job-peak-RSS and divide into the budget).

§12.3 Container hygiene

Containers (Docker / Podman) the project owns or relies on MUST:

1. Declare an explicit memory limit (`mem_limit` / `--memory` / `MemoryMax`).
2. Set `OOMPolicy=stop` in their `systemd` unit to avoid retry loops.
3. Use exponential-backoff restart policies, never immediate retry.
4. Be clean-slate destroyed and rebuilt after any host crash or session loss so stale lock files don't keep producing failures.

§12.6 Memory-Budget Ceiling — 60% MAXIMUM

Forensic anchor — direct user mandate:

"First make sure that whatever we do through our procedures related to this project **MUST NOT** use more than 60% of total system memory! All processes **MUST** be able to function normally!"

The mandate. Project procedures **MUST NOT** use more than **60% of total system RAM**. The remaining 40% is reserved for the operator's other workloads so the host can keep serving them while project work proceeds.

The protections:

1. `HOST_SAFETY_MAX_MEM_PCT` defaults to 60.
2. `HOST_SAFETY_BUDGET_GB` is computed at source-time from $\text{MemTotal} \times \text{MAX_PCT}/100$, in GiB.
3. Bounded execution scopes clamp `MemoryMax` down to the budget if the caller asks for more.
4. The build script's parallelism is computed as $\min(\text{nproc}, \text{floor}(\text{budget_gb} / \text{per_job_peak_rss_gb}))$.
5. Heavy work **MUST** be wrapped in a bounded execution scope so the kernel OOM-kills only the scope — `user@<uid>.service` stays alive.

No escape hatch. §12.6 has NO operator-facing override flag. The cap exists for the operator's own protection; bypassing it is the bluff the §11.4 covenant specifically prohibits.

§12.10 Continuation document — sacred invariant

Forensic anchor — direct user mandate:

"during any work we perform, during Phases implementation, debugging and fixing, during ANY effort we have the Continuation document **MUST BE** maintained and it **MUST NOT BE** out of sync with current work we are doing! If for any reason we stop our work, we **MUST BE** able to continue any time, with current work, exactly where we have left off and from any CLI agent or any LLM model we chose! Nothing can be broken or faulty in maintained Continuation document!"

The mandate. A single, canonical, machine-readable handoff document — `docs/CONTINUATION.md` — must always reflect the live state of the project. Any agent (human, Claude Code, Cursor, Aider, Codex, Gemini CLI, any future LLM) must be able to resume work **exactly where the previous session left off** by reading this single file.

Mandatory protections:

1. **docs/CONTINUATION.md MUST exist** at the project root. Its absence is a release blocker.
2. **Every non-trivial state change** MUST update this document in the same commit as the work itself.
3. **Top-of-file timestamp** is updated on every edit. Stale timestamps trigger gate failure.
4. **Section §3 "Active work"** lists every IN PROGRESS / BLOCKED item with enough detail that any agent can resume without conversation context — concrete commands, file paths, monitor IDs.
5. **Section §0 "How to use this document"** contains the verbatim resumption prompt — a single block any operator can paste into any CLI agent.
6. **Document MUST be self-contained.** No hyperlinks to ephemeral external systems as the only source of truth.

No escape hatch. §12.10 has NO operator-facing override flag for the existence requirement. The discipline exists for the operator's own protection.

Appendix A — Mutation testing — academic and industrial foundations

The anti-bluff / paired-mutation policy in §1.1 is rooted in the **mutation testing** literature. References that the consuming project SHOULD cite when explaining its meta-test harness:

- Jia, Y. & Harman, M. (2011). *An Analysis and Survey of the Development of Mutation Testing*. IEEE Transactions on Software Engineering, 37(5).
- DeMillo, R.A., Lipton, R.J., Sayward, F.G. (1978). *Hints on Test Data Selection: Help for the Practicing Programmer*. IEEE Computer.
- Open-source mutation testers worth studying:
 - **PIT** (Java) — <https://pitest.org/>
 - **Stryker** (JS / C# / Scala) — <https://stryker-mutator.io/>
 - **Cosmic Ray** (Python) — <https://github.com/sixty-north/cosmic-ray>
 - **mutmut** (Python) — <https://mutmut.readthedocs.io/>
 - **mull** (LLVM-IR) — <https://mull.readthedocs.io/>

The §1.1 paired-mutation policy is a **lightweight** variant of mutation testing applied at the gate-assertion layer rather than at the production-code layer. It does not need a mutation framework; it

needs ONE mutation per gate that proves the gate catches the break. This is computationally cheap ($O(\text{gates})$, not $O(\text{production code lines})$) and produces a strong "bluff-immunity" guarantee.

Appendix B — Recursive inheritance & path-independence

Projects that include this constitution submodule **MUST** tolerate **arbitrary submodule depth**. Between the main project root and any consuming submodule there may be N intermediate levels. To locate this constitution submodule from any depth, every project **SHOULD** provide a helper that walks up parents until it finds `constitution/Constitution.md` (the file you are reading right now) **OR** follows `git rev-parse --show-superproject-working-tree` recursively. The constitution submodule ships `find_constitution.sh` for exactly this purpose; nested submodules can source it without knowing their own depth.

Appendix C — Multi-upstream push

This constitution submodule is hosted on multiple Git providers, and consuming projects often are too. The submodule ships an `install_upstreams.sh` helper (or invokes the `install_upstreams` system command from the parent toolkit) that reads `Upstreams/*.sh` declarations and configures all remotes locally.

Every commit to the constitution submodule **MUST** be pushed to **ALL** configured upstreams. Use a shell helper that iterates `git remote` and pushes one by one, **OR** configure origin with multiple push URLs (`git remote set-url --add --push origin <url>` per remote).
