

README

1 1 4 1 4 0

Generated action-prefix slash commands (\$. .)

Auto-generated by `scripts/generate_agent_prefix_commands.sh` from `actions/registry.yaml`. DO NOT EDIT BY HAND – re-run the generator.

Two slash forms per action (GRAMMAR_ADDENDUM ` \$. .):

- `<name>` – the bare slash form `/<name>`.
- `default-<name>` – the namespaced slash form `/DEFAULT::<name>` alias (these agents disallow `::` in a command name). It maps to the IDENTICAL expansion, so `/<name>` $\equiv$ `/default-<name>`. **Collision fallback:** if `/<name>` ever collides with a host built-in command on a given agent, invoke `/default-<name>` (the always-safe form-equivalent).

Per-agent install targets (the install script wires these by reference):

Agent	Source here	Install location (consuming project)
Gemini CLI	<code>gemini/<name>.toml</code> , <code>gemini/default-<name>.toml</code>	<code>.gemini/commands/</code>
Qwen Code	<code>qwen/<name>.toml</code> , <code>qwen/default-<name>.toml</code>	<code>.qwen/commands/</code>
Codex CLI	<code>codex/<name>.md</code> , <code>codex/default-<name>.md</code>	<code>prompts/</code>

Generated action(s) (each as a bare + a `default-namespaced` command).