

Status

CodeGraph – Status

Field	Value
Revision	2
Created	2026-05-21
Last modified	2026-05-22
Status	active
Status summary	Append-only ledger of every CodeGraph-related event across the constitution submodule's consuming projects: npm updates, sync runs, index regenerations, validate runs, HRDs opened/closed against CodeGraph. Per Universal §11.4.80 + §11.4.65 (multi-format export). Both <code>scripts/code-graph_update.sh</code> and <code>scripts/codegraph_sync.sh</code> append here automatically. R2 (2026-05-22): replaced project-specific §107 anchor references with the universal §11.4 covenant anchor to keep this submodule fully decoupled per §11.4.28.
Issues	none
Issues summary	—
Fixed	(n/a — ledger doc)
Continuation	sibling <code>Status_Summary.md</code> carries the operator-readable digest per §11.4.53.

Table of contents

- [Cadence + automation](#)
- [Event ledger](#)

Cadence + automation

Per §11.4.80, every consuming project MUST run `codegraph_update.sh` at least weekly and `codegraph_sync.sh` after every update + on every meaningful source-change cadence (varies by project). Cadence floor: weekly. Cadence ceiling: per-CI-run.

The scripts append entries below automatically; manual entries are also acceptable when an operator runs the commands directly.

Event ledger

2 0 2 6 0 5 2 1 0 5 3 8 5 3

(events appended below by the automation; newest at the bottom)

codegraph update FAILED (\$: Z -
caught) bluff

- before: 0.6.8

- target: 0.8.0
2 0 2 6 0 5 2 1 0 5 4 0 0 1

- after: unknown (mismatch — npm exit 0 was bluffing)

2 5

codegraph rolled back to . .
(Node- incompatibility)

- before: 0.8.0 (installed but non-functional on Node 25.x — engine range + V8 WASM JIT bug)

- after: 0.6.8 (last known-working on Node 25.x)

- decision: pin codegraph to 0.6.8 until Node 25 V8 issue is resolved upstream OR operator installs Node 22 LTS alongside

- §11.4 trail: `codegraph_update.sh` correctly caught the failed upgrade via the post-update version check — script working as designed

2 0 2 6 0 5 2 1 1 2 4 9 0 3
• follow-up HRD: ENV-CODEGRAPH-NODE25 to track when 0.7+/0.8+ becomes safe again
1 1 4

– – T : : Z –
codegraph update FAILED (\$. bluff caught)

- before: 0.6.8
- 2 0 2 6 0 5 2 1 1 2 4 9 0 3
• target: 0.8.0
- after: unknown (mismatch — npm exit 0 was bluffing)

– – T : : Z –
codegraph version check

- current: 0.8.0
- 2 0 2 6 0 5 2 1 1 2 5 1 1 6
• latest: 0.8.0
- action: **no-op** (already at latest)

– – T : : Z –
codegraph version check

- current: 0.8.0
- 2 0 2 6 0 5 2 1 1 4 3 1 3 5
• latest: 0.8.0
- action: **no-op** (already at latest)

– – T : : Z –
codegraph version check

- current: 0.8.0
- latest: 0.8.0
- action: **no-op** (already at latest)

codegraph version check

- current: 0.8.0
- latest: 0.8.0
- action: **no-op** (already at latest)

codegraph version check

- current: 0.8.0
- latest: 0.8.0
- action: **no-op** (already at latest)

codegraph version check

- current: 0.8.0
- latest: 0.8.0
- action: **no-op** (already at latest)

codegraph version check

- current: 0.9.2
- latest: 0.9.2
- action: **no-op** (already at latest)

codegraph updated

- before: 0.9.4

• after: 0.9.6

• npm command: `npm install -g @colbymchenry/codegraph@0.9.6`

codegraph version check

• current: 0.9.6

• latest: 0.9.6

• action: **no-op** (already at latest)

codegraph version check

• current: 0.9.7

• latest: 0.9.7

• action: **no-op** (already at latest)

codegraph version check

• current: 1.0.1

• latest: 1.0.1

• action: **no-op** (already at latest)

codegraph version check

• current: 1.0.1

• latest: 1.0.1

• action: **no-op** (already at latest)

codegraph version check

- current: 1.0.1
- latest: 1.0.1
- action: **no-op** (already at latest)

codegraph version check

- current: 1.0.1
- latest: 1.0.1
- action: **no-op** (already at latest)

codegraph version check

- current: 1.0.1
- latest: 1.0.1
- action: **no-op** (already at latest)

codegraph updated

- before: 1.0.1
- after: 1.1.2
- npm command: `npm install -g @colbymchenry/codegraph@1.1.2`

codegraph version check

- current: 1.1.2

• latest: 1.1.2

- action: **no-op** (already at latest)

codegraph version check

• current: 1.1.2

• latest: 1.1.2

- action: **no-op** (already at latest)

codegraph version check

• current: 1.1.3

• latest: 1.1.3

- action: **no-op** (already at latest)

codegraph version check

• current: 1.1.3

• latest: 1.1.3

- action: **no-op** (already at latest)

codegraph updated

• before: 1.1.6

• after: 1.2.0

• npm command: `npm install -g @colbymchenry/codegraph@1.2.0`

codegraph version check

- current: 1.2.0
- latest: 1.2.0_{2 0 2 6 0 7 0 5 0 0 0 3 0 6}
- action: **no-op** (already at latest)

codegraph version check

- current: 1.2.0
- latest: 1.2.0_{2 0 2 6 0 7 0 5 0 5 4 7 5 5}
- action: **no-op** (already at latest)

codegraph version check

- current: 1.2.0
- latest: 1.2.0_{2 0 2 6 0 7 0 5 0 5 5 7 1 6}
- action: **no-op** (already at latest)

codegraph version check

- current: 1.2.0
- latest: 1.2.0_{2 0 2 6 0 7 0 5 0 6 2 8 4 9}
- action: **no-op** (already at latest)

codegraph version check

- current: 1.2.0

• latest: 1.2.0

• action: **no-op** (already at latest)

codegraph version check

• current: 1.2.0

• latest: 1.2.0

• action: **no-op** (already at latest)

codegraph version check

• current: 1.2.0

• latest: 1.2.0

• action: **no-op** (already at latest)

codegraph version check

• current: 1.2.0

• latest: 1.2.0

• action: **no-op** (already at latest)

codegraph version check

• current: 1.2.0

• latest: 1.2.0

• action: **no-op** (already at latest)

codegraph version check

- current: 1.2.0
- latest: 1.2.0
- action: **no-op** (already at latest)

codegraph version check

- current: 1.2.0
- latest: 1.2.0
- action: **no-op** (already at latest)