

helix_code_home.sh – Companion Guide

Revision: 1 Last modified: 2026-07-17T00:00:00Z

Overview

Sourced library that resolves `HELIX_CODE_HOME` (the HelixCode meta-repo location) using the 3-case contract defined in `docs/helix_code/INTEGRATION_PLAN.md §2.1`.

Prerequisites

- `bash` ≥ 4.0
- `git`
- Network access to `github.com:HelixDevelopment/HelixCode.git` (for case-b auto-clone)

Usage

```
# Source the library
source constitution/scripts/helix_code/helix_code_home.sh

# Resolve the HelixCode home (clones if needed)
home="$(hc_home)"
echo "HelixCode at: $home"

# Check remote base URL (empty if mode=local)
base="$(hc_remote_base)"

# Health check a service
hc_health localhost 8080 /health
```

Environment Variables

Variable	Source	Purpose
HELIX_CODE_HOME	~/.bashrc or project .env	Override meta-repo path
HELIX_CODE_MODE	~/.bashrc or project .env	local (default) or remote
HELIX_CODE_REMOTE_BASE_URL	~/api_keys.sh or pro- ject .env	Remote deploy- ment base URL
HELIX_PROJECT_ROOT	(rarely set)	Override project root detection

Resolution Order

1. \$HELIX_CODE_HOME env var
2. HELIX_CODE_HOME in project .env
3. Default: <project-root>/submodules/helix_code

Edge Cases

- **Path set but empty:** triggers full recursive clone (case b)
- **Path set, no `.git`** : triggers full recursive clone (case b)
- **Path unset:** defaults to submodule path, clones if absent (case c)
- **Path present + valid:** ensures submodules are initialized (case a)

Related Scripts

- `constitution/scripts/multitrack/multitrack_config.sh` — similar resolver pattern
- `constitution/scripts/subagent_tier.sh` — env-else-submodule-default idiom
- `constitution/scripts/release_prefix.sh` — 3-tier env → `.env` → default pattern

Cross-references

- `docs/helix_code/INTEGRATION_PLAN.md` §2 — env-var contract
- `docs/helix_code/CLAUDE_TOOLKIT_EXTENSION.md` §2 — mini-POC
- `docs/helix_code/CONSTITUTION_DESIGN.md` §3 — constitution mechanism
- Constitution §11.4.6 (no-guessing), §11.4.18 (script docs), §11.4.28 (decoupling)