

scoped_read.sh – Companion Guide

Revision: 1 Last modified: 2026-07-17T00:00:00Z

Overview

§11.4.141 M4 implementation. Prevents full-file loading when a targeted read suffices.

Functions

Function	Purpose	Example
<code>sr_grep_then_read</code>	Grep pattern → read matching lines with context	<code>sr_grep_then_read "func"</code> <code>"main.go" 5</code>
<code>sr_section_read</code>	Read section by heading match	<code>sr_section_read "## Usage"</code> <code>"README.md"</code>
<code>sr_cached_result</code>	Cache command results (5min TTL)	<code>sr_cached_result "key"</code> <code>"command"</code>
<code>sr_clear_cache</code>	Clear the cache	<code>sr_clear_cache</code>

Usage

```
source constitution/scripts/token_efficiency/scoped_read.sh
```

```
# Read 5 lines of context around "func main" in main.go
```

```
sr_grep_then_read "func main" "main.go" 5
```

```
# Read the "## Usage" section from README.md
```

```
sr_section_read "## Usage" "README.md"
```

```
# Cache a command result
```

```
sr_cached_result "git_status" "git status --short"
```

Cross-references

- Constitution §11.4.141 M4
- `token_efficiency_lib.sh` — for status and caching
- `context_compactor.sh` — for context pruning