

llm-alias-health

Revision: 1 Last modified: 2026-07-07T00:00:00Z

PWU-3 of the LLMsVerifier incorporation (see `docs/research/llmsverifier_incorporation_20260707/ANALYSIS_AND_PLAN.md`, PART D + PART F, in the ATMOSphere-Android-15 consuming repo) — the permanent, project-agnostic auto-select **health engine** for Claude-Code-CLI aliases (native accounts, provider-router routes via `ccr`, and provider-native routes), replacing the previous *reactive* cooldown-only rotation with a *proactive* out-of-band health probe.

What it does

For every alias in a YAML config, `llm-alias-health` :

1. **Execs** the LLMsVerifier `claude-alias-probe` bridge binary (§11.4.28(C) exec-decoupling — this util never imports LLMsVerifier as a Go dependency; the bridge path is injected via `llmsverifier_bin` in the config, never hardcoded).
2. Classifies the result into the closed-set status vocabulary `{ok, rate_limited, quota_exceeded, failed, unknown}` — `unknown` is reserved for cases where the bridge itself could not be run or its output could not be parsed (missing binary, crash, timeout, corrupted stdout); it is **never** conflated with a genuine `ok`.
3. Writes one evidence JSON file per alias (`ab_pass_with_evidence` style artefact, §11.4.69) plus an append-only `events.jsonl` real-time event trail (§11.4.116).
4. Atomically rewrites a native-preferred-ranked `health.json` snapshot a multitrack consumer can tail.

Config schema

```
llmsverifier_bin: /path/to/claude-alias-probe # required
timeout_seconds: 60 # optional, default 60
sentinel_prefix: "LLM_ALIAS_HEALTH_" # optional
aliases:
- alias: claude1
  kind: native # native | provider-native | provider-router
  config_dir: /home/user/.claude-claude1
  model: claude-opus-4-8 # optional
- alias: zai-glm-router
  kind: provider-router
  base_url: http://127.0.0.1:3456
- alias: some-provider
  kind: provider-native
  base_url: https://api.example.com
  auth_token_env: SOME_PROVIDER_TOKEN # NAME of the env var holding the secret
```

Usage

```
go build -o bin/llm-alias-health ./cmd/llm-alias-health
./bin/llm-alias-health \
  -config health_config.yaml \
  -health-out health.json \
  -events-out events.jsonl \
  -evidence-dir qa-results/llmsverifier_pwu3/evidence
```

Exit code `2` on config/usage error; otherwise `0` (a per-alias probe failure is reflected in `health.json`, it is never a reason for the whole sweep to fail).

Testing

`go test -p 2 ./...` — unit (config parse, status mapping, ranking, atomic write) + a full-sweep end-to-end run against a controllable stub bridge (`testdata/stubbridge`) + stress (100-iteration latency percentiles, 10-way concurrency) + chaos (corrupted/empty/missing-binary/hung-subprocess/unwritable-evidence-dir/pre-corrupted-events-file — all degrade honestly, never a fabricated `ok`).

```
go test -p 2 -tags integration ./... drives the real LLMsVerifier bridge via  
LLM_ALIAS_HEALTH_TEST_BRIDGE_BIN=<built-binary-path> (one real claude  
-p call via ccr , quota-minimal).
```

Status

Go code + full test suite (unit/stress/chaos/integration) complete. Four-format doc export (HTML/PDF/DOCX per §11.4.65/§11.4.73) and wiring into the shared `meta_test_false_positive_proof.sh` paired- mutation harness are tracked as PWU-6 follow-up per the incorporation plan's own phasing, not part of this PWU's Go-code deliverable.