

constitution/scripts/ multitrack – generic multi- track development engine

Revision: 2 **Last modified:** 2026-07-03T23:20:00Z **Status:** active **Classification:** universal (§11.4.17) — project-agnostic engine; zero project-specific literals (no consumer hardware / vendor / host / package names anywhere in this directory, per §11.4.28(B)).

Project-agnostic runtime for the §11.4.176 / §11.4.167 multi-track development system: worktree-per-alias resolution, the exactly-once claim registry (§11.4.176(A)), the capability-aware deadlock-proof device-lock (§11.4.176(B)), the orchestrator bind/fallback/cooldown lease, the cwd-hook contract, the single-builder rebuild queue, and the tmux launch entrypt. Every consuming project inherits this directory verbatim (§11.4.28(B) decoupling, §11.4.35 canonical-root) and supplies ONLY its own per-host config data.

What lives here (GENERIC) vs what the consumer supplies (PROJECT DATA)

File	Role
<code>multitrack_config.sh</code>	SOURCED library: per-host YAML loader + live-drive detect (by serial, §11.4.111) + protect-guard + track-plan. Provides <code>mt_repo_root</code> / <code>mt_config_dir</code> / <code>mt_config_file</code> / <code>mt_resolve_host</code> / <code>mt_load_config</code> / <code>mt_load_pool</code> + the scalar/list accessors <code>mt_config_conductor</code> / <code>mt_config_fallback_signatures</code> .
<code>multitrack.sh</code>	Entrypoint (<code>status</code> / <code>up</code>).
<code>multi-track_resolve_worktree.sh</code>	Alias → worktree resolution (<code>resolve</code>), alias → track resolution (<code>track</code> , used by bind-on-start), and the <code>map</code> table. Honors the <code>conductor: key</code> (conductor stays on /home), orchestrator binding (most-recent wins), else positional map.
<code>multitrack_registry.sh</code>	flock TSV get/set over <code><repo>/ws_state/streams.tsv</code> .
<code>multitrack_claim.sh</code>	Exactly-once item → track claim + TTL reap (§11.4.176(A)).
<code>multitrack_device_lock.sh</code>	Capability-aware deadlock-proof device-lock (§11.4.176(B)).
<code>multitrack_cwd_hook.sh</code>	Thin toolkit adapter: resolves WHICH consumer project this invocation is for (§11.4.177, see below), prints the alias's bound worktree AND fires a best-effort, non-fatal, fully-detached <code>orchestrator bind</code> (bind-on-start, §11.4.177), fallback monitor, AND constitution auto-sync for the resolved track (never for the conductor). <code>--consumer-root [alias]</code> reports the resolved consumer + why.

File	Role
<code>multi-track_constitution_sync.sh</code>	§11.4.35 constitution auto-sync: on every track activation, ancestor-guarded fast-forward-only advance of the activated worktree's <code>constitution/</code> submodule to latest <code><remote>/main</code> (WIP-preserving, never force/reset/rewind; never <code>git submodule update</code>). Keeps the constitution "always up to date with main, Everywhere!"
<code>multi-track_alias_orchestrator.sh</code>	Alias ↔ track bind / fallback / cooldown lease.
<code>multitrack_build.sh</code>	Single-builder FIFO rebuild queue.

The consumer supplies its per-host config file (the ONLY place project strings live):
 track → mount paths, project directory name, device serials + capabilities, the
 alias ↔ account map, priority/feature list. In the reference consumer that file is
`config/multitrack/<hostname>.yaml` .

11 4 177

Which consumer project? – the cwd-hook's consumer-root resolution (\$. .)

Every engine entry point EXCEPT the cwd-hook runs from INSIDE a consumer checkout, so self-location (below) is the right answer for them. The cwd-hook is the exception: the toolkit invokes it only when cwd is **not** a git repo, and it is customarily installed **once** on a shared PATH. Self-location there answers a question it cannot know — it returns whichever checkout physically holds the engine, shadowing every sibling consumer on the host that ships its own `config/multitrack/` .

`multitrack_cwd_hook.sh` therefore resolves the consumer root itself, first hit wins, and exports it as `MT_REPO_ROOT` so the resolver's existing pin honours it:

#	Source	Notes
1	MT_REPO_ROOT env	explicit pin (operator / launcher / test seam)
2	invocation context	nearest ancestor of \$PWD carrying config/multitrack/
3	operator binding file	MT_CONSUMER_ROOTS , default \${XDG_CONFIG_HOME:- \$HOME/.config}/multitrack/consumer_roots.conf
4	(nothing resolved)	export nothing → resolver keeps its unchanged self- location behaviour

Step 4 is the load-bearing back-compat guarantee: a host with no binding file and no cwd context behaves **exactly** as before this resolution existed.

Honest boundary (§11.4.6). When the hook fires there is, by construction, no cwd project context — so on a host running more than one consumer the alias → consumer mapping is host policy that nothing in-tree can derive. Step 3's operator-owned file is the minimal artifact that satisfies §11.4.177 (project-agnostic tooling) and §11.4.187 (automatic, out-of-the-box) at once.

Binding-file format — parsed, never sourced, so a typo can never execute:

```
# ${XDG_CONFIG_HOME:-$HOME/.config}/multitrack/consumer_roots.conf
default  = /mnt/track1/my_project
claude2  = /mnt/track1/other_project      # alias key beats `default`
```

A named path that does not carry config/multitrack/ is reported on stderr and **ignored** — never silently trusted (§11.4.6). Diagnose with:

```
multitrack_cwd_hook.sh --consumer-root <alias>
```

Installation note (§11.4.177). Resolution being project-agnostic is only half the rule. The shared PATH entry itself must not live inside a consumer checkout — a symlink from `~/local/bin/` into one project's tree couples every project's tooling availability and version to that one checkout. Install the engine from a location outside every consumer, or use the toolkit's per-project `<dir>/claude-cwd-hook` / `CMA_CWD_HOOK` seams.

Config contract – how a generic script finds project config

A generic script self-locates BOTH roots with zero hardcoding:

- **Constitution root** — via `constitution/find-constitution.sh` (honors an explicit `CONSTITUTION_DIR` override, else walks up for `constitution/Constitution.md` / `submodules/constitution/Constitution.md`, else follows the git superproject pointer). These scripts do not need it at runtime (they are self-contained), but it is the canonical self-location primitive when a caller needs the constitution root.
- **Project/repo root** — `MT_REPO_ROOT` (explicit override) else the script's `../..`. **Because these scripts live at `constitution/scripts/multitrack/`, their `../..` resolves to the constitution submodule, NOT the consuming project.** A consumer therefore MUST set `MT_REPO_ROOT` (or the explicit `MT_CONFIG` full path) so config, `.ws_state`, and the tmp namespace resolve against the project, not the constitution. The reference launcher exports `MT_REPO_ROOT` for every invocation.
- **Per-host config file** — resolved by `multitrack-config.sh` as:
 1. `MT_CONFIG` — explicit full path to a config file (wins), else
 2. `$MT_CONFIG_DIR/<host>.yaml` — where `MT_CONFIG_DIR` defaults to `$(mt_repo_root)/config/multitrack` and `<host> = MT_HOST` else the system hostname (`/etc/hostname`, else the first 16 of the machine-id). An unreadable `<hostname>.yaml` falls back to `<machine-id-16>.yaml`.

Schema: `schema_version: 1`, **one file per host.**

The `MT_*` environment contract (retained
verbatim, no renames)

Env	Meaning	Default
MT_REPO_ROOT	project/repo root	script <code>../..</code> (⇒ set this from the constitution location)
MT_CONFIG	explicit config-file path (overrides host resolution)	—
MT_CONFIG_DIR	per-host config directory	<code>\$(mt_repo_root)/config/multitrack</code>
MT_HOST	host key for <code><host>.yaml</code>	system hostname → machine-id-16
MT_ALIAS_DIR	orchestrator runtime dir (bindings/cool-downs/events)	<code>\${XDG_RUNTIME_DIR:-/tmp}/\$(basename "\$MT_REPO_ROOT")/multitrack/aliasorch</code>
MT_LOCK_DIR	device-lock runtime dir	<code>\${XDG_RUNTIME_DIR:-/tmp}/\$(basename "\$MT_REPO_ROOT")/multitrack/devicelock</code>
MT_REGISTRY_LOCK	streams-registry flock	<code>\${XDG_RUNTIME_DIR:-/tmp}/\$(basename "\$MT_REPO_ROOT")/multitrack/registry.lock</code>
MT_STREAMS_TSV	streams registry TSV	<code>\$MT_REPO_ROOT/.ws_state/streams.tsv</code>
MT_WS_STATE	per-repo state dir	<code>\$MT_REPO_ROOT/.ws_state</code>
MT_WORKTREE_SUBDIR	worktree subdir under a track mount	<code>\$(basename "\$MT_REPO_ROOT")</code>
MT_ALIAS_ROSTER	alias roster override (<code>name:kind,...</code>)	config <code>aliases:</code> block, else built-in

Env	Meaning	Default
<code>MT_BUILD_COMMAND</code>	build command string (the <code>build.command</code> config key)	auto-detect <code>scripts/ build_maxres.sh</code> else <code>scripts/build.sh</code>
<code>MT_BUILD_MIN_FREE_GB</code>	pre-build free-space floor (the <code>build.min_free_gb</code> config key)	<code>158</code>
<code>MT_LOCK_WAIT</code> / <code>MT_DEFAULT_TTL</code> / <code>MT_CLAIM_TTL</code> / <code>MT_ALIAS_TTL</code> / <code>MT_COOLDOWN</code>	flock/lease timers	see each script header

No `MT_*` var was renamed when this engine was lifted from the reference consumer — a rename would break the live host and every paired test (§11.4.6).

Consumer config keys (in `config/multitrack/<host>.yaml`)

Beyond `host` / `protected_drives` / `tracks` / `device_pool` / `lease_policy` / `aliases` , the config carries two OPTIONAL keys read by the engine. Both are **consumer data** (§11.4.28(B)) — the engine never hardcodes their values.

Key	Shape	Read by	Meaning
<code>conduct-</code> <code>or:</code>	top-level scalar (alias name)	<code>mt_con-</code> <code>fig_conduct-</code> <code>or</code> → the re- solver	§11.4.177 auto-conductor. The named alias is NEVER worktree-bound — its session stays on the shared <code>/home</code> checkout (<code>resolve</code> prints nothing / exit 0, and bind-on-start never binds it). Empty string (default) ⇒ no alias is special-cased (the <code>/home</code> session is simply whichever session is unbound). Consumer-overrideable (e.g. <code>conductor: claude3</code> , or a provider alias to dedicate a conductor account).
<code>fall-</code> <code>back.sig-</code> <code>natures:</code>	block- style list under a top-level <code>fall-</code> <code>back:</code>	<code>mt_con-</code> <code>fig_fall-</code> <code>back_signa-</code> <code>tures</code> → the (PWU-4) rate- limit monitor	§11.4.177 auto-fallback. The rate-limit transcript signatures the monitor matches to detect a usage/quota limit and trigger <code>orchestrator fall-back</code> . Surrounding single/double quotes are stripped (values that themselves contain <code>"</code> are single-quoted in YAML). Consumer-overrideable — a future rate-limit wording change is a one-line pin here, not a code change. Empty/absent ⇒ no signatures (the monitor decides its own default).

Reference-consumer seed (both keys are consumer data, so they live in the project config, never in this engine):

```
conductor: ""           # empty ⇒ /home session is conductor
fallback:
  signatures:
    - "'apiErrorStatus':429"
    - "'isApiErrorMessage':true"
```

Runtime namespace derivation

The tmp runtime dirs (`aliasorch` / `device.lock` / `registry.lock`) derive their top-level namespace from `$(basename "$MT_REPO_ROOT")` (via `mt_repo_root`), so a consumer's runtime state is namespaced by its own project directory name — no project literal is baked into the engine.

Quick start (consumer)

from the project root, with a config/multitrack/<hostname>.yaml present:

```
MT_REPO_ROOT="$PWD" bash constitution/scripts/multitrack/multitrack_resolve_worktree.sh map
```

or point at an explicit config file:

```
MT_CONFIG=config/multitrack/<host>.yaml MT_REPO_ROOT="$PWD" \  
bash constitution/scripts/multitrack/multitrack_resolve_worktree.sh resolve claudel
```

Genericization delta vs the reference consumer

Lifted from the reference project's `scripts/multitrack/` per §11.4.35 with a small, mechanical delta (three executed-code fixes + comment-literal scrub):

1. **Namespace literal** — the tmp-namespace defaults in `multitrack_registry.sh` , `multitrack_resolve_worktree.sh` , `multitrack_device_lock.sh` , and `multitrack_alias_orchestrator.sh` derive the top-level dir from `$(basename "$MT_REPO_ROOT")` instead of a hardcoded project name (orchestrator + resolve share one runtime dir, so both are fixed in lockstep).
2. **Build command** — `multitrack_build.sh` reads the `build.command` config key via `MT_BUILD_COMMAND` , falling back to a documented auto-detect default.
3. **Item-id param** — `multitrack_claim.sh` 's user-facing `atm-id` label is the scheme-agnostic `item-id` (the positional arg accepts any stable id — no named flag existed, so no back-compat alias is needed).

Consumer-side DATA (`config/multitrack/<host>.yaml` , serials, mount paths) stays in the consuming project and is NEVER copied here.

Alias priority, per-alias limit/subscription tracking, auto-rebind-on-recovery (§ . .)

The alias↔track binding layer (`multitrack_alias_orchestrator.sh`) implements the §11.4.196 mandate — the alias-binding + rate-limit/subscription-tracking layer of the §11.4.187 ruler:

Native-alias-first priority. `_next_available_alias` scans the `native` class COMPLETELY before the `provider` class, so an OPERATIONAL native (`claudeN`) alias is ALWAYS selected before ANY provider, regardless of roster file order (§11.4.111 resolve-by-CLASS-not-by-file-position). Within a class the operator-mandated order (native equal-capability; providers `deepseek` → `xiaomi` → `opencode` → `kimi-for-coding` → ...) is authoritative decision-DATA — the built-in `DEFAULT_ROSTER` encodes it and `config/multitrack/alias_priority.yaml` is its tracked, non-secret record (alias NAMES only, never keys — §11.4.10). `_alias_rank` exposes the same ordering as a comparable integer (native base 0 < provider base 100000).

Per-alias reason-class limit tracking (from REAL signals, never faked — §11.4.6). A cooled alias's `cooldowns.snapshot` row is `alias|until|reason|class` where `class` ∈ {`session` | `weekly` | `subscription`} and `until` is its operational-again epoch. The three classes have DIFFERENT windows:

class	window (<code>MT_COOLDOWN_*</code>)	meaning
<code>session</code>	<code>MT_COOLDOWN_SESSION</code> (=300s)	a 429 session rate-limit — self-heals at the reset
<code>weekly</code>	<code>MT_COOLDOWN_WEEKLY</code> (=604800s)	weekly-limit-reached — ~until the weekly reset
<code>subscription</code>	far-future sentinel (2100-01-01Z)	subscription expired — INDEFINITE until a REAL renewal

§11.4.6 NEVER guesses a renewal date — a caller MAY pass an exact `--until <epoch>` parsed from a real reset marker, which wins over the class default.

Commands.

- `mark-limited --alias A [--class session|weekly|subscription] [--until EPOCH] [--reason R]` — record a per-alias limit from a real signal (the `multitrack_fallback_monitor.sh` 429-signature classifier calls this / `fallback --class ...`). A limited alias is never auto-selected until `until` passes (session/weekly) or `mark-operational` clears it (subscription).
- `mark-operational --alias A` — clear an alias's cooldown NOW (a subscription renewal / operator-confirmed recovery). The next `auto-assign / promote` prefers it.
- `promote [--ttl S]` — auto-use-on-recovery: for EVERY bound track, if a strictly higher-priority (lower `_alias_rank`) NON-cooled alias exists, rebind the track UPWARD to it, PRESERVING the worktree AND device leases (leases key on the STABLE track id — §11.4.119). Idempotent. Run it after every reap/tick so a track that fell onto a provider returns to a recovered native automatically.
- `fallback --track T [--class ...] [--until ...]` — on a limit, cool the current alias (class-aware) and hand the track to the next available alias.
- `status` — the cooldown section now shows `class + operational-again-epoch`.

RB-02 host-budget guard fix (`multitrack_host_budget.sh` , §12.12 /

§11.4.196(D)). `_mt_host_budget_heavy_build_running` no longer trusts a bare `pgrep -f REGEX` substring match (which false-matched a live `claude` worker whose prompt QUOTED the `pgrep` pattern and REFUSED every spawn on a host with zero real builds — forensic FACT 2026-07-13). It re-reads each matched PID's REAL `/proc/<pid>/cmdline` (via the `_mt_host_budget_pid_cmdline` seam) and excludes the pattern-CARRIER / `multitrack-ENGINE / claude -worker / self+parent` classes; an UNREADABLE `cmdline` is conservatively counted as a build (REFUSE — the safe, reversible default, §11.4.101/§12.8), so a genuine `soong/gradle/JVM-daemon` build is still caught.

Tests (anti-bluff, §11.4.115 RED-polarity + §1.1 mutation + §11.4.50 determinism):

- `test_multitrack_host_budget_rb02_pgrep.sh` — RB-02 guard (hermetic stub + real- /proc E2E).
- `test_multitrack_alias_priority_limits.sh` — native-first rank + per-class limit windows + `promote` .
- `test_multitrack_native_first_fallback.sh` — native-first selection (pre-existing). Run each with `RED_MODE=1` (reproduce the defect on the mutated artifact) and `RED_MODE=0` (assert the fixed behaviour + §1.1 self-check).

Honest boundary (§11.4.6): these prove the selection / tracking / rebind / guard CONTRACT on the mechanism; genuine live per-subscription quota-isolation still needs live tokens exercising real rate-limit boundaries (an operator acceptance window).