

workable-items UPSTREAM EXTENSION – § . . LVA– OWED-subcommands + export pipeline

Revision: 1 Last modified: 2026-05-31T00:00:00Z

Adds the `update` / `reopen` / `block` subcommands + the `export` documentation pipeline that Lava's LVA-3 §11.4.74 migration found OWED. Project-agnostic per CONST-051 (no Lava-specific context; generic reusable subcommands only).

Files changed (inside the constitution submodule)

File	Change
<code>scripts/workable-items/cmd/workable-items/mutate.go</code>	NEW — <code>update</code> / <code>reopen</code> / <code>block</code> subcommands + helpers.
<code>scripts/workable-items/cmd/workable-items/export.go</code>	NEW — <code>export</code> subcommand + summary generators + pandoc-gated HTML/PDF/DOCX.
<code>scripts/workable-items/cmd/workable-items/mutate_test.go</code>	NEW — 8 table-driven tests for <code>update</code> / <code>reopen</code> / <code>block</code> .
<code>scripts/workable-items/cmd/workable-items/export_test.go</code>	NEW — 1 test (multi-assert) for <code>export</code> docs+summaries+honest no-fake siblings.
<code>scripts/workable-items/cmd/workable-items/main.go</code>	dispatch + usage extended for <code>update</code> / <code>reopen</code> / <code>block</code> / <code>export</code> .
<code>scripts/workable-items/README.md</code>	Revision 3 — documents the four new subcommands.

New subcommand contracts

- `update --id <ID> --db <p> [--title|--severity|--description|--type|--status|--created-by|--assigned-to ...] [--location Issues|Fixed]` — mutates ONLY the explicitly-set fields (`flag.Visit` -driven), regenerates `body_md` , appends an `item_history` `Updated` row (§11.4.34). Rejects unknown IDs, missing field flags, and a §11.4.91-too-short `--description` .
- `reopen --id <ID> --db <p> --why <closed-vocab> --who <AI|User> --when <ISO> --incident <path>` — sets `status=Reopened` , embeds `**Reopened-Details:**` in `body_md` , records the four §11.4.34 facts in `item_history` . Rejects any missing fact, a non-vocabulary `--why` , and a non- `AI|User` `--who` .

- `block --id <ID> --db <p> --details <text> [--why <text>] [--unblock <text>] [--who <text>] — sets status=Operator-blocked , embeds **Operator-Block-Details:** , writes an operator_block_details row (§11.4.21). Rejects empty --details .`
- `export --db <p> [--out-dir <d>] [--no-formats] [--out-issues|--out-fixed <p>] — regenerates Issues.md + Fixed.md (byte-identical round-trip) + Issues_Summary.md (§11.4.12 open-only Type×Status tally + per-item rows) + Fixed_Summary.md (§11.4.53 closed-only) + §11.4.65 HTML/PDF/DOCX siblings via pandoc. pandoc/weasyprint steps are exec.LookPath -gated — when absent the .md is still emitted and an HONEST message is printed; NO fake sibling is fabricated (§6.J / §11.4.6).`

pandoc / weasyprint availability in THIS environment

`pandoc` and `weasyprint` are BOTH PRESENT on this host:

```
go          -> /opt/homebrew/bin/go (go1.26.2 darwin/arm64)
pandoc      -> /opt/homebrew/bin/pandoc
weasyprint  -> /opt/homebrew/bin/weasyprint
```

Therefore the full HTML/PDF/DOCX generation path WAS exercised end-to-end here. The end-to-end smoke (below) shows all 4 `.md` docs each produced `.html` + `.docx` + `.pdf` siblings (16 files total). The `export_test.go` automated test exercises the `--no-formats` path AND asserts the honest no-fake-sibling behaviour.

go build (verbatim)

```
$ CGO_ENABLED=1 GOMAXPROCS=2 go build ./...
B_OK (exit 0)
```

go vet (verbatim)

```
$ CGO_ENABLED=1 GOMAXPROCS=2 go vet ./...  
V_OK (exit 0)
```

3 5

2 6

9

go test (verbatim) – full suite, tests, all PASS (pre-existing + new)

```
$ CGO_ENABLED=1 GOMAXPROCS=2 go test -count=1 ./...  
ok      github.com/HelixDevelopment/HelixConstitution/scripts/workable-  
items/cmd/workable-items 0.704s
```

New tests (verbatim `-v` , all PASS):

```
--- PASS: TestUpdateCmd_MutatesFieldsAndRecordsHistory (0.01s)  
--- PASS: TestUpdateCmd_RejectsShortDescription (0.01s)  
--- PASS: TestUpdateCmd_RejectsUnknownID (0.01s)  
--- PASS: TestUpdateCmd_RequiresAField (0.01s)  
--- PASS: TestReopenCmd_SetsReopenedWithFullAttribution (0.01s)  
--- PASS: TestReopenCmd_RejectsPartialAttribution (0.01s)  
--- PASS: TestBlockCmd_SetsOperatorBlockedWithDetails (0.01s)  
--- PASS: TestBlockCmd_RejectsEmptyDetails (0.01s)  
--- PASS: TestExportCmd_EmitsDocsAndSummaries (0.01s)  
PASS  
ok      github.com/HelixDevelopment/HelixConstitution/scripts/workable-  
items/cmd/workable-items 0.215s
```

`--help` (verbatim)

workable-items – §11.4.93 SQLite-SSoT for workable items

Usage:

workable-items <subcommand> [args...]

Subcommands:

sync md-to-db --db <p> [--issues <p>] [--fixed <p>] Parse trackers, upsert DB.

sync db-to-md --db <p> [--out-issues <p>] [--out-fixed <p>] Regenerate trackers from DB.

diff --db <p> [--issues <p>] [--fixed <p>] Show DB vs Markdown divergence.

validate --db <p> Closed-set + §11.4.91 invariants.

add <type> <severity> --db <p> --title <T> --description <D> [--id <id>] [--prefix <P>] [--created-by <h>] [--assigned-to <h>]

Create a new

Queued item in Issues.

update --id <ID> --db <p> [--title|--severity|--description|--type|--status|--created-by|--assigned-to ...] [--location Issues|Fixed]

Mutate fields on

an existing item (§11.4.34 audit).

reopen --id <ID> --db <p> --why <reason> --who <AI|User> --when <ISO> --incident <p> [--location Issues|Fixed]

Set

Status=Reopened with §11.4.34 source attribution.

block --id <ID> --db <p> --details <T> [--why <T>] [--unblock <T>] [--who <T>] [--location Issues|Fixed]

Set

Status=Operator-blocked with §11.4.21 details.

close <atm-id> --db <p> --status <fixed|implemented|completed|obsolete> --evidence <p>

Atomic

Issues→Fixed closure (§11.4.19).

report --db <p> [--by-type|--by-status|--by-severity|--by-assigned|--by-creator|--obsolete-audit]

Read-only grouped

tally / §11.4.90 audit.

export --db <p> [--out-dir <d>] [--issues <p>] [--fixed <p>] [--out-issues <p>] [--out-fixed <p>]

Regenerate

Issues.md + Fixed.md + Summary docs + HTML/PDF/DOCX (§11.4.12/§11.4.53).

Canonical authority: Constitution.md §11.4.93.

End-to-end smoke (real binary, all four new subcommands + export with pandoc PRESENT)

```
$ workable-items add Bug Critical --db wi.db --title "..." --description
"..."
add: created WIT-001 (Bug, status=Queued) in Issues
$ workable-items update --id WIT-001 --db wi.db --status "In progress"
update: WIT-001 updated in Issues (status=In progress, type=Bug)
$ workable-items reopen --id WIT-001 --db wi.db --why test-failed --who AI
--when 2026-05-31 --incident qa/x.log
reopen: WIT-001 reopened in Issues (By:AI On:2026-05-31 Reason:test-failed
Evidence:qa/x.log)
$ workable-items block --id WIT-001 --db wi.db --details "Needs operator
host"
block: WIT-001 set Operator-blocked in Issues (WHAT:Needs operator host)
$ workable-items export --db wi.db --out-dir ./out
export: wrote out/Issues.md
export: wrote out/Fixed.md
export: wrote out/Issues_Summary.md
export: wrote out/Fixed_Summary.md
export: wrote out/Issues.html
export: wrote out/Issues.docx
export: wrote out/Issues.pdf
export: wrote out/Fixed.html
export: wrote out/Fixed.docx
export: wrote out/Fixed.pdf
export: wrote out/Issues_Summary.html
export: wrote out/Issues_Summary.docx
export: wrote out/Issues_Summary.pdf
export: wrote out/Fixed_Summary.html
export: wrote out/Fixed_Summary.docx
export: wrote out/Fixed_Summary.pdf
```

Generated `Issues_Summary.md` content (proves the open-only Type×Status tally + per-item row reflect the block):

```
# Issues_Summary
```

Open workable items (current_location = Issues), regenerated from the SQLite single-source-of-truth (§11.4.12).

```
## Counts by Type × Status
```

```
| Type | Status | Count |
| --- | --- | --- |
| Bug | Operator-blocked | 1 |
| **TOTAL** | | **1** |
```

```
## Items
```

```
| ATM ID | Type | Status | Severity | Description |
| --- | --- | --- | --- | --- |
| WIT-001 | Bug | Operator-blocked | High | A smoke test bug with enough
words to clear the floor here |
```

`report --by-status` after the block (read-only cross-confirmation):

Workable items by Status:

```
Operator-blocked 1
```

```
-----
```

```
TOTAL 1
```

```
1 1
```

```
1 1 4 4 3
```

Falsifiability rehearsals (§ . / § . .) – each MUTATED → FAIL → reverted → PASS

Each rehearsal: ¹applied the mutation, ran the targeted test (exit 1 = FAIL = caught),
reverted from a clean backup, re-ran (exit 0 = PASS).

Rehearsal – update history append

- **Mutation:** removed the `recordHistory(tx, *id, "Updated", ...)` call in `updateCmd` .
- **Test:** `TestUpdateCmd_MutatesFieldsAndRecordsHistory`

- **Observed FAIL (exit 1):**

```
--- FAIL: TestUpdateCmd_MutatesFieldsAndRecordsHistory (0.01s)
    mutate_test.go:80: Updated history rows = 0, want 1
FAIL
```

- **Reverted:** yes (restored from backup; re-run exit 0).

Rehearsal — reopen \$. . attribution guard

- **Mutation:** removed the `--why` required + closed-vocab guards in `reopenCmd` .
- **Test:** `TestReopenCmd_RejectsPartialAttribution`
- **Observed FAIL (exit 1):** the test reported `reopenCmd` succeeded; want failure (§11.4.34) for the "missing why" + "bad why vocab" cases (assertion at ³`mutate_test.go:188`). ^{11 4 21}
- **Reverted:** yes (restored from backup; re-run exit 0).

Rehearsal — block \$. . empty-details guard

- **Mutation:** removed the empty- `--details` guard in `blockCmd` .
- **Test:** `TestBlockCmd_RejectsEmptyDetails`
- **Observed FAIL (exit 1):** `blockCmd` with blank `--details` succeeded; want failure (§11.4.21) (assertion at `mutate_test.go:256`).
- **Reverted:** yes (restored from backup; re-run exit 0).

Rehearsal — export Issues_Summary open-only filter

- **Mutation:** `renderIssuesSummary` made to include ALL items (closed leak).
- **Test:** `TestExportCmd_EmitsDocsAndSummaries`
- **Observed FAIL (exit 1):** `Issues_Summary` leaked closed item WIT-003 (assertion at `export_test.go:89`).

- **Reverted:** yes (restored from backup; full suite re-run exit 0, `ok ... 0.704s`).

\$. . working-tree quiescence

Post-rehearsal `grep -rl "MUTATED" cmd/` returns **0** files; `diff` confirms `mutate.go` + `export.go` are byte-identical to the verified-good backups — no mutation residue remains in the source tree.

Bluff-Audit stamp (ready to paste into the CONST-commit)

```
Bluff-Audit: mutate_test.go (TestUpdateCmd_MutatesFieldsAndRecordsHistory,
TestReopenCmd_RejectsPartialAttribution, TestBlockCmd_RejectsEmptyDetails)
+ export_test.go (TestExportCmd_EmitsDocsAndSummaries)
  Mutation 1: removed update's recordHistory("Updated") append
  Observed-Failure 1: mutate_test.go:80: Updated history rows = 0, want 1
  Mutation 2: removed reopen's --why required + closed-vocab guards
  Observed-Failure 2: mutate_test.go:188: reopenCmd succeeded; want
failure (§11.4.34)
  Mutation 3: removed block's empty --details guard
  Observed-Failure 3: mutate_test.go:256: blockCmd with blank --details
succeeded; want failure (§11.4.21)
  Mutation 4: made renderIssuesSummary include closed items (open-only
filter dropped)
  Observed-Failure 4: export_test.go:89: Issues_Summary leaked closed item
WIT-003
  Reverted: yes
```

MAIN-AGENT ACTION REQUIRED

This is a **constitution-submodule** change. The subagent did NOT commit or push anything. The MAIN AGENT MUST perform the **CONST-049 7-step pipeline** for the constitution submodule: fetch-first → careful conflict resolution → commit (with the Bluff-Audit stamp above) → push to ALL FOUR constitution upstreams (GitHub + GitLab + GitFlic + GitVerse per the submodule's own `install_upstreams.sh`) → then bump the parent `submodules/constitution` pin in the parent repo.